25D 10.5MM TWIN-SCREW HORIZONTAL EXTRUDER

The unique set up of our horizontal 12 mm 25D extruder **improves material flow** and provides **temperature management** across 4 autonomous heating zones. Additionally, our scalable geometric proportions allow for s**eamless transition from lab testing to industrial production.**

> **Durable material contact parts:** Experience minimal abrasion and extend machine lifespan with our optimized components.

> **Versatile screw design and die options:** Cater to diverse R&D and production applications with our flexible design features such as our cast film die with various width and thickness options.

> **Precise monitoring of process temperature:** With autonomous control for each of the 4 zones up to 300°C (450°C optional).

> **Integrated controls for feeders:** Enhance operational convenience with our advanced control panel and compatible feeders from which you can inject in-the-barrel additional materials, additives and even gases.

CUSTOMIZED PRODUCTS

POLİNAR
her şey çekirdekten gelişir

Screw diameter	12 mm
Length / Diameter	25:1
Screw speed	0-50 rpm
Screw configuration	Segmented screw design fully interchangeable
Dimensions	300mm x 800mm x 430mm
Motor power	0.18 KW
Electrical	0.75 kWh /13 A
Torque output	5 Nm per shaft maximum
Number of barrel zones	4 temperature-controlled zones (heating only)
Temperature range	15-300°C (or 15-450°C optional)
Dies	*Standard:* strand die *Options:* cast film, strip, tube, co-extrusion
Plug-and-play feeding	*Options:* top/side powder or pellet feeder *Options:* pellet, liquid and/or gas feeders
Outputs	uPVC: 1,75 Kg/hr. PP: 1,05 Kg/hr. PS: 1,9 Kg/hr. LDPE: 1,10 Kg/hr. HDPE: 0,73 Kg/hr. PA: 0,52 Kg/hr.
Product cooling systems	*Options:* stainless steel, water- or air-cooling systems
Plug-and-play downstream equipment	*Options:* haul off winder (filament, film or strip), fixed or varicut pelletizer, calendaring
interface	Trail, remote diagnostic tool *Option:* controlled by PC or Tablet
Requirements	24amp, 230V 1ph. 1N + 1PE, 50/60Hz (Europe)
Water supply requirements	4-6 bars

POLİNAR PLASTİK MAKİNE ve KALIP SANAYİ
TİCARET LİMİTED ŞİRKETİ
İkitelli O.S.B Eskoop San. Sit. D Blok
No: 34 Başakşehir / İSTANBUL - TURKEY

Phone : +90 212 549 88 20 – 21
Fax : +90 212 549 88 19
E-Mail : info@polinar.com.tr

www.polinar.com.tr

PTE (POLİNAR TEST EQUIPMENT)
İkitelli O.S.B. Eskoop San. Sit.
D Blok No.34 Başakşehir
İstanbul / TURKEY

Phone : +90 212 549 88 20 – 21
Fax : +90 212 549 88 19
E-Mail : info@polinar.com.tr

www.pte.com.tr

POLINAR GmbH
THE ICON VIENNA, Tower 24
Wiedner Gürtel 13 1100
Vienna AUSTRIA

Phone : +43 (0) 1 253535 4044
Fax : +43 (0) 1 253535 4044
Mobile : +43 676 5983869
E-Mail : office@polinar.at

www.polinar.at