SAFETY DATA SHEET
Regulation (EC) No 1907/2006 (REACH) and US OSHA HCS 29 CFR 1910.1200 | Page 1/2
Issue Date: 12.01.2025 | Version: 5.2 | Document ID: SDS-WS-205

SECTION 1: Identification of the Substance/Mixture and of the Company
1.1. Product Identifier
Trade Name: West System 205 Fast Hardener
CAS Number: 2855-13-2
EC Number: 220-666-8
1.2. Relevant Identified Uses
Fast-curing polyamine epoxy hardener for marine structural laminates, boat hulls and bonding.
1.3. Details of the Supplier
Gougeon Brothers, Inc. / West System International - Bay City, MI / Romsey UK
Emergency Telephone Number: Chemtrec 1-800-424-9300 / European Emergency 112

SECTION 2: Hazards Identification
2.1. Classification according to GHS / CLP
Acute Toxicity Oral Category 4, H302 | Skin Corrosion Category 1B, H314 | Serious Eye Damage Cat 1, H318
2.2. Label Elements
Signal Word: DANGER
Hazard Pictograms: GHS05, GHS07
Hazard Statements:
H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H317: May cause an allergic skin reaction.
H412: Harmful to aquatic life with long lasting effects.

SECTION 4: First-Aid Measures
4.1. Description of First Aid Measures
Eye Contact: Flush immediately with continuous stream of clean water for at least 20 minutes.
Hold eyelids open to ensure complete irrigation. Transport immediately to an ophthalmologist.
Skin Contact: Immediately remove all contaminated clothing. Wash skin with soap and water for 15 min.
Inhalation: Move exposed person to fresh air. If breathing is labored, administer oxygen.
Ingestion: Do NOT induce vomiting. Rinse mouth thoroughly. Call Emergency 112 immediately.

SECTION 5: Fire-Fighting Measures
Suitable Extinguishers: Carbon dioxide (CO2), dry chemical powder, alcohol-resistant foam, water spray.
Prohibited Extinguishers: High pressure solid water jet (risk of spreading hot chemical).
Specific Hazards: Burning produces toxic nitrogen oxides (NOx) and carbon monoxide.

SECTION 7: Handling and Storage
Handling: Do not breathe vapors. Avoid skin contact. Prevent exothermic runaway with epoxy resins.
Incompatible Materials: Strong oxidizing agents, concentrated mineral acids, uncontrolled epoxy mixtures.
Storage Conditions: Store in tightly sealed original containers between 10 C and 30 C in well-ventilated dry space.

SECTION 8: Exposure Controls / Personal Protection
Respirator Mask: Use NIOSH/CEN approved organic vapor cartridge with particulate pre-filter.
Glove Compatibility: Butyl rubber or heavy nitrile gloves. Latex gloves provide inadequate protection.
Eye Protection: Chemical splash goggles combined with full face shield.

SECTION 9: Physical and Chemical Properties
Appearance: Amber transparent liquid | Odor: Characteristic amine/ammoniacal
Flash Point: 110 °C (Pensky-Martens Closed Cup)
Boiling Point: > 230 °C | Specific Gravity: 1.05 g/cm3