Character-Level LSTM in PyTorch

In this notebook, I'm building a character-level RNN with PyTorch. The network will train character by character on some text, then generate new text character by character. As an example, I will train on all of Anna Karenina. It's a fairly surprising thing that the architecture below can learn enough about the structure of text to generate almost readable text.

This notebook is based off of the following blog post and the accompanying code in this repo. Below, I'm going to implement a few of the character-level models that I mention.

I'm also assuming that you have some familiarity with recurrent neural networks in general. If you're not, Andrej Karpathy's post is a good introduction.

```
In [1]: # import libraries
import numpy as np
import torch
from torch import nn, optim
from torch.utils.data import TensorDataset, DataLoader
```

Load in Data

Then, we'll load the Anna Karenina text file and convert it into integers for our network to use.

```
In [2]: # open text file and read in data as `text`
with open('data/anna.txt', 'r') as f:
    text = f.read()
```

Let's check out the first 100 characters, make sure everything is good to go, and then encode the text to integers.

```
In [3]: text[:100]
```

```
Out[3]: 'Chapter 1\n\n\nHappy families are all alike; every unhappy family is unhappy in its own\nway.\n\nEverythi'
```

```
In [4]: # encode the text and map each character to an integer and vice versa

# we create two dictionaries:
# 1. int2char, which maps integers to characters
# 2. char2int, which maps characters to integers
chars = tuple(set(text))
int2char = dict(enumerate(chars))
char2int = {ch: ii for ii, ch in int2char.items()}

# encode the text
encoded = np.array([char2int[ch] for ch in text])
```

And we can see those same characters from above encoded as integers.

```
In [5]: encoded[:100]
```

```
Out[5]: array([ 1, 31, 77, 68, 75, 75, 78, 17, 47, 49, 49, 49, 10, 10, 10, 31, 75,
       68, 61, 72, 78, 61, 75, 31, 68, 61, 31, 68, 75, 75, 31, 79, 64,
       61, 72, 72, 17, 31, 61, 75, 31, 79, 64, 68, 78, 31, 75, 68, 64,
       61, 72, 72, 17, 31, 61, 75, 31, 68, 75, 75, 31, 79, 64, 68, 78,
       31, 75, 68, 64, 61, 72, 72, 17, 10, 10, 10, 31, 75, 64, 61, 78,
       31, 61, 72, 72, 31, 79, 64, 68, 78, 31, 75, 68, 64, 61, 72, 72,
       17, 31, 61, 75, 31, 68, 75, 75, 31, 79, 64, 68, 78, 31, 75, 68])
```

Since the network is working with individual characters, it's similar to a classification problem in which we are trying to predict the next character from the previous text. Here's how many classes (or characters) we have to work with.

```
In [6]: len(chars)
```

```
Out[6]: 83
```

Tokenization

In the next cell, I'm creating a couple of **dictionaries** to convert the characters to and from integers. Encoding the characters to integers makes it easier to use as input in the network.

```
In [7]: # TODO: Create two dictionaries and tokenize the text (encode characters to integers)
```

Time to check your work

Write a function that returns `True` if the dictionaries are set correctly, `False` otherwise. This is just a quick sanity check to make sure things look okay before we get into training the network.

```
In [8]: def check_dictionaries():
    return "Dictionaries are not set correctly!"

check_dictionaries()
```

```
Out[8]: 'Dictionaries are not set correctly!'
```

And we can see those same characters from above encoded as integers.

```
In [9]: encoded[:100]
```

```
Out[9]: array([ 1, 31, 77, 68, 75, 75, 78, 17, 47, 49, 49, 49, 10, 10, 10, 31, 75,
       68, 61, 72, 78, 61, 75, 31, 68, 61, 31, 68, 75, 75, 31, 79, 64,
       61, 72, 72, 17, 31, 61, 75, 31, 79, 64, 68, 78, 31, 75, 68, 64,
       61, 72, 72, 17, 31, 61, 75, 31, 68, 75, 75, 31, 79, 64, 68, 78,
       31, 75, 68, 64, 61, 72, 72, 17, 10, 10, 10, 31, 75, 64, 61, 78,
       31, 61, 72, 72, 31, 79, 64, 68, 78, 31, 75, 68, 64, 61, 72, 72,
       17, 31, 61, 75, 31, 68, 75, 75, 31, 79, 64, 68, 78, 31, 75, 68])
```

Pre-processing the data

As you can see in our char-RNN image above, our LSTM expects an input that is **one-hot encoded** meaning that each character is converted into an integer (via our created dictionary) and then converted into a column vector where only it's corresponding integer index will have the value of 1 and the rest of the vector will be filled with 0's. Since we are one-hot encoding the data we'll also need to reshape it into a matrix (2D tensor).

```
In [10]: def one_hot_encode(arr, n_labels):

    # Initialize the the encoded array
    one_hot = np.zeros((arr.size, n_labels), dtype=np.float32)

    # Fill the appropriate elements with ones
    one_hot[np.arange(one_hot.shape[0]), arr.flatten()] = 1.

    # Finally reshape it to get back to the original array
    one_hot = one_hot.reshape((*arr.shape, n_labels))

    return one_hot
```

```
In [11]: # check that the function works as expected
test_seq = np.array([[3, 5, 1]])
one_hot = one_hot_encode(test_seq, 8)

print(one_hot)
```

```
[[[0. 0. 0. 1. 0. 0. 0. 0.]
  [0. 0. 0. 0. 0. 1. 0. 0.]
  [0. 1. 0. 0. 0. 0. 0. 0.]]]
```

Making training mini-batches

To train on this data, we also want to create mini-batches for training. Remember that we want our batches to be multiple sequences of some desired number of sequence steps. Considering a simple example, our batches would look like this:

In this example, we'll have two batches of two sequences (the batch size, `n_seqs`). Each sequence has three characters (the sequence length, `n_steps`). We also need to make sure that each batch contains all of the information that is fed into the network. For example, the target for the last character in the first sequence in the first batch is the first character in the first sequence in the second batch. (I'll also refer to this as the "next" batch throughout the code.)

To create these batches efficiently, we're going to discard any sequences that don't fit into a batch. For example, if we take the first 34 characters, that leaves two characters over, but we can't form another batch with that because we need all of the batches to have the same number of sequences. So, we'll discard those two characters.

Then, to get our batches, we split the data into N batches of sequences, where N is the batch size. After splitting the data into batches, we can concatenate the batches together for each step in the sequence. This batch concatenation is handled by the variable `nr_seqs`, which is the number of sequences in each batch. Then, we iterate over the batches by calling `yield` on slices of `nr_seqs` sequences. The slices are `n_steps` wide.

Note: We don't have to worry about training on the last few characters that don't form a full sequence. For instance, if we had a batch size of 10 and a sequence length of 50, then each batch would contain $10 \times 50 = 500$ characters. Any characters beyond the $N \times 500$ for some integer N are going to be discarded because they won't form a full batch. Normally this is a small amount of data to throw out relative to the full dataset and it shouldn't affect the performance of the model.

```
In [12]: def get_batches(arr, n_seqs, n_steps):
    '''Create a generator that returns batches of size
       n_seqs x n_steps from arr.

       Arguments
       ---------
       arr: Array you want to make batches from
       n_seqs: Batch size, the number of sequences per batch
       n_steps: Number of sequence steps per batch
    '''

    # Get the number of characters per batch and number of batches we can make
    characters_per_batch = n_seqs * n_steps
    n_batches = len(arr)//characters_per_batch

    # Keep only enough characters to make full batches
    arr = arr[:n_batches * characters_per_batch]

    # Reshape into n_seqs rows
    arr = arr.reshape((n_seqs, -1))

    # TODO: Make batches for the training data in the function below
    for n in range(0, arr.shape[1], n_steps):
        x = arr[:, n:n+n_steps]
        y = np.zeros_like(x)
        y[:, :-1], y[:, -1] = x[:, 1:], x[:, 0]
        yield x, y
```

Test Your Implementation

Now I'll make my data sets and we can check out what's going on as a batch size, step size, and number of batches. Play around with the numbers and see what's happening.

```
In [13]: batches = get_batches(encoded, 8, 50)
x, y = next(batches)

print('x\n', x[:10, :10])
print('\ny\n', y[:10, :10])
```

```
x
 [[ 1 31 77 68 75 75 78 17 47 49]
 [31 75 68 61 72 78 61 75 31 68]
 [75 64 61 78 31 61 72 72 31 79]
 [64 68 78 31 75 68 64 61 72 72]
 [17 31 61 75 31 68 75 75 31 79]
 [10 10 10 31 75 64 61 78 31 61]
 [31 79 64 68 78 31 75 68 64 61]
 [78 31 68 61 31 68 75 75 31 79]]

y
 [[31 77 68 75 75 78 17 47 49 49]
 [75 68 61 72 78 61 75 31 68 61]
 [64 61 78 31 61 72 72 31 79 64]
 [68 78 31 75 68 64 61 72 72 17]
 [31 61 75 31 68 75 75 31 79 64]
 [10 10 31 75 64 61 78 31 61 72]
 [79 64 68 78 31 75 68 64 61 72]
 [31 68 61 31 68 75 75 31 79 64]]
```

If you implemented `get_batches` correctly, the above output should look something like

```
x
 [[25  8 60 11 45 50 20 47 38 38]
 [49 44 38 13 43 52 10 30 58 47]
 [ 6 52 20 50 57 18 38 51 31 38]
 [ 5 24 48 59 10 37 37 24 26 53]
 [34 10 38 24 16 38 10 25 58 52]
 [ 8 38 26 49 10 37 37 24 47 32]
 [59 30 10 25 55 57 53 52 20 38]
 [38 47 10 35 47 10 37 37 24 47]]

y
 [[ 8 60 11 45 50 20 47 38 38 15]
 [44 38 13 43 52 10 30 58 47 38]
 [52 20 50 57 18 38 51 31 38 30]
 [24 48 59 10 37 37 24 26 53 59]
 [10 38 24 16 38 10 25 58 52 59]
 [38 26 49 10 37 37 24 47 32 32]
 [30 10 25 55 57 53 52 20 38 51]
 [47 10 35 47 10 37 37 24 47 32]]
```

although the exact numbers may be different. Check to make sure the data is shifted over one step for `y`.

Defining the network with PyTorch

Below is where you'll define the network.

We'll train the network in batches as we did above. Then, we'll add a fully-connected layer to get our output. Let's also add dropout to this network to help prevent overfitting. We usually see better performance with dropout around 20-50%.

In this network, we'll be using a LSTM cell. A nice dense cell is pictured below. Here, we're taking in our one-hot encoded data and input to the hidden layer. We'll also keep track of the hidden state that's output by the LSTM cell. This will be fed into the LSTM cell in the next step. Finally, the output of the LSTM cell will be fed into a fully-connected layer so we can get the predicted next character.

Typically in PyTorch, you'll make a class for the network. As you saw above when we built the model, we're going to want to use two methods: `__init__` to initialize the layers and `forward` to define the forward pass through the network. In `__init__` we pass in the number of characters (`n_chars`) which we'll need to make the layers. Then `n_hidden` is the number of units in the hidden layers and `n_layers` is the number of hidden layers. Finally `drop_prob` is the dropout probability. We'll default this to 0.5.

In the `forward` method, we need to pass in the input and the hidden state. The input will be fed through the LSTM cell and another layer to get the final output. The hidden state will be passed through the LSTM cell to be used in the next time step.

Model Structure

In `__init__` the suggested structure is as follows:

- Create a list of the hidden layer dimensions with the base hidden size
- Create a multi-layer LSTM using [`nn.LSTM`](http://pytorch.org/docs/master/nn.html#lstm) with the hidden layer sizes and number of layers
- Add a dropout layer with [`nn.Dropout`](http://pytorch.org/docs/master/nn.html#dropout)
- Create a fully-connected layer with [`nn.Linear`](http://pytorch.org/docs/master/nn.html#linear) and the number of output units equal to the number of characters
- Initialize the weights and biases, if desired

Also the suggested structure for `forward` is as follows:

- Get the outputs and the new hidden state from passing the input and hidden state into the LSTM
- Pass the LSTM outputs through the dropout layer
- Stack up the outputs using [`view`](http://pytorch.org/docs/master/tensors.html#torch.Tensor.view) so you can pass them into the fully-connected layer
- Put the output of the fully-connected layer into a variable named `out`
- Return `out` and the hidden state

LSTM Inputs/Outputs

You can find the details of the LSTM cell in the [documentation](http://pytorch.org/docs/master/nn.html#lstm). Namely, the inputs we need to worry about are the input, the hidden state, and the cell state, `(x, (h, c))`. The outputs are the output from the cell and the new hidden state, `(out, (h, c))`. Essentially the hidden state is a tuple containing the short and long term memory, `(h, c)`.

```
In [14]: # check if GPU is available
train_on_gpu = torch.cuda.is_available()
if(train_on_gpu):
    print('Training on GPU!')
else:
    print('No GPU available, training on CPU; consider making n_epochs very small.')
```

```
No GPU available, training on CPU; consider making n_epochs very small.
```

```
In [15]: import torch.nn.functional as F

class CharRNN(nn.Module):
    def __init__(self, tokens, n_hidden=256, n_layers=2,
                               drop_prob=0.5, lr=0.001):
        super().__init__()
        self.drop_prob = drop_prob
        self.n_layers = n_layers
        self.n_hidden = n_hidden
        self.lr = lr

        # creating character dictionaries
        self.chars = tokens
        self.int2char = dict(enumerate(self.chars))
        self.char2int = {ch: ii for ii, ch in self.int2char.items()}

        ## TODO: define the layers of the model
        ## self.lstm = nn.LSTM(<FILL IN>)
        ## self.dropout = nn.Dropout(<FILL IN>)
        ## self.fc = nn.Linear(<FILL IN>)

        ## TODO: define the final, fully-connected output layer
        ## self.fc = nn.Linear(<FILL IN>)

        ## TODO: initialize the weights
        ## self.init_weights()

    def forward(self, x, hc):
        ''' Forward pass through the network.
            These inputs are x, and the hidden/cell state `hc`. '''

        ## TODO: Get x, and the new hidden state (h, c) from the lstm
        ## x, (h, c) = self.lstm(<FILL IN>)

        ## TODO: pass x through the dropout layer
        ## x = self.dropout(<FILL IN>)

        ## TODO: Stack up LSTM outputs using view
        ## x = x.view(<FILL IN>)

        ## TODO: put x through the fully-connected layer
        ## x = self.fc(<FILL IN>)

        ## TODO: return x and the hidden state (h, c)
        ## return <FILL IN>

    def init_weights(self):
        ''' Initialize weights for fully connected layer '''
        initrange = 0.1
        # Set bias tensor to all zeros
        self.fc.bias.data.fill_(0)
        # FC weights as random uniform
        self.fc.weight.data.uniform_(-initrange, initrange)
```

Test Your Implementation

Now I'll instantiate the network with the tokens and hidden layers that I want.

```
In [16]: n_hidden=512
n_layers=2

net = CharRNN(chars, n_hidden, n_layers)
print(net)
```

```
CharRNN(
  (dropout): Dropout(p=0.5)
  (lstm): LSTM(83, 512, num_layers=2, dropout=0.5)
  (fc): Linear(in_features=512, out_features=83, bias=True)
)
```

Time to train

Now the training will take a while to run, so I'll set it to 20 epochs by default. The training can be cut short whenever you want. After a while, the loss should be pretty low and the network will start outputting readable text.

A couple of other things to note:

- Within the training, we detach the hidden state from its history. This is because each batch has a new hidden state, and we don't want to backpropagate all the way through the previous batches.
- We're using [`clip_grad_norm_`](http://pytorch.org/docs/master/nn.html#clip_grad_norm_) to prevent the exploding gradient problem in RNNs / LSTMs. Essentially, this truncates the gradient if it grows too large.

```
In [17]: def train(net, data, epochs=10, n_seqs=10, n_steps=50, lr=0.001, clip=5, val_frac=0.1, print_every=10):
    ''' Training a network

        Arguments
        ---------

        net: CharRNN network
        data: text data to train the network
        epochs: Number of epochs to train
        n_seqs: Number of mini-sequences per mini-batch, aka batch size
        n_steps: Number of sequence steps per mini-batch
        lr: learning rate
        clip: gradient clipping
        val_frac: Fraction of data to hold out for validation
        print_every: Number of steps for printing training and validation loss

    '''
    net.train()

    opt = torch.optim.Adam(net.parameters(), lr=lr)
    criterion = nn.CrossEntropyLoss()

    # create training and validation data
    val_idx = int(len(data)*(1-val_frac))
    data, val_data = data[:val_idx], data[val_idx:]

    if(train_on_gpu):
        net.cuda()

    counter = 0
    n_chars = len(net.chars)
    for e in range(epochs):
        # initialize hidden state
        h = net.init_hidden(n_seqs)
        for x, y in get_batches(data, n_seqs, n_steps):
            counter += 1

            # One-hot encode our data and make them Torch tensors
            x = one_hot_encode(x, n_chars)
            inputs, targets = torch.from_numpy(x), torch.from_numpy(y)

            if(train_on_gpu):
                inputs, targets = inputs.cuda(), targets.cuda()

            # Creating new variables for the hidden state, otherwise
            # we'd backprop through the entire training history
            h = tuple([each.data for each in h])

            # zero accumulated gradients
            net.zero_grad()

            # get the output from the model
            output, h = net(inputs, h)

            # calculate the loss and perform backprop
            loss = criterion(output, targets.view(n_seqs*n_steps).type(torch.LongTensor))
            loss.backward()
            # `clip_grad_norm` helps prevent the exploding gradient problem in RNNs / LSTMs.
            nn.utils.clip_grad_norm_(net.parameters(), clip)
            opt.step()

            # loss stats
            if counter % print_every == 0:
                # Get validation loss
                val_h = net.init_hidden(n_seqs)
                val_losses = []
                net.eval()
                for x, y in get_batches(val_data, n_seqs, n_steps):
                    # One-hot encode our data and make them Torch tensors
                    x = one_hot_encode(x, n_chars)
                    x, y = torch.from_numpy(x), torch.from_numpy(y)

                    # Creating new variables for the hidden state, otherwise
                    # we'd backprop through the entire training history
                    val_h = tuple([each.data for each in val_h])

                    inputs, targets = x, y
                    if(train_on_gpu):
                        inputs, targets = inputs.cuda(), targets.cuda()

                    output, val_h = net(inputs, val_h)
                    val_loss = criterion(output, targets.view(n_seqs*n_steps).type(torch.LongTensor))

                    val_losses.append(val_loss.item())

                net.train() # reset to train mode after iterationg through validation data

                print("Epoch: {}/{}...".format(e+1, epochs),
                      "Step: {}...".format(counter),
                      "Loss: {:.4f}...".format(loss.item()),
                      "Val Loss: {:.4f}".format(np.mean(val_losses)))
```

Instantiating the model

Now we're ready to train the network. First I'll create the model itself with some given hyperparameters. Then, define the mini-batches sizes, and start training.

```
In [18]: n_hidden=512
n_layers=2

net = CharRNN(chars, n_hidden, n_layers)
print(net)
```

```
CharRNN(
  (dropout): Dropout(p=0.5)
  (lstm): LSTM(83, 512, num_layers=2, dropout=0.5)
  (fc): Linear(in_features=512, out_features=83, bias=True)
)
```

Set your training hyperparameters!

Here are the hyperparameters for the network.

In defining the model:

- `n_hidden` - The number of units in the hidden layers.
- `n_layers` - Number of hidden LSTM layers to use.

We assume that dropout probability and learning rate will be kept at the default, in this example.

And in training:

- `batch_size` - Number of sequences running through the network in one pass.
- `num_steps` - Number of characters in the sequence the network is trained on. Larger is better typically, the network can learn more long range dependencies, but takes longer to train. 100 is typically a good number here.
- `lr` - Learning rate for training

Here's some good advice from Andrej Karpathy on training the network. I'm going to copy it in here for your reference. For more information, read the original post.

Tips and Tricks:

Monitoring Validation Loss vs. Training Loss

If you're somewhat new to Machine Learning or Neural Networks it can take a bit of expertise to get good models. The most important quantity to keep track of is the difference between your training loss (printed every `print_every` iterations) and the validation loss (printed every `print_every` iterations). In particular:

- If your training loss is much lower than validation loss then this means the network might be **overfitting**. Solutions for this are to decrease your network size, or to increase dropout. For example you could try dropout of 0.5 and so on.
- If your training and validation loss are about equal then your model is **underfitting**. Increase the size of your model (either number of layers or the number of neurons per layer).

Approximate number of parameters

The two most important parameters that control the model are `n_hidden` and `n_layers`. I would advise that you always use `n_layers` of either 2/3. The `n_hidden` can be adjusted based on how much data you have. The two important quantities to keep track of here are:

- The number of parameters in your model. This is printed when you start training.
- The size of your dataset. 1MB file is approximately 1 million characters.

These two should be about the same order of magnitude. It's a little tricky to tell. Here are some common sense examples:

- You have a 100MB dataset and you're using a network with 10 million parameters. That's probably too large. Unless you're willing to wait a long time for it to converge, your network will almost certainly overfit hard. You can probably reduce your network size by a factor of 2 or so.
- You have a 100MB dataset and you're using a network with 1000 parameters. That's probably too small. Your network will be learning very slowly and could probably benefit from a larger network.

Best models strategy

The winning strategy to obtaining good models (if you have the time) is to always err on making the network larger (as large as you're willing to wait for it to compute) and then try different dropout values (between 0.1 and 0.5). Whatever model has the best validation performance (the loss, written in the checkpoint name, low is good) is the one you should use in the end.

It is very common in deep learning to run many different models with many different hyperparameter settings, and in the end take whatever checkpoint gave the best validation performance.

By the way, the size of your training and validation splits are also parameters. Make sure you have a decent amount of data in your validation set or otherwise the validation performance will not be very informative.

```
In [19]: batch_size = 128
num_steps = 100
n_hidden = 512
n_layers = 2
lr = 0.001
```

Checkpoint

After training, we'll save the model so we can load it again later if we need to. Here I'm saving the parameters needed to create the same architecture, the hidden layer hyperparameters and the text characters.

```
In [20]: # change the name, for saving multiple files
model_name = 'rnn_20_epoch.net'

checkpoint = {'n_hidden': net.n_hidden,
              'n_layers': net.n_layers,
              'state_dict': net.state_dict(),
              'tokens': net.chars}

with open(model_name, 'wb') as f:
    torch.save(checkpoint, f)
```

Making Predictions

Now that the model is trained, we'll want to sample from it and make predictions about next characters! To sample, we pass in a character and have the network predict the next character. Then we take these characters and pass them back in to the network to predict the next character. And we keep doing this to generate all of the new text. I also included an option to prime the network with some text before making predictions. This is useful for building a context for the model.

A note on the `predict` function

The output of our RNN is from a fully-connected layer and it outputs a **distribution of next character scores**.

To actually get the next character, we apply a softmax function, which gives us a probability distribution that we can then sample to predict the next character.

Top-K sampling

Our predictions come from a softmax distribution over all of the possible characters. We can make the predictions harder to mess up by restricting the network to only consider the `top_k` most likely characters. This will prevent the network from giving us completely absurd characters while allowing it to introduce some noise and randomness into the sampled text. Read more about `top_k` here.

```
In [21]: def predict(net, char, h=None, top_k=None):
        ''' Given a character, predict the next character.
            Returns the predicted character and the hidden state.
        '''

        # tensor inputs
        x = np.array([[net.char2int[char]]])
        x = one_hot_encode(x, len(net.chars))
        inputs = torch.from_numpy(x)

        if(train_on_gpu):
            inputs = inputs.cuda()

        # detach hidden state from history
        h = tuple([each.data for each in h])
        # get the output of the model
        out, h = net(inputs, h)

        # get the character probabilities
        p = F.softmax(out, dim=1).data
        if(train_on_gpu):
            p = p.cpu() # move to cpu

        # get top characters
        if top_k is None:
            top_ch = np.arange(len(net.chars))
        else:
            p, top_ch = p.topk(top_k)
            top_ch = top_ch.numpy().squeeze()

        # select the likely next character with some element of randomness
        p = p.numpy().squeeze()
        char = np.random.choice(top_ch, p=p/p.sum())

        # return the encoded value of the predicted char and the hidden state
        return net.int2char[char], h
```

Priming and generating text

Typically you'll want to prime the network so you can build up a hidden state. Otherwise the network will start generating random characters. I'm going to build the function to prime the network, and then it will be used in a sample function coming next.

```
In [22]: def sample(net, size, prime='The', top_k=None):

    if(train_on_gpu):
        net.cuda()
    else:
        net.cpu()

    net.eval() # eval mode

    # First off, run through the prime characters
    chars = [ch for ch in prime]
    h = net.init_hidden(1)
    for ch in prime:
        char, h = predict(net, ch, h, top_k=top_k)

    chars.append(char)

    # Now pass in the previous character and get a new one
    for ii in range(size):
        char, h = predict(net, chars[-1], h, top_k=top_k)
        chars.append(char)

    return ''.join(chars)
```

```
In [23]: print(sample(net, 1000, prime='Anna', top_k=5))
```

```
Annaeee
```