

Erebus Labs

STEM SENSORS

BUDGET

Version 1.4

6/1/2014

SCOTT LAWSON

BRYAN BUTTON

CHRIS CLARY

MAX COPE

VERSION HISTORY

Version #	Implemented By	Revision Date	Reason
1.4	Scott Lawson	6/1/2014	Removed 2.2 – Remaining Costs section Separated BOM section into Initial Estimation and Final
1.3	Scott Lawson	2/1/2014	Fixed Header and cover sheet typos Split Total Anticipated Budget & Remaining Costs
1.2	Scott Lawson	1/31/2014	Added development boards cost to section 2.2 Fixed type in BOM costs
1.1	Scott Lawson	1/30/2014	Changed to Standardized Format Added microcontroller costs
1.0	Scott Lawson	1/28/2014	Initial Release

NOTE TO READER

This is a template obtained from:

<http://www2.cdc.gov/cdcup/library/templates/default.htm>

Template Name: Product Design

UP Template Version: 12/31/07

TABLE OF CONTENTS

1	INTRODUCTION.....	5
1.1	Purpose of The Document.....	5
1.2	Objective Statement	5
1.3	Overview	5
2	DEVELOPMENT COSTS	6
2.1	Ledger.....	6
2.2	Initial Estimation	7
3	BOM COSTS.....	8
3.1	Final.....	8
3.2	Initial Estimation	8
	APPENDIX A: GLOSSARY.....	9
A.1	Acronyms	9
A.2	System Architecture	9

1 INTRODUCTION

1.1 PURPOSE OF THE DOCUMENT

This document describes the budget allotted and cost estimations for the Erebus Labs STEM Sensor. This document is intended to be a living document. As such, it should be updated whenever new budget-related information is available. The reader should be aware that information contained in this document may change at any time.

1.2 OBJECTIVE STATEMENT

Encourage an interest in STEM in K-12 students by delivering a working prototype of an affordable, simple and flexible device to collect environmental data.

1.3 OVERVIEW

This document is divided into two sections:

1. Development Costs

This section contains estimated costs related to the development of the STEM Sensor. This section is further divided into two sections: a ledger to track purchases that have already been made, and a summary of the total anticipated development budget from the beginning of the project.

2. Bill of Materials Costs

These are costs associated with the production of a single sensor unit, excluding amortized development costs. This section contains both the final BOM cost as well as a copy of the initial estimation before many design decisions were made for comparison.

2.2 INITIAL ESTIMATION

Item	Cost (Ea)	Quantity	Ext. Cost	Cost Factors
Sensor	1.00 – 25.00	5 – 8	5.00 – 50.00 ₁	Type, Quantity of each type
μController	1.50 – 5.00	5 – 8	7.50 – 40.00	Onboard Features, power consumption
Batteries	0.75 – 12.00	5 – 16 ₂	12.00 – 60.00 ₂	Rechargeable, composition, form factor
Passives₄	0.05 – 2.00	50 – 100	20.00 – 30.00 ₁	Values and tolerances required
Interfaces₅	0.50 – 8.00	16 – 25	8.00 – 50.00	Wireless vs. Wired
PCBs₆	4.00 – 18.00	4 – 6	24.00 – 48.00	PCB Area, sensor requirements
Other SI₇	0.50 – 2.00	16 – 30	8.00 – 50.00 ₁	Battery selection, sensor output
Packaging	3.00 – 75.00	2 – 3	9.00 – 225.00	Materials: laser-cut acrylic vs. 3D-printer
Software	0.00	0.00	0.00	Only utilizing free development software
Development Boards	10.00 – 60.00	4	40.00 – 240.00	Options available for selected controller
Total:				300.00 – 700.00

1. Extended cost does not scale linearly with quantity because it is assumed that the maximum quantity would not be entirely comprised of the most expensive components.
2. Quantity and extended cost assume either a small amount of expensive rechargeable proprietary batteries, or a larger amount of cheap (AA or 9V) batteries.
3. Resistors, capacitors, inductors, LEDs
4. Antennas, transceivers, receivers, cable jacks
5. Assumes a PCB for the base unit as well as separate PCBs for the interchangeable sensors.
Example: Minimum extended cost is based on a 2in x 2in base unit PCB with two 1in x 1in sensor PCBs at \$2.00 per square inch, x2 prototypes.
6. Other semiconductors: op-amps, voltage regulators, discrete transistors

3 BOM COSTS

3.1 FINAL

(TBD)

Item	Cost (Ea)	Quantity	Ext. Cost	Notes
Sensor	\$4.00	2	\$8.00	Temperature Sensor, CO sensor
μController	\$5.52	1	\$5.52	PSoC3 CY8C3245PVI-150
Batteries	\$0.50	4	\$2.00	AA Batteries
Passives	\$0.50	1	\$0.50	Misc resistors, capacitors, LEDs
Interfaces	\$0.50	4	\$2.00	Generic jack for sensors, USB for base
PCBs	\$6.00	1	\$6.00	2"x2" base PCB, 1"x2" PCB per sensor
Packaging	\$3.00	1	\$3.00	Laser-cut acrylic from EPL, hand assembled
Total:				\$27.02

3.2 INITIAL ESTIMATION

Item	Cost (Ea)	Quantity	Ext. Cost	Notes
Sensor	\$4.00	2	\$8.00	Temperature Sensor, CO sensor
μController	\$5.52	1	\$5.52	PSoC3 CY8C3245PVI-150
Batteries	\$0.50	4	\$2.00	AA Batteries
Passives	\$0.50	1	\$0.50	Misc resistors, capacitors, LEDs
Interfaces	\$0.50	4	\$2.00	Generic jack for sensors, USB for base
PCBs	\$6.00	1	\$6.00	2"x2" base PCB, 1"x2" PCB per sensor
Packaging	\$3.00	1	\$3.00	Laser-cut acrylic from EPL, hand assembled
Total:				\$27.02

APPENDIX A: GLOSSARY

A.1 ACRONYMS

Acronym	Meaning
ADC	Analog-to-Digital Converter
BOM	Bill of Materials
CO	Carbon Monoxide
CSV	Comma-separated-value formatted file
EEPROM	Electrically Erasable Programmable Read-Only Memory
EPL	The Portland State University Engineering and Prototyping Lab
I ² C	The Inter-Integrated Circuit communication protocol
ISR	Interrupt Service Routine
K-12	Kindergarten through 12 th grade school
LED	Light Emitting Diode
PCB	Printed Circuit Board
PSoC	Programmable System On Chip
SI	Silicon
SPI	Serial Peripheral Interface Bus
STEM	Science, Technology, Engineering and Math
TRM	Technical Reference Manual
USB	Universal Serial Bus

A.2 SYSTEM ARCHITECTURE

Base Unit

The central device that manages power, communication, and data storage, and has one or more sensors attached to it.

Sensor

The individual data collection devices such as VOC detectors and thermometers that are attached to the base unit.

User Interface

The program that will be run on a laptop or desktop computer that allows the user to view and interact with the data collected.

System

The operational product comprised of base units with attached sensors and a user interface.