


Analysis of Noisy Gradient-Descent Bit Flipping (NGDBF)

Using MATLAB and the PRISM Model Checking Tool

Eric Reiss
Utah State University



LDPC Codes and Trapping Sets

- Low-Density Parity Check (LDPC) codes were introduced by Gallager in 1963




Figure 1: $(8,8)$ Absorbing set that is dominant in the 802.3an 10GBASE-T LDPC Code [2].

LDPC Codes and Trapping Sets

- ▶ Low-Density Parity Check (LDPC) codes were introduced by Gallager in 1963
- ▶ LDPC codes are commonly represented as sparse Tanner graph




Figure 1: (8,8) Absorbing set that is dominant in the 802.3an 10GBASE-T LDPC Code [2].

LDPC Codes and Trapping Sets

- ▶ Low-Density Parity Check (LDPC) codes were introduced by Gallager in 1963
- ▶ LDPC codes are commonly represented as sparse Tanner graph
- ▶ Trapping sets are a sub-set of the graph that limit the performance of decoding algorithms, creating an error-floor




Figure 1: (8,8) Absorbing set that is dominant in the 802.3an 10GBASE-T LDPC Code [2].

LDPC Codes and Trapping Sets

- ▶ Low-Density Parity Check (LDPC) codes were introduced by Gallager in 1963
- ▶ LDPC codes are commonly represented as sparse Tanner graph
- ▶ Trapping sets are a sub-set of the graph that limit the performance of decoding algorithms, creating an error-floor
- ▶ Absorbing sets are a special case of a trapping sets that are stable in a bit flipping decoder [1]




Figure 1: (8,8) Absorbing set that is dominant in the 802.3an 10GBASE-T LDPC Code [2].

Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms

Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms
- ▶ Improves upon the Gradient-Descent Bit Flipping (GDBF) Decoding Algorithm proposed by Wadayama et al. [3]



Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms
- ▶ Improves upon the Gradient-Descent Bit Flipping (GDBF) Decoding Algorithm proposed by Wadayama et al. [3]

▶ GDBF gets “stuck” in local minima while decoding

Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms
- ▶ Improves upon the Gradient-Descent Bit Flipping (GDBF) Decoding Algorithm proposed by Wadayama et al. [3]

▶ GDBF gets “stuck” in local minima while decoding

- ▶ NGDBF introduces psuedo-random noise to escape local minima

Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms
- ▶ Improves upon the Gradient-Descent Bit Flipping (GDBF) Decoding Algorithm proposed by Wadayama et al. [3]

▶ GDBF gets “stuck” in local minima while decoding

- ▶ NGDBF introduces psuedo-random noise to escape local minima
- ▶ Algorithm steps [4]:



Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms
- ▶ Improves upon the Gradient-Descent Bit Flipping (GDBF) Decoding Algorithm proposed by Wadayama et al. [3]

▶ GDBF gets “stuck” in local minima while decoding

- ▶ NGDBF introduces psuedo-random noise to escape local minima
- ▶ Algorithm steps [4]:

▶ Let H be an $n \times m$ parity check matrix, N_i be the adjacency for bit i , M_j be the adjacency for parity check j

Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms
- ▶ Improves upon the Gradient-Descent Bit Flipping (GDBF) Decoding Algorithm proposed by Wadayama et al. [3]

▶ GDBF gets “stuck” in local minima while decoding

- ▶ NGDBF introduces psuedo-random noise to escape local minima
- ▶ Algorithm steps [4]:

- ▶ Let H be an $n \times m$ parity check matrix, N_i be the adjacency for bit i , M_j be the adjacency for parity check j
- ▶ Given channel samples, \vec{y} , initialize \vec{x} to be the $\text{sign}(\vec{y})$

Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms
- ▶ Improves upon the Gradient-Descent Bit Flipping (GDBF) Decoding Algorithm proposed by Wadayama et al. [3]

▶ GDBF gets “stuck” in local minima while decoding

- ▶ NGDBF introduces psuedo-random noise to escape local minima
- ▶ Algorithm steps [4]:

- ▶ Let H be an $n \times m$ parity check matrix, N_i be the adjacency for bit i , M_j be the adjacency for parity check j
- ▶ Given channel samples, \vec{y} , initialize \vec{x} to be the $\text{sign}(\vec{y})$
- ▶ Compute the syndrome, $s_j = \prod_{i \in M_j} x_i$

Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms
- ▶ Improves upon the Gradient-Descent Bit Flipping (GDBF) Decoding Algorithm proposed by Wadayama et al. [3]

▶ GDBF gets “stuck” in local minima while decoding

- ▶ NGDBF introduces psuedo-random noise to escape local minima
- ▶ Algorithm steps [4]:

- ▶ Let H be an $n \times m$ parity check matrix, N_i be the adjacency for bit i , M_j be the adjacency for parity check j
- ▶ Given channel samples, \vec{y} , initialize \vec{x} to be the $\text{sign}(\vec{y})$
- ▶ Compute the syndrome, $s_j = \prod_{i \in M_j} x_i$
- ▶ Calculate the energy for bit i , $E_i = y_i x_i + w \sum_{j \in N_i} s_j + z_i$, where w is i.i.d white noise and z_i is a zero mean noise perturbation

Algorithm Overview

- ▶ NGDBF is part of a family of bit flipping decoding algorithms
- ▶ Improves upon the Gradient-Descent Bit Flipping (GDBF) Decoding Algorithm proposed by Wadayama et al. [3]

▶ GDBF gets “stuck” in local minima while decoding

- ▶ NGDBF introduces psuedo-random noise to escape local minima
- ▶ Algorithm steps [4]:

- ▶ Let H be an $n \times m$ parity check matrix, N_i be the adjacency for bit i , M_j be the adjacency for parity check j
- ▶ Given channel samples, \vec{y} , initialize \vec{x} to be the $\text{sign}(\vec{y})$
- ▶ Compute the syndrome, $s_j = \prod_{i \in M_j} x_i$
- ▶ Calculate the energy for bit i , $E_i = y_i x_i + w \sum_{j \in N_i} s_j + z_i$, where w is i.i.d white noise and z_i is a zero mean noise perturbation
- ▶ Given a threshold θ flip bit i if $E_i < \theta$

Model Construction

- ▶ The Markov Chain structure used in the tool was proposed in [1]

Model Construction

- ▶ The Markov Chain structure used in the tool was proposed in [1]
- ▶ For a given (a,b) trapping set, the state space is described by the a -bit binary representation of the numbers from 0 to $2^a - 1$



Model Construction

- ▶ The Markov Chain structure used in the tool was proposed in [1]
- ▶ For a given (a,b) trapping set, the state space is described by the a-bit binary representation of the numbers from 0 to $2^a - 1$

- ▶ For example, the (3,3) trapping set would have 8 states, 000 - 111

Model Construction

- ▶ The Markov Chain structure used in the tool was proposed in [1]
- ▶ For a given (a,b) trapping set, the state space is described by the a-bit binary representation of the numbers from 0 to $2^a - 1$
 - ▶ For example, the (3,3) trapping set would have 8 states, 000 - 111
 - ▶ A transition from 010 to 000 implies that the middle bit flipped

Model Construction

- ▶ The Markov Chain structure used in the tool was proposed in [1]
- ▶ For a given (a,b) trapping set, the state space is described by the a-bit binary representation of the numbers from 0 to $2^a - 1$

- ▶ For example, the (3,3) trapping set would have 8 states, 000 - 111
- ▶ A transition from 010 to 000 implies that the middle bit flipped

- ▶ Transition

MATLAB Tool

Sources

- ▶ [1] Tasnuva Dissertation

Sources

- ▶ [1] Tasnuva Dissertation
- ▶ [2] T. Tithi, C. Winstead, and G. Sundararajan, Gopalakrishnan, “Decoding LDPC codes via Noisy Gradient Descent Bit-Flipping with Re-Decoding”, 2015.

Sources

- ▶ [1] Tasnuva Dissertation
- ▶ [2] T. Tithi, C. Winstead, and G. Sundararajan, Gopalakrishnan, “Decoding LDPC codes via Noisy Gradient Descent Bit-Flipping with Re-Decoding”, 2015.
- ▶ [3] T. wadayama, K. Nakamura, M. Yagita, Y. Funahashi, S. Usami, and I. Takumi, “Gradient descent bit flipping algorithms for decoding LDPC codes”, *Communications, IEEE Transactions on*, vol. 58, no. 6, pp. 1610-1614, 2010.

Sources

- ▶ [1] Tasnuva Dissertation
- ▶ [2] T. Tithi, C. Winstead, and G. Sundararajan, Gopalakrishnan, “Decoding LDPC codes via Noisy Gradient Descent Bit-Flipping with Re-Decoding”, 2015.
- ▶ [3] T. wadayama, K. Nakamura, M. Yagita, Y. Funahashi, S. Usami, and I. Takumi, “Gradient descent bit flipping algorithms for decoding LDPC codes”, *Communications, IEEE Transactions on*, vol. 58, no. 6, pp. 1610-1614, 2010.
- ▶ [4] NGDBF demo

Making slides

- ▶ I like HTML presentations based on Slidy, but many prefer PDF slides produced by \LaTeX /Beamer.

Making slides

- ▶ I like HTML presentations based on Slidy, but many prefer PDF slides produced by \LaTeX /Beamer.
- ▶ It can be a challenge to write code in either HTML or \LaTeX .

Making slides

- ▶ I like HTML presentations based on Slidy, but many prefer PDF slides produced by \LaTeX /Beamer.
- ▶ It can be a challenge to write code in either HTML or \LaTeX .
- ▶ Markdown and Pandoc provide an easy text-based syntax for writing papers and presentations.

Making slides

- ▶ I like HTML presentations based on Slidy, but many prefer PDF slides produced by \LaTeX /Beamer.
- ▶ It can be a challenge to write code in either HTML or \LaTeX .
- ▶ Markdown and Pandoc provide an easy text-based syntax for writing papers and presentations.
- ▶ This template is designed to work with Pandoc to simultaneously:



Making slides

- ▶ I like HTML presentations based on Slidy, but many prefer PDF slides produced by \LaTeX /Beamer.
- ▶ It can be a challenge to write code in either HTML or \LaTeX .
- ▶ Markdown and Pandoc provide an easy text-based syntax for writing papers and presentations.
- ▶ This template is designed to work with Pandoc to simultaneously:

- ▶ Produce html output based on slidy

Making slides

- ▶ I like HTML presentations based on Slidy, but many prefer PDF slides produced by \LaTeX /Beamer.
- ▶ It can be a challenge to write code in either HTML or \LaTeX .
- ▶ Markdown and Pandoc provide an easy text-based syntax for writing papers and presentations.
- ▶ This template is designed to work with Pandoc to simultaneously:

- ▶ Produce html output based on slidy
- ▶ Produce matching PDF output based on \LaTeX /Beamer

Procedure

1. Prepare slides in a text document using Markdown syntax.

Procedure

1. Prepare slides in a text document using Markdown syntax.
2. Place any images in the `figures/` subdirectory.

Procedure

1. Prepare slides in a text document using Markdown syntax.
2. Place any images in the `figures/` subdirectory.
3. Edit the included `Makefile` to specify the presentation name and other details.

Procedure

1. Prepare slides in a text document using Markdown syntax.
2. Place any images in the `figures/` subdirectory.
3. Edit the included `Makefile` to specify the presentation name and other details.
4. Build the presentation by running `make`

Including Figures

To include a figure using Markdown, use this syntax:

```
![Optional figure caption.](figures/example.png){width=60%}
```

Result:




Figure 2: Optional figure caption.


Two-Column Slides

Starting two-column mode:

Here is a column.

► Text.

And another column.




Two-Column Slides

Starting two-column mode:

Here is a column.

- ▶ Text.
- ▶ More text.

And another column.




Two-Column Slides

Starting two-column mode:

Here is a column.

- ▶ Text.
- ▶ More text.
- ▶ Description.

And another column.




Two-Column Slides

Starting two-column mode:

Here is a column.

- ▶ Text.
- ▶ More text.
- ▶ Description.
- ▶ Discussion.

And another column.



Two-Column Slides

Starting two-column mode:

Here is a column.

► Text.

And another column.




Figure 4: A tall figure.

Columns are now over.

Two-Column Slides

Starting two-column mode:

Here is a column.

- ▶ Text.
- ▶ More text.

And another column.




Figure 4: A tall figure.

Columns are now over.

Two-Column Slides

Starting two-column mode:

Here is a column.

- ▶ Text.
- ▶ More text.
- ▶ Description.

And another column.




Figure 4: A tall figure.

Columns are now over.

Two-Column Slides

Starting two-column mode:

Here is a column.

- ▶ Text.
- ▶ More text.
- ▶ Description.
- ▶ Discussion.

And another column.




Figure 4: A tall figure.

Columns are now over.