

Air Conditioning Systems

Cooling Only Series



Scan for more
information or call
1300 722 228

Only available in Nth QLD, WA & NT



Cooling Only Series

The Cooling Only Series provides excellent airflow and impressively quiet operation. The new addition of MSY-GY90 unit extends the capacity range of the Cooling Only Series up to 9.0 kW.



MSY-GW25/35/42VFD2-A1
H 290 x W 799 x D 232 mm



MSY-GW50/60VFD2-A1
H 305 x W 923 x D 250 mm



MSY-GW71/80VFD2-A1
H 325 x W 1,100 x D 238 mm



MSY-GY90VFD2-A1
H 365 x W 1,170 x D 295 mm

Capacity Range (kW)

2.5 | 3.5 | 4.2 | 4.8 | 6.0 | 7.1
8.0 (MSY-GW25-80) | 9.0 (MSY-GY90)

Available Colours



Natural White

Outdoor Units



MUY-GW25/35/42/50VFD2-A1



MUY-GW60VFD2-A1



MUY-GW71/80VFD2-A1
MUY-GY90VFD2-A1

Key Features



Wireless Controller

A 7-day programmable wireless controller comes standard with the unit. It allows the user to set when the unit turns on/off and at which temperature setpoint it operates at different times of the day. This feature helps reduce power consumption without compromising comfort conditions.



Bluefin

Anti-corrosion treatment has been applied to the heat exchanger of the outdoor units. This coating helps to prevent corrosion of the aluminum fins caused by salt in the air especially in coastal areas. Corrosion of the heat exchanger will affect the efficiency and performance of the air conditioner.



Wide & Long Airflow^{*1}

Wide and long airflow modes allow the airflow direction to be adjusted (wide airflow 150° and longer reach up to 12m). It is especially beneficial for large spaces, helping to ensure that the air is well circulated within the comfort of your living space. This can be activated at the touch of a button on your remote controller.



Demand Response Capable^{*2}

Our MUY-GW and MUY-GY outdoor units include a demand response enabling device (DRED), allowing your electricity provider to activate and control the system at 3 preprogrammed modes, in response to signals sent from the electricity provider at times when it is necessary to help reduce peak demand.



Nano Platinum Filter

The Nano Platinum Deodorising Filter reduces airborne bacteria^{*3} while improving air quality.



Quiet Operation

A 'Quiet Mode' setting has been added to the fan speed settings, ensuring super quiet operation down to 19dB^{*4}. Perfect for bedrooms; it's so quiet you'll check to see if it's on.



Wi-Fi Control^{*5}

Unlock the door to smarter cooling systems, for total home comfort. This innovative technology connects your Mitsubishi Electric air conditioner to your smartphone, tablet or online account, giving you the freedom to fully control each unit on-the-go via an internet connection from anywhere in the world.

^{*1} Models MSY-GW50-80 and MSY-GY90 only.

^{*2} This requires an additional adapter from your power provider and is installed in accordance with AS/NZS 4755.3.1:2014.

^{*3} Testing Standard JIS L1902.

^{*4} Models MSY-GW25/35 only.


^{*5} Optional Wi-Fi adapter required per unit. Requires an internet connection and the App downloaded on your smartphone or tablet with the latest operating system available.

^{*6} To use Google Assistant to control your air conditioner you will need a Google Home Smart speaker.

^{*7} To use Amazon Alexa to control your air conditioner you will need an Amazon Alexa Echo device.



^{*6}



^{*7}

MSY-GW Series (Wall Mounted Cooling Only)							
Indoor Unit			MSY-GW25VFD2-A1	MSY-GW35VFD2-A1	MSY-GW42VFD2-A1	MSY-GW50VFD2-A1	
Outdoor Unit			MUY-GW25VFD2-A1	MUY-GW35VFD2-A1	MUY-GW42VFD2-A1	MUY-GW50VFD2-A1	
Refrigerant			R32				
Cooling	Capacity [Rated]*3		kW	2.50	3.50	4.20	4.90
	Capacity [Min-Max]		kW	1.10 - 3.40	1.10 - 4.10	0.90 - 4.80	1.50 - 6.00
	Total Input [Rated]*3		kW	0.58	0.87	1.18	1.24
	Total Input [Min-Max]		kW	0.19 - 0.99	0.19 - 1.18	0.17 - 1.90	0.32 - 2.00
	EER			4.31	4.02	3.56	3.95
	AEER			4.19	3.95	3.51	3.90
	TCSPF (Residential)		Hot	6.29	7.26	5.82	6.19
			Mixed	5.28	6.06	5.16	5.51
			Cold	5.35	6.33	5.41	5.77
	ZERL Star Rating*1		Hot	4.5	5.5	4.0	4.5
			Average	3.5	4.5	3.5	4.0
			Cold	3.5	4.5	3.5	4.0
Running Current [Rated]*2 *3		A	3.30	4.20	5.60	5.60	
SPL	In [Quiet-Lo-Mid-Hi-SHI]		dB(A)	19 - 24 - 31 - 38 - 45		26 - 29 - 35 - 40 - 46	28 - 33 - 38 - 44 - 49
	Out [PWL]		dB(A)	46 (59)		50 (62)	51 (64)
Air Volume (In) [Quiet-SHI]		L/S	72 - 208	72 - 215		82 - 218	143 - 307
Indoor Unit	Dimensions [HxWxD]		mm	290 x 799 x 232			305 x 923 x 250
	Weight		kg	9.5			12.5
Outdoor Unit	Dimensions [HxWxD]		mm	550 x 800 x 285			
	Weight		kg	29.5	32.5	33.0	
Ext. Piping	Diameter [Liquid/Gas]		mm	ø6.35/ø9.52			ø6.35/ø12.70
	Max. Length/Height		m	20/12			
Guaranteed Operating Range [Outdoor]		Cooling	°C	21 ~ 46			

MSY-GW and MSY-GY Series (Wall Mounted Cooling Only)												
Indoor Unit			MSY-GW60VFD2-A1		MSY-GW71VFD2-A1		MSY-GW80VFD2-A1		MSY-GY90VFD2-A1			
Outdoor Unit			MUY-GW60VFD2-A1		MUY-GW71VFD2-A1		MUY-GW80VFD2-A1		MUY-GY90VFD2-A1			
Refrigerant			R32									
Cooling	Capacity [Rated]*3		kW		6.00		7.10		8.00		9.0	
	Capacity [Min-Max]		kW		1.50 - 7.20		2.40 - 8.70		2.40 - 9.20		2.0 - 10.3	
	Total Input [Rated]*3		kW		1.58		1.83		2.27		2.63	
	Total Input [Min-Max]		kW		0.33 - 2.20		0.48 - 3.20		0.48 - 3.34		0.43 - 3.98	
	EER				3.80		3.88		3.52		3.42	
	AEER				3.76		3.84		3.50		3.42	
	TCSPF (Residential)		Hot		6.09		6.17		5.18		5.13	
			Mixed		5.60		5.58		4.80		4.91	
			Cold		5.89		5.84		5.04		5.25	
	ZERL Star Rating*1		Hot		4.5				3.5			
			Average		4.0				3.0			
			Cold		4.0				3.5			
Running Current [Rated]*2 *3			A		7.20		8.20		10.60		12.00	
SPL		In [Quiet-Lo-Mid-Hi-SHi]		dB(A)		29 - 37 - 41 - 45 - 50		30 - 37 - 41 - 45 - 51		30 - 36 - 42 - 48 - 54		
		Out [PWL]		dB(A)		55 (67)		57 (69)		56 (69)		
Air Volume (In) [Quiet-SHi]			L/S		113 - 317		152 - 345		168 - 463			
Indoor Unit	Dimensions [HxWxD]		mm		305 x 923 x 250		325 x 1100 x 238		365 x 1170 x 295			
	Weight		kg		12.5		14.7		20.0			
Outdoor Unit	Dimensions [HxWxD]		mm		714 x 800 x 285		880 x 840 x 330					
	Weight		kg		39.0		48.5		53.0			
Ext. Piping	Diameter [Liquid/Gas]		mm				ø6.35/ø12.70					
	Max. Length/Height		m		20/12		30/15					
Guaranteed Operating Range [Outdoor]		Cooling		°C		21 ~ 46				-10 ~ 46		

*3 Cooling: Indoor 27°C D.B./19°C W.B.
Outdoor 35°C D.B./24°C W.B.