

## ENERGY DATA

CODE 16008

### CA 100 V0 D

In-line centrifugal fans in self-extinguishing plastic



| ATTRIBUTO                                                                 | VALORE ATTRIBUTO        |
|---------------------------------------------------------------------------|-------------------------|
| Supplier's name or trade mark                                             | Vortice                 |
| Declared type                                                             | UVNR-U                  |
| Type of drive                                                             | a velocità multiple: VM |
| Type of heat recovery system HRS                                          | nessuno                 |
| AEC annual electric energy consumption (kWh of primary energy/y)          | 747,54                  |
| Thermal efficiency of heat recovery (%)                                   | NA                      |
| Nominal NRVU airflow (m3/s)                                               | 0,05528                 |
| Effective electric power input [kW]                                       | 0,048                   |
| Face velocity at nominal flowrate (m/s)                                   | 7,03819                 |
| Nominal external pressure (Pa)                                            | 32                      |
| Internal pressure drop of ventilation components (Pa)                     | 200                     |
| Internal pressure drop of non-ventilation components (Pa)                 | 0                       |
| Fan static efficiency according to Regulation (EU) No 327/2011 (%)        | 26,7                    |
| Declared maximum internal leakage rate of the ventilation unit casing (%) | NA                      |
| Declared maximum external leakage rate of the ventilation unit casing (%) | NA                      |
| Filter energy performance or classification                               | NA                      |
| Description of visual filter warning                                      | NA                      |
| Casing sound power level (LWA) [dB(A)]                                    | 53,3                    |