

Technical Data Sheet

CODE 17148

LINEO 200 Q

Mixed flow extractor fans



Certifications




CB TEST CERTIFICATE

Technical and performance data

Frequency (Hz)	50	Breakout sound pressure at 3m at Min speed Lp [dB (A)]	26,6
Insulation class	II°	Max airflow at Max speed (l/s)	263,9
IP	44	Max airflow at Max speed (m³/h)	950
Max absorbed current at Max speed (A)	0,37	Max pressure at Max speed (mmH2O)	29
Max absorbed current at Min speed (A)	0,22	Max pressure at Max speed (Pa)	284,5
Max absorbed power at Max speed (W)	75	Max RPM	2740
Max ambient temperature for continuous operation (°C)	60	Min RPM	1780
Nominal diameter (mm)	200	Potenza sonora at supply side at Min speed LWA [dB (A)]	59,5
Power absorbed at 1st speed (W)	45	Pressure at 1st speed (mmH2O)	13
Voltage (V)	220-240	Pressure at 1st speed (Pa)	127,5
Weight (Kg)	4,3	Sound power at extract side at Max speed LWA [dB (A)]	68,0
Airflow at 1st speed (l/s)	194,4	Sound power at extract side at Min speed LWA [dB (A)]	61,9
Airflow at 1st speed (m³/h)	700	Sound power at supply side at Max speed LWA [dB (A)]	68,3
Breakout sound power LWA at Max speed [dB (A)]	57,4	Sound pressure at extract side at 3m at Max speed Lp [dB (A)]	50,4
Breakout sound power LWA at Min speed [dB (A)]	47,1	Sound pressure at extract side at 3m at Min speed Lp [dB (A)]	44,4
Breakout sound pressure at 3m at Max speed Lp [dB (A)]	36,9	Sound pressure at suply side at 3m at Max speed Lp [dB (A)]	50,7
		Sound pressure at suply side at 3m at Min speed Lp [dB (A)]	42,0

Dimensions



Size A (mm)	234,5
Size B (mm)	266
Size C (mm)	300
Size D (mm)	196
Size E (mm)	125,5
Size F (mm)	235
Size G (mm)	140
Size H (mm)	100
Size L (mm)	94
Size M (mm)	5,5

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com

Technical Data Sheet

CODE 17148

LINEO 200 Q

Mixed flow extractor fans




Description

- Enclosures made of fire resistant plastic resin, E2 class, according with ISO EN 11925-2: 2010, in areas close to motor and electrical components.
- Nominal diameter 200 mm.
- Induction motor, thermally protected, with shaft mounted on ball

- bearing supports, coupled with a centrifugal impeller.
- High water resistance: IPX5 (if installed in a duct).
- Speed adjustable through Vortice speed devices.

Curves



Accessories



LINEO-G 200

Code 22705



DUO

Code 22914



LINEO-SF 500

Code 22593



IREM D

Code 12867



C TEMP

Code 12992



C SMOKE

Code 12993



C HCS

Code 12994



C PIR

Code 12998



C TIMER

Code 12999



IN-LINE-S 200

Code 22566



LINEO-C 200

Code 22588

**LINEO-PF 200**

Code 22582

**C 1.5
(COMANDO EL.
1.5 A)**

Code 12966

**KIT SCB
(TRASF.E.C.)**

Code 22481

PER INFORMAZIONI / FOR INFORMATION**ITALY**

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com**UNITED KINGDOM & REP. OF****IRELAND**

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk**OTHER COUNTRIES**

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com