

## ENERGY DATA

CODE 11282

# VORT HRI 350 FLAT

Ceiling-mounting residencial heat recovery units



| ATTRIBUTO                                                                                       | VALORE ATTRIBUTO         |
|-------------------------------------------------------------------------------------------------|--------------------------|
| Supplier's name or trade mark                                                                   | Vortice                  |
| Specific Energy Consumption (SEC) class in temperate climate zone                               | A                        |
| Declared type                                                                                   | UVR-B: bidirezionale     |
| Type of drive                                                                                   | velocità multiple: VM    |
| Type of heat recovery system HRS                                                                | a recupero               |
| Control factor CTRL                                                                             | 0,85                     |
| Control type                                                                                    | amb. centralizzato       |
| Specific Energy Consumption (SEC) class in temperate climate zone [kWh/m2y]                     | -38,0                    |
| Specific Energy Consumption class SEC in cold climate zone [kWh/m2y]                            | -77,0                    |
| Specific Energy Consumption class SEC in warm climate zone [kWh/m2y]                            | -13,0                    |
| Thermal efficiency of heat recovery at reference airflow [%]                                    | 90,4                     |
| Max airflow [m3/h]                                                                              | 280                      |
| Fan drive electric power input, including any motor control equipment, at maximum flow rate [W] | 165,0                    |
| Sound power LWA [dB(A)]                                                                         | 51                       |
| Reference airflow [m3/s]                                                                        | 0,0544                   |
| Reference ? pressure [Pa]                                                                       | 70                       |
| SPI [W/(m3/h)]                                                                                  | 0,35204                  |
| Max internal leakage rate [%]                                                                   | 3,2                      |
| Max external leakage rate [%]                                                                   | 5,3                      |
| Mixing rate                                                                                     | NA                       |
| Position and description of visual filter warning                                               | Vedi libretto istruzioni |
| Airflow sensitivity to pressure variations at + 20 Pa and – 20 Pa                               | NA                       |
| Indoor/outdoor air tightness [m3/h]                                                             | NA                       |
| Annual electricity consumption (AEC) [kWh electricity/y]                                        | 364                      |
| AHS temperate annual energy saved [kWh primary energy/y]                                        | 4641                     |
| AHS cold annual energy saved [kWh primary energy/y]                                             | 9078                     |
| AHS warm annual energy saved [kWh primary energy/y]                                             | 2098                     |