

Header.jsx



```
function Header() {  
  return ( // A new Header Component  
    <header>  
      <div className="container">  
        <h2>Feedback UI</h2>  
      </div>  
    </header>  
  );  
}  
  
export default Header;
```

App.Js



```
import Header from "../components/Header";

function App() {
  return (
    <>
      <Header />
      <div className="container">
        <h1>My App</h1>
      </div>
    </>
  );
}

export default App;
```

Feedback UI

My App

---on above Feedback UI comes from Header Component, MyApp comes from App.JS

Header.Jsx

```
function Header(props) { // We added props as param to our function
  // We can also use Header({text}) for add param to our function
  return (
    <header>
      <div className="container">
        <h2>{props.text}</h2>    / // We added text props for our page(Comes from App.JS)
        // Like above we can use just {text} like above.
        // But we have to use same syntax (props) and {props.text} or ({text}) and {text} ==
      </div>
    </header>
  );
}

export default Header;
```

App.JS

```
import Header from "../components/Header";

function App() {
  return (
    <>
      <Header text="Hello World" /> // That text is a props for Header Component. Used the code block
      above.
      <div className="container">
        <h1>My App</h1>
      </div>
    </>
  );
}

export default App;
```

After that change, here it is! our new page.

Hello World

My App

```

Header.JSX
import PropTypes from "prop-types";

function Header({ text }) {
  return (
    <header>
      <div className="container">
        <h2>{text}</h2>
      </div>
    </header>
  );
}
// If we didn't pass a prop to our Header component at App.js we can set default text string with
// defaultProps

Header.defaultProps = {
  text: "Feedback UI",
};

//We can set the propTypes like at below, we can set string, boolean, int,etc.
// also we can add isRequired method.

Header.propTypes = {
  text : PropTypes.string
}

export default Header;

App.js

import Header from "../components/Header";

function App() {
  return (
    <>
      <Header />
      <div className="container">
        <h1>My App</h1>
      </div>
    </>
  );
}

export default App;

```

Feedback UI

My App

