WhyCode

Why is this code like this? Ask its own history.

TEAM FORTEC · HACKFRONT INDIA 2026 · AI AND DEVELOPER TOOLS (T-1)

Ronit Shrimankar (lead) · Anshul Kamthe · Udita Singh
Built on django/django

The problem

- Codebases accumulate **decisions nobody can explain** any more
- A new developer reads an odd function and **guesses** why it exists
- A **wrong guess breaks something** the original author fixed on purpose
- The reasons live **scattered** across commits, pull requests, and tickets — never in one place, never linked to the code they explain

The solution: WhyCode

Ingest a public repo's history into a **graph**, then ask it plain-language *why* questions.

- **Ingest** — commits, PRs, and tickets into one connected store
- **Ask** — get a **cited evidence chain** and a confidence score
- **Refuse** — when the graph holds **no evidence**, it refuses instead of inventing an answer

> No invented answers, ever. The refusal is a feature, not a gap.

How it works

1. **Ingest** — GitHub API via `gh` CLI (commits, PRs) **plus Trac tickets**, since Django uses Trac, not GitHub Issues
2. **Graph** — entities: commit, PR, ticket, file, person · edges: authored, fixes, references, touches, supersedes
3. **Ask** — match the question, walk the evidence chain, flag superseded decisions, refuse when evidence is absent
4. **Runs anywhere** — the bundled SQLite database needs **no credentials, no paid APIs**

Demo: a real answer from Django's history

```
$ python -m whycode.cli --question \
    "Why does ignore_warnings match substrings by default?"

refused: false   confidence: 0.99

Best match: Fixed #37089 — Made ignore_warnings()
match substrings by default. (commit)

Evidence:
→ fixes      Trac ticket #37089
→ authored by HelmiDev03
```

Demo: the template-tags option

```
$ python -m whycode.cli --question \
    "Why is there a transitional option to disable
     multiline template tags?"

refused: false   confidence: 0.86

Best match: Refs #35899 — Added allow_multiline_tags
transitional template option. (commit)

Evidence:
→ references Trac ticket #35899
→ authored by boxed
```

The refusal, honestly demonstrated

```
$ python -m whycode.cli --question \
    "Why does Django use a microservices architecture?"

refused: true   confidence: 0.0
```

> “No evidence in the graph answers this. Refusing to invent an answer.”

An earlier version answered this from an unrelated docs commit. The **absent-term rule plus a regression test** fixed that for good.

Engineering: runnable, tested, no magic

Graph	200 commits · 100 PRs · 100 Trac tickets · 161 files · 90 people · **630 edges**
Stack	Python standard library only · SQLite graph · `gh` CLI
Tests	**10/10** automated, including refusal and supersession cases
Demo	Bundled database — runs with **zero credentials**

WhyCode — by FORTEC

Repo: github.com/eres0045/hackfront-fortec

Demo:

```
python -m whycode.cli --db data/whycode.db --question "Why ...?"
```

Built during the hackFront league timeline, from Django's real, public history.

Questions welcome.