

Social Network

Homework 2



Full Name:

Erfan Shahabi

Student ID:

810103166

Course:

Social Networks

Submission Date:

16-Feb-2025

Github Link:

https://github.com/erfanshababi/Social-Networks-Fall-2025/tree/main/SN_HW2_810103166

Table of Contents

List of Figures.....	3
List of Tables.....	3
1. <i>Theoretical Framework</i>	4
1.1. Identifying Cell Structure	4
Part a:	4
Part b:	5
Part c:	6
1.2. Power and Control in Networks.....	7
Part a:	7
Part b:	8
Part c:	9
3.1. Modularity and Partition Quality	12
Part a:	12
Part b:	14
Part c:	15
2. Practical Implementation	17
1.2. Givan Newman Algorithm	17
Part a:	17
Part b:	18
Part c:	19
2.2. Operation "Rapid Detection" - Algorithm Comparison	21
Part a:	22
Part b:	23
Part c:	25
3.2. Operation "Dormant Cell" Detection	28
Part a:	28
Part b:	29
Part c:	31

List of Figures

Figure 1	4
Figure 2	17
Figure 3	22
Figure 4	28

List of Tables

Table 1	6
Table 2	22

1. Theoretical Framework

1.1. Identifying Cell Structure

Part a:




Figure 1

- i. Find all cliques of size 3 or larger

A clique is a complete subgraph where every node is connected to every other node.

Cell A Analysis:

- Nodes: {1, 2, 3, 4}
- Edges: (1, 2), (1, 3), (1, 4), (2, 3), (2, 4), (3, 4)
- All 6 possible edges exist => complete graph K_4
- Clique: {1, 2, 3, 4} (size 4)

Cell B Analysis:

- Nodes: {5, 6, 7, 8}
- Edges: (5, 6), (5, 7), (5, 8), (6, 7), (6, 8), (7, 8)
- All 6 possible edges exist => Complete graph K_4
- Clique: {5, 6, 7, 8} (size 4)

Cell C Analysis:

- Nodes: {9, 10, 11, 12}
- Edges: (9, 10), (9, 11), (9, 12), (10, 11), (10, 12), (11, 12)
- All 6 possible edges exist => complete graph K_4
- Clique: {9, 10, 11, 12} (size 4)

All Cliques (size ≥ 3):

Size 4: {1, 2, 3, 4}, {5, 6, 7, 8}, {9, 10, 11, 12}

Size 3: All possible triangles within each K_4

Cell A: {1,2,3}, {1,2,4}, {1,3,4}, {2,3,4} $\rightarrow$ 4 triangles

Cell B: {5,6,7}, {5,6,8}, {5,7,8}, {6,7,8} $\rightarrow$ 4 triangles

Cell C: {9,10,11}, {9,10,12}, {9,11,12}, {10,11,12} → 4 triangles

Total: 3 maximal 4-cliques + 12 3-cliques

ii. Which cell is more cohesive?

All equally cohesive. Each cell is complete K_4 with density = 1.0.

Security implications:

- Maximum redundancy (6 channels for 4 agents)
- Optimal information spread (diameter = 1)
- No compartmentalization (one capture → 4 exposed)
- Graceful degradation (remove 1 node → triangle remains)

iii. If edge (2,4) removed?

Cliques destroyed:

{1,2,3,4} (4-clique)

{1,2,4}, {2,3,4} (2 triangles)

Impact:

Max clique: 4 → 3

Density: 1.0 → 0.833

Cell A now weaker than B & C

Agents 2-4 must route via 1 or 3

Part b:

i. All 2-cliques

1. {1,2,3,4} (Cell A)
2. {5,6,7,8} (Cell B)
3. {9,10,11,12} (Cell C)
4. {1,2,3,4,5} (A + bridge)
5. {4,5,6,7,8} (bridge + B)
6. {5,6,7,8,9} (B + bridge)
7. {8,9,10,11,12} (bridge + C)

ii. Which are 2-clans?

All 7 are 2-clans (internal diameter ≤ 2).

iii. Most realistic for spy cells?

2-clan is most realistic.

Table 1

Feature	Clique	2-Clan
Models Cutouts	No	Yes
Compartmentalization	No	Yes
Realistic Comms	No Direct only	Yes Via intermediaries

Reasoning: 2-clan allows communication via one intermediary (≤ 2 hops) while maintaining compartmentalization within trusted subgraph.

Part c:

i. Identify cores

Node degrees:

- Nodes {1,2,3,6,7,10,11,12}: degree = 3
- Nodes {4,5,8,9}: degree = 4 (bridges)

Cores:

- 2-core: All 12 nodes
- 3-core: All 12 nodes (everyone has degree ≥ 3)
- 4-core: Empty (after removing degree-3 nodes, bridges drop below 4)

ii. Spy 4 core membership?

- In 2-core yes
- In 3-core yes
- In 4-core No

Centrality: K-core doesn't differentiate (everyone in 3-core). True power comes from bridge position and degree = 4.

iii. Clique vs k-core for finding central core?

For this network: Neither works well.

- Clique: Identifies 3 cells but NP-complete
- K-core: Everyone in same core (no hierarchy)

Better approach: Community detection + degree analysis

For general networks: K-core more practical ($O(m)$ vs NP-complete, robust to noise).

1.2. Power and Control in Networks

Part a:

i. Calculate embeddedness of each edge

Embeddedness(u,v) = # common neighbors of u and v

Cell A edges:

(1,2): Common = {3,4} $\rightarrow$ embeddedness = 2

(1,3): Common = {2,4} $\rightarrow$ embeddedness = 2

(1,4): Common = {2,3} $\rightarrow$ embeddedness = 2

(2,3): Common = {1,4} $\rightarrow$ embeddedness = 2

(2,4): Common = {1,3} $\rightarrow$ embeddedness = 2

(3,4): Common = {1,2} $\rightarrow$ embeddedness = 2

Cell B edges: All have embeddedness = 2 (same K_4 structure)

Cell C edges: All have embeddedness = 2

Bridge edges:

(4,5): Common neighbors = $\emptyset \rightarrow$ embeddedness = 0

(8,9): Common neighbors = $\emptyset \rightarrow$ embeddedness = 0

ii. Identify all local bridges

Local bridge = edge with embeddedness = 0

Local bridges: (4,5) and (8,9)

These connect different cells with no mutual connections.

iii. Power Index for spies 4 and 8

Design Power Index:

Power Index = (# local bridges controlled) $\times$ 10 + (1 / (avg embeddedness + 1)) $\times$ 5
+ (degree within cell) $\times$ 2

Spy 4 analysis:

Local bridges controlled: 1 (edge 4-5)

Avg embeddedness of bridges: 0 $\rightarrow$ score = 5

Degree within Cell A: 3 connections {1,2,3}

Power Index = $1 \times 10 + 5 + 3 \times 2 = 21$

Spy 8 analysis:

Local bridges controlled: 1 (edge 8-9)

Avg embeddedness: 0 → score = 5

Degree within Cell B: 3 connections {5,6,7}

Power Index = $1 \times 10 + 5 + 3 \times 2 = 21$

Result: Spies 4 and 8 have EQUAL power (by symmetry).

Both are critical bridge nodes connecting cells.

Part b:

i. Why do structural holes create power?

Mechanisms:

1. Information brokerage: Bridge nodes access non-redundant information from multiple clusters
2. Control: They control information flow between groups
3. Negotiation advantage: Can play groups against each other
4. Arbitrage: Exploit differences between groups (ideas, resources, norms)

In dense clusters: Everyone has same information (redundant ties). No brokerage opportunity.

ii. Who has greatest access to structural holes?

Spies with structural hole access: 4, 5, 8, 9 (bridge nodes)

Degree of access:

- Spies 4 & 5: Span hole between Cells A-B
- Spies 8 & 9: Span hole between Cells B-C

Greatest access: All 4 bridge nodes equal (each spans one structural hole).

Operational advantage:

- See information from 2 cells
- Control inter-cell coordination
- Critical for network cohesion

iii. Who is more powerful?

Comparison:

High-degree spy within dense cell (e.g., spy 1):

- Degree = 3
- Embedded in Cell A
- All neighbors know each other (redundant information)
- Power: Local influence only

Bridge spy with lower internal degree (e.g., spy 4):

- Degree = 4 (higher total)
- Spans structural hole
- Accesses non-redundant information from 2 cells
- Power: Network-level control

Answer: Bridge spy (4) is more powerful.

Reasoning:

- Burt's theory: structural holes > degree
- Bridge position = information + control advantage
- Remove spy 4 → Cells A-B disconnect
- Remove spy 1 → Cell A still functions (redundancy)

Part c:

i. Which type spreads new information?

Definitions:

- Strong tie = within cell (e.g., 1-2 in Cell A)
- Weak tie = between cells (e.g., 4-5)

Answer: Weak ties are more important.

Granovetter's reasoning:

- Strong ties: Connect people in same cluster → information redundancy
- Weak ties: Connect different clusters → new, non-redundant information
- "Strength of weak ties": Bridges are critical for diffusion

In our network:

- Strong ties (within K_4): Everyone already knows same info
- Weak ties (bridges): Only path for info to cross cells

ii. Disinformation campaign strategy

KGB objective: Spread false intelligence throughout entire CIA network

Target edges: (4,5) and (8,9) - the two weak ties

Strategy:

1. Plant disinformation with spy 5 (Cell B)
2. Info reaches spy 4 via bridge (4,5) → spreads to Cell A
3. Info reaches spy 8 within Cell B → crosses to spy 9 via (8,9)
4. Spy 9 spreads to Cell C

Result: 2 weak ties enable cascade across all 3 cells.

Alternative: Targeting strong ties (e.g., 1-2) only affects local cluster.

iii. The Paradox of weak ties

Paradox explanation:

"Weak" in social terms:

- Less frequent contact
- Lower emotional intimacy
- Fewer shared activities

"Strong" for network structure:

- Only connections between clusters
- Critical for cohesion (remove → network fragments)
- Enable global information flow

What happens if all weak ties removed?

Remove (4,5) and (8,9):

- Network fragments into 3 disconnected components
- No information flow between cells

- Network diameter: ∞ (some pairs unreachable)
- Operational coordination impossible

Strong ties alone:

- Create local cohesion
- Cannot maintain global connectivity
- Network collapses into isolated clusters

Conclusion: Weak ties are structurally stronger because they're non-redundant and irreplaceable.

3.1. Modularity and Partition Quality

Part a:

i. Degree Table

Table 2

Node	Neighbors	Degree
1	{2, 3}	2
2	{1, 3, 8}	3
3	{1, 2, 4}	3
4	{3, 5, 6}	3
5	{4, 6, 7}	3
6	{4, 5, 7}	3
7	{5, 6, 8, 9}	4
8	{2, 7, 9}	3
9	{7, 8}	2

Total edges: $m = 13$

ii. Calculate modularity Q

Newman's formula:

$$Q = (1/2m) \sum [A_{ij} - (k_i \times k_j) / 2m] \delta(C_i, C_j)$$

Where:

- $m = 13$
- $A_{ij} = 1$ if edge exists, 0 otherwise
- $\delta(C_i, C_j) = 1$ if i, j in same community

Calculate for each community:

Community A: {1,2,3}

Pairs in A:

- (1,2): $A_{12} - k_1k_2/2m = 1 - (2 \times 3)/26 = 1 - 6/26 = 20/26$
- (1,3): $A_{13} - k_1k_3/2m = 1 - (2 \times 3)/26 = 1 - 6/26 = 20/26$
- (2,3): $A_{23} - k_2k_3/2m = 1 - (3 \times 3)/26 = 1 - 9/26 = 17/26$

Sum for A = $(20 + 20 + 17)/26 = 57/26$

Community B: {4,5,6}

Pairs in B:

- (4,5): $1 - (3 \times 3)/26 = 17/26$
- (4,6): $1 - (3 \times 3)/26 = 17/26$
- (5,6): $1 - (3 \times 3)/26 = 17/26$

Sum for B = $(17 + 17 + 17)/26 = 51/26$

Community C: {7,8,9}

Pairs in C:

- (7,8): $1 - (4 \times 3)/26 = 1 - 12/26 = 14/26$
- (7,9): $1 - (4 \times 2)/26 = 1 - 8/26 = 18/26$
- (8,9): $1 - (3 \times 2)/26 = 1 - 6/26 = 20/26$

Sum for C = $(14 + 18 + 20)/26 = 52/26$

Total modularity:

$Q = (1/2m) \times (\text{Sum A} + \text{Sum B} + \text{Sum C})$
 $Q = (1/26) \times (57/26 + 51/26 + 52/26)$
 $Q = (1/26) \times (160/26)$
 $Q = 160/676$
 $Q \approx 0.237$

iii. Interpret the result

$Q = 0.237$

Interpretation:

- Q range: -0.5 to +1.0
- $Q > 0.3$: Generally indicates good community structure
- $Q = 0.237$: Moderate community structure

Meaning:

- Below the "good" threshold (0.3)
- Communities exist but with significant inter-community edges
- 4 out of 13 edges cross communities (31%)
- Partition could be improved

Part b:

i. Calculate ΔQ for both options

Current state before moving node 3:

For node 3:

- $k_i = 3$ (degree)
- Community A: $\Sigma_{in} = 6$ (edges within A: $3 \times 2 = 6$), $\Sigma_{tot} = 2 + 3 + 3 = 8$
- Connections: $3 \rightarrow 1$ (in A), $3 \rightarrow 2$ (in A), $3 \rightarrow 4$ (external to B)

Option 1: Move 3 from A to B

$k_{i,in}$ (edges from 3 to B) = 1 (edge 3-4)

Before move (Community A):

- $\Sigma_{in} = 6$, $\Sigma_{tot} = 8$

After adding 3 to B:

- B's $\Sigma_{in} = 6$ (current) + 0 (3 brings no internal edges to B) = 6
- B's $\Sigma_{tot} = 9$ (current) + 3 = 12

$$\Delta Q = [6+0]/26 - [12/26]^2 - [6/26 - (8/26)^2 - (3/26)^2] \Delta Q = 6/26 - 144/676 - [6/26 - 64/676 - 9/676] \Delta Q = 6/26 - 144/676 - 6/26 + 73/676 \Delta Q = -71/676 \Delta Q \approx -0.105 \text{ (worse!)}$$

ii. Which move is better?

Neither move improves modularity.

- Option 1: $\Delta Q = -0.105$
- Option 2: $\Delta Q = -0.15$

Recommendation: Keep node 3 in Community A (current partition is locally optimal).

Why moving fails:

- Node 3 has 2 edges to A, only 1 to B, 0 to C
- Strong internal connections to A
- Moving breaks existing structure

Part c:

- i. Explain resolution limit concept

Mathematical:

Modularity formula has implicit resolution scale $\approx \sqrt{m}$.

Communities smaller than this scale cannot be detected because:

- Expected random edges $\propto (k_i \times k_j)/2m$
- For small communities: expected random > actual internal edges
- Modularity optimization merges small communities

Operational:

In large networks, small cells (3-4 nodes) get merged into larger communities even if they're structurally distinct.

- ii. Why can't it detect small communities?

Formula structure problem:

$$Q = \sum [\text{actual_edges} - \text{expected_random}]$$

For small community (k nodes):

- Actual internal edges: $\approx k^2/2$
- Expected random: $\propto k^2 \times m_{\text{total}}$
- When network large: expected > actual $\rightarrow$ negative contribution
- Algorithm merges to maximize Q

Example:

- Network: 1000 nodes
- Small cell: 3 nodes with 3 edges (triangle)
- Expected random edges $\approx (3 \times 3)/(2 \times 1000) \times \text{total edges}$
- If total edges ≈ 5000 : expected $\approx 22.5 \gg 3$ actual

- Modularity penalizes this partition

iii. Applied scenario: Dormant cell detection

Scenario:

- 2-agent dormant cell
- Single link to main network

Will modularity detect it? NO.

Reasons:

1. Too small: 2 nodes < resolution limit
2. Expected edges: $(k_1 \times k_2) / 2m$ likely > 1 actual edge
3. Optimization: Will merge with larger community to maximize Q

Example calculation:

Dormant cell: nodes {A, B}, 1 internal edge, 1 bridge

- Actual internal: 1
- Expected: $(2 \times 2) / 2m = 2/m$
- If $m > 2$: expected > actual $\rightarrow$ negative Q contribution
- Gets absorbed into neighboring community

2. Practical Implementation

1.2. Givan Newman Algorithm

Part a:

OPERATION: CHAIN BREAKER

Target Network: Zachary's Karate Club

Nodes: 34

Edges: 78

OPERATION RESULTS:

- Total edges removed: 11
- Maximum Modularity: 0.3600
- Optimal step: 11
- Critical Edge: (2, 13)
- Final community sizes: [15, 19]
- Accuracy vs Ground Truth: 94.12%




Figure 2

Part b:

Modularity Progression Analysis

At which step did modularity reach its maximum value?

The maximum modularity was achieved at step 11 with a value of 0.3600.

Is maximum modularity achieved when the network first splits into 2 components?

Yes, the maximum modularity occurred exactly when the network first fragmented into 2 connected components. This is shown in the Network Fragmentation plot where the number of components jumps from 1 to 2 at step 11, coinciding with the peak in the Modularity Progression plot.

Why does modularity eventually decrease after reaching the optimum?

After reaching the optimum at step 11, modularity would decrease because:

1. Further edge removals fragment the communities unnecessarily
2. Creating smaller isolated components that do not reflect meaningful community structure
3. The network becomes over-fragmented, with many small disconnected pieces
4. This reduces the quality metric (modularity) as the partition no longer represents natural community boundaries

Critical Edge Analysis

Which edge was the first to fragment the network?

Edge (2, 13) was the first edge to fragment the network into two components.

What special characteristics does this critical link possess?

Degree of connected nodes:

- Node 2 has relatively high degree within its community
- Node 13 connects to multiple members of the other community

Edge betweenness value:

- This edge had the highest betweenness centrality among all edges at the time of removal
- As shown in the "Top 10 Removed Edges" chart, edge 10 (which corresponds to this critical edge) has the highest betweenness value around 0.25

Position in network structure:

- Serves as the primary bridge between two densely connected clusters
- Acts as a bottleneck for information flow between the two factions
- Located at the structural boundary between communities

Was this edge actually connecting the two real factions?

Yes, examining the Ground Truth Labels visualization shows that node 2 (red faction - Mr.

Hi) and node 13 (blue faction - Officer) belong to different actual factions. This edge was indeed the critical link connecting the two real factions in the original karate club split.

Ground Truth Comparison

What accuracy was achieved?

The algorithm achieved 94.12% accuracy compared to known faction membership.

Which agents were misclassified?

According to the Confusion Matrix:

- 2 nodes from faction 0 (Mr. Hi) were misclassified as faction 1
- 0 nodes from faction 1 (Officer) were misclassified
- Total misclassifications: 2 out of 34 nodes

Why were these specific agents difficult to classify?

Analysis of the misclassified nodes reveals:

1. They have strong connections to BOTH communities
2. Their edge counts to each faction are similar
3. They acted as bridge nodes in the network structure
4. Based solely on structural properties, they appear equally connected to both groups
5. Their local network structure shows mixed loyalty patterns
6. These nodes likely maintained friendships across both factions even during the split

Part c:

Operation Summary

Total number of communication links severed:

11 edges were removed before achieving network fragmentation into 2 components.

Identification of the critical communication channel:

Edge (2, 13) served as the critical communication channel. This edge:

- Had the highest betweenness centrality
- Connected the two main factions
- Was the structural bottleneck between communities
- Its removal immediately fragmented the network

Scalability Analysis

Time complexity: $O(m^2n)$

Where:

- m = number of edges
- n = number of nodes

Breakdown:

- Edge betweenness calculation: $O(mn)$
- Must recalculate after each edge removal
- Remove approximately m edges total

- Total: $O(m) \times O(mn) = O(m^2n)$

Is this algorithm viable for large-scale networks (>1000 nodes)?

NO, this algorithm is NOT viable for large-scale networks because:

- For a network with 1000 nodes and ~5000 edges: $(5000)^2 \times 1000 = 25$ billion operations
- Runtime would extend to hours or days
- Memory requirements grow substantially
- Becomes computationally prohibitive

Computational bottlenecks and limitations:

1. Edge betweenness recalculation is expensive ($O(mn)$ per iteration)
2. Must store betweenness values for all edges
3. Graph updates after each removal require memory operations
4. No parallelization opportunities in sequential edge removal
5. Quadratic growth in edge count makes it impractical for dense networks

Operational Recommendation

Would you recommend this method for rapid intelligence operations?

NO, this method is NOT recommended for rapid intelligence operations.

Trade-offs between accuracy and speed:

Advantages:

- High accuracy (94.12% in our test)
- Identifies critical edges effectively
- Provides interpretable results

Disadvantages:

- Very slow computational speed
- Does not scale to large networks
- Time complexity $O(m^2n)$ is prohibitive

Alternative approaches for time-critical scenarios:

1. Louvain Algorithm:

- Fast: $O(n \log n)$ complexity
- Good accuracy: ~0.56 modularity
- Best balance of speed and quality
- Recommended for most operational scenarios

2. Label Propagation:

- Ultra-fast: $O(m+n)$ complexity
- Acceptable accuracy: ~0.52 modularity
- Use when speed is absolutely critical
- Good for networks >10,000 nodes

3. Greedy Modularity:

- Moderate speed: $O(mn)$ complexity
- Deterministic results
- Use when reproducibility required

2.2. Operation "Rapid Detection" - Algorithm Comparison

Part a:

OPERATION: RAPID DETECTION

Target Network: Les Miserables

Nodes: 77

Edges: 254

Density: 0.0868

Algorithm Comparison Table

Table 3

Algorithm	Time(s)	Std Time	#Comm	Modularity	Std Mod	Largest	Smallest
Louvain	0.0028	0.0008	6.0	0.5658	0.0005	24.0	6.0
Label Propagation	0.0019	0.0012	5.0	0.5219	0.0154	31.2	6.4
Greedy Modularity	0.0049	0.0004	5.0	0.5006	0.0000	26.0	6.0

BEST ALGORITHM: Louvain

Modularity: 0.5658 (± 0.0005)

Time: 0.0028s (± 0.0008 s)

Communities: 6.0




Figure 3

Part b:

Speed Analysis

Which algorithm executed fastest?

Label Propagation was the fastest with average time of 0.0019 seconds, followed by Louvain (0.0028s) and Greedy Modularity (0.0049s).

Explain based on computational complexity:

- Label Propagation: $O(m+n)$ - linear in edges and nodes
- Louvain: $O(n \log n)$ - logarithmic scaling
- Greedy Modularity: $O(mn)$ - quadratic scaling

The speed ranking directly matches theoretical complexity predictions.

Does empirical runtime match theoretical complexity?

YES, perfectly:

- Label Propagation is 1.47× faster than Louvain
- Label Propagation is 2.58× faster than Greedy
- Louvain is 1.75× faster than Greedy

These ratios match the expected complexity differences for a network of this size.

Which algorithm achieved highest modularity?

Louvain achieved the highest modularity of 0.5658, demonstrating superior community detection quality.

Is there a clear speed-quality trade-off?

YES, there is a clear inverse relationship:

- Fastest (Label Prop): 0.5219 modularity
- Middle (Louvain): 0.5658 modularity (BEST BALANCE)
- Slowest (Greedy): 0.5006 modularity

Interestingly, Louvain breaks the expected trade-off pattern by achieving both good speed AND the highest quality. This is why Louvain is the recommended algorithm for most applications.

Do all algorithms find similar number of communities?

Almost - they found 5-6 communities:

- Louvain: 6 communities
- Label Propagation: 5 communities
- Greedy: 5 communities

This indicates consistent detection of the underlying community structure across different methodologies.

Determinism Analysis

Compare standard deviation of modularity:

- Louvain: std = 0.0005 (very consistent)
- Label Propagation: std = 0.0154 (30× more variable)
- Greedy: std = 0.0000 (perfectly deterministic)

Why does Label Propagation show higher variance?

Label Propagation is non-deterministic because:

1. Random node processing order in each iteration
2. Random tie-breaking when multiple labels have equal frequency
3. Different random seeds produce different community structures
4. Can converge to different local optima

Is non-determinism a bug or feature?

FEATURE - Non-determinism provides advantages:

Advantages:

- Explores different valid community structures
- Can escape poor local optima
- Running multiple times gives ensemble of solutions
- Reveals network ambiguity (if high variance)

Disadvantages:

- Results not reproducible without fixed seed
- Requires multiple runs for stable results
- Higher variance means less reliable single-run performance
- Difficult to compare results across different runs

Recommendation

Which algorithm would you deploy for operational use?

LOUVAIN is recommended for most operational scenarios.

When should each algorithm be used?

Louvain Algorithm:

- Default choice for most applications
- Best balance of speed (0.0028s) and quality (0.5658)
- Network size: Up to 100,000 nodes
- Use when: You need reliable, fast results

Label Propagation:

- When speed is absolutely critical
- Network size: >10,000 nodes
- Acceptable to sacrifice some accuracy
- Use when: Processing very large networks in real-time

Greedy Modularity:

- When deterministic results required
- Need reproducible partitions
- Network size: Small to medium (<10,000 nodes)
- Use when: Reproducibility more important than speed

Part c:

Bridge Character Analysis

From the visualizations, the network analysis revealed:

Bridge Statistics:

- Total bridges identified: 17 characters
- Total communities: 6
- Largest community: 22 nodes
- Inter-community edges: 60
- Intra-community edges: 194
- Ratio: 3.23

Key bridge characters connecting 3+ communities:

Based on the "Bridge Nodes Highlighted" visualization (shown in red), the main bridges include central characters who appear in multiple storylines.

Research on their roles in the novel:

1. Jean Valjean: The protagonist who moves between multiple social circles - from criminal underworld to respectable society to revolutionary students
2. Javert: Police inspector who connects law enforcement with criminal networks and respectable society
3. Marius: Young revolutionary who connects the student revolutionaries, his grandfather's aristocratic circle, and Valjean's protective sphere around Cosette
4. Cosette: Connects Valjean's isolated world with Marius and the young revolutionaries

Whether narrative role justifies bridge position:

YES, absolutely. The network structure perfectly mirrors narrative structure:

- Protagonists naturally move between different social groups
- Bridge characters drive plot by connecting isolated communities
- Their structural centrality reflects their narrative importance
- Without these bridges, separate storylines would never intersect

Community Leaders

Most central character in the largest community:

Based on the network analysis, the largest community contains 22 nodes. The most central character is Valjean.

Centrality metrics:

- Degree centrality: Highest in the network (connected to most characters)
- Betweenness centrality: Highest (lies on most shortest paths)
- This is visible in the network visualization where Valjean occupies the central hub position

Does this align with the story's protagonist?

YES, perfectly aligned:

- Jean Valjean IS the protagonist of Les Miserables
- The entire novel follows his journey and redemption
- Most other characters' stories intersect with his
- His structural centrality = narrative centrality

What does this tell us about narrative vs network structure?

Powerful insight: Network analysis can identify story protagonists automatically!

Findings:

1. Narrative importance translates to structural centrality
2. Main characters occupy central network positions
3. Character relationships create measurable network properties
4. Network metrics could be used to analyze story structure across literature
5. Co-occurrence networks reveal hidden narrative patterns

This demonstrates that mathematical network analysis captures fundamental aspects of storytelling and human social organization.

Network Disruption Strategy**Which characters should be targeted for removal?**

To maximally fragment the network, target characters with:

Primary targets (highest betweenness):

1. Valjean - Central hub connecting all communities
2. Javert - Bridge between law and criminal worlds
3. Marius - Connects revolutionaries to other groups
4. Cosette - Links Valjean to younger generation

Justification using network metrics:

- High betweenness centrality: Lie on many shortest paths
- Bridge positions: Connect 3+ communities (17 total bridges identified)
- Removing them isolates communities
- Creates maximum fragmentation with minimum removals

Simulation: What happens if all bridge characters removed?

Based on the network statistics:

- Current: 6 communities, 1 connected component

- After removing 17 bridges:
 - Estimated: 12-15 disconnected components
 - Each original community splits into isolated subgroups
 - Inter-community edges (60) completely removed
 - Only intra-community edges (194) remain
 - Network becomes completely fragmented

This simulation shows that just 22% of characters (17 of 77) are responsible for maintaining network cohesion. Removing these strategic nodes causes catastrophic fragmentation, demonstrating the critical importance of bridge characters in maintaining connected narratives.

3.2. Operation "Dormant Cell" Detection

Part a:

OPERATION: DORMANT CELL DETECTION

Analyzing 6 detected communities

DORMANT CELL DETECTED

Community ID: 4

Suspicion Score: 0.852/1.000

Members (6):

Bamatambois, Chenildieu, Judge, Cochepaille, Brevet, Champmathieu

Characteristics:

- Internal density: 1.000 (perfect interconnection)
- External connectivity: 0.019 (highly isolated)
- Size: 6 nodes (near optimal)
- Peripherality: 0.592 (operates at network edges)




Figure 4

Part b:

Weight Justification

Why is internal density most important?

Weight distribution:

- $w_1 = 0.35$ (Internal Density) - HIGHEST
- $w_2 = 0.35$ (External Isolation) - HIGHEST
- $w_3 = 0.15$ (Size Optimality)
- $w_4 = 0.15$ (Peripheralality)

Internal density receives highest weight because:

1. PRIMARY indicator of dormant cell behavior
2. Operational security requires complete internal trust
3. All members must communicate directly for coordination
4. Loose internal connections indicate weak operational capability
5. Historical dormant cells show near-complete internal connectivity

External isolation equally important (0.35) because:

- Compartmentalization is core security principle
- Minimal external contact reduces detection risk
- Limits exposure if other cells compromised
- Standard tradecraft for covert operations

Critical Factors Explanation

Why these four factors are critical:

1. Internal Density ($w_1=0.35$):

Critical because:

- Ensures all members can coordinate directly
- Complete graph structure = maximum operational efficiency
- No single point of failure in communication
- Indicates tight operational security
- Historical precedent: Successful dormant cells show >0.8 density

2. External Isolation ($w_2=0.35$):

Critical because:

- Compartmentalization prevents cascade failures
- Reduces surveillance detection probability
- Limits intelligence leakage
- Standard counter-intelligence tradecraft
- Low external connectivity = intentional isolation

3. Size Optimality ($w_3=0.15$):

Critical because:

- Too large: Conspicuous, hard to coordinate, higher detection risk

- Too small: Ineffective, cannot accomplish complex operations
- Optimal range: 4-10 members for most operations
- Deviations indicate non-operational groups

4. Network Peripherality (w4=0.15):

Critical because:

- Central positions attract attention and surveillance
- Peripheral operations avoid detection
- Lower visibility = longer operational lifespan
- Easier to maintain cover identities at network edges

Alternative Formulation

Alternative approach: Equal weights (0.25 each)

Formulation:

Suspicion = $0.25 \times \text{density} + 0.25 \times (1 - \text{connectivity}) + 0.25 \times \text{size_score} + 0.25 \times \text{peripherality}$

Trade-offs:

Advantages:

- Simpler, more interpretable
- No bias toward any single factor
- May catch cells that excel in size/peripherality but not density

Disadvantages:

- Reduces emphasis on MOST important factors (density and isolation)
- May generate more false positives
- Historical dormant cells prioritize density/isolation over size/location
- Less aligned with actual operational security principles

Conclusion: Current weighted formulation (0.35, 0.35, 0.15, 0.15) is superior for detecting classic dormant cells because it prioritizes the factors that truly matter for operational security.

Potential Weaknesses

What types of cells might this formula miss?

1. Very large dormant cells (>15 members):

- Size penalty reduces their suspicion score
- Real-world example: Large sleeper networks
- Mitigation: Adjust size_score formula to accept larger groups

2. Centrally positioned cells (reverse psychology):

- Operating in plain sight to avoid suspicion
- Peripherality score penalizes them

- Mitigation: Add behavioral analysis component
3. Cells with moderate external connectivity (cover operations):
- Maintain normal-looking external connections
 - Blend in with regular communities
 - Mitigation: Temporal analysis of connection patterns
4. Single-agent sleeper cells:
- Require minimum 2 members by design
 - Cannot detect solo operatives
 - Mitigation: Separate anomaly detection for isolates
5. Distributed cells (members not fully connected):
- Hub-and-spoke structure instead of complete graph
 - Lower internal density
 - Mitigation: Adjust density threshold or detect hub patterns

Part c:

Working Implementation

The implementation correctly calculated all four metrics:

Metric calculations confirmed:

- Internal Density = 1.000: All 6 members fully connected (15/15 possible edges)
- External Connectivity = 0.019: Only 8 external connections out of 426 possible
- Size = 6.000: Near average community size
- Peripherality = 0.592: Average closeness centrality = 0.408

Combined suspicion score:

$$\begin{aligned}
 \text{Suspicion} &= 0.35 \times 1.000 + 0.35 \times (1 - 0.019) + 0.15 \times \text{size_score} + 0.15 \times 0.592 \\
 &= 0.35 + 0.343 + \text{size_component} + 0.089 \\
 &= 0.852
 \end{aligned}$$

This extremely high score (0.852/1.000) indicates strong dormant cell characteristics.

Identification and Analysis

Which community has highest suspicion score?

Community ID 4 (shown in RED in the Suspicion Scores Comparison chart) has the highest suspicion score of 0.852.

All members of this "dormant cell":

1. Bamatabois - Wealthy man who assaults Fantine
2. Chenildieu - Convict and false witness
3. Judge - Presides over Champmathieu trial
4. Cochepaille - Convict and false witness

5. Brevet - Convict and false witness
6. Champmathieu - Man mistaken for Valjean

Research: What are these characters' roles in the story?

All six characters appear together in the Champmathieu trial scene (Book 7, Chapter 8-11):

- Champmathieu: Arrested as supposedly being Jean Valjean
- Brevet, Chenildieu, Cochepaille: Former convicts who falsely "identify" Champmathieu as Valjean
- Judge: Presides over the trial
- Bamatabois: Connected to the case through his earlier assault on Fantine

These characters form a self-contained episode in the novel, appearing together in courtroom scenes but rarely interacting with main plot threads outside this context.

Why does network structure flag them as suspicious?

Network analysis reveals:

1. Perfect internal density (1.000):
 - All appear in same scenes together
 - Form complete subgraph in co-occurrence network
 - Indicates isolated narrative episode
2. Extreme external isolation (0.981):
 - Minimal connections to other characters
 - Self-contained storyline
 - No integration with main plot
3. Peripheral positioning (0.592):
 - Located at network edges
 - Not central to overall narrative
 - Episode could be removed without affecting main story

Does this make narrative sense, or is it a false positive?

TRUE POSITIVE - This is actually a valid detection!

Narrative analysis confirms:

- These characters genuinely form a distinct narrative cluster
- The trial scene is a self-contained episode
- Their structural isolation reflects their narrative isolation
- They serve a specific plot function then disappear
- Classic example of an isolated subplot

The detection algorithm successfully identified a structurally and narratively isolated community. In intelligence terms, this group exhibits all characteristics of a compartmentalized cell: complete internal knowledge, minimal external exposure, and peripheral operations.