

# CS2109s - Tutorial 9

Eric Han

Nov 8, 2023

## Student Feedback on Teaching (SFT)

Your feedback is important to me; optional, but highly encouraged:



Figure 1: NUS Student Feedback on Teaching - <https://blue.nus.edu.sg/blue/>

## Student Feedback on Teaching (SFT)

NUS Student Feedback <https://blue.nus.edu.sg/blue/> 27/Oct - 24/Nov:

- Don't Mix module/grading/project feedback - **feedback only for teaching**.
- Feedback is confidential to university and anonymous to us.
- Feedback is optional but highly encouraged.
- Past student feedback improves teaching; see <https://www.eric-han.com/teaching>
  - ie. Telegram access, More interactivity.
- Your feedback is important to me, and will be used to improve my teaching.
  - Good > Positive feedback > Encouragement
    - \* Teaching Awards (nominate)
    - \* Steer my career path
  - Bad > Negative feedback (nicely pls) > Learning
    - \* Improvement
    - \* Better learning experience

## Announcements

### Important admin

- PS7 is due **11 Nov 23:59** (One more to go!!)

### PS6 Feedback

- Question 3: Task 1.3 - Observations on different model configurations
  - `polyfit(x, y, mse, 3, 1e-6, 5000)` > Not enough iterations (Still poor fit)
  - `polyfit(x, y, mse, 3, 1e6, 5000)` > Does not converge, 'overshoots'
  - `polyfit(x, y, mse, 1, 1e-3, 5000)` > Underfitting

- `polyfit(x, y, mse, 6, 1e-3, 5000) > Numerical instability`
- Question 6: Task 2.3 - Different random seeds
  - How should we compare different neural network models given your observation to ensure fairness?

## Question 1

### Question 1a [G]

$$\mathbf{x} = \begin{bmatrix} 0.50 & 0.20 & 0.10 & 0.70 \\ 0.10 & 0.60 & 0.90 & 0.50 \\ 0.00 & 0.80 & 0.20 & 0.70 \\ 0.20 & 0.40 & 0.00 & 0.40 \end{bmatrix}, \quad \mathbf{W} = \begin{bmatrix} 0.10 & 0.20 & 0.60 \\ 0.40 & 0.30 & 0.50 \\ 0.90 & 0.80 & 0.70 \end{bmatrix}$$

1. Find the cross-correlation ('convolution' as per CNN),  $\mathbf{x} \otimes \mathbf{W}$ .
2. Also, find the convolution,  $\mathbf{x} * \mathbf{W}$ .
3. What is the difference? Why are most CNNs implemented as cross-correlation?

### Recap

- How to calculate 'convolution' as per CNN?

---

### Answer

$$\mathbf{x} \otimes \mathbf{W} = \begin{bmatrix} 1.60 & 2.59 \\ 1.51 & 1.91 \end{bmatrix}$$

$$\mathbf{x} * \mathbf{W} = \begin{bmatrix} 1.37 & 2.21 \\ 1.88 & 2.61 \end{bmatrix}$$

---

### Question 1b

- Image input is  $H \times W \times C = 224 \times 224 \times 3$
- First layer is Convolutional Layer with  $C_1 = 96$  kernels of size  $11 \times 11$ , stride  $4 \times 4$  without padding

### Recap

How to calculate the output of a convolution?

...

- Output height = (Input height + padding height top + padding height bottom - kernel height) / (stride height) + 1
- Output width = (Input width + padding width right + padding width left - kernel width) / (stride width) + 1

---

### Answer

$$H_1 = \left\lfloor \frac{H - K + 2P}{S} \right\rfloor + 1 = 54$$

There are 96 filters so,  $54 \times 54 \times 96$

### Question 1c [G]

Images are often batched  $B$ .  $B$  can take values such as 8, 16, 32, 64.

- Comment on the output shape if we feed the large CNN in part (b) with a batch.
- What are the advantages of using a batch of images rather than a single image?
- [Ⓜ] Impact of large/small batch sizes and how to determine the optimal size?

...

### Answer

- $B \times H_1 \times W_1 \times C_1$
- Using a batch of images is computationally efficient and more stable in gradient descent convergence.

## Question 2 [G]

Identify the type of RNN model and the characteristics required for the task:

- Image Captioning
- Text Classification
- Language Translation

### Recap




Figure 2: Rectangle is a vector and arrows represent matrix multiply; Input - red, output - blue and green - RNN's state. Taken from <https://karpathy.github.io/2015/05/21/rnn-effectiveness/>

### Answer

- One-to-many model
  - Input: One image. Output: Multiple words as captions.
- Many-to-one model
  - Many words. Output: Which class this text belongs to.
- Many-to-many model
  - Input: Many words / code of language A. Output: Many words / code of language B.

## Question 3 [G]

- Performing sentiment analysis on Covid-19 posts on X. Explain what characteristics of RNN make it a standard model for sentiment analysis and which RNN model you want to use to tackle this problem.
- Would it be possible to perform sentiment analysis using CNN? Explain why or why not.
- Image recognition. Suppose we now want to recognize whether the image contains Chihuahua or muffin, briefly explain why CNN is good for image recognition.
- Examine RNNs for image processing, formulate one.

### Recap

- What are CNNs good at?
- What are RNNs good at?

### Answer

- RNN is the method for dealing with sequential input; Many/One RNN - Input: Sentence. Output: Sentiment(+/-).
- Sentiment analysis strongly relies on context of the whole sentence; CNN convolution need many layers to detect higher level features to capture context.
  - I like durian
  - I do not like durain

- I do not do not like durain
- c. CNNs are very good at capture spatial structure - locality, ie. pixels near to each other are useful together
  - to recognize eye and layers above to compose the features.
- d. Window as a token and we can slide it across to generate the input.
  - <https://karpathy.github.io/2015/05/21/rnn-effectiveness/>

## Question 4 [G]

Dying ReLU Problem - majority of the activations are 0 (meaning the underlying pre-activations are mostly negative), resulting in the network dying midway.




Figure 3: The Rectified Linear Unit (ReLU) (left) vs The Leaky Rectified Linear Unit (Leaky ReLU) with  $a$  as the slope when the values are negative. (right)

- How does Leaky ReLU fix this? What happens if we set  $a = 1$  in the Leaky ReLU?
- [Q] How popular is Leaky ReLU - So why don't we switch to Leaky ReLU?

## Answer

$$\text{ReLU}(x) = \max(0, x), \quad \frac{\partial \text{ReLU}(x)}{\partial x} = \begin{cases} 0, & \text{if } x < 0 \\ 1, & \text{if } x > 0 \end{cases}$$

- ReLU being stuck at 0 because the gradient is 0<sup>1</sup>.
- Leaky ReLU get around this by creating small positive gradient  $a$
- When  $a = 1$ , the activation function becomes a linear function (NN loses power)

## Bonus Qn

### Tasks

1. Implement `correlate2d(x, W)` and `convolve2d(x, W)` using `numpy`.
2. Calculate the values for question 1.
3. Compare it with `scipy.correlate2d(x, W, mode='valid')` and `scipy.convolve2d(x, W, mode='valid')`.

## Buddy Attendance Taking

Take Attendance for your buddy: <https://forms.gle/Ckkq639TNwWEx3NT6>

1. Random checks will be conducted - `python ../checks.py TGO`

<sup>1</sup>Segway to last week calculations



Figure 4: Buddy Attendance