

# CS2109s - Tutorial 5

Eric Han

Oct 11, 2023

## Annoucements

### Important admin

1. Congratulations on clearing your Midterm exams!
2. Some changes to the Tutorial EXP rubrics to better align with broader rubrics:
  1. +25 Active Discussion (Contribute to Group/Buddy Discussion)
  2. +25 Active Participation (Contribute to Class Discussion)
  3. (+25/+50) Answer a [ @ ] question, mostly correctly (only 1/2 per class)
3. PS4: Q13 Becareful with your analysis - you need to pick the step appropriately, without which anyone can proof anything!

### Question 1 [G]

Decide whether a bunny is ready to be released into the wild based on two features: **Feature A** is a bunny's cuteness score and **Feature B** is a bunny's fluffiness score.




Figure 1: Feature A/B; Ready to be released into the wild?

- a. Which *min* set of features that will perfectly classify?
- 
- b. After changing production methods, samples are collected below; *min* features?
  - c. [ @ ] How can we always find a *min* set of features, how does it relate to kernels?




Figure 2: New Production Method.

## Recap

- What is linear separability, why is it desirable?
  - How to achieve linear separability?
- 

### Answer 1a

Notice that an ellipse with major and minor axis parallel to y-axis and x-axis is sufficient to classify the data. Hence,

- $(A^2, B^2, A, B)$  minimally suffices.

For more general ellipses (or conics) you can use the more general set of features:

- $(A^2, AB, B^2, A, B)$ .




Figure 3: Centered Ellipse; If axis-parallel  $AB$  is not needed. If centered,  $A, B$  is not needed.

---

### Answer 1b

We can use just use  $A$ .

## Question 2 [G]

Logistic Regression model which has the following hypothesis, where,  $h_w(x)$  could be interpreted as a probability  $p$  assigned by the model such that  $y = 1$ . The probability of  $y = 0$  is therefore  $1 - p$ .

$$h_w(x) = \frac{1}{1 + e^{-w^T x}}$$

- Calculate the derivative of  $\log(p)$  with respect to each weight  $w_i$ .
- Calculate the derivative of  $\log(1 - p)$  with respect to each weight  $w_i$ .
- Derive  $\frac{\partial L}{\partial w_i}$ , where  $L$  is the loss function of logistic regression model.

## Recap

- What is logistic regression?
    - What is logistic? what is regression?
- 

### Answer 2a

First we write the probability  $p$  as a function of  $x$ .  $p = \frac{1}{1 + e^{-w^T x}} = \frac{1}{1 + e^{-w \cdot x}} = \frac{1}{1 + e^{-\sum_{i=1}^n w_i x_i}}$

Take the log of both sides,

$$\log(p) = \log\left(\frac{1}{1 + e^{-\sum_{i=1}^n w_i x_i}}\right) = -\log(1 + e^{-\sum_{i=1}^n w_i x_i})$$

Now we differentiate  $\log(p)$  with respect to  $w_i$

$$\begin{aligned}
\frac{\partial \log(p)}{\partial w_i} &= - \left( \frac{1}{1 + e^{\sum_{i=1}^n -w_i x_i}} \frac{\partial}{\partial w_i} (1 + e^{\sum_{i=1}^n -w_i x_i}) \right) \\
&= -p \frac{\partial}{\partial w_i} (1 + e^{\sum_{i=1}^n -w_i x_i}) \\
&= -p(-x_i) e^{\sum_{i=1}^n -w_i x_i} \\
&= \boxed{(1-p)x_i}
\end{aligned}$$


---

### Answer 2b

First we write the probability  $1-p$  as a function of  $x$ .  $1-p = 1 - \frac{1}{1+e^{-w^T x}} = \frac{e^{-w^T x}}{1+e^{-w^T x}} = \frac{1}{1+e^{w^T x}} = \frac{1}{1+e^{w \cdot x}} = \frac{1}{1+e^{\sum_{i=1}^n w_i x_i}}$

Take the log of both sides,

$$\log(1-p) = \log\left(\frac{1}{1+e^{\sum_{i=1}^n w_i x_i}}\right) = -\log(1+e^{\sum_{i=1}^n w_i x_i})$$

Now we differentiate  $\log(1-p)$  with respect to  $w_i$

$$\begin{aligned}
\frac{\partial \log(1-p)}{\partial w_i} &= - \left( \frac{1}{1 + e^{\sum_{i=1}^n w_i x_i}} \frac{\partial}{\partial w_i} (1 + e^{\sum_{i=1}^n w_i x_i}) \right) \\
&= -(1-p) \frac{\partial}{\partial w_i} (1 + e^{\sum_{i=1}^n w_i x_i}) \\
&= -(1-p)(x_i) e^{\sum_{i=1}^n w_i x_i} \\
&= -(1-p)(x_i) \left( \frac{p}{1-p} \right) \\
&= \boxed{-px_i}
\end{aligned}$$


---

### Answer 2c

$$L = -y \log(h_w(x)) - (1-y) \log(1-h_w(x))$$

First we substitute  $h_w(x)$  as  $p$ :

$$L = -y \log(p) - (1-y) \log(1-p)$$

Now we differentiate  $L$  with respect to  $w_i$ :

$$\begin{aligned}
\frac{\partial L}{\partial w_i} &= -y \frac{\partial \log(p)}{\partial w_i} - (1-y) \frac{\partial \log(1-p)}{\partial w_i} \\
&= -y(1-p)x_i - (1-y)(-px_i) \\
&= -x_i(y-p) \\
&= \boxed{x_i(h_w(x) - y)}
\end{aligned}$$

### Question 3 [G]

Which of the following evaluation metrics is the **least** appropriate when comparing a logistic regression model's output with the target label?

1. Accuracy
2. Binary Cross Entropy Loss
3. Mean Squared Error
4. AUC-ROC
5. Mean Absolute Error

[@] What is the difference between evaluation metrics vs cost functions / loss? Which would be the best for LR loss?

## Recap

1. Which methods are primarily used for classification?
  2. What are some of the key limitations of each method?
- 

## Answer 3

Metrics	Type	Formula
Accuracy	Class	$\frac{TP+TN}{TP+FP+FN+TN}$
Binary Cross Entropy Loss	Class	$-y \log(h_w(x)) - (1-y) \log(1-h_w(x))$
Mean Squared Error	Reg.	$\frac{1}{2}(y-h_w(x))^2$
Mean Absolute Error	Reg.	$\frac{1}{2}( y-h_w(x) )$
AUC-ROC	Class	Area under a ROC curve

M1 classifies better than M2:  $y = [0, 0, 1], \hat{y}_1 = [0.2, 0.4, 0.6], \hat{y}_2 = [0.1, 0.6, 0.9]$

.	MSE	MAE	BCE
M1	0.08	0.20	0.511
M2	0.063	0.133	0.376

---

Depends on the task / objective (performance/model uncertainty) and context:

- Accuracy:
    - Dataset must be close to being uniform to be meaningful
  - Binary Cross Entropy Loss:
    - Suffers from problem with being objective performance measure
    - Maybe appropriate if objective is model uncertainty comparing within LR classes
    - Designed for loss, popular and has properties to rely on:
      - \* Measure difference in 2 probability distribution
  - MAE/MSE:
    - Suffers from problem with being objective performance measure
    - Designed for regression, essentially distance measures
  - AUC-ROC:
    - Usually the most robust
    - More complicated to calculate
- 

## Question 4

Logistic Regression for Multi-Class Classification:

$$W = \begin{pmatrix} w_{cat} \\ w_{horse} \\ w_{elephant} \end{pmatrix} = \begin{pmatrix} 4.2 & -0.01 & -0.12 \\ -20 & -0.08 & 35 \\ -1250 & 0.82 & 0.9 \end{pmatrix}, \quad X = \begin{pmatrix} 1 & 4.2 & 0.4 \\ 1 & 720 & 2.4 \\ 1 & 2350 & 5.5 \end{pmatrix}$$

- a. Compute the probability of an animal belonging to a certain class and classify them.
- b. What if we want to extend the classification task to classify other animals? Can we train a new model while keeping the weights of the previous models?

## Recap

1. What is the equation for Logistic Regression?
  2. How can we compute this efficiently?
-

#### Answer 4a

$$-X \times W^T = \begin{pmatrix} -4.1100 & 6.3360 & 1246.1960 \\ 3.2880 & -6.4000 & 657.4400 \\ 19.9600 & 15.5000 & -681.9500 \end{pmatrix}, \quad P = \begin{pmatrix} 0.9839 & 0.0018 & 0.0000 \\ 0.0360 & 0.9983 & 0.0000 \\ 0.0000 & 0.0000 & 1.0000 \end{pmatrix}$$

$$Y = \begin{pmatrix} cat \\ horse \\ elephant \end{pmatrix}$$

#### Answer 4b

If the new class has distinct features then yes. Otherwise no. However, the model may still benefit from retraining.

#### Question 5

Model  $M$  outputs 1 if  $M(x)$  is greater than or equal to the threshold  $p$ , otherwise 0.




Figure 4: Model probability output and tumor size

- For the threshold  $p = 0.5$ , come up with the confusion matrix.
- For the threshold  $p = 0.5$ , find the precision, recall and F1 score.
- Based on the figure, derive the ROC curve.

---

#### Answer 5a

	Prediction 0	Prediction 1
Actual 0	10	1
Actual 1	1	8

#### Answer 5b

$$Precision = \frac{TP}{TP + FP} = \frac{8}{8 + 1} = \frac{8}{9}$$

$$Recall = \frac{TP}{TP + FN} = \frac{8}{8 + 1} = \frac{8}{9}$$

$$F1 = \frac{2 * TP}{2 * TP + FP + FN} = \frac{2 * 8}{2 * 8 + 1 + 1} = \frac{8}{9}$$

---




Figure 5: ROC curve

## Answer 5c

### Question 5d-f [G]

- Based on the ROC curve you derived, decide which threshold you want to choose among  $p = 0.2$ ,  $p = 0.5$  and  $p = 0.8$ .
- Detecting tumours, should we maximize precision or recall?
- Detect plagiarism, should we maximize precision or recall?

Maximize precision / recall = Minimize FP / FN = Minimize Type 1 / Type 2 Error.




Figure 6: Intuition

For the application, which is more severe?

- Type 2 error - Missing diagnosis of tumor when actually tumor
- Type 1 error - Wrongly diagnosis of tumor when no tumor

If regular check up > Min start treatment on healthy > Min Type 1 > Max Precision

If monitoring > Min stop cancer treatment on sick > Min Type 2 > Max Recall

## Bonus Qn

To help you further your understanding, not compulsory; Work for Snack/EXP!

### Tasks

- Implement code to solve Q3,4,5, no boilerplate code given.
  - Calculation for the Q3 illustration between MSE/MAE/BCE
  - Calculation for Q4a using `numpy` matrices
  - Calculation for Q5a,b precision and recall.

## Updated EXP Policy, From now on

EXP	Category	Comments
400	Valid MC	Valid MC must be submitted.
0	Absent	Absent w/o valid excuse
250	Silent	Attended but tutorial not attempted.

EXP	Category	Comments
300	Silent, Attempted Tutorial	Incomplete Tutorial
350	Completed Tutorial	Completed Tutorial
375	Active	Completed Tutorial w Active Discussion
400	Active	Completed Tutorial w Active Participation
450	Exceptional	Completed Tutorial w Active Participation w Bonus
500	Exceptional	Completed Tutorial w Active Participation w Bonus w Exceptional insights

## Buddy Attendance Taking

Take Attendance for your buddy: <https://forms.gle/Ckkq639TNwWEx3NT6>

1. Random checks will be conducted - `python ../checks.py` TGO



Figure 7: Buddy Attendance