

Computer Architecture

Problem Set #1

Institute of Computer Science and Engineering
National Yang Ming Chiao Tung University

This problem set is **ungraded and not collected**. We will release solutions two weeks after the problem set is released. Please stop by office hours if you have questions.

1. Compute the Clocks Per Instruction (CPI) of a machine which has an average CPI for ALU operations of 1.1, a CPI for branches/jumps of 3.0, and a hit rate of 60% in the cache. A hit in the cache takes 1 cycle pipelined and a cache miss takes 120 cycles. Assume 22% of instructions are loads, 12% are stores, 20% are branches/jumps and the balance are ALU operations.

2. You are a processor designer and have to make a decision between building a processor which executes at 1GHz and has an average CPI 1.2 and a processor which executes at 2GHz, but has a CPI of 2. Which is better to build and why?

3. For the following RISC-V code snippet, identify all of the RAW, WAW, and WAR hazards. Provide a list for each hazard. Hint: remember that you have to check more than just neighboring instructions.

```
add x1, x2, x3
sub x3, x4, x6
mul x5, x4, x7
addi x5, x5, 1
sub x6, x3, x9
andi x2, x1, x9
```

4. For each of the characteristics below, complete the table by checking the appropriate entry (Architecture or Implementation) to indicate whether each feature is most often a characteristic of a computer architecture or of a particular CPU implementation.

Characteristic	Architecture?	Implementation?
# of bits in an instruction		
# of registers visible to programmers		
# of floating-point divider units		
RISC vs. CISC		
# of instructions issued per cycle		
Clock rate of the processor		
Pipeline depth		

5. Page B-60 in H&P6, Problem B.2 a,b

6. Which of the following statements about Instruction Set Architectures (ISAs) and their design trade-offs are true?
- A. The ISA specifies the visible programmer interface, while the microarchitecture determines how these are implemented in hardware.
 - B. CPI (Cycles Per Instruction) is determined solely by the ISA definition, regardless of the chosen microarchitecture.
 - C. Amdahl's Law implies that ISA extensions targeting only a small portion of execution may have limited overall performance impact.
 - D. Technology constraints such as limited storage, tight encoding space, and the move to multi-core/manycore have historically shaped ISA design choices.
 - E. If the number of architected registers in an ISA is halved, the freed opcode encoding space could be used to expand immediate fields or introduce new instructions, at the potential cost of increased memory traffic due to fewer registers.