
PRE-FLIGHT BATTERY CONSUMPTION MODEL FOR UAV MISSIONS

Eric R. Altenburg
Computer Science
Stevens Institute of Technology
Hoboken, NJ
ealtenbu@stevens.edu

John H. Graves
Computer Science
Brown University
Providence, RI
john_graves@brown.edu

Qijun Gu
Computer Science
Texas State University
San Marcos, TX
qg11@txstate.edu

August 6, 2019

ABSTRACT

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Keywords Unmanned Aerial Vehicle · UAV · Drone · Battery · Battery Consumption · Battery Usage · Predict

1 Introduction

As unmanned aerial vehicle (UAV) technology improves, these devices become more and more integrated into society as they allow for tasks to be easily completed by a user in a route location. For example, Amazon and other distribution companies are developing methods that use these devices to deliver packages to their users in a fast and simple manner. Aside from being able to easily deliver packages, it is possible that by replacing delivery trucks all together, the total amount of emissions could be reduced which would have an overall positive impact on the environment. This technology is not limited to the aforementioned companies, instead, it is also used by archeological sites and other sports companies to conduct surveillance missions for certain dig sites where a camera might not be the best choice, or at a football game. Another use these UAVs have are with the police force as there are often situations where it is not entirely safe to send in an officer, however, by allowing that officer to remotely control a drone, it allows him and many others to be safe.

One of the many things holding UAVs back from doing such things are the simple fact that the battery usage is not easily predictable. By having the ability to know how much battery a given drone will consume can put the user at a much higher advantage as they can now determine whether or not a certain flight mission is feasible. Going back to the previous example with Amazon, their delivery drones will not always be charged to maximum capacity, therefore, if they can see how much battery a delivery will take up, then they can determine whether or not they will need to send a different drone or replace the battery. Up until now, most UAV software can only communicate to the user how much battery is remaining in real time, and while that may be enough, in some situations—like the one mentioned previously—it is important to know how much will be consumed before the UAV leaves the ground.

While there have been some attempts at creating such a model, there has not been a successful method that results in an accurate or efficient prediction. This is partially due to drones being relatively new, having only been introduced in the past few years, and as a result, not much research has been conducted. It is from this lack of literature that many have had difficulty creating a functional model. Specifically, one of the assumptions made about these drones is that the total battery energy consumption is constant from flight-to-flight [1], however, through various data samples, this is not the

case; it is variable. This and many other assumptions make up some of the shortcomings in existing literature, that if not proven correctly, can result in a considerable setback in the UAV field.

2 Related Work

Blah blah blah blah

blah blah

3 Background

Background Info

See Section 3.

3.1 Previous Research

Previous research

Equation Example:

$$\xi_{ij}(t) = P(x_t = i, x_{t+1} = j | y, v, w; \theta) = \frac{\alpha_i(t) a_{ij}^{w_t} \beta_j(t+1) b_j^{v_{t+1}}(y_{t+1})}{\sum_{i=1}^N \sum_{j=1}^N \alpha_i(t) a_{ij}^{w_t} \beta_j(t+1) b_j^{v_{t+1}}(y_{t+1})} \quad (1)$$

Paragraph The Mentioned paragraph continues onto multiple lines it is a paragraph after all. What else do I write? I don't know

4 Methods

When you have a paragraph you can also cite it. [1] and see [2] and see [3].

And for a URL, the documentation for natbib may be found at

<http://mirrors.ctan.org/macros/latex/contrib/natbib/natnotes.pdf>

Of note is the command `\citet`, which produces citations appropriate for use in inline text. For example,

```
\citet{hasselmo} investigated\dots
```

produces

Hasselmo, et al. (1995) investigated...

<https://www.ctan.org/pkg/booktabs>

4.1 Figures

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi. See Figure 1. Here is how you add footnotes. ¹ Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

¹Sample of the first footnote.




Figure 1: Sample figure caption.

Table 1: Sample table title

Part		
Name	Description	Size (μm)
Dendrite	Input terminal	~ 100
Axon	Output terminal	~ 10
Soma	Cell body	up to 10^6

4.2 Tables

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetur tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo. See awesome Table 1.

4.3 Lists

- Lorem ipsum dolor sit amet
- consectetur adipiscing elit.
- Aliquam dignissim blandit est, in dictum tortor gravida eget. In ac rutrum magna.

References

- [1] A. S. Prasetya, R. Wai, Y. Wen, and Y. Wang, "Mission-based energy consumption prediction of multirotor uav," *IEEE Access*, vol. 7, pp. 33055–33063, 2019.
- [2] Y. Chen, D. Baek, A. Bocca, A. Macii, E. Macii, and M. Poncino, "A case for a battery-aware model of drone energy consumption," pp. 1–8, 10 2018.
- [3] L. Corral, I. Fronza, N. El Ioini, and A. Ibershimi, *A Measurement Tool to Track Drones Battery Consumption During Flights*. 01 2016.