

CS112: Friday 2 October, 12:15 to 1:20

Wednesday our `append` stopped copying everything. It doubles the room when it runs out, and the debugger showed the address in the watch window changing under us as the array moved.

Today: nothing ever gives that array back. And copying a `PyList` copies the address, so two objects end up owning one block. Three functions fix both.

TIME	BEAT
12:15	Daily quiz
12:20	1. It leaks right now
12:34	2. The copy that bites
12:50	3. Our own block: the copy constructor
13:04	4. <code>operator=</code> and the rule of three
13:16	5. Close

Beat 1. It leaks right now (14 min)

Talk to your neighbor. A `PyList` goes out of scope at the end of a function. What happens to the array it asked for?

The answer comes from rebuilding what we already have, with one extra flag.

```
g++ -std=c++17 -g -fsanitize=address -o test *.cpp && ./test
```

```
SUMMARY: AddressSanitizer: 8 byte(s) leaked in 1 allocation(s).
```

Two appends, capacity 2, two ints. The growth code already freed the block of capacity 1, so exactly one allocation is left holding.

What one line fixes this, and where does it go?

```
PyList::~PyList() { delete [] myArray; myArray = nullptr; }
```

The compiler writes a destructor for you and it destroys the **members**. It destroys the pointer. It does not touch what the pointer points at.

If your class calls `new`, your class defines a destructor.

The sanitizer runs again. Clean.

Beat 2. The copy that bites (16 min)

```
PyList a;  
a.append(3);  
a.append(7);  
  
PyList b = a;           // what exactly got copied?
```

Talk to your neighbor. `b` is a new object with its own three members. What is in them?

On the board: two objects on the stack, one arrow out of each, both arrows landing on the same block.

```
free(): double free detected in tcache 2  
Aborted (core dumped)
```

Two faults from one line. `b[0] = 9` changes `a[0]`. The second destructor frees a block that is already gone, which is the crash above. Same crash as the lab, returning a list by value.

Beat 3. Our own block: the copy constructor (14 min)

What has to happen instead, for `b` to be independent?

```
PyList::PyList(const PyList &orig) {  
    mySize      = orig.mySize;  
    myCapacity  = orig.myCapacity;  
    myArray     = new Item[myCapacity]; // our own block  
    for (int i = 0; i < mySize; ++i)  
        myArray[i] = orig.myArray[i]; // copy the values  
}
```

Same moves as Wednesday's growth code: allocate, copy across, own it. Now each object has its own block.

It runs in three places, and only the first one looks like a copy:

```
PyList b = a;           // 1. written down
void show(PyList v);     // 2. passed by value
PyList makeList();       // 3. returned by value
```

Which of the three have we already written without noticing?

Beat 4. `operator=` and the rule of three (12 min)

`b = a;` on an object that already exists is not the copy constructor at all. It is assignment, and the default one copies the address the same way.

```
PyList& PyList::operator=(const PyList &rhs) {
    if (this != &rhs) {        // a = a would free its own array
        delete [] myArray;
        mySize = rhs.mySize;
        myCapacity = rhs.myCapacity;
        myArray = new Item[myCapacity];
        for (int i = 0; i < mySize; ++i)
            myArray[i] = rhs.myArray[i];
    }
    return *this;              // so that a = b = c works
}
```

The rule of three. A class that needs one of the destructor, the copy constructor or the assignment operator needs all three. All three answer the same question: who frees this block?

Beat 5. Close (4 min)

`PyList` can now be copied, assigned and destroyed without losing an array or freeing one twice.

Monday: `PyList` stops caring whether it holds ints.