

CS112: Wednesday 30 September, 12:15 to 1:20

Monday we wrote `PyList` together. A class holding `Item *myArray`, `mySize` and `myCapacity`; a constructor that sets the pointer to `nullptr`; an `append` that makes room for one more item every time it is called. It compiles, it passes its test, and every line in it is correct.

Today: the object is not the data. `myArray` holds an address, the items sit somewhere else, and that address moves every time the array grows. Once that is on the board, our `append` turns out to be doing far more work than it needs to.

PART

Daily quiz

1. What does our `append` cost?
2. Make it cost less, and ? :
3. The debugger, on our own class
4. What this unlocks

Part 1. What does our `append` cost?

Open `PyList.cpp`. Run `make test`. It passes, as expected. Nothing here is broken. Now let's think about what these operations cost.

Talk to your neighbor. Every `append` asks for a new array and copies everything across. How many item copies is that, for 100 appends?

Answers first, confirmation after. The first `append` copies nothing, the second copies 1, the third copies 2, and the hundredth copies 99. The sum goes on the board:

$$\text{copies} = \sum_{i=0}^{n-1} i = \frac{n(n-1)}{2} = \frac{100 \times 99}{2} = 4950$$

The closed form is the point, not the number: **n^2 over 2**, so ten times the appends is a hundred times the copying. Measured on our own file: **4,950 item copies and 100 allocations**.

Then the problem goes back to the room, not the answer:

Talk to your neighbor. The copying is what costs. How could we copy less often?

Whatever comes back gets costed on the board.

| Strategy | 100 appends | 1000 appends | |---| | one more slot each time |
4,950 copies | 499,500 copies | | ten more slots each time | 450 copies |
49,500 copies | | twice the room each time | 127 copies | 1,023 copies |

Ten extra slots is a real improvement and still the wrong shape: ten times the appends, a hundred times the copying. Only the doubling row barely moves.

Part 2. Make it cost less, and ? :

Live coding, starting from the condition. When does the array need to grow? `mySize == myCapacity`, from the room.

```
void PyList::append(Item it) {
    if (mySize == myCapacity) {        // full; empty is full too
        int cap;
        if (myCapacity == 0) cap = 1;
        else cap = myCapacity * 2;
        Item *bigger = new Item[cap];
        for (int i = 0; i < mySize; ++i)
            bigger[i] = myArray[i];
        delete [] myArray;
        myArray = bigger;
        myCapacity = cap;
    }
    myArray[mySize] = it;
    ++mySize;
}
```

The empty list was never a special case: it is an array with no room left, which the one condition already catches.

The four lines that choose `cap` then collapse into one:

```
int cap = (myCapacity == 0) ? 1 : myCapacity * 2;
```

Read aloud: "if this, then that, otherwise the other".

`if` is a **statement**: it *does* something. `? :` is an **expression**: it *is* a value. That is why it can sit on the right of an `=` and the `if` cannot.

Three rules: choose **between two values for one variable**, never nest them, no side effects inside. Then the trap, on screen:

```
cout << x > 0 ? "positive" : "negative";
```

```
error: no match for 'operator>' ('std::basic_ostream<char>' and 'int')
```

`<<` binds tighter, so the compiler read `(cout << x) > 0`. Parenthesise it inside any larger expression.

Monday's test runs again and still passes. After two appends the capacity is still 2, because doubling goes 0, 1, 2. **The test cannot tell the two versions apart.**

What does a passing test prove, and what does it not?

Part 3. The debugger, on our own class

Set up on `PyList` on the projector, the room following on their own machines.

1. **Breakpoint.** Gutter left of the line number, red dot, on `int cap = ...`.
2. **F5**, pick the configuration. It stops on the dot.
3. **Variables.** Expand `this`; add `myArray` to **Watch**.
4. **F10** over, **F11** into, **F5** continue.

Append nine items. Before each F5: will it stop again? Will the address change?

Monday's version stops on every append, with a new address every time. Today's stops five times: capacity 1, 2, 4, 8, 16.

Why do the stops get further apart?

The array moves, and anything holding the old address is holding a lie.

Part 4. What this unlocks

You have written the thing that makes a list a list. Everything that grows works this way: ask for more room, copy across, release the old, repoint. Python's `list` does it, and so does C++'s `vector`.

Friday: the array is still out there after the object is gone.