

CS112: Monday 28 September, 12:15 to 1:20

Friday we closed on `typedef int Item;`. One line at the top of `Pair.h`, and every method below it says `Item`, so changing what the class holds is a one-line edit instead of a hunt through two files. Before that, the whole of week 3 again: classes, `const` methods, `operator<<`.

Today: a size nobody knows until the program runs. Every array so far had a number you chose while writing the code. Today the number arrives from a file, or from the user, and no value you write in those brackets is right. `new` moves the decision to where the answer exists, and hands back an **address** rather than an array. That is the split the rest of the course is built on: the object on the stack holds an address, the data sits on the heap.

TIME	BEAT	SLIDE
12:15	Daily quiz, <code>week04d1</code>	
12:20	1. An array whose size you do not know	3
12:28	2. <code>new</code> , <code>delete</code> , and <code>nullptr</code>	4
12:40	3. Where it actually lives, measured not drawn	5
12:50	4. A class that owns an array	6
13:05	5. The index trap	
13:13	6. Tomorrow	

Typed, not shown. If the clock slips, cut beat 3. Beats 2 and 4 are the ones a05 cannot start without, and slides 5 onward are Wednesday.

Beat 1. The wall (8 min)

```
int n;
cout << "How many numbers? ";
cin >> n;

int data[n];           // this is the line to stare at
data[0] = 42;
```

It compiles, which is the surprise worth having. Then recompile in front of them:

```
$ g++ -Wall -std=c++17 -pedantic vla.cpp
warning: ISO C++ forbids variable length array 'data' [-Wvla]
```

Ask what the compiler would have to know, at compile time, to lay that variable out, and let them get to it: how big it is. `n` is not known then, and cannot be.

```
char grid[64][128];
```

 in a03, you chose that. Now a lap of telemetry has as many samples as the file turns out to have. Too small and the program breaks on the next circuit. Too large and you waste most of it every lap.

Beat 2. `new`, `delete`, and `nullptr` (12 min)

```
int n;  cin >> n;

int *data = new int[n];           // the size can be a
variable
for (int i = 0; i < n; ++i)
    data[i] = 0;

delete [] data;                  // give it back
data = nullptr;                  // and stop holding the
address
```

While typing: `new` hands back an address, which is why the variable is a pointer; **the size may be a variable**, which is the reason this week exists; `delete []` for arrays, plain `delete` for one object.

Then the part tomorrow's first TODO cannot be written without:

```
nullptr
```

 is C++ for "this pointer deliberately points at nothing", which is not the same as a pointer you never initialised. `delete[]` on `nullptr` is safe and does nothing; `delete[]` on garbage is a crash. A constructor that sets its pointer to `nullptr` has a destructor that is already correct, before you have written one.

Beat 3. Where it actually lives (10 min)

Do not draw the stack and the heap. Print them.

```
int onStack = 7;
int *heap = new int[3];
cout << "stack addr = " << (void*)&onStack << endl;
cout << "heap  addr = " << (void*)heap << endl;
```

```
stack addr = 0x7ffc09a5f334
heap  addr = 0x55f5f217f270
```

Let them count the digits. The stack holds locals, is freed at end of scope, and is sized at compile time. The heap holds whatever **new** hands you, is freed only when **you** say so, and is sized while running.

Beat 4. A class that owns an array (15 min)

Start from the header and let them dictate the members.

```
typedef int Item;

class PyList {
public:
    PyList();                // empty
    PyList(int n);           // n items, all zero
    int getSize() const;
private:
    Item *myArray;           // the ADDRESS of an array on the
    heap
    int    mySize, myCapacity;
};
```

Ask before writing the body: **what should the empty one do with the pointer?** Take the answer from them. That is beat 2 landing.

```
PyList::PyList() {
    myArray    = nullptr;
    mySize     = 0;
    myCapacity = 0;
}
```

Then the measurement that makes the design visible, and it takes 30 seconds:

```
PyList a;  PyList b(1000);
cout << sizeof(a) << " " << sizeof(b) << endl;    // 16 16
```

The object holding a thousand items is the same size as the empty one. The items are not in the object. If one sentence survives today, this

is it.

Say the capacity line here and leave it alone: two counts, not one, how many it holds and how much room the array has. Wednesday answers why.

Beat 5. The index trap (8 min)

```
Item PyList::getIndex(int i) const {
    if (i >= mySize) throw range_error("index out of range");
    return myArray[i];
}
```

Someone will ask why there is no `i < 0`. Answer by running it:

```
unsigned i = -1;
cout << i << endl;                // 4294967295
cout << (i >= mySize) << endl;    // 1, caught
```

An `unsigned` index can never be negative, which is a trap rather than a convenience. Pass `-1` and it arrives as 4294967295, so one test catches both a negative argument and a too-large one. With `-Wextra` the compiler says the `i < 0` half is always false.

The bound is `mySize`, not `myCapacity`: the array may have room the container is not using, and those slots are not theirs.

Beat 6. Tomorrow (5 min)

1. **Read `Trace.h` first.** The whole class on one page, opening with the `typedef` we ended Friday on.
2. **Run `make`, then `make test`.** It should report **1 / 36**. Both are correct: the starter compiles and almost nothing works yet.
3. **Do the TODOs in order**, running `make test` after each. **Do not skip to TODO 9**, which asks you to run something and watch what happens.

TODO 1 wants `nullptr` (beats 2, 4). TODO 2 wants `new Item[n]`, the size as a variable, and the `n == 0` branch (beats 2, 4). TODO 4 wants the unsigned bound (beat 5).