

LeadCommand: GoHighLevel Integration Helpfile

A quick setup guide for connecting a client GHL location to LeadCommand. GoHighLevel remains the CRM/backend engine; LeadCommand is the client-facing dashboard layer.

1. What You Need Before Starting

- Access to the correct GoHighLevel sub-account/location.
- Permission to create or view Private Integrations in GHL.
- LeadCommand Settings access as an admin.
- Supabase environment variables already added once for the LeadCommand app.

2. Create The GHL Private Integration

- Log into GoHighLevel and switch into the client sub-account/location.
- Open Settings, then go to Private Integrations.
- Create a private integration for LeadCommand.
- Grant read-only scopes first. LeadCommand is a dashboard, so write/edit access is not needed for the MVP test.
- Copy the private integration access token after GHL generates it.

Recommended read-only scopes for the MVP:

- Contacts / People: view or readonly
- Opportunities / Pipelines: view or readonly
- Calendars: view or readonly
- Calendar Events / Appointments: view or readonly
- Conversations: view or readonly, only if you want SMS/call history later
- Locations or Businesses: view or readonly, if needed for account information

Avoid write scopes at first, such as contacts.write, opportunities.write, calendars.write, message sending, workflow write access, or appointment creation. Add those later only for specific features.

3. Details To Enter In LeadCommand

Field	Required?	Where To Get It / What To Use
Connection Mode	Yes	Use Private Integration for the first GHL test.
Location ID	Yes	Inside the client GHL location. Often found in Settings, Business Profile, Company, or location/account details.
Private Integration Access Token	Yes	Generated inside GHL Settings > Private Integrations. Keep it private.

API Version	Yes	Use 2021-07-28.
Webhook URL	Optional	Use later for live push events. Production format: https://yourdomain.com/api/webhooks/ghl .
Webhook Secret	Optional	A strong shared secret you create and use in both GHL and LeadCommand.
Pipeline ID	Optional	Needed only if LeadCommand should read one specific GHL pipeline.
Calendar ID	Optional	Needed only if LeadCommand should sync one specific GHL calendar.

4. Save And Test In LeadCommand

- Open LeadCommand and go to Settings.
- Choose GoHighLevel and click Configure.
- Enter the client Location ID, private integration token, and API version.
- Click Save Configuration.
- Click Test Connection.
- A successful test should say: GHL connection test passed. LeadCommand can reach this location.

5. Supabase Setup Note

Supabase environment keys are added once per LeadCommand deployment, not once per client. The database schema is also run once per Supabase project. After that, each new client should be added as records inside LeadCommand and stored in Supabase.

One LeadCommand app + one Supabase project can support many clients, each with their own GHL connection details.

6. Security Rules

- Never paste private integration tokens into screenshots, public chats, GitHub, or client-facing docs.
- If a token is exposed, rotate or expire it inside GHL and save the new token in LeadCommand.
- Keep Supabase service role keys server-side only. Never expose them in frontend code.
- Start with read-only GHL scopes. Add write access only when LeadCommand needs a specific action feature.

7. Quick Troubleshooting

Message / Issue	Meaning	Fix
Configuration accepted for this session	Supabase service role key is missing or not loaded.	Add SUPABASE_SERVICE_ROLE_KEY to .env.local and restart the app.
Could not find public.integrations	The Supabase tables have not been created.	Run <code>supabase/leadcommand-supabase-setup.sql</code> in Supabase SQL Editor.
GHL connection failed	Token, Location ID, API version, or permissions may be wrong.	Check read scopes, copy the Location ID again, and test with a fresh token.
Webhook not firing locally	GHL cannot send events to localhost.	Use a public production URL or a tunnel for local testing.

Production Reminder

Before going live, use a real domain for webhooks, rotate any exposed test keys, and add client management so each client has isolated GHL credentials and dashboard data.