

Parameterized algorithms for thinness via the cluster module number

Flavia Bonomo^{1,2} Eric Brandwein^{1,*} Ignasi Sau³

¹ Universidad de Buenos Aires, Facultad de Ciencias Exactas y Naturales, Departamento de Computación, Buenos Aires, Argentina. {fbonomo,ebrandwein}@dc.uba.ar

² CONICET-Universidad de Buenos Aires. Instituto de Investigación en Ciencias de la Computación (ICC), Buenos Aires, Argentina.

³ LIRMM, Université de Montpellier, CNRS, Montpellier, France. ignasi.sau@lirmm.fr

Keywords: Thinness – Vertex cover – Cluster module number – Parameterized complexity – Graph parameters – Polynomial kernels.

In 2007, Mannino et al. defined k -thin graphs as a generalization of interval graphs, and defined the thinness of a graph to be the minimum k such that the graph is k -thin. When given a k -thin representation of a graph, several NP-complete problems can be solved in XP time parameterized by k . Thus, the problem of computing the thinness of a graph, as well as the corresponding representation, has various algorithmic applications. In this work we define a new graph parameter that we call the *cluster module number* of a graph, which generalizes twin-cover and neighborhood diversity, and can be computed in linear time. We then present a linear kernel for the problem of calculating the thinness on graphs with bounded cluster module number. As a corollary, this results in a linear kernel for THINNESS when the input graph has bounded neighborhood diversity, and exponential kernels when the input graph has bounded twin-cover or vertex cover. On the negative side, we observe that THINNESS parameterized by treewidth, pathwidth, bandwidth, (linear) mim-width, clique-width, modular-width, or the thinness itself, has no polynomial kernel assuming $\text{NP} \not\subseteq \text{coNP/poly}$.