

Project 4: Machine Language

This project introduces low-level machine language programming. You will write some programs using the Hack *assembly language*, translate them into binary code using a supplied *assembler* (a translation program) and test the resulting binary code by executing it. Normally, binary code is executed on the computer's hardware; since the Hack computer will be completed only in the next project, in this project you will execute binary code using a supplied *CPU emulator*. The CPU emulator is a computer program that executes binary code using software emulation.

Objectives

- Get a hands-on taste of low-level programming in machine language;
- Get acquainted with the Hack instruction set, before building the Hack computer in project 5;
- Get acquainted with the assembly process, before building an assembler in project 6.

Tools

Editor: The assembler of the online [Nand2Tetris IDE](#) features an editor panel (labeled “Source”) for writing and inspecting assembly programs. If you use the legacy desktop Nand2Tetris tools instead, use a plain text editor for reading and writing assembly programs.

Assembler: The supplied assembler is designed to translate Xxx.asm source files containing symbolic Hack instructions into Xxx.hack files containing binary code that can be executed by computers and emulators that implement the Hack instruction set.

CPU Emulator: The supplied CPU emulator is designed to execute code written in the Hack instruction set. During the code's execution, the emulator displays the current states of the simulated Hack computer's memory, registers, and program counter. The emulator also displays the computer's screen, and allows entering inputs using the physical keyboard of the host PC.

Executing machine language programs

Before writing assembly programs of your own, we recommend reading and executing existing programs. In particular, experiment with the following assembly programs, stored in the projects/6 folder:

Add.asm: Adds the constants 2 and 3, and puts the result in R0 (recall that Ri refers to RAM[i]).

Max.asm: Computes $\max(R0, R1)$ and puts the result in R2. Before executing, put some test values in R0 and R1.

Rect.asm: Draws a rectangle at the top left corner of the screen. The rectangle is 16 pixels wide, and R0 pixels high. Before executing, put some test value in R0.

Pong.asm: A classic single-player arcade game. A ball repeatedly bounces off the walls of the screen while the player moves a paddle using the left-arrow and right-arrow keys. Each time you successfully hit the ball, you score a point and the paddle becomes slightly smaller, making the game progressively more challenging. If you miss the ball, the game is over. To quit, press ESC.

Before starting the game, click *Enable Keyboard*. Use the speed slider to adjust the game speed, from slow motion to fast and challenging.

Background note: The Pong program was developed using tools from Part II of the Nand to Tetris course and book. Specifically, the game software was written in the high-level, Java-like *Jack* language. Organized in several Jack classes, the Pong game implementation consists of some 300 lines of high-level Jack code. This program, *along with the Jack OS*, was compiled by the Jack compiler into a single Pong.asm file containing 27,000+ machine language instructions (lines of code). This is a large file, and it may take a few seconds to load and translate, so be patient.

For each Prog.asm program mentioned above, use the Assembler and the CPU emulator, as follows:

1. Load the program (from the projects/6 folder) into the Assembler. Use the editor to read its documentation, inspect the symbolic code, and translate it into binary code.
2. In the Binary Code panel, click Load. This launches the CPU Emulator and loads the binary code into it.
3. If the program expects input, use the CPU Emulator to enter test values into the appropriate RAM locations.
4. Execute the program. Before running Pong.asm, click *Enable Keyboard*. You can also adjust the execution speed and screen size.
5. Observe the program's behavior and how its execution affects the registers, program counter, and memory.

Program execution tips

[The CPU emulator of the new online IDE](#) is self-explanatory.

If, alternatively, you use the legacy desktop CPU emulator, navigate to the folder on your PC where the Prog.asm file is located, and launch the CPU emulator by entering "CPUEmulator.sh" (Mac) or "CPUEmulator" (Windows) from the terminal / command line.

The CPU emulator has a builtin assembler: When you load an .asm file into the emulator, it translates each symbolic instruction into its binary version. In the process, all the symbolic variables and labels are translated into physical memory addresses. You can inspect the loaded code in its symbolic version (which is the default), or in its binary version (by choosing "bin" from the display format menu of the ROM panel).

Change the program execution speed by controlling the CPU emulator's speed slider. In interactive programs, like Pong, you can also change the screen size.

In the legacy desktop version of the CPU Emulator, the *animation option* is set by default to "program flow". This selection, which highlights the instruction which is currently executing, is good for debugging, but may be sluggish in other cases. In particular, when testing the Pong program and the Fill program (described below), and any program that uses the keyboard or the screen, select 'No animation' from the 'Animation' menu (meaning, no animation of code execution).

Tasks

After inspecting and executing the assembly programs mentioned above, you are ready to develop programs of your own. Write and test the following two programs:

Mult.asm (example of an arithmetic task): The inputs of this program are the values stored in R0 and R1 (RAM[0] and RAM[1]). The program computes the product $R0 * R1$ and stores the result in R2 (RAM[2]). Assume that $R0 \geq 0$, $R1 \geq 0$, and $R0 * R1 < 32768$ (your program need not test these conditions). Your code should not change the values of R0 and R1. The supplied Mult.test script and Mult.cmp compare file are designed to test your program on the CPU emulator, using some representative R0 and R1 values.

Fill.asm (example of an input/output task): This program runs an infinite loop that listens to the keyboard. When a key is pressed (any key), the program blackens the entire screen by writing "black" in every pixel. When no key is pressed, the program clears the screen by writing "white" in every pixel. You may choose to blacken and clear the screen in any spatial order (top-down, bottom-up, spiral, etc.), as long as pressing a key continuously for long enough will result in a fully blackened screen, and not pressing any key for long enough will result in a cleared screen.

The projects/4 folder contains skeletal Mult.asm and Fill.asm programs. These are the assembly programs that you have to develop. For each Xxx.asm program we also supply Xxx.tst and Xxx.cmp files, for testing the evolving programs on the CPU emulator.

Developing assembly programs

[If you are using the Nand2Tetris IDE Online](#) (the recommended option):

1. To start working on the assembly program Xxx.asm, load the Xxx.asm file into the assembler's editor (the "source" panel).
2. Write/edit the Xxx.asm file. All the changes will be saved automatically in your browser's memory. To save a copy on your local PC, click the *download* button. The current version of all the project's Xxx.asm files will be downloaded to your PC as one zip file.
3. Use the *translate* controls to translate the assembly program into binary code. Notice that the assembler creates and displays a *symbol table*. In this project there is no need to review or understand this symbol table, or the translation process (we'll do it in project 6). For now, simply translate the program; If there are syntax errors, go to step 2.
4. Click the "load" control of the "binary code" panel. This action will launch the CPU emulator, and load the binary code into it.
5. Informal testing: If the code expects to read values from RAM addresses, enter test values in these addresses; If the code expects to get inputs from the keyboard, click *enable keyboard*. Next, execute the code using the *step/run/reset* controls. If there are run-time errors, or incorrect outputs, go to step 2.
6. Formal testing: Notice that the test panel is already loaded with an Xxx.tst test script. Execute the test script. If there are run-time errors, or incorrect outputs, go to step 2.

If you are using the legacy desktop Nand2Tetris assembler follow these steps:

1. Start by launching the three tools that you will need for writing and executing assembly programs. Launch the assembler by entering “Assembler.sh” (Mac) or “Assembler” (Windows) from the terminal / command line. The assembler will be launched in a graphical window. Next, launch the CPU emulator by entering “CPUEmulator.sh” (Mac) or “CPUEmulator” (Windows) from the terminal / command line. Finally, to start working on the assembly program Xxx.asm, load the projects/4/Xxx/Xxx.asm file into a plain text editor of your choice. At this point you will have three active windows: the editor, the assembler, and the CPU emulator.
2. Write/edit the Xxx.asm file in the editor, and save it in the current folder.
3. Load the Xxx.asm file into the assembler, and translate it. If there are syntax errors, go to step 2.
4. Save the translated Xxx.hack file in the current folder (this step is optional).
5. Load the Xxx.asm file (or the Xxx.hack file, it does not matter) into the CPU Emulator.
6. Informal testing: If the code expects to read values from RAM addresses, enter test values in these addresses; If the code expects to get inputs from the keyboard, click *enable keyboard*. Next, execute the code using the *step/run/reset* controls. If there are run-time errors, or incorrect outputs, go to step 2.
7. Formal testing: click the *load script* control, load the projects/4/Xxx/Xxx.tst file into the CPU Emulator, and execute it. If there are run-time or incorrect outputs, go to step 2.

The Fill program has two test scripts: Fill.tst and FillAutomatic.tst. The first test is visual: it guides you to verify that the screen turns black when a key is pressed and turns back to white when the key is released. The second test is automatic: it changes the value of the keyboard register and checks that your program responds by correctly changing values in the screen memory. To execute the automatic test, load your translated Fill.hack into the CPU Emulator, then load and run the FillAutomatic.tst test script. For more testing guidelines, read the documentation of FillAutomatic.tst.

Assembly tips

A legacy command-line assembler is also available. If you wish to use it, enter “Assembler.sh Xxx.asm” (Mac) or “Assembler Xxx.asm” (Windows) from the terminal / command line. If Xxx.asm is error-free, you will get no feedback, and a file named Xxx.hack will be created in the current folder (if you translate again, the file’s new version will override the previous one). Otherwise, you will get an error message.

Known bug: According to the Hack language C-instruction specification, two of the possible eight destinations are DM=... and ADM=... (these directives allow storing the ALU output in more than one destination, simultaneously). However, some Hack assemblers flag these destination codes as syntax errors, expecting instead MD=... and AMD=...

The simple solution is to always use MD=... or AMD= instead of DM=... or ADM= (if you ever have to use such assembly instructions).

Programming tips

The symbolic Hack language is case sensitive. A common programming error occurs when one writes, say, `@foo` and `@Foo` in different parts of the program, thinking that both instructions refer to the same symbol. In fact, the assembler treats them as two unique symbols.

Another common error is using lower case, or spaces, when writing instructions. For example, either `m=1` or `M = 1` results in syntax errors. The correct syntax is `M=1`

Best practice:

- Use upper-case letters for labels, like `LOOP`, and lower-case letters for variables, like `sum`.
- Indent your code: Start all lines that are not label declarations a few characters to the right.
- Write comments, as needed, to make your code readable (to yourself, and others).
- See the programs in the lecture or in the book, and follow their example.
- As always, strive to write elegant, efficient, and self-explanatory programs.

Tutorials

The tutorials below illustrate the legacy desktop version of the tools used in this project. However, the same working principles apply also to the online IDE tools.

[CPU Emulator demo](#)

[Assembler tutorial](#) (click *slideshow*)

[CPU Emulator tutorial](#) (click *slideshow*)