KTH – School of Engineering Sciences (SCI)

SF1546 Numerical Methods, Basic Course

Heat Transfer: From Theory to Numerical Solutions

Project VT2026

Name	Personal ID	E-mail
Enderborg, Eric	920816-2637	ericend@kth.se

Group 41

April 27, 2026

Contents

1 Introduction **2**

2 Mathematical Model and Numerical Methods **2**
2.1 Part 1 – Heat Exchanger . . . 2
2.1.1 Newton's Method for a Non-Linear Equation . . . 3
2.1.2 Newton's Method for a Non-linear System of Equations . . . 3
2.2 Part 2 - Heat Sinks . . . 5
2.2.1 Approximating the static heat equation . . . 5
2.2.2 Solving the System . . . 6

3 Results **6**
3.1 Part 1 – Heat Exchanger . . . 6
3.1.1 Numerical Solution of non-linear equation . . . 6
3.1.2 Numerical Solution of the non-linear system . . . 7
3.2 Part 2 - Heat Sinks . . . 9
3.2.1 Verification for the infinite length case . . . 9
3.2.2 Method order of accuracy . . . 10
3.2.3 Non-Linear Case: SS AISI 316, Aluminium, and Copper . . . 11

4 Discussion **15**

A Python Source Code **16**

1 Introduction

In modern engineering we are often faced with challenges of optimization, whether they are about minimizing cost or maximizing efficiency each case relies on mathematical models to try and predict a systems behaviour. In the first part of this report we analyse a heat exchanger which has a range of parameters already set and attempt to find optimal geometric parameters that satisfies the specifications. We do this by showing how the problem can be converted into a *root finding problem* and solved using Newton's Method with python code. Furthermore, we verify that our solution is reasonable by comparing it to theoretical expectations of such an implementation as well as comparing results with those obtained using established libraries such as scipy.
The second part of the report is spent on modelling a one-dimensional heat sink and it's thermal diffusion properties relating to choice of material and size. We show, in a similar way to the heat exchange model, how this boundary value problem can be formulated as a system of equations and solved using finite differences approximation and Newton's Method. The results are compared to a analytical case where simplifications to the model are made such that we can find an analytical solution to the governing equation and calculate an approximate error with which we can determine the models order of accuracy and when this analytical approximation makes sense. Finally we evaluate three materials with different thermal properties and assert a optimal length and choice of material for the heat sink.

2 Mathematical Model and Numerical Methods

2.1 Part 1 – Heat Exchanger

We are tasked with determining a numerical value of the outer tube diameter d that fulfils the specification of the other parameters given below. An equation for the heat flux is given by Equation (1).

$$Q = A_{\text{ex}} \cdot U_f \cdot \Delta T_m, \tag{1}$$

where $Q = 801368$ W is the total heat flux, $A_{\text{ex}} = 64.15$ m^2 is the heat transfer area, $\Delta T_m = 29.6$ °C is the mean temperature difference between the two fluids, and U_f is the overall heat transfer coefficient given by

$$U_f = \left(\frac{d}{D_s h_t} + \frac{dR_{fi}}{D_s} + \frac{d \ln(d/D_s)}{2k_w} + R_{fo} + \frac{1}{h_s} \right)^{-1}. \tag{2}$$

Here, d is the outer tube diameter which is as of yet unknown and, $D_s = 1.219$ m is the inner shell diameter, R_{fi}, R_{fo}, h_s, h_t, k_w are material and thermodynamic parameters given in Table 1.

Parameter	Value	Unit
R_{fi}	$1.76 \cdot 10^{-4}$	$\frac{\text{m}^2\,°\text{C}}{\text{W}}$
R_{fo}	$1.76 \cdot 10^{-4}$	$\frac{\text{m}^2\,°\text{C}}{\text{W}}$
h_s	356	$\frac{\text{W}}{\text{m}^2\,°\text{C}}$
h_t	356	$\frac{\text{W}}{\text{m}^2\,°\text{C}}$
k_w	60	$\frac{\text{W}}{\text{m}\,°\text{C}}$

Table 1: Material and Thermodynamic Parameter values.

2.1.1 Newton's Method for a Non-Linear Equation

To find a numerical value for d we apply Newton's method for scalar problems programmatically as outlined in Algorithm 1.

Algorithm 1 Newton's method – scalar equation

```
Let the initial guess be d_0 and the tolerance ε
k ← 0
while |f(d_k)| > ε do
    d_{k+1} ← d_k − f(d_k)/f'(d_k)
    k ← k + 1
end while
return d_k
```

We must therefore first find our function $f(d_k)$ on which we can apply Newton's method. We begin by rearranging Equation (1) into:

$$U_f = \frac{Q}{A_{\text{ex}} \cdot \Delta T_m}, \tag{3}$$

Newton's method is a *root finding* algorithm and as such solves $f(d_k) = 0$ by definition. We therefore subtract Equation (3) from Equation (2) and arrive at our expression for $f(d_k)$:

$$f(d_k) = \left(\frac{d_k}{D_s h_t} + \frac{d_k R_{fi}}{D_s} + \frac{d_k \ln(d_k/D_s)}{2k_w} + R_{fo} + \frac{1}{h_s} \right)^{-1} - \frac{Q}{A_{\text{ex}} \cdot \Delta T_m} = 0 \tag{4}$$

Taking the derivative with respect to d, our second term vanishes. Applying the chain rule:

$$\frac{\mathrm{d}}{\mathrm{d}d_k} f(d_k) = f'(d_k) = -\frac{\dfrac{1}{D_s h_t} + \dfrac{R_{fi}}{D_s} + \dfrac{\ln(d_k/D_s) + 1}{2k_w}}{\left(\dfrac{d_k}{D_s h_t} + \dfrac{d_k R_{fi}}{D_s} + \dfrac{d_k \ln(d_k/D_s)}{2k_w} + R_{fo} + \dfrac{1}{h_s} \right)^2} \tag{5}$$

We can now assemble the final expression for Newton's Method, the update is given by:

$$d_{k+1} = d_k - \frac{f(d_k)}{f'(d_k)} \tag{6}$$

This is implemented and solves for the unknown d using the python code in Listing 1.

2.1.2 Newton's Method for a Non-linear System of Equations

We must now also consider the pressure drop ΔP and surface area of heat transfer A_{ex} as functions of the inner shell diameter D_s in our system along with the added restriction that the *maximum* ΔP allowed is 49080 Pa. We must therefore now move to solving a *system* of equations since ΔP and A_{ex} are expressed with Equation (7) and Equation (8) respectively. Table 2 give the parameter values for Equation (7) and Equation (8).

$$\Delta P = \frac{c}{D_s^2 (S_t - d)^2} \tag{7}$$

$$A_{ex} = \pi K_1 \frac{D_s^{n_1}}{d^{n_1 - 1}} \tag{8}$$

Parameter	Value	Unit
c	0.389	$\mathrm{W\,s \cdot m}$
S_t	0.016	m
K_1	0.249	m
n_1	2.207	–

Table 2: Additional parameter values.

Since we now have to solve a system of equations for both the tube diameter d as well as the inner shell diameter D_s we move to Newton's Method for a *system* of equations:

Algorithm 2 Newton's method – system

Let the initial guess be $\mathbf{x}_0 = (d_0,\, D_{s,0})^T$ and tolerance ε
$k \leftarrow 0$
while $\|\mathbf{F}(\mathbf{x}_k)\| > \varepsilon$ **do**
  Solve $J\mathbf{F}(\mathbf{x}_k)\,\boldsymbol{\delta} = -\mathbf{F}(\mathbf{x}_k)$ for $\boldsymbol{\delta}$
  $\mathbf{x}_{k+1} \leftarrow \mathbf{x}_k + \boldsymbol{\delta}$
  $k \leftarrow k+1$
end while
return $\mathbf{x}_k = (d,\, D_s)^T$

At each iteration, the linear system $J\mathbf{F}(\mathbf{x}_k)\,\boldsymbol{\delta} = -\mathbf{F}(\mathbf{x}_k)$ is solved for the correction $\boldsymbol{\delta} = \mathbf{x}_{k+1} - \mathbf{x}_k$, which is then used to update the current guess.
We now formulate the Newton function $\mathbf{F}(d, D_s) = \mathbf{0}$ by combining Equations (1), (2), (7) and (8) into

$$F_1(d, D_s) = \left(\frac{d}{D_s h_t} + \frac{dR_{fi}}{D_s} + \frac{d\ln(d/D_s)}{2k_w} + R_{fo} + \frac{1}{h_s}\right)^{-1} - \frac{Q\,d^{n_1-1}}{\pi K_1 D_s^{n_1}\Delta T_m} \tag{9}$$

$$F_2(d, D_s) = \frac{c}{D_s^2(S_t - d)^2} - \Delta P \tag{10}$$

Combine into our Newton vector:

$$\mathbf{F}(d, D_s) = \begin{pmatrix} F_1(d, D_s) \\ F_2(d, D_s) \end{pmatrix} = \mathbf{0}, \quad \text{with } F_1, F_2 \text{ given by Equations (9) and (10)} \tag{11}$$

To apply Newton's Method in higher dimensions we need the Jacobian $J\mathbf{F}$ which is computed analytically. Denoting $g(d, D_s) = \frac{d}{D_s h_t} + \frac{dR_{fi}}{D_s} + \frac{d\ln(d/D_s)}{2k_w} + R_{fo} + \frac{1}{h_s}$ for brevity, the entries are:

$$J\mathbf{F}(d, D_s) = \begin{pmatrix} \partial_d F_1 & \partial_{D_s} F_1 \\ \partial_d F_2 & \partial_{D_s} F_2 \end{pmatrix} = \begin{pmatrix} -\dfrac{g_d}{g^2} + \dfrac{(n_1-1)Q\,d^{n_1-2}}{\pi K_1 D_s^{n_1}\Delta T_m} & \dfrac{g_{D_s}}{g^2} + \dfrac{n_1 Q\,d^{n_1-1}}{\pi K_1 D_s^{n_1+1}\Delta T_m} \\ \dfrac{2c}{D_s^2(S_t-d)^3} & \dfrac{-2c}{D_s^3(S_t-d)^2} \end{pmatrix} \tag{12}$$

Where $g_d = \partial g/\partial d$ and $g_{D_s} = \partial g/\partial D_s$ are:

$$g_d = \frac{1}{D_s h_t} + \frac{R_{fi}}{D_s} + \frac{\ln(d/D_s) + 1}{2k_w} \tag{13}$$

$$g_{D_s} = -\frac{d}{D_s^2 h_t} - \frac{dR_{fi}}{D_s^2} - \frac{d}{2k_w D_s} \tag{14}$$

This system is then solved using the python code in Listing 2

2.2 Part 2 - Heat Sinks

For the second part we shift our focus to the dispersion of heat in a one-dimensional rod and study the governing equation, a case of the static heat equation:

$$\frac{d^2T}{dx^2} = \alpha_1(T(x) - T_\infty) + \alpha_2 f(T(x)), \quad 0 \le x \le L \tag{15}$$

where $f(t) = T^4(x) - T_\infty^4$, $\alpha_1 = \frac{4h_c}{DK}$, $\alpha_2 = \frac{4\epsilon\sigma}{DK}$ and our Dirichlet boundary conditions are $T(0) = T_s$, $T(L) = T_L$. [1]

2.2.1 Approximating the static heat equation

Now, to be able to numerically solve Equation (15) we apply the finite difference model, more specifically a central finite difference for the second derivative and solve for the temperature distribution $T(x)$ using Newtons method for a system of equations: Algorithm 2.

For some second-order differential equation:

$$\frac{d^2T}{dx^2} = \omega(x), \qquad \omega(x_j) = \omega_j, \quad x \in [0, L]$$

a second-order central finite difference approximation is given by

$$\left.\frac{d^2T}{dx^2}\right|_{x_j} \approx \frac{T_{j+1} - 2T_j + T_{j-1}}{h^2} + \mathcal{O}(h^2).$$

Where, for easier notation we let $T(x_j) = T_j$.
Divide the interval $[0, L]$ into N sub intervals and let $N = 4$, so our grid points are

$$j \in \{0, 1, 2, 3, 4\},$$

with interior points $j = 1, 2, 3$. The step size is given by

$$h = \frac{x_{end} - x_{start}}{N} = \frac{L - 0}{4} = \frac{L}{4}.$$

Therefore our points of evaluation becomes,

$$x_0 = 0, \quad x_1 = h = \frac{L}{4}, \quad x_2 = 2h = \frac{L}{2}, \quad x_3 = 3h = \frac{3L}{4}, \quad x_4 = 4h = L.$$

Now, in our case as stated in Equation (15):

$$\omega_j = \alpha_1(T(x_j) - T(\infty)) + \alpha_2 f(T(x_j)).$$

Applying the approximation on each of the interior points we obtain a system of equations:

$$\begin{cases} \dfrac{T_2 - 2T_1 + T_0}{h^2} = \alpha_1(T_1 - T(\infty)) + \alpha_2 f(T_1), \\ \dfrac{T_3 - 2T_2 + T_1}{h^2} = \alpha_1(T_2 - T(\infty)) + \alpha_2 f(T_2), \\ \dfrac{T_4 - 2T_3 + T_2}{h^2} = \alpha_1(T_3 - T(\infty)) + \alpha_2 f(T_3). \end{cases}$$

applying the boundary conditions and moving the known boundaries to the right hand-side our system takes the form:

$$\begin{cases} \dfrac{T_2 - 2T_1}{h^2} = \alpha_1(T_1 - T(\infty)) + \alpha_2 f(T_1) - \dfrac{T_s}{h^2}, \\ \dfrac{T_3 - 2T_2 + T_1}{h^2} = \alpha_1(T_2 - T(\infty)) + \alpha_2 f(T_2), \\ \dfrac{T_2 - 2T_3}{h^2} = \alpha_1(T_3 - T(\infty)) + \alpha_2 f(T_3) - \dfrac{T_L}{h^2}. \end{cases}$$

[1] See Table 5 for the constants.

Rewriting the system in compact matrix form, which can be generalized for an arbitrary N:

$$A\mathbf{T} = \mathbf{r}(\mathbf{T}),$$

where

$$\mathbf{T} = \begin{bmatrix} T_1 \\ T_2 \\ T_3 \end{bmatrix}, \qquad A = \begin{bmatrix} -2 & 1 & 0 \\ 1 & -2 & 1 \\ 0 & 1 & -2 \end{bmatrix},$$

and

$$\mathbf{r}(\mathbf{T}) = \begin{bmatrix} h^2\big[\alpha_1\big(T_1 - T(\infty)\big) + \alpha_2 f(T_1)\big] - T_s \\ h^2\big[\alpha_1\big(T_2 - T(\infty)\big) + \alpha_2 f(T_2)\big] \\ h^2\big[\alpha_1\big(T_3 - T(\infty)\big) + \alpha_2 f(T_3)\big] - T_L \end{bmatrix}.$$

2.2.2 Solving the System

As for Equation (11), we apply Newton's method to our system, define the Newton function $\mathbf{F}(\mathbf{T})$:

$$\mathbf{F}(\mathbf{T}) = A\mathbf{T} - \mathbf{r}(\mathbf{T}) = \mathbf{0}.$$

Newton's method then solves

$$\mathbf{J}_F(\mathbf{T})\,\boldsymbol{\delta} = -\mathbf{F}(\mathbf{T}),$$

where the Jacobian is

$$\mathbf{J}_F = \frac{\partial \mathbf{F}}{\partial \mathbf{T}} = A - \frac{\partial \mathbf{r}}{\partial \mathbf{T}}.$$

and therefore:

$$\mathbf{J}_F = \begin{bmatrix} -2 - h^2\big(\alpha_1 + \alpha_2 f'(T_1)\big) & 1 & 0 \\ 1 & -2 - h^2\big(\alpha_1 + \alpha_2 f'(T_2)\big) & 1 \\ 0 & 1 & -2 - h^2\big(\alpha_1 + \alpha_2 f'(T_3)\big) \end{bmatrix}.$$

With the code provided in Listing 3 we then solve for the temperature distribution function $\mathbf{T}(x)$.

3 Results

3.1 Part 1 – Heat Exchanger

3.1.1 Numerical Solution of non-linear equation

The implementation of Newton's Method on this problem using the Python-code in Listing 1 produces the results shown in Table 3.

Table 3 shows that the method, using the prescribed initial guess $d_0 = 7.00$ mm, converges on a diameter of $d_1^* \approx 19.13$ mm after three iterations. Increasing the initial guess in even increments reveals a *second* root at $d_2^* \approx 0.8314$ m, which is also evident from the plot of $f(d)$ in Figure 1. Since both these roots satisfy the heat transfer specifications we opt for the larger outer tube diameter — a larger tube diameter requires fewer tubes for the same transfer area A_{ex}, reducing both material cost and manufacturing complexity.

The observed order of convergence p varies across starting guesses but tend towards $p \approx 2$ as we approach a root, which is consistent with the theoretical *local* quadratic convergence of Newton's method. Cases where p deviates noticeably from the theoretical $p = 2$, such as at $d_0 = 353.5$ mm with $p \approx 0.917$, can be attributed to starting values that lie far from a root and therefore outside the local neighbourhood where the quadratic convergence theorem applies.[2] Inspecting Figure 1, we see that

[2] A known limitation of Newton's Method is that one has to select an initial value that is already sufficiently close to a root for the method to be numerically stable.

d_0 (mm)	d^* (mm)	Iterations	p	Scipy d^* (mm)	$\lvert d^* - \text{Scipy}\rvert$ (mm)
7.0000	19.131407149325682	3	2.332896	19.131407149308625	1.71×10^{-14}
64.7500	19.131407149308647	4	2.322647	19.131407149308629	2.08×10^{-17}
122.5000	19.131407149308622	5	2.086488	19.131407149308611	1.04×10^{-17}
180.2500	19.131407151041735	5	1.850623	19.131407149308608	1.73×10^{-12}
238.0000	19.131407149308654	6	1.548516	19.131407149308618	3.82×10^{-17}
295.7500	19.131407149308636	6	1.058250	19.131407149308622	1.39×10^{-17}
353.5000	831.392740792126460	5	0.917235	831.392740793674875	1.55×10^{-12}
411.2500	831.392740793626103	7	1.350690	831.392740793672374	4.63×10^{-14}
469.0000	831.392740793674875	7	1.635620	831.392740793674761	1.11×10^{-16}
526.7500	831.392740791717188	6	1.774351	831.392740793674648	1.96×10^{-12}
584.5000	831.392740793674875	6	1.856506	831.392740793666690	8.22×10^{-15}
642.2500	831.392740791158303	5	1.911815	831.392740793674761	2.52×10^{-12}
700.0000	831.392740793674761	5	1.951238	831.392740793674761	0.00×10^{0}

Table 3: Newton convergence results for all starting guesses d_0, compared against `scipy.optimize.fsolve`. The horizontal rule separates the two points of convergence: $d^* \approx 0.01913$ m and $d^* \approx 0.8314$ m.

the starting value $d_0 = 353.5$ mm lies in a region where $f(d)$ is very steep and very far from both of the two roots. In this region, the tangent-based update

$$d_{k+1} = d_k - \frac{f(d_k)}{f'(d_k)}$$

has step length

$$|d_{k+1} - d_k| = |-\frac{f(d_k)}{f'(d_k)}|$$

and can produce updates with large steps that move far across the graph due the still very large function values before the iterates starts trending towards a specific root. In this initial phase, the error sequence is dominated by the global shape of $f(d)$ rather than its local quadratic behavior near the root, so the observed order of convergence is closer to linear than quadratic. This can be observed in Figure 2 where the first step with starting guess $d_0 = 353.50$ mm appears notably more linear than subsequent steps.



Figure 1: Graph of $f(d)$ over $d \in (0, 1]$ m, with the approximated roots marked. See Listing 1 for the implementation.



Figure 2: Residual $|d_k - d^*|$ versus iteration k for different starting guesses with Newton's method . See Listing 1 *"Order of Convergence"* section for implementation.

3.1.2 Numerical Solution of the non-linear system

Using the Python code in Listing 2 we simultaneously solve for both the outer tube diameter d and the inner shell diameter D_s by implementing Algorithm 2. This code produces the results shown in Table 4:

Table 4: Convergence results for the nonlinear system of equations solved using Newton's method as defined in Algorithm 2. The table displays the iterates $(d_k, D_{s,k})$, the 2-norm of the residual vector $\|\mathbf{F}(\mathbf{x}_k)\|_2$, the error relative to the final solution $\|\mathbf{x}_k - \mathbf{x}^*\|_2$, and the observed order of convergence p_k. See Listing 2 for the corresponding Python implementation.

k	d_k **(mm)**	$D_{s,k}$ **(mm)**	$\|F(x_k)\|_2$	$\|x_k - x^*\|_2$	p_k
0	15.000000	800.000000	5.58732501×10^{5}	$1.15566350 \times 10^{-1}$	–
1	14.512150	777.419100	2.41670069×10^{5}	$9.29805713 \times 10^{-2}$	0.262897
2	13.883940	772.267000	9.65862053×10^{4}	$8.78141296 \times 10^{-2}$	2.901072
3	13.145660	758.858800	3.38316968×10^{4}	$7.43938660 \times 10^{-2}$	2.157826
4	12.479150	736.485600	8.77327269×10^{3}	$5.20133509 \times 10^{-2}$	1.984354
5	12.085780	710.043100	1.28077228×10^{3}	$2.55683086 \times 10^{-2}$	1.531381
6	11.942580	693.093400	1.09162252×10^{2}	$8.61795814 \times 10^{-3}$	1.142165
7	11.902210	686.964200	9.17536055×10^{0}	$2.48864323 \times 10^{-3}$	1.023955
8	11.891160	685.173200	1.00172096×10^{0}	$6.97587461 \times 10^{-4}$	1.006337
9	11.888110	684.669600	$2.08936633 \times 10^{-1}$	$1.93969995 \times 10^{-4}$	1.001770
10	11.887270	684.529400	$5.62105801 \times 10^{-2}$	$5.38129237 \times 10^{-5}$	1.000495
11	11.887030	684.490500	$1.55480745 \times 10^{-2}$	$1.49197955 \times 10^{-5}$	1.000138
12	11.886970	684.479700	$4.30933832 \times 10^{-3}$	$4.13582602 \times 10^{-6}$	1.000039
13	11.886950	684.476700	$1.19450353 \times 10^{-3}$	$1.14640944 \times 10^{-6}$	1.000015
14	11.886950	684.475900	$3.31101187 \times 10^{-4}$	$3.17767263 \times 10^{-7}$	1.000017
15	11.886950	684.475700	$9.17765805 \times 10^{-5}$	$8.80783172 \times 10^{-8}$	1.000052
16	11.886940	684.475600	$2.54391336 \times 10^{-5}$	$2.44118045 \times 10^{-8}$	1.000185
17	11.886940	684.475600	$7.05135466 \times 10^{-6}$	$6.76437517 \times 10^{-9}$	1.000667
18	11.886940	684.475600	$1.95453191 \times 10^{-6}$	$1.87276678 \times 10^{-9}$	1.002413
19	11.886940	684.475600	$5.41767464 \times 10^{-7}$	$5.16884874 \times 10^{-10}$	1.008796
20	11.886940	684.475600	$1.50169740 \times 10^{-7}$	$1.41054272 \times 10^{-10}$	1.032962
21	11.886940	684.475600	$4.16249602 \times 10^{-8}$	$3.68797212 \times 10^{-11}$	1.138833
22	11.886940	684.475600	$1.15377952 \times 10^{-8}$	$8.00396433 \times 10^{-12}$	–
23	11.886940	684.475600	$3.19796218 \times 10^{-9}$	0.00000000×10^{0}	–

The method converges on values $d = 11.886940\ mm$ and $D_s = 684.475600\ mm$ for the sought after diameters. However, in the results we note that the order of convergence is not $p \approx 2$ as expected. Studying Figure 3 and Figure 4 we conclude that the convergence appear linear instead of the theoretically expected quadratic behaviour. This is most likely due to the Jacobian being ill conditioned and close to singular near the solution.



Figure 3: Convergence evolution of the Newton system, showing the error at the next iteration, $\|\mathbf{x}_{k+1} - \mathbf{x}^*\|_2$, as a function of the current error, $\|\mathbf{x}_k - \mathbf{x}^*\|_2$ illustrating linear convergence. See Listing 2 for the implementation.



Figure 4: Residual $|x_k - x^*|$ versus iteration k for Newton's method. See Listing 2 *"Order of Convergence"* section for implementation.

3.2 Part 2 - Heat Sinks

3.2.1 Verification for the infinite length case

To get some sense of whether or not our implementation seems reasonable, we test it against a case where the heat sink is so long that at some sufficiently large x we expect the rod to reach ambient temperature T_∞ and where radiative effects are neglected, this case has the analytical solution:

$$T(x) = T_\infty + (T_s - T_\infty)e^{-\sqrt{\alpha_1}x}. \tag{16}$$

We use the values in Table 5 and approximate the temperature distribution function $T(x)$ for $N = 400$ using the code in Listing 3 and compare the results with Equation (16), the results of which is shown in Figure 6 and Figure 5.

Table 5: Heat Sink parameter values for implementation test.

Parameter	Value	Unit
h_c	40	$\frac{W}{m^2 \cdot K}$
K	240	$\frac{W}{m \cdot K}$
ϵ	0.4	
σ	$5.67 \cdot 10^{-8}$	$\frac{W}{m^2 K^4}$
D	$4.13 \cdot 10^{-3}$	m
T_s	450	K (Kelvin)
T_∞	293	K (Kelvin)



Figure 5: Temperature distribution of approximate Newton solution compared to the analytical case Equation (16) showing convergence.



Figure 6: Pointwise error of approximate Newton solution compared to the analytical case Equation (16) showing early discrepancy due to boundary conditions.

Judging from Figure 5, the numerical approximation follows the analytical solution closely enough for practical use. For small values of x, however, Figure 6 shows a relatively large bump in the pointwise error. This is a boundary effect: the fixed Dirichlet condition at $x = 0$ makes the first interior node strongly depend on the prescribed value, so the leading $O(h^2)$ error term of a Taylor expansion around this point might still be quite large. As a result, the first "step" away from the boundary is less accurate, even though the method remains globally $O(h^2)$ accurate.

3.2.2 Method order of accuracy

Using the same coefficients as in the previous section, we now evaluate the error as a function of N. For each $N \in \{50, 100, 200, 400, 800\}$ we solve the boundary value problem numerically and compare the result to the analytical reference solution Equation (16). The discrete 2-norm of the error is defined as

$$\|\mathbf{r}\|_2 = \left(\frac{1}{N-1} \sum_{k=1}^{N-1} |r_k|^2 \right)^{1/2}, \tag{17}$$

where $r_k = T_N(x_k) - T_{\text{ref}}(x_k)$ is the pointwise error at the interior grid point x_k.
To estimate the observed order of accuracy p we use consecutive pairs (N_{k-1}, N_k) and their corresponding

errors $e_{N_{k-1}}, e_{N_k}$:

$$p_k = \frac{\log\left(\dfrac{e_{N_{k-1}}}{e_{N_k}}\right)}{\log\left(\dfrac{N_k}{N_{k-1}}\right)}. \tag{18}$$

If the method is second-order, we expect $p_k \approx 2$ for sufficiently large N.
The results are presented in Table 6 and Figure 7, the discrete 2-norm e_N decreases approximately like N^{-2}, and the estimated orders p_k are close to 2, which confirms that the finite difference method is globally second-order accurate.

N	e_N	p
50	2.3051×10^{-1}	—
100	5.8648×10^{-2}	1.9747
200	1.4681×10^{-2}	1.9981
400	3.6668×10^{-3}	2.0014
800	9.1589×10^{-4}	2.0013

Table 6: Discrete 2-norm error e_N and estimated order of accuracy p for different number of intervals N.



Figure 7: Discrete 2-norm error as a function of N showing N^{-2} proportionality.

3.2.3 Non-Linear Case: SS AISI 316, Aluminium, and Copper

We now include the second term ($\alpha_2 \neq 0$) and solve the full non-linear Equation (15) for three materials: stainless steel (AISI 316), aluminium alloy, and copper.
The geometry and boundary conditions are equal for all materials and is: $L = 0.30$ m, $D = 5.0 \times 10^{-3}$ m, $T(0) = 373.15$ K, and $T(L) = T_\infty = 293.15$ K. The material-specific coefficients are

$$\alpha_1 = \frac{4h_c}{DK}, \qquad \alpha_2 = \frac{4\epsilon\sigma}{DK}, \tag{19}$$

with σ being Boltzmann's constants[3] and the remaining parameters taken from Table 7.

[3] $\sigma = 5.67 \times 10^{-8}\ \mathrm{W\,m^{-2}\,K^{-4}}$

Material	K $[\frac{\mathrm{W}}{\mathrm{m\,K}}]$	h_c $[\frac{\mathrm{W}}{\mathrm{m^2K}}]$	ϵ	α_1 $[\mathrm{m}^{-2}]$	α_2 $[\mathrm{m}^{-2}\mathrm{K}^{-3}]$
SS AISI 316	14	100	0.17	5714.29	5.508×10^{-7}
Aluminium	180	100	0.82	444.44	2.066×10^{-7}
Copper	398	100	0.03	201.00	3.419×10^{-9}

Table 7: Material parameters and computed coefficients.

Using the code in Listing 3 with $N = 400$, the temperature distributions for each material are plotted in Figure 8.



Figure 8: Temperature distribution $T(x)$ along the heat sink for three materials, with ($\alpha_2 \neq 0$), $N = 400$.

The three profiles in Figure 8 differ substantially, why that is is evident directly from α_1 in Table 7. Since $\alpha_1 \propto K^{-1}$, a lower thermal conductivity produces a *larger* α_1 and therefore a steeper exponential decay toward T_∞. The stainless steel drop to near-ambient temperature within the first few centimeters due to it's poor thermal conductivity. The aluminum decays more gradually, while the copper disperses the energy the most, maintaining an elevated temperature almost across the full 0.30 m length. α_2 plays a minor role here since its values are several orders of magnitude smaller than α_1.

Required length for the infinite assumption. The analytical solution for the infinite case (Equation (16)) assumes that the temperature decreases exponentially and to an infinitesimal degree approaches the ambient temperature as $x \to \infty$. If we apply a threshold for when we may say that this approximation is valid, e.g when the deviation is less than 1%, we get a practical first estimate of a cut-off length: Let $\theta(L)$ and $\theta(b)$ be the temperature at $x = L$ and $x = 0$ respectively, we assume that:

$$\theta(L) = \theta_b e^{-\sqrt{\alpha_1}L} \implies \frac{\theta(L)}{\theta_b} = e^{-\sqrt{\alpha_1}L} \tag{20}$$

We wish this ratio to be $\leq 1\%$. Solving for L we get:

$$L > \frac{-4.605}{-\sqrt{\alpha_1}} \approx \frac{4.6}{\sqrt{\alpha_1}} \tag{21}$$

Thus, for a heat sink to satisfy the infinite-length assumption, its length must exceed approximately $4.6/\sqrt{\alpha_1}$.
Applying Equation (21) to each material gives the minimum lengths in Table 8.

Material	$\sqrt{\alpha_1}$ [m^{-1}]	$L_{\min} = 4.6/\sqrt{\alpha_1}$ [m]	Valid at $L = 0.30$ m?
SS AISI 316	75.6	0.061	Yes
Aluminium	21.1	0.218	Yes
Copper	14.2	0.324	**No**

Table 8: Minimum length for the infinite-length assumption to hold ($< 1\%$ error at the tip).

The stainless steel satisfies the criterion at just 6.1 cm since its low conductivity traps the majority of energy near the base. The aluminium requires roughly 22 cm, which is within the simulated 30 cm. And lastly, the copper *does not* satisfy the criterion at $L = 0.30$ m: its high conductivity means the temperature disperses rapidly and well throughout and has not decayed sufficiently by the tip. Therefore the infinite-length formula Equation (16) would underestimate the tip temperature and overestimate the total heat loss for copper heat sinks of this length.
Using Listing 3 we calculate the full temperature distribution for several lengths for each of the different materials using Newton's Method as described in Section 2.2.2, the results are presented in Figure 9a, Figure 9b, Figure 9c and confirm our earlier first estimates that the approximation is valid for all the materials except copper.



(a) SS AISI 316



(b) Aluminium



(c) Copper

Figure 9: Temperature distribution $T(x)$ for AISI316, Aluminium and Copper, illustrating how the temperature distribution for different lengths of the heat sink diverges or converges with the infinite-length approximation.

4 Discussion

The numerical simulations performed in this project demonstrate that Newton's method is a highly effective tool for solving the non-linear problems associated with thermal design, provided that the initial guesses are chosen within the appropriate local convergence neighbourhoods.
In the heat exchanger analysis, we observed that the scalar formulation of the design problem yields two mathematically valid roots for the outer tube diameter d.
By choosing the larger of the two roots, we satisfy the requirements while optimizing the design for lower material usage and reduced manufacturing complexity illustrating that careful consideration of the physics of the problem is crucial to be able to choose the final solution.
While the scalar version of the method converges quadratically in most cases, Newton's method for the (d, D_s) pair showed more complex convergence behaviour, likely linked to the poor conditioning of the Jacobian near the solution, highlighting the need for well behaved systems for Newton's Method.
For the heat sink analysis, the finite difference approximation was validated through a comparison with an analytical solution for an infinitely long heat sink. The error analysis confirmed that the implementation is globally second-order accurate ($\mathcal{O}(h^2)$), as demonstrated by the convergence order $p \approx 2$ observed.
Furthermore, the simulation of three distinct materials illustrated that thermal conductivity (K) is most likely the dominant factor in heat sink efficiency; materials with low conductivity, such as stainless steel, trap heat near the base, whereas high-conductivity materials like copper disperse heat very effectively making it very effective as a heat sink material.
The evaluation of the "infinite length" assumption confirms that this design approximation is valid for stainless steel and aluminium fins of ≈ 0.30 m length. However, for copper or other high conductivity materials, the resulting model shows insufficient temperature decay at the tip, indicating that the infinite-length formula would significantly underestimate the actual temperature distribution and is therefore not useful in such cases.
These findings highlight the importance of not only choosing the right numerical method but also validating when simplified theoretical models are appropriate for practical engineering applications.

References

[1] Y. Ali Kara, Ö. Güraras, *A computer program for designing of shell-and-tube heat exchangers*, Appl. Therm. Eng. 24, pp. 1797–1805 (2004).

[2] Frank P. Incropera, David P. Dewitt, Theodore L. Bergman, Andrienne S. Levine, *Principles of Heat and Mass Transfer*, Seventh Edition, 2013 John Wiley & Sons, pp. 112–228.

[3] Timothy Sauer, *Numerical Analysis*, Third Edition, 2018 Pearson Education.

A Python Source Code

Heat Exchanger – Newton's Method for non-linear equation

Listing 1: Heat Exchanger – Newton's Method for non-linear equation

```python
from dataclasses import dataclass
from pathlib import Path
from typing import Callable

import matplotlib.pyplot as plt
import matplotlib.ticker as ticker
import numpy as np
import scipy.optimize as opt

ROOT = Path(__file__).parent
plot_dir: Path = ROOT / "Plots"
plot_dir.mkdir(exist_ok=True)
# Results Save directory
results_path: Path = ROOT / "Results"
results_path.mkdir(exist_ok=True)


@dataclass
class NewtonRaphsonResult:
    """
    Result container for scalar Newton-Raphson iterations.

    Parameters
    ------
    fs : list[float]
        Sequence of function values f(x_k) at each iteration k.
    xs : list[float]
        Sequence of iterates x_k produced by Newton's method.
    ns : list[int]
        Iteration indices corresponding to each x_k (typically [0, 1, ..., n]).
    deltas : list[float]
        Step sizes Deltax_k = x_{k+1} - x_k (often useful for convergence diagnostics).
    final_x : float
        Final iterate x_* returned by the method (last element of xs).
    converged : bool
        Flag indicating whether the stopping criterion was satisfied.
    """

    fs: list[float]
    xs: list[float]
    ns: list[int]
    deltas: list[float]
    final_x: float
    converged: bool


def NewtonRaphson(
    f: Callable[[float], float],
    f_prime: Callable[[float], float],
    x0: float,
    tolerance: float,
    max_iterations: int,
) -> NewtonRaphsonResult:
```

```
    """
    Newton-Raphson method to find a root of a scalar function f starting from x0.

    Parameters
    ----------
    f : Callable[[float], float]
        Scalar function f(x).
    f_prime : Callable[[float], float]
        Derivative f'(x) of the function f.
    x0 : float
        Initial guess for the root.
    tolerance : float
        Convergence tolerance on |f(x_k)|.
    max_iterations : int
        Maximum allowed number of iterations.

    Returns
    -------
    NewtonRaphsonResult
        Result container with iterates x_k, residuals f(x_k), step sizes Deltax_k,
        iteration indices, final iterate, and convergence flag.
    """
    ns: list[int] = []
    fs: list[float] = []
    xs: list[float] = []
    deltas: list[float] = []

    x = x0
    n = 0
    fx = f(x)

    xs.append(x)
    fs.append(fx)
    deltas.append(float("inf"))  # placeholder for initial step
    ns.append(n)

    converged = abs(fx) <= tolerance

    while abs(fx) > tolerance and n < max_iterations:
        n += 1
        df = f_prime(x)
        if df == 0:
            # Derivative zero -> Newton step undefined
            break

        x_new = x - fx / df
        delta_x = float(np.abs(x_new - x))
        x = x_new
        fx = f(x)

        xs.append(x)
        fs.append(fx)
        deltas.append(delta_x)
        ns.append(n)

    converged = abs(fx) <= tolerance

    return NewtonRaphsonResult(
        fs=fs,
```

```python
        xs=xs,
        deltas=deltas,
        ns=ns,
        final_x=x,
        converged=converged,
    )


def main():
    # ============= Setup =============
    Q: float = 801368  # Heat Flux
    Aex: float = 64.15  # Heat transfer area
    dTm: float = 29.6  # Mean temp. delta of the two fluids
    Ds: float = 1.219  # Shell inner diameter
    # Material and Thermodynamic parameters:
    Rfi: float = 1.76e-4
    Rfo: float = 1.76e-4
    hs: float = 356
    ht: float = 356
    kw: float = 60

    U_f: float = Q / (Aex * dTm)  # Heat transfer coefficient
    d_0: float = 0.007  # Reference initial guess
    tolerance: float = 1e-8

    def g(d) -> float:
        return (
            d / (Ds * ht) + d * Rfi / Ds + d * np.log(d / Ds) / (2 * kw) + Rfo + 1 / hs
        )

    def g_prime(d) -> float:
        return 1 / (Ds * ht) + Rfi / Ds + (np.log(d / Ds) + 1) / (2 * kw)

    def f(d) -> float:
        return 1 / g(d) - U_f

    def f_prime(d) -> float:
        return -g_prime(d) / (g(d) ** 2)

    starting_vals: np.ndarray = np.linspace(d_0, 0.7, 13)

    # [PLOT_START]
    # ============= Plot Setup =============
    plt.style.use("seaborn-v0_8-whitegrid")
    SMALL, MED, BIG = 11, 13, 14
    plt.rcParams.update(
        {
            "font.family": "serif",
            "font.size": MED,
            "axes.titlesize": BIG,
            "axes.labelsize": MED,
            "xtick.labelsize": SMALL,
            "ytick.labelsize": SMALL,
            "legend.fontsize": SMALL,
            "figure.dpi": 300,
        }
    )

    fig_conv, ax_conv = plt.subplots(figsize=(6, 4))
    # [PLOT_END]
```

```python

    # Run the reference Newton (for summary)
    ref_result: NewtonRaphsonResult = NewtonRaphson(
        f=f, f_prime=f_prime, x0=d_0, tolerance=tolerance, max_iterations=100
    )
    ref_root = ref_result.final_x
    ref_residual = abs(f(ref_root))

    # ============= Results file =============
    results_file = results_path / "Newton Scalar Results.txt"
    with results_file.open("w", encoding="utf-8") as out:
        # Header
        out.write("Newton's Method for Scalar Nonlinear Equation (d)\n")
        out.write("=" * 100 + "\n\n")

        # Summary for reference run
        out.write("Reference run (starting from d0 = 0.007 m):\n")
        out.write(f"  d*   = {ref_root: .8e} m\n")
        out.write(f"  |f(d*)| = {ref_residual: .3e}\n")
        out.write(f"  Iterations = {len(ref_result.xs) - 1:d}\n\n")

        # Table header for all starting guesses
        out.write(
            f"{'d0 [mm]':>12}  {'d* [mm]':>22}  {'Iterations':>10}  "
            f"{'p (first)':>10}  {'Scipy d* [mm]':>22}  {'|d* - Scipy|':>15}\n"
        )
        out.write("-" * 100 + "\n")

        # ============= Loop over starting guesses =============
        for x0 in starting_vals:
            results: NewtonRaphsonResult = NewtonRaphson(
                f=f, f_prime=f_prime, x0=x0, tolerance=tolerance, max_iterations=100
            )

            # Order of convergence (estimate from error to final_x)
            errors: list[float] = [abs(x - results.final_x) for x in results.xs]
            p: list[float] = [
                np.log(abs(errors[k + 1] / errors[k]))
                / np.log(abs(errors[k] / errors[k - 1]))
                for k in range(1, len(errors) - 1)
                if errors[k] > 0 and errors[k - 1] > 0 and errors[k + 1] > 0
            ]

            # Verification with SciPy
            root, info, exitflag, output = opt.fsolve(
                func=f, x0=x0, fprime=f_prime, full_output=True
            )
            scipy_result = root[0]

            # Write one row for this starting guess
            p_str = f"{p[0]:.6f}" if p else "N/A"
            delta_scipy = abs(results.final_x - scipy_result)
            out.write(
                f"{x0 * 1000:>11.4f}  "  # x0 in mm
                f"{results.final_x * 1000:>22.15f}  "  # d* in mm
                f"{len(results.xs) - 1:>10}  "
                f"{p_str:>10}  "
```

```
                f"{scipy_result * 1000:>22.15f}  "  # scipy d* in mm
                f"{delta_scipy:>15.2e}\n"
            )

            # [PLOT_START]
            # ------------- Add to convergence plot -------------
            residuals = [abs(fx) for fx in results.fs]

            is_special = abs(x0 - 0.35350) < 1e-9

            ax_conv.semilogy(
                results.ns,
                residuals,
                linestyle="-",
                color="black" if is_special else None,
                lw=1 if is_special else 0.8,
                marker="o" if is_special else "",
                ms=1.25 if is_special else 1,
                alpha=1.0 if is_special else 0.90,
                zorder=5 if is_special else 2,
                label=rf"$d_0 = {x0 * 1000:.2f}$ mm",
            )
            # [PLOT_END]

    print(f"Scalar Newton results written to {results_file}")

    # [PLOT_START]
    # ------------- Plot f(d) -------------
    fig1, ax1 = plt.subplots(figsize=(6, 4))
    d_plot = np.linspace(0.003, 1, 600)
    f_plot = [f(d) for d in d_plot]
    final_result = NewtonRaphson(
        f=f, f_prime=f_prime, x0=d_0, tolerance=tolerance, max_iterations=100
    )

    ax1.plot(d_plot * 1000, f_plot, lw=2, label=r"$f(d)$")
    ax1.fill_between(d_plot * 1000, f_plot, alpha=0.07)
    ax1.axhline(0, color="gray", lw=1, ls="--")
    ax1.plot(
        final_result.final_x * 1000,
        0,
        "o",
        ms=8,
        label=rf"$d_1^* = {final_result.final_x * 1000:.2f}$ mm",
    )
    ax1.annotate(
        rf"$d_1^* = {final_result.final_x * 1000:.2f}$ mm",
        xy=(final_result.final_x * 1000, 0),
        xytext=(final_result.final_x * 1000 + 100, -300),
        arrowprops=dict(arrowstyle="->", color="black"),
        fontsize=SMALL,
    )
    ax1.plot(
        results.final_x * 1000,
        0,
        "o",
        ms=8,
        label=rf"$d_2^* = {results.final_x * 1000:.2f}$ mm",
    )
    ax1.annotate(
```

```
        rf"$d_2^* = {results.final_x * 1000:.2f}$ mm",
        xy=(results.final_x * 1000, 0),
        xytext=(results.final_x * 1000 - 370, -300),
        arrowprops=dict(arrowstyle="->", color="black"),
        fontsize=SMALL,
    )
    ax1.set_xlabel(r"$d$ (mm)")
    ax1.set_ylabel(r"$f(d)$")
    ax1.set_title(r"Root of $f(d)$ - Newton's Method")
    ax1.legend(frameon=False)
    fig1.tight_layout()
    fig1.savefig(plot_dir / "outerdim_newton_roots.png", dpi=300, bbox_inches="tight")

    # ------------- Save convergence plot -------------
    ax_conv.set_xlabel(r"Iteration $k$")
    ax_conv.set_ylabel(r"$|f(d_k)|$")
    ax_conv.set_title("Residual vs Starting Guess - Newton's Method")
    ax_conv.xaxis.set_major_locator(ticker.MultipleLocator(1))
    ax_conv.legend(frameon=False, fontsize="xx-small", loc="lower left")
    fig_conv.tight_layout()
    fig_conv.savefig(
        plot_dir / "outerdim_newton_convergence.png", dpi=300, bbox_inches="tight"
    )
    # [PLOT_END]


if __name__ == "__main__":
    main()
    plt.show()
```

Heat Exchanger – Newton's Method for non-linear system

Listing 2: Heat Exchanger – Newton's Method for non-linear system

```
from dataclasses import dataclass
from pathlib import Path
from typing import Callable

import matplotlib.pyplot as plt
import matplotlib.ticker as ticker
import numpy as np

# Plot save directory
ROOT = Path(__file__).parent
plot_dir: Path = ROOT / "Plots"
plot_dir.mkdir(exist_ok=True)
# Results Save directory
results_path: Path = ROOT / "Results"
results_path.mkdir(exist_ok=True)


@dataclass
class NewtonSystemResult:
    """
    Result container for Newton's method applied to systems of nonlinear equations.

    Parameters
```

```
    ------
    xs : list[np.ndarray]
        Sequence of iterates x_k  in  R^n at each step (shape (n,) per iterate).
    Fs : list[np.ndarray]
        Sequence of residual vectors F(x_k)  in  R^n at each iteration.
    final_x : np.ndarray
        Final iterate x_*  in  R^n returned by the method (last element of xs).
    ns : list[int]
        Iteration indices corresponding to each x_k (typically [0, 1, ..., n]).
    """

    xs: list[np.ndarray]  # iterates x_k
    Fs: list[np.ndarray]  # F(x_k)
    final_x: np.ndarray  # x_* at termination
    ns: list[int]  # iteration indices


def newton_system(
    F_func: Callable,
    JF_func: Callable,
    x0: np.ndarray,
    tol: float,
    max_iter: int,
    args: tuple,
    jac_args: tuple | None = None,
) -> NewtonSystemResult:
    """
    Newton's method for systems of nonlinear equations.

    At each iteration k, solves the linear system
        JF(x_k) * delta = -F(x_k)
    for the correction delta, then updates
        x_{k+1} = x_k + delta,
    until ||F(x_k)||_2 <= tol or the iteration limit is reached.

    Parameters
    ----------
    F_func : Callable
        Vector-valued function F(x, *args) returning np.ndarray of shape (n,).
    JF_func : Callable
        Jacobian function JF(x, *jac_args) returning np.ndarray of shape (n, n).
    x0 : np.ndarray
        Initial guess vector x_0  in  R^n (shape (n,)).
    tol : float
        Convergence tolerance on the 2-norm ||F(x_k)||_2.
    max_iter : int
        Maximum allowed number of iterations.
    args : tuple
        Additional parameters passed to F_func.
    jac_args : tuple, optional
        Additional parameters passed to JF_func. Defaults to args if not provided.

    Returns
    -------
    NewtonSystemResult
```

```
    """
    jac_args = jac_args if jac_args is not None else args

    x = x0.astype(float)
    xs = [x.copy()]
    Fx = F_func(x, *args)
    Fs = [Fx]
    ns = [0]

    for k in range(max_iter):
        if np.linalg.norm(Fx, ord=2) <= tol:
            break

        J = JF_func(x, *jac_args)
        delta = np.linalg.solve(J, -Fx)
        x = x + delta

        Fx = F_func(x, *args)

        xs.append(x.copy())
        Fs.append(Fx)
        ns.append(k + 1)

    return NewtonSystemResult(xs=xs, Fs=Fs, final_x=x, ns=ns)


# ============= Model Definition =============


def g(
    d: float, Ds: float, ht: float, Rfi: float, kw: float, Rfo: float, hs: float
) -> float:
    """
    g(d, Ds) from the report:
        g(d, D_s) = d/(D_s h_t) + d R_fi / D_s + d ln(d/D_s)/(2 k_w) + R_fo + 1/h_s
    """
    return (
        d / (Ds * ht) + d * Rfi / Ds + d * np.log(d / Ds) / (2.0 * kw) + Rfo + 1.0 / hs
    )


def g_d(d: float, Ds: float, ht: float, Rfi: float, kw: float) -> float:
    """
    dg/dd from the report:
        g_d = 1/(D_s h_t) + R_fi / D_s + (ln(d/D_s) + 1)/(2 k_w)
    """
    return 1.0 / (Ds * ht) + Rfi / Ds + (np.log(d / Ds) + 1.0) / (2.0 * kw)


def g_Ds(d: float, Ds: float, ht: float, Rfi: float, kw: float) -> float:
    """
    dg/dD_s from the report:
        g_{D_s} = -d / (D_s^2 h_t) - d R_fi / D_s^2 - d/(2 k_w D_s)
    """
    return -d / (Ds**2 * ht) - d * Rfi / (Ds**2) - d / (2.0 * kw * Ds)


# Newton Function vector
```

```python
def F(
    x: np.ndarray,
    Q: float,
    dTm: float,
    K1: float,
    n1: float,
    c: float,
    S_t: float,
    hs: float,
    ht: float,
    Rfi: float,
    Rfo: float,
    kw: float,
    dP_max: float,
) -> np.ndarray:
    """
    Vector function F(d, Ds) = (F1, F2)^T corresponding to eqs. (F1) and (F2) in eq. (11) in report.

    F1(d, Ds) = g(d, Ds)^(-1) - Q d^{n1-1} / (pi K1 Ds^{n1} DeltaT_m)
    F2(d, Ds) = c / (Ds^2 (S_t - d)^2) - DeltaP_max
    """
    d, Ds = x
    g_val = g(d, Ds, ht, Rfi, kw, Rfo, hs)

    F1 = (1.0 / g_val) - Q * d ** (n1 - 1.0) / (np.pi * K1 * Ds**n1 * dTm)
    F2 = c / (Ds**2 * (S_t - d) ** 2) - dP_max

    return np.array([F1, F2], dtype=float)


# Jacobian for Newton Function vector
def JF(
    x: np.ndarray,
    Q: float,
    dTm: float,
    K1: float,
    n1: float,
    c: float,
    S_t: float,
    hs: float,
    ht: float,
    Rfi: float,
    Rfo: float,
    kw: float,
    dP_max: float,
) -> np.ndarray:
    """
    Jacobian matrix JF(d, Ds) corresponding to eq. (12) in report:

        JF = [[dF1/dd,  dF1/dDs],
              [dF2/dd,  dF2/dDs]]
    """
    d, Ds = x
    g_val = g(d, Ds, ht, Rfi, kw, Rfo, hs)
    gd = g_d(d, Ds, ht, Rfi, kw)
    gDs = g_Ds(d, Ds, ht, Rfi, kw)

    # dF1/dd
    J11 = -gd / (g_val**2) + (n1 - 1.0) * Q * (d ** (n1 - 2.0)) / (
        np.pi * K1 * Ds**n1 * dTm
```

```
    )

    # dF1/dDs
    J12 = gDs / (g_val**2) + n1 * Q * d ** (n1 - 1.0) / (
        np.pi * K1 * Ds ** (n1 + 1.0) * dTm
    )

    # dF2/dd
    J21 = 2.0 * c / (Ds**2 * (S_t - d) ** 3)

    # dF2/dDs
    J22 = -2.0 * c / (Ds**3 * (S_t - d) ** 2)

    return np.array([[J11, J12], [J21, J22]], dtype=float)


# ============= Main  =============


def main() -> None:
    # ------------- Parameters -------------
    # Heat / thermo parameters
    Q: float = 801_368.0  # Heat flux
    dTm: float = 29.6  # Mean temp. difference
    dP_max: float = 49_080.0  # Max allowed pressure drop

    # Material parameters
    c: float = 0.389
    S_t: float = 0.016
    K_1: float = 0.249
    n_1: float = 2.207

    # Thermal parameters / coefficients
    Rfi: float = 1.76e-4
    Rfo: float = 1.76e-4
    hs: float = 356.0
    ht: float = 356.0
    kw: float = 60.0

    # Newton settings
    tol: float = 1e-8
    max_iter: int = 50

    # Initial guess for (d, Ds)
    d0: float = 0.015
    Ds0: float = 0.8
    x0 = np.array([d0, Ds0], dtype=float)

    # Pack parameters in the order F, JF expect
    params = (Q, dTm, K_1, n_1, c, S_t, hs, ht, Rfi, Rfo, kw, dP_max)

    # ============= Newton solve =============
    result = newton_system(
        F_func=F,
        JF_func=JF,
        x0=x0,
        tol=tol,
        max_iter=max_iter,
        args=params,
    )

```

```python
    d_star, Ds_star = result.final_x
    residual_norm = np.linalg.norm(result.Fs[-1], ord=2)

    print(f"Converged in {len(result.ns) - 1} iterations")
    print(f"d*  = {d_star:.6e} m")
    print(f"Ds* = {Ds_star:.6e} m")
    print(f"||F(x*)||_2 = {residual_norm:.3e}")

    # ============= Convergence analysis =============

    # ------------- Per-iteration residuals and errors -------------
    residuals = [np.linalg.norm(Fk, ord=2) for Fk in result.Fs]
    x_star = result.final_x
    errors = [np.linalg.norm(x_k - x_star, ord=2) for x_k in result.xs]

    # Pairs of e_k, e_k+1 for error plot
    e_k = np.array(errors[:-1])
    e_kp1 = np.array(errors[1:])

    # ------------- Per-iteration Jacobian determinant and condition number -------------
    det_Js: list[float] = []
    cond_Js: list[float] = []
    for x_k in result.xs:
        J_k = JF(x_k, *params)
        det_Js.append(np.linalg.det(J_k))
        cond_Js.append(np.linalg.cond(J_k))

    # ------------- Per-iteration order p_k (aligned with k) -------------
    p_vals: list[float | None] = [None] * len(errors)
    for k in range(1, len(errors) - 1):
        e_km1, e_k, e_kp1 = errors[k - 1], errors[k], errors[k + 1]
        if e_km1 > 0 and e_k > 0 and e_kp1 > 0:
            p_k = np.log(e_kp1 / e_k) / np.log(e_k / e_km1)
            p_vals[k] = p_k

    # Jacobian at final iterate (for summary)
    J_star = JF(x_star, *params)
    det_J = np.linalg.det(J_star)
    cond_J = np.linalg.cond(J_star)

    # ============= Write Results to .txt file =============
    results_file = results_path / "Newton System Results.txt"
    with results_file.open("w", encoding="utf-8") as out:
        out.write("Newton's Method for Nonlinear System (d, D_s)\n")
        out.write("=" * 80 + "\n\n")
        out.write("Initial Guess:\n")
        out.write(f"d_0 = {d0}\n")
        out.write(f"D_s0 = {Ds0}\n\n")
        out.write("Final solution:\n")
        out.write(f"  d*   = {d_star: .8e} m\n")
        out.write(f"  D_s* = {Ds_star: .8e} m\n")
        out.write(f"  ||F(x*)||_2 = {residual_norm: .3e}\n")
        out.write(f"  Iterations  = {len(result.ns) - 1:d}\n\n")

        out.write("Jacobian at x*:\n")
        out.write(f"  det(J(x*))  = {det_J: .8e}\n")
        out.write(f"  cond(J(x*)) = {cond_J: .3e}\n\n")

        out.write("Per-iteration data:\n")
        out.write(
```

```
            f"{'k':>4}  {'d_k [mm]':>12}  {'D_s,k [mm]':>12}  "
            f"{'||F(x_k)||_2':>18}  {'||x_k - x*||_2':>18}  "
            f"{'det(J_k)':>12}  {'cond(J_k)':>12}  {'p_k':>12}\n"
        )
        out.write("-" * 120 + "\n")

        for k, (x_k, res_k, err_k, det_k, cond_k, p_k) in enumerate(
            zip(result.xs, residuals, errors, det_Js, cond_Js, p_vals)
        ):
            d_k, Ds_k = x_k
            if p_k is not None:
                out.write(
                    f"{k:4d}  {d_k * 1000:12.6e}  {Ds_k * 1000:12.6e}  "
                    f"{res_k:18.8e}  {err_k:18.8e}  "
                    f"{det_k:12.4e}  {cond_k:12.3e}  {p_k:12.6f}\n"
                )
            else:
                out.write(
                    f"{k:4d}  {d_k * 1000:12.6e}  {Ds_k * 1000:12.6e}  "
                    f"{res_k:18.8e}  {err_k:18.8e}  "
                    f"{det_k:12.4e}  {cond_k:12.3e}  {'-':>12}\n"
                )

    print(f"Results written to {results_file}")

    # [PLOT_START]
    # ============= Plot Setup =============
    plt.style.use("seaborn-v0_8-whitegrid")
    SMALL, MED, BIG = 11, 13, 14
    plt.rcParams.update(
        {
            "font.family": "serif",
            "font.size": MED,
            "axes.titlesize": BIG,
            "axes.labelsize": MED,
            "xtick.labelsize": SMALL,
            "ytick.labelsize": SMALL,
            "legend.fontsize": SMALL,
            "figure.dpi": 300,
        }
    )

    # ========= 1) Residual norm vs iteration (semilogy) =========
    fig_res, ax_res = plt.subplots(figsize=(6, 4))
    residuals = [np.linalg.norm(Fk, ord=2) for Fk in result.Fs]

    ax_res.semilogy(result.ns, residuals, "o-", lw=1.5, ms=5, label="System Newton")
    ax_res.set_xlabel(r"Iteration $k$")
    ax_res.set_ylabel(r"$\|F(x_k)\|_2$")
    ax_res.set_title(r"Residual norm vs iteration - Newton's method (system)")
    ax_res.xaxis.set_major_locator(ticker.MultipleLocator(1))
    ax_res.legend(frameon=False)
    fig_res.tight_layout()
    fig_res.savefig(
        plot_dir / "system_newton_residuals.png",
        dpi=300,
        bbox_inches="tight",
    )
```

```python
    # ========= 2) Error norm vs iteration (semilogy) =========
    fig_err, ax_err = plt.subplots(figsize=(6, 4))
    x_star = result.final_x
    errors = [np.linalg.norm(x_k - x_star, ord=2) for x_k in result.xs]

    ax_err.semilogy(
        result.ns,
        errors,
        "o-",
        lw=1.5,
        ms=5,
        label=r"$e_k = \|x_k - x^*\|_2$",
    )
    ax_err.set_xlabel(r"Iteration $k$")
    ax_err.set_ylabel(r"$\|x_k - x^*\|_2$")
    ax_err.set_title(r"Error norm vs iteration - Newton's method (system)")
    ax_err.xaxis.set_major_locator(ticker.MultipleLocator(1))
    ax_err.legend(frameon=False)
    fig_err.tight_layout()
    fig_err.savefig(
        plot_dir / "system_newton_errors.png",
        dpi=300,
        bbox_inches="tight",
    )

    # ========= Log-log plot of e_{k+1} vs e_k =========
    fig_ek, ax_ek = plt.subplots(figsize=(6, 4))
    e_k = np.array(errors[:-1])
    e_kp1 = np.array(errors[1:])

    ax_ek.loglog(
        e_k,
        e_kp1,
        "o-",
        lw=1.5,
        ms=5,
        label=r"Newton iterates",
    )
    ax_ek.set_xlabel(r"$e_k = \|x_k - x^*\|_2$")
    ax_ek.set_ylabel(r"$e_{k+1} = \|x_{k+1} - x^*\|_2$")
    ax_ek.set_title(r"Log-log plot of $e_{k+1}$ versus $e_k$")

    # Reference slopes p = 1 and p = 2 in the log-log plot
    ref_x = e_k[len(e_k) // 2]  # pick a mid error as reference (must be > 0)

    for p_ref, color, label in [
        (1.0, "gray", r"Reference $e_{k+1} \propto e_k^1$"),
        (2.0, "black", r"Reference $e_{k+1} \propto e_k^2$"),
    ]:
        ref_y = ref_x**p_ref
        x_line = np.array([ref_x / 10, ref_x * 10])
        y_line = ref_y * (x_line / ref_x) ** p_ref
        ax_ek.loglog(
            x_line,
            y_line,
            "--",
            color=color,
            lw=1,
            label=label,
        )
```

```python

    ax_ek.legend(frameon=False)
    fig_ek.tight_layout()
    fig_ek.savefig(
        plot_dir / "system_newton_loglog_errors.png",
        dpi=300,
        bbox_inches="tight",
    )

    # ========= Newton Path  =========
    fig_path, ax_path = plt.subplots(figsize=(6, 4))
    d_vals = [x[0] for x in result.xs]
    Ds_vals = [x[1] for x in result.xs]

    ax_path.plot(Ds_vals, d_vals, "o-", ms=5, lw=1.5, label="Newton path")
    ax_path.plot(Ds_vals[0], d_vals[0], "s", ms=7, label="Initial guess")
    ax_path.plot(Ds_vals[-1], d_vals[-1], "o", ms=7, label="Final iterate")

    ax_path.set_xlabel(r"$D_s$ (m)")
    ax_path.set_ylabel(r"$d$ (m)")
    ax_path.set_title(r"Newton iteration path in $(D_s, d)$-plane")
    ax_path.legend(frameon=False)
    fig_path.tight_layout()
    fig_path.savefig(
        plot_dir / "system_newton_path.png",
        dpi=300,
        bbox_inches="tight",
    )
    # [PLOT_END]


if __name__ == "__main__":
    main()
    plt.show()
```

Heat Sink – Newton's Method for non-linear system

Listing 3: Heat Sink – Newton's Method for non-linear system

```python
from dataclasses import dataclass
from pathlib import Path
from typing import Callable

import matplotlib.pyplot as plt
import numpy as np

# ============= Paths =============
ROOT = Path(__file__).parent
plot_dir: Path = ROOT / "Plots"
plot_dir.mkdir(exist_ok=True)


@dataclass
class NewtonSystemResult:
    """
    Result container for Newton's method applied to systems of nonlinear equations.

    Parameters
    ------
```

```
    xs : list[np.ndarray]
        Sequence of iterates x_k  in  R^n at each step (shape (n,) per iterate).
    Fs : list[np.ndarray]
        Sequence of residual vectors F(x_k)  in  R^n at each iteration.
    final_x : np.ndarray
        Final iterate x_*  in  R^n returned by the method (last element of xs).
    ns : list[int]
        Iteration indices corresponding to each x_k (typically [0, 1, ..., n]).
    """

    xs: list[np.ndarray]  # iterates x_k
    Fs: list[np.ndarray]  # F(x_k)
    final_x: np.ndarray  # x_* at termination
    ns: list[int]  # iteration indices


def newton_system(
    F_func: Callable,
    JF_func: Callable,
    x0: np.ndarray,
    tol: float,
    max_iter: int,
    args: tuple,
    jac_args: tuple | None = None,
) -> NewtonSystemResult:
    """
    Newton's method for systems of nonlinear equations.

    At each iteration k, solves the linear system
        JF(x_k) * delta = -F(x_k)
    for the correction delta, then updates
        x_{k+1} = x_k + delta,
    until ||F(x_k)||_2 <= tol or the iteration limit is reached.

    Parameters
    ----------
    F_func : Callable
        Vector-valued function F(x, *args) returning np.ndarray of shape (n,).
    JF_func : Callable
        Jacobian function JF(x, *jac_args) returning np.ndarray of shape (n, n).
    x0 : np.ndarray
        Initial guess vector x_0  in  R^n (shape (n,)).
    tol : float
        Convergence tolerance on the 2-norm ||F(x_k)||_2.
    max_iter : int
        Maximum allowed number of iterations.
    args : tuple
        Additional parameters passed to F_func.
    jac_args : tuple, optional
        Additional parameters passed to JF_func. Defaults to args if not provided.

    Returns
    -------
    NewtonSystemResult
    """
```

```python
    jac_args = jac_args if jac_args is not None else args

    x = x0.astype(float)
    xs = [x.copy()]
    Fx = F_func(x, *args)
    Fs = [Fx]
    ns = [0]

    for k in range(max_iter):
        if np.linalg.norm(Fx, ord=2) <= tol:
            break

        J = JF_func(x, *jac_args)
        delta = np.linalg.solve(J, -Fx)
        x = x + delta

        Fx = F_func(x, *args)

        xs.append(x.copy())
        Fs.append(Fx)
        ns.append(k + 1)

    return NewtonSystemResult(xs=xs, Fs=Fs, final_x=x, ns=ns)


# [PLOT_START]
# ============= Plot Setup =============
plt.style.use("seaborn-v0_8-whitegrid")
SMALL, MED, BIG = 11, 13, 14
plt.rcParams.update(
    {
        "font.family": "serif",
        "font.size": MED,
        "axes.titlesize": BIG,
        "axes.labelsize": MED,
        "xtick.labelsize": SMALL,
        "ytick.labelsize": SMALL,
        "legend.fontsize": SMALL,
        "figure.dpi": 500,
    }
)
# [PLOT_END]
# ============= Model Definition =============


def make_A(N: int) -> np.ndarray:
    """(N-1) x (N-1) FD matrix with -2 on diagonal, +1 on off-diagonals."""
    n = N - 1
    return (
        np.diag([-2] * n) + np.diag([1] * (n - 1), k=1) + np.diag([1] * (n -
            1), k=-1)
    )


def f(T: float, T_inf: float) -> float:
    return T**4 - T_inf**4


def f_prime(T: float) -> float:
    return 4 * T**3

```

```python

def interior_grid(N: int, L: float) -> np.ndarray:
    """Interior grid points x_1, ..., x_{N-1}."""
    h = L / N
    return np.linspace(h, L - h, N - 1)


def rhs_vector(
    a: float,
    b: float,
    h: float,
    T_s: float,
    T_L: float,
    T: np.ndarray,
    T_inf: float,
    f: callable,
) -> np.ndarray:
    """RHS vector r(T), same shape as T."""
    rhs = h**2 * (a * (T - T_inf) + b * np.vectorize(f)(T, T_inf))
    rhs[0] -= T_s
    rhs[-1] -= T_L
    return rhs


def F_func(
    T: np.ndarray,
    A: np.ndarray,
    a: float,
    b: float,
    h: float,
    T_s: float,
    T_L: float,
    T_inf: float,
    f: callable,
) -> np.ndarray:
    return A @ T - rhs_vector(a, b, h, T_s, T_L, T, T_inf, f)


def JF_func(
    T: np.ndarray,
    A: np.ndarray,
    a: float,
    b: float,
    h: float,
    f_prime: callable,
) -> np.ndarray:
    d = -(h**2) * (a + b * np.vectorize(f_prime)(T))
    return A + np.diag(d)


def discrete_2_norm(r_vec: np.ndarray) -> float:
    """Discrete 2-norm (eq. 17): sqrt(1/(N-1) * sum |r_k|^2)."""
    return np.sqrt(np.sum(r_vec**2) / (len(r_vec) - 1))


def solve(
    N: int,
    L: float,
    a: float,
    b: float,
    T_s: float,
```

```python
    T_L: float,
    T_inf: float,
) -> tuple:
    """Run Newton solver and return (result, x_grid)."""
    h = L / N
    A_mat = make_A(N)
    T0 = np.linspace(T_s, T_L, N - 1)
    result = newton_system(
        F_func,
        JF_func,
        T0,
        tol=1e-10,
        max_iter=1000,
        args=(A_mat, a, b, h, T_s, T_L, T_inf, f),
        jac_args=(A_mat, a, b, h, f_prime),
    )
    return result, interior_grid(N, L)


# ============= 8.3 =============


def run_83() -> None:
    # ------------- Parameters (Table 3) -------------
    h_c: float = 40
    K: float = 240
    D: float = 4.13e-3
    T_s: float = 450
    T_inf: float = 293
    T_L: float = T_inf
    L: float = 2.5

    a: float = (4 * h_c) / (D * K)  # alpha_1
    b: float = 0.0  # alpha_2 = 0

    Ns: list[int] = [50 * 2**k for k in range(5)]  # [50, 100, 200, 400, 800]
    N_main: int = 400

    results = {}
    grids = {}
    for N in Ns:
        results[N], grids[N] = solve(N, L, a, b, T_s, T_L, T_inf)

    # ------------- 8.3.a: N=400 vs analytical -------------
    T_num = results[N_main].final_x
    x_grid = grids[N_main]
    T_exact = T_inf + (T_s - T_inf) * np.exp(-np.sqrt(a) * x_grid)
    r_vec = T_num - T_exact
    e_400 = discrete_2_norm(r_vec)

    print("=== 8.3.a ===")
    print(f"Converged in {len(results[N_main].ns) - 1} iterations")
    print(f"Discrete 2-norm ||r||_2 = {e_400:.3e} K")
    print(f"Max pointwise error:      {np.abs(r_vec).max():.3e} K")
    print(f"Error at x=h:             {np.abs(r_vec[0]):.3e} K")
    print(f"Error at x=L-h:           {np.abs(r_vec[-1]):.3e} K")

    fig1, ax1 = plt.subplots(figsize=(7, 4))
    ax1.plot(x_grid, T_num, lw=1.5, label=f"Numerical (FD, N={N_main})")
```

```python
    ax1.plot(x_grid, T_exact, lw=1.0, linestyle="--", label="Analytical (eq. 16)")
    ax1.set_xlabel(r"$x$ (m)")
    ax1.set_ylabel(r"$T(x)$ (K)")
    ax1.set_title(
        r"Temperature distribution - numerical vs analytical ($\alpha_2 = 0$)"
    )
    ax1.legend(frameon=False)
    fig1.tight_layout()
    fig1.savefig(plot_dir / "8_3a_solution.png", bbox_inches="tight")

    fig2, ax2 = plt.subplots(figsize=(7, 4))
    ax2.plot(x_grid, np.abs(r_vec), lw=1.5)
    ax2.set_xlabel(r"$x$ (m)")
    ax2.set_ylabel(r"$|T_{\mathrm{num}} - T_{\mathrm{exact}}|$ (K)")
    ax2.set_title(r"Pointwise error over $[0, L]$")
    fig2.tight_layout()
    fig2.savefig(plot_dir / "8_3a_error.png", bbox_inches="tight")

    # ------------- 8.3.b: Convergence study -------------
    print("\n=== 8.3.b ===")
    norms = []
    for N in Ns:
        T_num_N = results[N].final_x
        T_exact_N = T_inf + (T_s - T_inf) * np.exp(-np.sqrt(a) * grids[N])
        norms.append(discrete_2_norm(T_num_N - T_exact_N))

    # Order of accuracy: eN = Ch^p = C(L/N)^p -> p = log(e_k/e_{k+1}) / log(N_{k+1}/N_k)
    orders = [None] + [
        np.log(norms[k - 1] / norms[k]) / np.log(Ns[k] / Ns[k - 1])
        for k in range(1, len(Ns))
    ]

    print(f"\n{'N':>6}  {'e_N':>12}  {'order p':>10}")
    print("-" * 34)
    for N, e, p in zip(Ns, norms, orders):
        p_str = f"{p:.4f}" if p is not None else "-"
        print(f"{N:>6}  {e:>12.4e}  {p_str:>10}")

    fig3, ax3 = plt.subplots(figsize=(7, 4))
    ax3.semilogy(Ns, norms, "o-", lw=1.0, ms=3, label=r"$e_N$")
    ref = norms[0] * (Ns[0] / np.array(Ns)) ** 2
    ax3.semilogy(
        Ns, ref, "--", lw=1, color="crimson", label=r"$\mathcal{O}(N^{-2})$ reference"
    )
    ax3.set_xlabel(r"$N$")
    ax3.set_ylabel(r"$e_N$")
    ax3.set_title(r"Discrete 2-norm error $e_N$ vs $N$")
    ax3.set_xticks(Ns)
    ax3.legend(frameon=False)
    fig3.tight_layout()
    fig3.savefig(plot_dir / "8_3b_convergence.png", bbox_inches="tight")


# ============= 8.4 =============


def run_84() -> None:
```

```python
    # ------------- Parameters (8.4) -------------
    sigma: float = 5.67e-8
    D: float = 5.0e-3
    T_s: float = 373.15
    T_inf: float = 293.15
    T_L: float = T_inf
    L_84a: float = 0.30  # length for 8.4.a
    N: int = 400

    # ------------- Table 4 -------------
    materials = ["SS AISI 316", "Aluminium (Al)", "Copper (Cu)"]
    Ks: list[float] = [14, 180, 398]
    h_cs: list[float] = [100, 100, 100]
    epss: list[float] = [0.17, 0.82, 0.03]

    # ============= 8.4 Calculations =============
    L_tests: list[float] = [L_84a] + [0.1 + k for k in np.linspace(0, 1, 10)
        ]

    results_84: dict[str, dict[float, np.ndarray]] = {}
    grids_84: dict[str, dict[float, np.ndarray]] = {}

    for mat, K_i, h_c_i, eps_i in zip(materials, Ks, h_cs, epss):
        results_84[mat] = {}
        grids_84[mat] = {}

        a_i = (4 * h_c_i) / (D * K_i)
        b_i = (4 * eps_i * sigma) / (D * K_i)

        for L in L_tests:
            result, x_grid = solve(N, L, a_i, b_i, T_s, T_L, T_inf)
            results_84[mat][L] = result
            grids_84[mat][L] = x_grid

    # ------------- 8.4.a Results -------------
    print("\n=== 8.4.a ===")

    L_first = L_tests[0]

    fig4, ax4 = plt.subplots(figsize=(7, 4))

    for mat in materials:
        result = results_84[mat][L_first]
        x_grid = grids_84[mat][L_first]

        print(f"{mat}: converged in {len(result.ns) - 1} iterations")

        ax4.plot(x_grid, result.final_x, lw=1.5, label=mat)

    ax4.set_xlabel(r"$x$ (m)")
    ax4.set_ylabel(r"$T(x)$ (K)")
    ax4.set_title(r"Temperature distribution for different materials ($N=400
        $)")
    ax4.legend(frameon=False)
    fig4.tight_layout()
    fig4.savefig(plot_dir / "8_4a_materials.png", bbox_inches="tight")

    # ------------- 8.4.b Results -------------
    tol_frac = 0.01  # e.g. 1% error

    print("\n=== 8.4.b ===")
```

```python

    for mat in materials:
        # Sort lengths to have a clear order
        Ls_sorted = sorted(L_tests)
        L_ref = Ls_sorted[-1]  # longest length as 'infinite' reference (good enough)

        # Reference solution for this material
        result_ref = results_84[mat][L_ref]
        x_ref = grids_84[mat][L_ref]
        T_ref = result_ref.final_x

        # Compute relative error for each shorter length
        rel_errs = {}
        for L in Ls_sorted[:-1]:  # exclude L_ref
            result_L = results_84[mat][L]
            x_L = grids_84[mat][L]
            T_L = result_L.final_x

            # Interpolate reference onto x_L
            T_ref_on_L = np.interp(x_L, x_ref, T_ref)

            diff = T_L - T_ref_on_L
            err = discrete_2_norm(diff)
            ref_norm = discrete_2_norm(T_ref_on_L)
            rel_err = err / ref_norm if ref_norm > 0 else 0.0

            rel_errs[L] = rel_err

        # Pick smallest L with rel_err < tol_frac
        L_min = next((L for L in Ls_sorted[:-1] if rel_errs[L] < tol_frac), None)

        print(f"\n{mat}: reference length L_ref = {L_ref:.2f} m")
        print(f"  {'L (m)':>8}  {'rel_err':>12}  {'converged':>10}")
        print("  " + "-" * 34)
        for L in Ls_sorted[:-1]:
            re = rel_errs[L]
            print(f"  {L:>8.2f}  {re:>12.4e}  {'yes' if re < tol_frac else 'no':>10}")
        print(rf"  -> Estimated L_min \approx {L_min} m")

        # [PLOT_START]
        # Plot profile comparison for this material
        fig, ax = plt.subplots(figsize=(7, 4))
        ax.plot(x_ref, T_ref, "k--", lw=1.5, label=f"Reference (L={L_ref:.2f} m)")

        for L in Ls_sorted[:-1]:
            result_L = results_84[mat][L]
            x_L = grids_84[mat][L]
            T_L = result_L.final_x
            re = rel_errs[L]
            converged = re < tol_frac

            label = f"L={L:0.2f} m  (err={re:0.2e}){'  conv' if converged else '  div'}"
            ax.plot(x_L, T_L, lw=1.0, label=label)
            ax.set_xlim(right=0.4)

        ax.set_xlabel(r"$x$ (m)")
```

```
        ax.set_ylabel(r"$T(x)$ (K)")
        ax.set_title(f"Finite vs 'infinite' heat sink profiles   {mat}")
        ax.legend(frameon=False, fontsize=8)
        fig.tight_layout()
        fig.savefig(
            plot_dir / f"8_4b_{mat.replace(' ', '_')}.png",
            bbox_inches="tight",
        )
        # [PLOT_END]


# ============= Entry Point =============


def main() -> None:
    run_83()
    run_84()
    plt.show()


if __name__ == "__main__":
    main()
```