

Project 5 Documentation

Jason Otter, Eric Van Der Roest, Jordan Wermuth

In this API, there are two routes, and two ways to use each of them:

Note: POST requests **must** have header: **content-type: application/json**

Sending/Retrieving DMs for a particular user:

> /users/<username>/dms

a) **listDirectMessagesFor(username)**

GET: Returns a json object with the DMs for the given username

Interacting with this endpoint only requires the ***username to be supplied in the request url.***

b) **sendDirectMessage(to, from, message)**

POST: Send a DM to a user with the following

Interacting with this endpoint requires ***the recipient to be supplied in the request url,*** and the sender/message to be provided in the request body like so:

```
{
  "from": "some_user",
  "message": "some message"
}
```

Optionally, ***quick replies*** can be used like so:

Note: If using ***quick replies***, remember the keys used when replying to a DM.

```
{
  "from": "some_user",
  "message": "some message"
  "quickReplies": {
    "1": "quick reply 1",
    "2": "quick reply 2",
    "3": "quick reply 3"
  }
}
```

Sending/Receiving Replies for a particular DM:

> /dms/<id>/replies

a) **listRepliesTo(messageId)**

GET: Returns replies to the given message by ID

Interacting with this endpoint only requires the *message id to be supplied in the request url*.

b) **replyToDirectMessage(messageId, reply)**

POST: Reply to a DM with the supplied ID

Interacting with this endpoint requires *the message id to be in the url*, and the reply to be provided in the request body like so:

Note: If using *quick replies*, just provide the key that corresponds to the desired response

```
{  
    "message": "your_reply_here"  
}
```