

# Hamiltonian Simulation for Physical Systems: A Comparative Study of Trotterization and Advanced Methods

Eric Kim                      Michael Lee

C191A: Introduction to Quantum Computing, Fall 2025

## 1 Introduction: Problem Definition & Key Question

The simulation of quantum systems is a foundational application of quantum computing, first envisioned by Richard Feynman. Many important problems in quantum chemistry and condensed matter physics involve understanding the behavior of quantum systems, which is governed by a Hamiltonian operator,  $H$ . Classically simulating the time evolution of these systems, described by the Schrödinger equation, is often an intractable problem. The state of an  $N$ -qubit system resides in a  $2^N$ -dimensional Hilbert space, and classical methods struggle to store and manipulate the state vectors or matrices involved.

A quantum computer, by its very nature, is well-suited to this task. The core problem of digital quantum simulation is to develop an efficient quantum algorithm that approximates the time-evolution operator,

$$U(t) = e^{-iHt},$$

for a given Hamiltonian and a specified evolution time  $t$ . An efficient algorithm allows us to prepare an initial state  $|\psi(0)\rangle$  and evolve it to a final state  $|\psi(t)\rangle = U(t)|\psi(0)\rangle$ , from which we can measure physical observables to understand the system's dynamics or properties.

This project focuses on the practical application and analysis of such algorithms. We will explore how different simulation techniques can be used to model realistic physical systems and what their fundamental trade-offs are. This leads to our key question:

*How can digital quantum simulation be used to model the properties of physical systems like the  $H_2$  molecule and the Heisenberg spin chain, and what are the fundamental trade-offs between foundational algorithms like Trotterization and state-of-the-art methods like LCU/QSP in terms of accuracy and quantum resources?*

## 2 Prior Work: The Foundational Method of Trotter-Suzuki Decomposition

To simulate physical systems on a quantum computer, the problem must first be mapped to a qubit representation. For systems involving fermions, such as the electronic structure of the  $H_2$  molecule, the Hamiltonian is first expressed in second quantization. This

fermionic Hamiltonian must then be mapped onto a system of qubits using a transformation such as the Jordan–Wigner or Bravyi–Kitaev transformation. The resulting qubit Hamiltonian is typically a sum of many simple terms, often Pauli strings:

$$H = \sum_k H_k.$$

The primary challenge in implementing the evolution operator  $e^{-iHt}$  is that the terms  $H_k$  in the sum do not, in general, commute with each other. This means that

$$e^{-i(\sum_k H_k)t} \neq \prod_k e^{-iH_k t}.$$

While the individual exponentials  $e^{-iH_k t}$  are easy to implement with quantum gates, the exponential of the sum is not.

The standard and foundational solution to this problem is the Trotter–Suzuki decomposition. This method approximates the desired evolution by breaking the total time  $t$  into  $n$  small steps of duration  $\Delta t = t/n$ . For each small step, the evolution is approximated by a product of the individual evolutions. The first-order Trotter formula is given by:

$$e^{-iHt} = e^{-i(\sum_k H_k)t} \approx \left( \prod_k e^{-iH_k t/n} \right)^n.$$

The error in this approximation, known as the *Trotter error*, is proportional to  $(t^2/n)$  and depends on the commutators of the Hamiltonian terms. To achieve a desired simulation accuracy  $\epsilon$ , the number of Trotter steps  $n$  must be increased, which in turn increases the depth and gate count of the quantum circuit. Higher-order Trotter formulas (e.g., second-order) exist that provide a more accurate approximation for each step, reducing the total number of steps required but increasing the complexity of each individual step. Trotterization remains the cornerstone of many digital quantum simulation proposals due to its straightforward implementation.

### 3 State of the Art: Advanced Simulation Techniques Beyond Trotterization

While Trotter–Suzuki methods are foundational, their resource scaling with respect to the desired simulation precision ( $\epsilon$ ) can be inefficient, often scaling polynomially as  $1/\epsilon$ . This has driven the development of more advanced algorithms that can achieve significantly better performance, particularly for high-precision simulations.

A major breakthrough in this area came from a class of algorithms based on *Linear Combination of Unitaries (LCU)* and *Quantum Signal Processing (QSP)*. A landmark paper by Berry, Childs, and Kothari (2015) presented a Hamiltonian simulation algorithm with a complexity that is nearly optimal in all relevant parameters.

The key features of these advanced methods are as follows:

#### Improved Precision Scaling

The most significant advantage is the improvement in how the cost scales with precision. Instead of a polynomial dependence on  $1/\epsilon$ , these algorithms achieve a cost that

grows nearly logarithmically with  $1/\epsilon$ , specifically as  $\tilde{O}(\log(1/\epsilon))$ . This represents an exponential speedup for high-precision simulations.

## Novel Techniques

These algorithms move beyond the simple product-formula approach of Trotterization. They use more sophisticated quantum primitives. The Berry et al. algorithm, for instance, combines ideas from quantum walks with an LCU-based method that implements a truncated Taylor series of the evolution operator. This allows for a much more efficient phase approximation than Trotterization.

## Trade-offs

While these state-of-the-art methods offer superior asymptotic scaling, their implementation can be more complex and may involve larger overhead in terms of qubit count or gate complexity for small problems. Understanding the crossover point where these advanced methods become more practical than simpler Trotter-based approaches remains an active area of research.

## 4 Proposed Project Scope

This project will provide a hands-on exploration of these concepts. Our group will use the **Qiskit** framework to implement and analyze Hamiltonian simulation for two distinct physical systems:

1. **Quantum Chemistry (Static Property):** We will generate the electronic structure Hamiltonian for the  $H_2$  molecule and use Trotter-based time evolution (within an iterative phase estimation algorithm) to calculate its ground state energy.
2. **Condensed Matter Physics (Dynamics):** We will construct the Hamiltonian for a 3- to 4-qubit Heisenberg spin chain and simulate the time-evolution of physical observables, such as local magnetization, starting from an initial state like  $|100\dots\rangle$ .

Our analysis will focus on the practical trade-offs of the Trotter method. We will produce energy error curves as a function of Trotter steps for the  $H_2$  simulation and visualize the spin dynamics of the Heisenberg model with heatmaps. By comparing our practical implementation with a theoretical analysis of advanced methods like QSP/LCU, we aim to gain a concrete understanding of the resource requirements and accuracy limitations of digital quantum simulation.