

Introduction to Backbone.js

8th Light University
Mike Jansen



Goals



An Immediate Digression on Javascript











Backbone.is



Jeremy Ashkenas





Structure



Model

```
var Task = Backbone.Model.extend({
  defaults: {
    'complete': false
  }
});
```



Model

```
var task = new Task({
  description: "Set up lightning rod on
  top of laboratory"
});
task.get("description");

> "set up lightning rod on top of
laboratory"
```



Collection

```
var Tasks = Backbone.Collection.extend({
   model: Todo.models.Task,
   url: "tasks"
});
```



Collection

```
var tasks = new Tasks();
tasks.create(
{
  description: "Dig up some brains at the cemetery"
});
```



Pick and Choose



```
var TodoRouter = new
Backbone.Router.extend({
  initialize: function(options) {
    this.tasks = new Tasks(options.tasks)
    this.tasksView = new
    TasksView({collection: this.tasks});
  },
...
```



routes: {
 "": "loadTasks",
 "tasks/:id/edit": "editTask"
},



editTask: function(id) {
 var view = new TaskEditView({id: id,
 collection: this.tasks});
 view.render();
}
);



```
Todo.router = new TodoRouter(options);
Backbone.history.start();
```



0

www.drfrankenstein.com/todo#tasks/34/edit



So...







What about the







"...more convention than they are code"



```
var TasksView = Backbone.View.extend({
  tagName: 'div',
  className: 'task-list',
```

• • •



```
events: {
  'keyup #new-task' : 'createOnEnter'
},
```



```
createOnEnter : function (event) {
    ...
    this.collection.create({ description:
    inputValue });
    ...
},
```



```
render : function () {
  this.collection.each(this.addTask);
  return this;
},
```



```
addTask: function (task) {
  var view = new
   Todo.views.TaskView({ model: task});
  var taskEl = view.render().el;
  $('.tasks').prepend(taskEl);
},
```




Summary











Homework

Enhance this todo app:

https://github.com/mjansen401/todo

-Complete tasks

-Remove tasks

-Add due date

-Clear completed tasks