


The First Monad Tutorial


Philip Wadler

University of Edinburgh

YOW! Melbourne, Brisbane, Sydney

December 2013







monads are burritos?



and functors?



-
1. remove astronaut from suit
 2. put naked astronaut in station
 3. send out whatever the station sends out (well... almost)








makeameme.org


BRACE YOURSELVES



memegenerator.net



Amount of known monad tutorials



Church and State 1: Evaluating monads

Philip Wadler

~~University of Glasgow~~

Bell Labs, Lucent Technologies



Pure vs. impure

| Modification | Impure language (Standard ML, Scheme) | Pure language (Miranda*, Haskell†) |
|------------------|---|--|
| Error messages | use exceptions | rewrite |
| Execution counts | use state | rewrite |
| Output | use output | rewrite |
| Backwards output | rewrite | modify output |

*Miranda is a trademark of Research Software Limited.

†Haskell is not a trademark.

Variations on an evaluator

monad *n.* 1. *Philosophy* a. any fundamental entity, esp. if autonomous.

– *Collins English Dictionary*

Variation zero: The basic evaluator

```
data Term = Con Int | Div Term Term  
eval      :: Term → Int  
eval(Con a) = a  
eval(Div t u) = eval t ÷ eval u
```

Using the evaluator

Test data:

```
answer, error :: Term
answer          = (Div (Div (Con 1972) (Con 2)) (Con 23))
error           = (Div (Con 1) (Con 0))
```

A sample run:

```
?eval answer
42

?eval error
<BOOM!>
```

Variation one: Exceptions

```
data M a      = Raise Exception | Return a
type Exception = String

eval          :: Term → M Int
eval (Con a)   = Return a
eval (Div t u) = case eval t of
                    Raise e → Raise e
                    Return a →
                      case eval u of
                        Raise e → Raise e
                        Return b →
                          if b = 0
                            then Raise "divide by zero"
                            else Return (a ÷ b)
```

Using the evaluator

A sample run:

?eval answer

Return 42

?eval error

Raise "divide by zero"

Variation two: State

```
type Ma      = State → (a, State)
type State   = Int
eval         :: Term → M Int
eval (Con a) x = (a, x)
eval (Div t u) x = let (a, y) = eval t x in
                   let (b, z) = eval u y in
                     (a ÷ b, z + 1)
```

Using the evaluator

Test data:

```
answer :: Term  
answer = (Div (Div (Con 1972) (Con 2)) (Con 23))
```

A sample run:

```
?eval answer 0  
(42, 2)
```

Variation three: Output

```
type Ma      = (Output, a)
type Output = String

eval          :: Term → M Int
eval (Con a)  = (line (Con a) a, a)
eval (Div t u) = let (x, a) = eval t in
                  let (y, b) = eval u in
                  (x ++ y ++ line (Div t u) (a ÷ b), a ÷ b)

line          :: Term → Int → Output
line t a      = showterm t ++ " = " ++ showint a ++ " ←"
```

Using the evaluator

A sample run:

```
?eval answer
( "Con 1972 = 1972←
Con 2 = 2←
Div (Con 1972) (Con 2) = 986←
Con 23 = 23←
Div (Div (Con 1972) (Con 2)) (Con 23)) = 42←
", 42)
```

Changing output order

Replace

$x \text{ ++ } y \text{ ++ } \text{line}(\text{Div } t \ u)(a \div b)$

with

$\text{line}(\text{Div } t \ u)(a \div b) \text{ ++ } y \text{ ++ } x.$

Modified sample run:

```
?eval answer
("Div (Div (Con 1972) (Con 2)) (Con 23)) = 42←
Con 23 = 23←
Div (Con 1972) (Con 2) = 986←
Con 2 = 2←
Con 1972 = 1972←
", 42)
```

Monads

monad *n.* **1. b.** (in the metaphysics of Leibnitz) a simple indestructible nonspatial element regarded as the unit of which reality consists.

– *Collins English Dictionary*

What is a monad?

1. For each type a of *values*, a type $M a$ to represent *computations*.

In general, $a \rightarrow b$ becomes $a \rightarrow M b$.

In particular, $\text{eval} :: \text{Term} \rightarrow \text{Int}$ becomes $\text{Term} \rightarrow M \text{Int}$.

2. A way to turn values into computations.

$\text{unit} :: a \rightarrow M a$

3. A way to combine computations.

$(*) :: M a \rightarrow (a \rightarrow M b) \rightarrow M b$

Compare \star with **let**

$$\frac{\Gamma \vdash m :: Ma \quad \Gamma, x :: a \vdash n :: Mb}{\Gamma \vdash (m \star \lambda x. n) :: Mb}$$

$$\frac{\Gamma \vdash m :: a \quad \Gamma, x :: a \vdash n :: b}{\Gamma \vdash (\text{let } x = m \text{ in } n) :: b}$$

Monad laws

Left unit

$$\text{unit } x * \lambda y. n = n[x/y]$$

Right unit

$$m * \lambda x. \text{unit } x = m$$

Associative (when x is not free in o).

$$m * (\lambda x. n * \lambda y. o) = (m * \lambda x. n) * \lambda y. o$$

These resemble the laws for a *monoid*, except for λ binding.

Monad Laws

$$return v \gg= \lambda x. k x = k v$$

$$m \gg= \lambda x. return x = m$$

$$m \gg= (\lambda x. k x \gg= (\lambda y. h y)) = (m \gg= (\lambda x. k x)) \gg= (\lambda y. h y)$$

Do notation

$$\left(\begin{array}{c} \text{do } x \leftarrow return v \\ \quad k x \\ \left(\begin{array}{c} \text{do } x \leftarrow m \\ \quad return x \end{array} \right) \end{array} \right) = k v$$

$$= m$$

$$\left(\begin{array}{c} \text{do } y \leftarrow \text{do } x \leftarrow m \\ \quad k x \\ \quad h y \end{array} \right) = \left(\begin{array}{c} \text{do } x \leftarrow m \\ \quad y \leftarrow k x \\ \quad h y \end{array} \right)$$

The evaluator revisited

monad *n.* 1. c. (in the pantheistic philosophy of Giordano Bruno) a fundamental metaphysical unit that is spatially extended and psychically aware.

– *Collins English Dictionary*

Monadic evaluator

$\text{eval} :: \text{Term} \rightarrow M \text{Int}$

$\text{eval}(\text{Con } a) = \text{unit } a$

$\text{eval}(\text{Div } t u) = \text{eval } t * \lambda a. \text{eval } u * \lambda b. \text{unit } (a \div b)$

Variation zero, revisited: The basic evaluator

```
type Ma = a
unit      :: a → Ma
unit a    = a
(*)       :: Ma → (a → Mb) → Mb
a * k     = ka
```

Variation one, revisited: Exceptions

```
data M a      = Raise Exception | Return a
type Exception = String
unit          :: a → M a
unit a        = Return a
(*)           :: M a → (a → M b) → M b
m * k         = case m of
                  Raise e → Raise e
                  Return a → k a
raise         :: Exception → M a
raise e       = Raise e
```

Modifying the evaluator

```
eval          :: Term → M Int
eval(Con a)   = unit a
eval(Div t u) = eval t * λa.
                  eval u * λb.
                  if b = 0
                      then raise "divide by zero"
                      else unit(a ÷ b)
```

Variation two, revisited: State

```
type Ma    = State → (a, State)
type State = Int

unit          :: a → Ma
unit a        = λx.(a, x)

(*)           :: Ma → (a → Mb) → Mb
m ∗ k         = λx.let (a, y) = mx in
                  let (b, z) = kay in
                  (b, z)

tick          :: M()
tick          = λx.(((), x + 1))
```

Modifying the evaluator

```
eval      :: Term → M Int
eval(Con a) = unit a
eval(Div t u) = eval t * λa.
                  eval u * λb.
                  tick * λ().
                  unit(a ÷ b)
```

Variation three, revisited: Output

```
type Ma      = (Output, a)
type Output = String

unit          :: a → Ma
unit a        = ("", a)

(*)           :: Ma → (a → Mb) → Mb
m ∗ k         = let (x, a) = m in
                  let (y, b) = k a in
                  (x ++ y, b)

out           :: Output → M()
out x         = (x, ())
```

Modifying the evaluator

```
eval      :: Term → MInt
eval(Con a) = out(line(Con a)a)           ★λ().
                           unit a
eval(Div t u) = eval t                   ★λa.
                           eval u                   ★λb.
                           out(line(Div t u)(a ÷ b))★λ().
                           unit(a ÷ b)
```

Changing output order

$$\begin{aligned} (*) \quad :: \quad & M a \rightarrow (a \rightarrow M b) \rightarrow M b \\ m * k \ = \ & \text{let } (x, a) = m \text{ in} \\ & \text{let } (y, b) = k a \text{ in} \\ & (y ++ x, b) \end{aligned}$$

Conclusions

monad *n.* 2. a single-celled organism, especially a flagellate protozoan

– *Collins English Dictionary*

The Glasgow Haskell compiler

Joint work with

Cordy Hall, Kevin Hammond,
Will Partain, Simon Peyton Jones.

Glasgow Haskell compiler is written in Haskell.

Each phase uses a monad.

Has proved easy to modify in practice.

Monads in the Glasgow Haskell compiler

Type inference phase.

- Exceptions for errors,
- state for current substitution,
- state for fresh variable names,
- read-only state for current location.

Simplification phase.

- State for fresh variable names.

Code generator phase.

- Output for code generated so far,
- state for table mapping variables to addressing modes,
- state for table to cache known state of stack.

Origins

Eugenio Moggi, *Computational λ -calculus and monads*, 1989.

values (*int*) vs. computations ($T \text{ int}$)

call-by-value ($\text{int} \rightarrow T \text{ int}$)

call-by-name ($T \text{ int} \rightarrow T \text{ int}$)

Michael Spivey, *A functional theory of exceptions*, 1990.

John Reynolds, *The essence of Algol*, 1981.

data types (*int*) vs. phrase types (int exp)

call-by-value ($\text{int} \rightarrow \text{int exp}$)

call-by-name ($\text{int exp} \rightarrow \text{int exp}$)

But Reynolds missed *unit* and \star .

monadism or monadology *n.* (esp. in writings of Leibnitz) the philosophical doctrine that monads are the ultimate units of reality.

– *Collins English Dictionary*

Monads

$$(1) \quad \text{return } v \gg= \lambda x. k \ x = k \ v$$

$$(2) \quad m \gg= \lambda x. \text{return } x = m$$

$$(3) \quad m \gg= (\lambda x. k \ x \gg= (\lambda y. h \ y)) = (m \gg= (\lambda x. k \ x)) \gg= (\lambda y. h \ y)$$

- Eugenio Moggi, Computational Lambda Calculus and Monads, *Logic in Computer Science*, 1989.
- Philip Wadler, Comprehending Monads, *International Conference on Functional Programming*, 1990.
- Philip Wadler, The Essence of Functional Programming, *Principles of Programming Languages*, 1992.

Arrows

(1)

$$\text{arr } id \ggg f = f$$

(2)

$$f \ggg \text{arr } id = f$$

(3)

$$(f \ggg g) \ggg h = f \ggg (g \ggg h)$$

(4)

$$\text{arr } (g \cdot f) = \text{arr } f \ggg \text{arr } g$$

(5)

$$\text{first } (\text{arr } f) = \text{arr } (f \times id)$$

(6)

$$\text{first } (f \ggg g) = \text{first } f \ggg \text{first } g$$

(7)

$$\text{first } f \ggg \text{arr } (id \times g) = \text{arr } (id \times g) \ggg \text{first } f$$

(8)

$$\text{first } f \ggg \text{arr } fst = \text{arr } fst \ggg f$$

(9)

$$\text{first } (\text{first } f) \ggg \text{arr } assoc = \text{arr } assoc \ggg \text{first } f$$

- John Hughes, Generalising Monads to Arrows, *Science of Computer Programming*, 2000.

Idioms (Applicative Functors)

$$(1) \quad u = \text{pure } id \otimes u$$

$$(2) \quad \text{pure } f \otimes \text{pure } p = \text{pure } (f \ p)$$

$$(3) \quad u \otimes (v \otimes w) = \text{pure } (\cdot) \otimes u \otimes v \otimes w$$

$$(4) \quad u \otimes \text{pure } x = \text{pure } (\lambda f. f \ x) \otimes u$$

- Conor McBride and Ross Patterson, Applicative Programming with Effects, *Journal of Functional Programming*, 2008.

