

Predictive Modeling of Fluid Flows Using Conditional Score-Based Diffusion Models

Wilfried Genuist^{1,2}, Éric Savin¹, Filippo Gatti², Didier Clouteau²

¹Université Paris-Saclay, ONERA, 91120 Palaiseau, France

²Université Paris-Saclay, CentraleSupélec, ENS Paris-Saclay, CNRS, LMPS-Laboratoire de Mécanique Paris-Saclay,
91190 Gif-sur-Yvette, France


wilfried.genuist@{centralesupelec,onera}.fr



Sorbonne Université, Paris, France, December 19th, 2024

Using Machine Learning in CFD

- ▶ Accelerating direct numerical simulations: improving discretization schemes, correcting coarse-resolution simulations, reducing the computational domain...
- ▶ Improving turbulence closure models (RANS), subgrid-scale models (LES), wall models, ROMs, DMD;
- ▶ Reconstructing complex flows: filling space-wave number and/or time-frequency gaps (e.g. super-resolution), inverse problems in optimization or control...



From M. Buziccotti, *Europhys. Lett.* **142**, 23001 (2023)

- ▶ Supervised learning: $\hat{\mathbf{y}} \simeq \arg \max_{\theta} p_{\theta}(\mathbf{y}|\mathbf{X} = \hat{\mathbf{x}})$ where $p_{\theta}(\mathbf{y}|\mathbf{x})$ is trained from a dataset $\{\mathbf{X}_i, \mathbf{Y}_i\}_{i=1}^N$;
- ▶ Unsupervised learning: $\hat{\mathbf{x}} \simeq \arg \max_{\theta} p_{\theta}(\mathbf{x})$ where $p_{\theta}(\mathbf{x})$ is trained from a dataset $\{\mathbf{X}_i\}_{i=1}^N$;
- ▶ Unsupervised learning can be made supervised by conditioning the inference $\hat{\mathbf{x}} \simeq \arg \max_{\theta} p_{\theta}(\mathbf{x}|\mathbf{Y} = \hat{\mathbf{y}})$ whenever $p_{\theta}(\mathbf{x}, \mathbf{y})$ is trained from a dataset $\{\mathbf{X}_i, \mathbf{Y}_i\}_{i=1}^N$;
- ▶ Generative adversarial networks (GANs), variational auto-encoders (VAEs), normalizing flows, generative diffusion models... aim at computing and sampling complex **conditional distributions** on (very) high-dimensional sets;
- ▶ **This talk:** predicting missing data in fluid flows by conditional inference using generative diffusion models.

- ▶ **Step #1:** modeling $\{p_\theta(\mathbf{x})\}_\theta$ or $\{p_\theta(\mathbf{x}|\mathbf{y})\}_\theta$ —typically Gibbs distributions $p_\theta(\mathbf{x}) = e^{F_\theta - U_\theta(\mathbf{x})}$ with internal energy $U_\theta(\mathbf{x})$ and free energy F_θ , or stationary distributions of Markov processes, beyond Gaussian distributions $U_\theta(\mathbf{x}) = \frac{1}{2}\mathbf{x}^\top \mathbf{C}_\theta^{-1}\mathbf{x}$ which are usually not able to capture high-dimensional complex, structured data;
- ▶ **Step #2:** optimizing $\hat{\theta} = \arg \min_\theta D(p, p_\theta)$ for some relevant "distance" D between the true distribution p and the parametric model p_θ —typically the Kullback-Leibler divergence D_{KL} :

$$D_{\text{KL}}(p, p_\theta) = \mathbb{E}_p\{\log p - \log p_\theta\} \geq 0;$$

- ▶ **Step #3:** inferring from p_θ —typically transforming it into a simple distribution, *i.e.* Gaussian $\mathcal{N}(\mu, \sigma)$, and reversing the transformation.

- ▶ **Fast Inference:** diffusion models enable significantly faster inference compared to traditional PDE solvers.
- ▶ **Multi-scale and multi-domain turbulence:** ability to capture turbulent features across various spatial and temporal scales, adaptable to different application contexts.
- ▶ **Extrapolation capabilities:** diffusion models provide improved generalization to unseen turbulent configurations or extrapolation to spatial regions not covered by training data.
- ▶ **Prediction stability:** enhanced numerical stability of predictions compared to traditional solvers constrained by time-step and resolution limitations.
- ▶ **Reduced computational cost:** Reduction in computation costs for complex predictions, especially for high-dimensional datasets.
- ▶ **Uncertainty modeling:** Natural integration of uncertainty estimation through the stochastic process inherent in diffusion models.

Objectives and dataset


The training and test data (Kohl et al. [6]) address the case of von Kármán vortex around a 2D cylinder (compressible + transonic) for Reynolds number $Re = 10^4$ and a Mach number $M \in [0.53, 0.63] \cup [0.69, 0.90]$.

- Each image has a resolution of $R = 128 \times 64$ pixels for velocity fields $\mathbf{u} = (u, v)$ and pressure P over a spatial domain Ω at time steps $\tau \in \{0, 1, \dots, \mathcal{T}\}$;

Objectives and dataset

The training and test data (Kohl et al. [6]) address the case of von Kármán vortex around a 2D cylinder (compressible + transonic) for Reynolds number $Re = 10^4$ and a Mach number $M \in [0.53, 0.63] \cup [0.69, 0.90]$.

- Each image has a resolution of $R = 128 \times 64$ pixels for velocity fields $\mathbf{u} = (u, v)$ and pressure P over a spatial domain Ω at time steps $\tau \in \{0, 1, \dots, \mathcal{T}\}$;



Objectives and dataset


The training and test data (Kohl et al. [6]) address the case of von Kármán vortex around a 2D cylinder (compressible + transonic) for Reynolds number $Re = 10^4$ and a Mach number $M \in [0.53, 0.63] \cup [0.69, 0.90]$.

- ▶ Each image has a resolution of $R = 128 \times 64$ pixels for velocity fields $\mathbf{u} = (u, v)$ and pressure P over a spatial domain Ω at time steps $\tau \in \{0, 1, \dots, \mathcal{T}\}$;
- ▶ We write $\mathbf{x}_{0,\tau} = \{\mathbf{u}(\mathbf{r}_j, \tau), P(\mathbf{r}_j, \tau) \mid \mathbf{r}_j \in \Omega, 1 \leq j \leq R, 0 \leq \tau \leq \mathcal{T}\}$ (sample at time τ);

Objectives and dataset

The training and test data (Kohl et al. [6]) address the case of von Kármán vortex around a 2D cylinder (compressible + transonic) for Reynolds number $Re = 10^4$ and a Mach number $M \in [0.53, 0.63] \cup [0.69, 0.90]$.

- ▶ Each image has a resolution of $R = 128 \times 64$ pixels for velocity fields $\mathbf{u} = (u, v)$ and pressure P over a spatial domain Ω at time steps $\tau \in \{0, 1, \dots, \mathcal{T}\}$;
- ▶ We write $\mathbf{x}_{0,\tau} = \{\mathbf{u}(\mathbf{r}_j, \tau), P(\mathbf{r}_j, \tau) \mid \mathbf{r}_j \in \Omega, 1 \leq j \leq R, 0 \leq \tau \leq \mathcal{T}\}$ (sample at time τ);



Objectives and dataset

The training and test data (Kohl et al. [6]) address the case of von Kármán vortex around a 2D cylinder (compressible + transonic) for Reynolds number $Re = 10^4$ and a Mach number $M \in [0.53, 0.63] \cup [0.69, 0.90]$.

- ▶ Each image has a resolution of $R = 128 \times 64$ pixels for velocity fields $\mathbf{u} = (u, v)$ and pressure P over a spatial domain Ω at time steps $\tau \in \{0, 1, \dots, \mathcal{T}\}$;
- ▶ We write $\mathbf{x}_{0,\tau} = \{\mathbf{u}(\mathbf{r}_j, \tau), P(\mathbf{r}_j, \tau) \mid \mathbf{r}_j \in \Omega, 1 \leq j \leq R, 0 \leq \tau \leq \mathcal{T}\}$ (sample at time τ);
- ▶ $\mathcal{D} = \{\mathbf{x}_{0,0}, \mathbf{x}_{0,1}, \dots, \mathbf{x}_{0,\mathcal{T}}\}$ with $\mathcal{T} = 1000$, denotes the dataset consisting of regularly sampled images for a given Mach number M , initial conditions \mathcal{I} and boundary conditions \mathcal{B} ;

Objectives and dataset

The training and test data (Kohl et al. [6]) address the case of von Kármán vortex around a 2D cylinder (compressible + transonic) for Reynolds number $Re = 10^4$ and a Mach number $M \in [0.53, 0.63] \cup [0.69, 0.90]$.

- ▶ Each image has a resolution of $R = 128 \times 64$ pixels for velocity fields $\mathbf{u} = (u, v)$ and pressure P over a spatial domain Ω at time steps $\tau \in \{0, 1, \dots, \mathcal{T}\}$;
- ▶ We write $\mathbf{x}_{0,\tau} = \{\mathbf{u}(\mathbf{r}_j, \tau), P(\mathbf{r}_j, \tau) \mid \mathbf{r}_j \in \Omega, 1 \leq j \leq R, 0 \leq \tau \leq \mathcal{T}\}$ (sample at time τ);
- ▶ $\mathcal{D} = \{\mathbf{x}_{0,0}, \mathbf{x}_{0,1}, \dots, \mathbf{x}_{0,\mathcal{T}}\}$ with $\mathcal{T} = 1000$, denotes the dataset consisting of regularly sampled images for a given Mach number M , initial conditions \mathcal{I} and boundary conditions \mathcal{B} ;

Generative modeling assumption: $\mathbf{x}_{0,\tau} \sim p_{\text{data}} \equiv p_0$

Objectives and dataset

The training and test data (Kohl et al. [6]) address the case of von Kármán vortex around a 2D cylinder (compressible + transonic) for Reynolds number $Re = 10^4$ and a Mach number $M \in [0.53, 0.63] \cup [0.69, 0.90]$.

- ▶ Each image has a resolution of $R = 128 \times 64$ pixels for velocity fields $\mathbf{u} = (u, v)$ and pressure P over a spatial domain Ω at time steps $\tau \in \{0, 1, \dots, \mathcal{T}\}$;
- ▶ We write $\mathbf{x}_{0,\tau} = \{\mathbf{u}(\mathbf{r}_j, \tau), P(\mathbf{r}_j, \tau) \mid \mathbf{r}_j \in \Omega, 1 \leq j \leq R, 0 \leq \tau \leq \mathcal{T}\}$ (sample at time τ);
- ▶ $\mathcal{D} = \{\mathbf{x}_{0,0}, \mathbf{x}_{0,1}, \dots, \mathbf{x}_{0,\mathcal{T}}\}$ with $\mathcal{T} = 1000$, denotes the dataset consisting of regularly sampled images for a given Mach number M , initial conditions \mathcal{I} and boundary conditions \mathcal{B} ;

Generative modeling assumption: $\mathbf{x}_{0,\tau} \sim p_{\text{data}} \equiv p_0$

Objective:

$$\hat{\mathbf{x}}_{0,\tau} = \arg \max_{\mathbf{x}_{0,\tau}} p_0(\mathbf{x}_{0,\tau} | \tau, \mathcal{I}(\mathbf{x}_{0,0}), \mathcal{B}(\mathbf{x}_{0,\tau})).$$

- ▶ Based on VAE concept and ancestral sampling techniques;

Diffusion models: the discrete setting

Introduction

- ▶ Based on VAE concept and ancestral sampling techniques;
- ▶ Denoising diffusion probabilistic models (DDPMs, [Ho et al. \[5\]](#)) are composed of two Markov chains:

Diffusion models: the discrete setting

Introduction

- ▶ Based on VAE concept and ancestral sampling techniques;
- ▶ Denoising diffusion probabilistic models (DDPMs, Ho et al. [5]) are composed of two Markov chains:
 - Forward chain (forward process): perturb data with noise,
 - Backward chain (reverse process): denoising chain to go back to data;

Diffusion models: the discrete setting

Introduction

- ▶ Based on VAE concept and ancestral sampling techniques;
- ▶ Denoising diffusion probabilistic models (DDPMs, Ho et al. [5]) are composed of two Markov chains:
 - Forward chain (forward process): perturb data with noise,
 - Backward chain (reverse process): denoising chain to go back to data;
- ▶ The forward process is designed to transform data samples to a chosen (simple) prior distribution, typically standard normal Gaussian distribution, *i.e.* $p_{\text{ref}} = \mathcal{N}(\mathbf{0}, \mathbf{I})$;

Diffusion models: the discrete setting

Introduction

- ▶ Based on VAE concept and ancestral sampling techniques;
- ▶ Denoising diffusion probabilistic models (DDPMs, Ho et al. [5]) are composed of two Markov chains:
 - Forward chain (forward process): perturb data with noise,
 - Backward chain (reverse process): denoising chain to go back to data;
- ▶ The forward process is designed to transform data samples to a chosen (simple) prior distribution, typically standard normal Gaussian distribution, *i.e.* $p_{\text{ref}} = \mathcal{N}(\mathbf{0}, \mathbf{I})$;
- ▶ The reverse process is built by learning a transition kernel;

Diffusion models: the discrete setting


Introduction

- ▶ Based on VAE concept and ancestral sampling techniques;
- ▶ Denoising diffusion probabilistic models (DDPMs, Ho et al. [5]) are composed of two Markov chains:
 - Forward chain (forward process): perturb data with noise,
 - Backward chain (reverse process): denoising chain to go back to data;
- ▶ The forward process is designed to transform data samples to a chosen (simple) prior distribution, typically standard normal Gaussian distribution, *i.e.* $p_{\text{ref}} = \mathcal{N}(\mathbf{0}, \mathbf{I})$;
- ▶ The reverse process is built by learning a transition kernel;
- ▶ Samples are generated by sampling the prior distribution and follow the backward Markov chain:

Diffusion models: the discrete setting

Introduction


- ▶ Based on VAE concept and ancestral sampling techniques;
- ▶ Denoising diffusion probabilistic models (DDPMs, [Ho et al. \[5\]](#)) are composed of two Markov chains:
 - Forward chain (**forward process**): perturb data with noise,
 - Backward chain (**reverse process**): denoising chain to go back to data;
- ▶ The **forward process** is designed to transform data samples to a chosen (simple) prior distribution, typically standard normal Gaussian distribution, *i.e.* $p_{\text{ref}} = \mathcal{N}(\mathbf{0}, \mathbf{I})$;
- ▶ The **reverse process** is built by learning a **transition kernel**;
- ▶ Samples are generated by sampling the prior distribution and follow the **backward Markov chain**:



Diffusion models: the discrete setting

Introduction

- ▶ Based on VAE concept and ancestral sampling techniques;
- ▶ Denoising diffusion probabilistic models (DDPMs, [Ho et al. \[5\]](#)) are composed of two Markov chains:
 - Forward chain (**forward process**): perturb data with noise,
 - Backward chain (**reverse process**): denoising chain to go back to data;
- ▶ The **forward process** is designed to transform data samples to a chosen (simple) prior distribution, typically standard normal Gaussian distribution, *i.e.* $p_{\text{ref}} = \mathcal{N}(\mathbf{0}, \mathbf{I})$;
- ▶ The **reverse process** is built by learning a **transition kernel**;
- ▶ Samples are generated by sampling the prior distribution and follow the **backward Markov chain**:



Diffusion models: the continuous setting

Forward-backward system and SDEs

Let $\{\mathbf{x}_t; 0 \leq t < \infty\}$ be a **random process** defined on \mathbb{R}^p and indexed on $t \in \mathbb{R}_+$.

- \mathbf{x}_t verifies the **Itô Stochastic Differential Equation** (SDE) (**Oksendal [7]**) describing the evolution of \mathbf{x}_0 to a state \mathbf{x}_T :

$$d\mathbf{x}_t = \boldsymbol{\mu}(\mathbf{x}_t, t)dt + \boldsymbol{\sigma}(\mathbf{x}_t, t)d\mathbf{W}_t, \quad \mathbf{x}_0 \sim p_0, \quad (1)$$

where $\boldsymbol{\mu}(\cdot, t) : \mathbb{R}^p \rightarrow \mathbb{R}^p$ is the drift coefficient, $\boldsymbol{\Sigma}(\cdot, t) : \mathbb{R}^p \rightarrow \mathbb{R}^{p \times p}$ is the diffusion coefficient and $\{\mathbf{W}_t; t \geq 0\}$ is a p -dimensional Brownian motion (or Wiener process).

Diffusion models: the continuous setting


Forward-backward system and SDEs

Let $\{\mathbf{x}_t; 0 \leq t < \infty\}$ be a **random process** defined on \mathbb{R}^p and indexed on $t \in \mathbb{R}_+$.

- \mathbf{x}_t verifies the **Itô Stochastic Differential Equation** (SDE) (**Oksendal [7]**) describing the evolution of \mathbf{x}_0 to a state \mathbf{x}_T :

$$d\mathbf{x}_t = \boldsymbol{\mu}(\mathbf{x}_t, t)dt + \boldsymbol{\sigma}(\mathbf{x}_t, t)d\mathbf{W}_t, \quad \mathbf{x}_0 \sim p_0, \quad (1)$$

where $\boldsymbol{\mu}(\cdot, t) : \mathbb{R}^p \rightarrow \mathbb{R}^p$ is the drift coefficient, $\boldsymbol{\Sigma}(\cdot, t) : \mathbb{R}^p \rightarrow \mathbb{R}^{p \times p}$ is the diffusion coefficient and $\{\mathbf{W}_t; t \geq 0\}$ is a p -dimensional Brownian motion (or Wiener process).



Diffusion models: the continuous setting

Forward-backward system and SDEs

Let $\{\mathbf{x}_t; 0 \leq t < \infty\}$ be a **random process** defined on \mathbb{R}^p and indexed on $t \in \mathbb{R}_+$.

- Time reversal of Eq. (1) $t \rightarrow T - t$ (**Anderson [1], Haussmann and Pardoux [4]**), leading to the **reverse-time SDE** of the diffusion process:

$$d\mathbf{x}_t = \tilde{\boldsymbol{\mu}}(\mathbf{x}_t, t)dt + \boldsymbol{\sigma}(\mathbf{x}_t, t)d\overline{\mathbf{W}}_t, \quad \mathbf{x}_T \sim p_T,$$

where $\tilde{\boldsymbol{\mu}}(\cdot, t) = \boldsymbol{\mu}(\cdot, t) - \nabla_{\mathbf{x}} \cdot \boldsymbol{\Sigma}(\cdot, t) - \boldsymbol{\Sigma}(\cdot, t) \nabla_{\mathbf{x}} \log p_t(\cdot)$, $\boldsymbol{\Sigma}(\cdot, t) = \boldsymbol{\sigma}(\cdot, t)\boldsymbol{\sigma}(\cdot, t)^T$, p_t is the marginal probability density function of \mathbf{x}_t , and $(\overline{\mathbf{W}}_t)_{t \geq 0}$ is a time reversed Brownian motion.

Diffusion models: the continuous setting


Forward-backward system and SDEs

Let $\{\mathbf{x}_t; 0 \leq t < \infty\}$ be a **random process** defined on \mathbb{R}^p and indexed on $t \in \mathbb{R}_+$.

- Time reversal of Eq. (1) $t \rightarrow T - t$ (**Anderson [1], Haussmann and Pardoux [4]**), leading to the **reverse-time SDE** of the diffusion process:

$$d\mathbf{x}_t = \tilde{\mu}(\mathbf{x}_t, t)dt + \sigma(\mathbf{x}_t, t)d\overline{\mathbf{W}}_t, \quad \mathbf{x}_T \sim p_T,$$

where $\tilde{\mu}(\cdot, t) = \mu(\cdot, t) - \nabla_{\mathbf{x}} \cdot \Sigma(\cdot, t) - \Sigma(\cdot, t) \nabla_{\mathbf{x}} \log p_t(\cdot)$, $\Sigma(\cdot, t) = \sigma(\cdot, t)\sigma(\cdot, t)^T$, p_t is the marginal probability density function of \mathbf{x}_t , and $(\overline{\mathbf{W}}_t)_{t \geq 0}$ is a time reversed Brownian motion.



Diffusion models: the continuous setting


Forward-backward system and SDEs

Let $\{\mathbf{x}_t; 0 \leq t < \infty\}$ be a **random process** defined on \mathbb{R}^p and indexed on $t \in \mathbb{R}_+$.

- Time reversal of Eq. (1) $t \rightarrow T - t$ (**Anderson [1], Haussmann and Pardoux [4]**), leading to the **reverse-time SDE** of the diffusion process:

$$d\mathbf{x}_t = \tilde{\mu}(\mathbf{x}_t, t)dt + \sigma(\mathbf{x}_t, t)d\bar{\mathbf{W}}_t, \quad \mathbf{x}_T \sim p_T,$$

where $\tilde{\mu}(\cdot, t) = \mu(\cdot, t) - \nabla_{\mathbf{x}} \cdot \Sigma(\cdot, t) - \Sigma(\cdot, t) \nabla_{\mathbf{x}} \log p_t(\cdot)$, $\Sigma(\cdot, t) = \sigma(\cdot, t)\sigma(\cdot, t)^T$, p_t is the marginal probability density function of \mathbf{x}_t , and $(\bar{\mathbf{W}}_t)_{t \geq 0}$ is a time reversed Brownian motion.



Score-matching technique

Unconditional objective

- The **score function** $\mathbf{s}(\mathbf{x}_t, t) = \nabla_{\mathbf{x}} \log p_t(\mathbf{x}_t)$ is usually intractable, so $\mathbf{s}_{\theta}(\mathbf{x}_t, t)$ is learned instead, using **denoising score-matching** (Song et al. [8], Vincent [9]):

$$\begin{aligned}\hat{\theta} &= \arg \min_{\theta} \mathbb{E}_{\mathbf{x}_t \sim p_t(\cdot)} \left\{ \left\| \nabla_{\mathbf{x}} \log p_t(\mathbf{x}_t) - \mathbf{s}_{\theta}(\mathbf{x}_t, t) \right\|^2 \right\} \\ &= \arg \min_{\theta} \mathbb{E}_{\mathbf{x}_0 \sim p_0(\cdot)} \mathbb{E}_{\mathbf{x}_t \sim p_{t|0}(\cdot | \mathbf{x}_0)} \left\{ \left\| \nabla_{\mathbf{x}} \log p_{t|0}(\mathbf{x}_t | \mathbf{x}_0) - \mathbf{s}_{\theta}(\mathbf{x}_t, t) \right\|^2 \right\} ;\end{aligned}$$

Score-matching technique

Unconditional objective

- The **score function** $\mathbf{s}(\mathbf{x}_t, t) = \nabla_{\mathbf{x}} \log p_t(\mathbf{x}_t)$ is usually intractable, so $\mathbf{s}_{\theta}(\mathbf{x}_t, t)$ is learned instead, using **denoising score-matching** (Song et al. [8], Vincent [9]):

$$\begin{aligned}\hat{\theta} &= \arg \min_{\theta} \mathbb{E}_{\mathbf{x}_t \sim p_t(\cdot)} \left\{ \left\| \nabla_{\mathbf{x}} \log p_t(\mathbf{x}_t) - \mathbf{s}_{\theta}(\mathbf{x}_t, t) \right\|^2 \right\} \\ &= \arg \min_{\theta} \mathbb{E}_{\mathbf{x}_0 \sim p_0(\cdot)} \mathbb{E}_{\mathbf{x}_t \sim p_{t|0}(\cdot | \mathbf{x}_0)} \left\{ \left\| \nabla_{\mathbf{x}} \log p_{t|0}(\mathbf{x}_t | \mathbf{x}_0) - \mathbf{s}_{\theta}(\mathbf{x}_t, t) \right\|^2 \right\} ;\end{aligned}$$

- Choose an easy (solvable) and reversible SDE: usually linear coefficients, e.g. Ornstein-Uhlenbeck process;

Score-matching technique

Unconditional objective

- ▶ The **score function** $\mathbf{s}(\mathbf{x}_t, t) = \nabla_{\mathbf{x}} \log p_t(\mathbf{x}_t)$ is usually intractable, so $\mathbf{s}_{\theta}(\mathbf{x}_t, t)$ is learned instead, using **denoising score-matching** (Song et al. [8], Vincent [9]):

$$\begin{aligned}\hat{\theta} &= \arg \min_{\theta} \mathbb{E}_{\mathbf{x}_t \sim p_t(\cdot)} \left\{ \left\| \nabla_{\mathbf{x}} \log p_t(\mathbf{x}_t) - \mathbf{s}_{\theta}(\mathbf{x}_t, t) \right\|^2 \right\} \\ &= \arg \min_{\theta} \mathbb{E}_{\mathbf{x}_0 \sim p_0(\cdot)} \mathbb{E}_{\mathbf{x}_t \sim p_{t|0}(\cdot | \mathbf{x}_0)} \left\{ \left\| \nabla_{\mathbf{x}} \log p_{t|0}(\mathbf{x}_t | \mathbf{x}_0) - \mathbf{s}_{\theta}(\mathbf{x}_t, t) \right\|^2 \right\} ;\end{aligned}$$

- ▶ Choose an easy (solvable) and reversible SDE: usually linear coefficients, e.g. Ornstein-Uhlenbeck process;
- ▶ Knowing the **transition kernel**, one can sample on the diffusion path: $\mathbf{x}_t \sim p_{t|0}(\cdot | \mathbf{x}_0)$;

Score-matching technique

Unconditional objective

- ▶ The **score function** $\mathbf{s}(\mathbf{x}_t, t) = \nabla_{\mathbf{x}} \log p_t(\mathbf{x}_t)$ is usually intractable, so $\mathbf{s}_{\theta}(\mathbf{x}_t, t)$ is learned instead, using **denoising score-matching** (Song et al. [8], Vincent [9]):

$$\begin{aligned}\hat{\theta} &= \arg \min_{\theta} \mathbb{E}_{\mathbf{x}_t \sim p_t(\cdot)} \left\{ \left\| \nabla_{\mathbf{x}} \log p_t(\mathbf{x}_t) - \mathbf{s}_{\theta}(\mathbf{x}_t, t) \right\|^2 \right\} \\ &= \arg \min_{\theta} \mathbb{E}_{\mathbf{x}_0 \sim p_0(\cdot)} \mathbb{E}_{\mathbf{x}_t \sim p_{t|0}(\cdot|\mathbf{x}_0)} \left\{ \left\| \nabla_{\mathbf{x}} \log p_{t|0}(\mathbf{x}_t|\mathbf{x}_0) - \mathbf{s}_{\theta}(\mathbf{x}_t, t) \right\|^2 \right\};\end{aligned}$$

- ▶ Choose an easy (solvable) and reversible SDE: usually linear coefficients, e.g. Ornstein-Uhlenbeck process;
- ▶ Knowing the **transition kernel**, one can sample on the diffusion path: $\mathbf{x}_t \sim p_{t|0}(\cdot|\mathbf{x}_0)$;
- ▶ Compute the score function on different noise scales with weighting function $\lambda(t)$ on the Fisher divergence:

$$\mathcal{L}_{\text{DSM}}(\theta) = \int_0^T \lambda(t) \mathbb{E}_{\mathbf{x}_0 \sim p_0(\cdot)} \mathbb{E}_{\mathbf{x}_t \sim p_{t|0}(\cdot|\mathbf{x}_0)} \left\{ \left\| \nabla_{\mathbf{x}} \log p_{t|0}(\mathbf{x}_t|\mathbf{x}_0) - \mathbf{s}_{\theta}(\mathbf{x}_t, t) \right\|^2 \right\} dt.$$

Score-matching technique

Autoregressive conditional objective

- Recall the minimization objective:

$$\hat{\mathbf{x}}_{0,\tau} = \arg \max_{\mathbf{x}_{0,\tau}} p_0(\mathbf{x}_{0,\tau} | \tau, \mathcal{I}(\mathbf{x}_{0,0}), \mathcal{B}(\mathbf{x}_{0,\tau}));$$

Score-matching technique

Autoregressive conditional objective

- Recall the minimization objective:

$$\hat{\mathbf{x}}_{0,\tau} = \arg \max_{\mathbf{x}_{0,\tau}} p_0(\mathbf{x}_{0,\tau} | \tau, \mathcal{I}(\mathbf{x}_{0,0}), \mathcal{B}(\mathbf{x}_{0,\tau}));$$

- Instead, consider an **autoregressive** formulation (Kohl et al. [6]), conditioning on the last n_f physical states ($\mathbf{c}(\tau, n_f)$ conditioning):

$$\hat{\mathbf{x}}_{0,\tau} = \arg \max_{\mathbf{x}_{0,\tau}} p_0(\mathbf{x}_{0,\tau} | \mathbf{c}(\tau, n_f));$$

Score-matching technique

Autoregressive conditional objective

- Recall the minimization objective:

$$\hat{\mathbf{x}}_{0,\tau} = \arg \max_{\mathbf{x}_{0,\tau}} p_0(\mathbf{x}_{0,\tau} | \tau, \mathcal{I}(\mathbf{x}_{0,0}), \mathcal{B}(\mathbf{x}_{0,\tau}));$$

- Instead, consider an **autoregressive** formulation (Kohl et al. [6]), conditioning on the last n_f physical states ($\mathbf{c}(\tau, n_f)$ conditioning):

$$\hat{\mathbf{x}}_{0,\tau} = \arg \max_{\mathbf{x}_{0,\tau}} p_0(\mathbf{x}_{0,\tau} | \mathbf{c}(\tau, n_f));$$

- We build a conditional denoiser, taking both time and physical state as external inputs: $\mathbf{s}_\theta(\mathbf{x}_{t,\tau}, \mathbf{c}(\tau, n_f), t)$;

Score-matching technique

Autoregressive conditional objective

- Recall the minimization objective:

$$\hat{\mathbf{x}}_{0,\tau} = \arg \max_{\mathbf{x}_{0,\tau}} p_0(\mathbf{x}_{0,\tau} | \tau, \mathcal{I}(\mathbf{x}_{0,0}), \mathcal{B}(\mathbf{x}_{0,\tau}));$$

- Instead, consider an **autoregressive** formulation (**Kohl et al. [6]**), conditioning on the last n_f physical states ($\mathbf{c}(\tau, n_f)$ conditioning):

$$\hat{\mathbf{x}}_{0,\tau} = \arg \max_{\mathbf{x}_{0,\tau}} p_0(\mathbf{x}_{0,\tau} | \mathbf{c}(\tau, n_f));$$

- We build a conditional denoiser, taking both time and physical state as external inputs: $\mathbf{s}_\theta(\mathbf{x}_{t,\tau}, \mathbf{c}(\tau, n_f), t)$;
- With **Bayes' theorem** (+ **Batzolis et al. [2]**), we can rewrite the conditional objective and train the conditional score function:

$$\mathcal{L}_{\text{DSM}}(\theta) = \int_0^T \lambda(t) \mathbb{E}_{\substack{\mathbf{x}_{0,\tau}, \mathbf{c}(\tau, n_f) \sim p_0(\cdot, \mathbf{c}) \\ \mathbf{x}_{t,\tau} \sim p_{t|0}(\cdot | \mathbf{x}_{0,\tau})}} \left\{ \left\| \nabla_{\mathbf{x}} \log p_{t|0}(\mathbf{x}_{t,\tau} | \mathbf{x}_{0,\tau}) - \mathbf{s}_\theta(\mathbf{x}_{t,\tau}, \mathbf{c}(\tau, n_f), t) \right\|^2 \right\} dt.$$

Score-matching technique

Autoregressive conditional objective


- ▶ Since we choose an autoregressive formulation, we impose consistency in between predictions via a regularization term of the type: $\mathcal{R}(f(\mathbf{x}_\tau, \mathbf{x}_{\tau-n_f}), f(\hat{\mathbf{x}}_\tau, \hat{\mathbf{x}}_{\tau-n_f}))$;

Score-matching technique


Autoregressive conditional objective

- ▶ Since we choose an autoregressive formulation, we impose consistency in between predictions via a regularization term of the type: $\mathcal{R}(f(\mathbf{x}_\tau, \mathbf{x}_{\tau-n_f}), f(\hat{\mathbf{x}}_\tau, \hat{\mathbf{x}}_{\tau-n_f}))$;
- ▶ Covariance penalization to conserve fluid properties (Dryden [3]) \rightarrow mean field decomposition:
mean part \mathbf{U} + random fluctuations \mathbf{u}' (s.t. $\mathbf{u}'(\mathbf{r}, \tau) = \mathbf{U}(\mathbf{r}, \tau) - \mathbf{u}(\mathbf{r}, \tau)$ & zero mean $\mathbb{E}\{\mathbf{u}'(\mathbf{r}, \tau)\} = \mathbf{0}$);

Mean field $\mathbf{U}(\mathbf{r}, \tau)$



Fluctuations $\mathbf{u}'(\mathbf{r}, \tau)$



Score-matching technique

Autoregressive conditional objective

- ▶ Since we choose an autoregressive formulation, we impose consistency in between predictions via a regularization term of the type: $\mathcal{R}(f(\mathbf{x}_\tau, \mathbf{x}_{\tau-n_f}), f(\hat{\mathbf{x}}_\tau, \hat{\mathbf{x}}_{\tau-n_f}))$;
- ▶ Covariance penalization to conserve fluid properties (Dryden [3]) \rightarrow mean field decomposition:
mean part \mathbf{U} + random fluctuations \mathbf{u}' (s.t. $\mathbf{u}'(\mathbf{r}, \tau) = \mathbf{U}(\mathbf{r}, \tau) - \mathbf{u}(\mathbf{r}, \tau)$ & zero mean $\mathbb{E}\{\mathbf{u}'(\mathbf{r}, \tau)\} = \mathbf{0}$);
 - Reconstruct the estimated field $\hat{\mathbf{u}}$ from: $\hat{\mathbf{x}}_{0,\tau} \simeq \mathbf{x}_{t,\tau} + \boldsymbol{\Sigma}_t \mathbf{s}_\theta(\mathbf{x}_{t,\tau}, \mathbf{c}(\tau, n_f), t)$;

Score-matching technique

Autoregressive conditional objective

- ▶ Since we choose an autoregressive formulation, we impose consistency in between predictions via a regularization term of the type: $\mathcal{R}(f(\mathbf{x}_\tau, \mathbf{x}_{\tau-n_f}), f(\hat{\mathbf{x}}_\tau, \hat{\mathbf{x}}_{\tau-n_f}))$;
- ▶ Covariance penalization to conserve fluid properties (Dryden [3]) \rightarrow mean field decomposition:
mean part \mathbf{U} + random fluctuations \mathbf{u}' (s.t. $\mathbf{u}'(\mathbf{r}, \tau) = \mathbf{U}(\mathbf{r}, \tau) - \mathbf{u}(\mathbf{r}, \tau)$ & zero mean $\mathbb{E}\{\mathbf{u}'(\mathbf{r}, \tau)\} = \mathbf{0}$);
 - Reconstruct the estimated field $\hat{\mathbf{u}}$ from: $\hat{\mathbf{x}}_{0,\tau} \simeq \mathbf{x}_{t,\tau} + \boldsymbol{\Sigma}_t \mathbf{s}_\theta(\mathbf{x}_{t,\tau}, \mathbf{c}(\tau, n_f), t)$;
 - Compute the 2×2 autocorrelation matrix of the velocity field fluctuations between consecutive predictions:

$$\mathbf{R}_u(\mathbf{r}_1, \mathbf{r}_2, \tau_1, \tau_2) = \mathbb{E}\{\mathbf{u}'(\mathbf{r}_1, \tau_1) \otimes \mathbf{u}'(\mathbf{r}_2, \tau_2)\};$$

Score-matching technique

Autoregressive conditional objective

- ▶ Since we choose an autoregressive formulation, we impose consistency in between predictions via a regularization term of the type: $\mathcal{R}(f(\mathbf{x}_\tau, \mathbf{x}_{\tau-n_f}), f(\hat{\mathbf{x}}_\tau, \hat{\mathbf{x}}_{\tau-n_f}))$;
- ▶ Covariance penalization to conserve fluid properties (Dryden [3]) \rightarrow mean field decomposition:
mean part \mathbf{U} + random fluctuations \mathbf{u}' (s.t. $\mathbf{u}'(\mathbf{r}, \tau) = \mathbf{U}(\mathbf{r}, \tau) - \mathbf{u}(\mathbf{r}, \tau)$ & zero mean $\mathbb{E}\{\mathbf{u}'(\mathbf{r}, \tau)\} = \mathbf{0}$);
 - Reconstruct the estimated field $\hat{\mathbf{u}}$ from: $\hat{\mathbf{x}}_{0,\tau} \simeq \mathbf{x}_{t,\tau} + \boldsymbol{\Sigma}_t \mathbf{s}_\theta(\mathbf{x}_{t,\tau}, \mathbf{c}(\tau, n_f), t)$;
 - Compute the 2×2 autocorrelation matrix of the velocity field fluctuations between consecutive predictions:
- Compute the L_2 error on the covariance matrices on the space distribution:

$$\mathbf{R}_u(\mathbf{r}_1, \mathbf{r}_2, \tau_1, \tau_2) = \mathbb{E}\{\mathbf{u}'(\mathbf{r}_1, \tau_1) \otimes \mathbf{u}'(\mathbf{r}_2, \tau_2)\};$$

$$\mathcal{L}_\varepsilon(\theta) = \lambda_\varepsilon \mathbb{E}_{\mathbf{r}_1, \mathbf{r}_2 \in \Omega} \mathbb{E}_{\mathbf{u} \in \mathcal{D}} \left\{ \|\mathbf{R}_u(\mathbf{r}_1, \mathbf{r}_2, \tau, \tau - n_f) - \mathbf{R}_{\hat{\mathbf{u}}}(\mathbf{r}_1, \mathbf{r}_2, \tau, \tau - n_f)\|_2 \right\};$$

Score-matching technique

Autoregressive conditional objective

- ▶ Since we choose an autoregressive formulation, we impose consistency in between predictions via a regularization term of the type: $\mathcal{R}(f(\mathbf{x}_\tau, \mathbf{x}_{\tau-n_f}), f(\hat{\mathbf{x}}_\tau, \hat{\mathbf{x}}_{\tau-n_f}))$;
- ▶ Covariance penalization to conserve fluid properties (Dryden [3]) \rightarrow mean field decomposition:
mean part \mathbf{U} + random fluctuations \mathbf{u}' (s.t. $\mathbf{u}'(\mathbf{r}, \tau) = \mathbf{U}(\mathbf{r}, \tau) - \mathbf{u}(\mathbf{r}, \tau)$ & zero mean $\mathbb{E}\{\mathbf{u}'(\mathbf{r}, \tau)\} = \mathbf{0}$);
 - Reconstruct the estimated field $\hat{\mathbf{u}}$ from: $\hat{\mathbf{x}}_{0,\tau} \simeq \mathbf{x}_{t,\tau} + \boldsymbol{\Sigma}_t \mathbf{s}_\theta(\mathbf{x}_{t,\tau}, \mathbf{c}(\tau, n_f), t)$;
 - Compute the 2×2 autocorrelation matrix of the velocity field fluctuations between consecutive predictions:

$$\mathbf{R}_u(\mathbf{r}_1, \mathbf{r}_2, \tau_1, \tau_2) = \mathbb{E}\{\mathbf{u}'(\mathbf{r}_1, \tau_1) \otimes \mathbf{u}'(\mathbf{r}_2, \tau_2)\};$$

- Compute the L_2 error on the covariance matrices on the space distribution:

$$\mathcal{L}_\varepsilon(\theta) = \lambda_\varepsilon \mathbb{E}_{\mathbf{r}_1, \mathbf{r}_2 \in \Omega} \mathbb{E}_{\mathbf{u} \in \mathcal{D}} \left\{ \|\mathbf{R}_u(\mathbf{r}_1, \mathbf{r}_2, \tau, \tau - n_f) - \mathbf{R}_{\hat{\mathbf{u}}}(\mathbf{r}_1, \mathbf{r}_2, \tau, \tau - n_f)\|_2 \right\};$$

- ▶ By averaging over the physical state in time, the resulting loss function reads:

$$\mathcal{L}_{\text{total}}(\theta) = \int_{n_f}^{\tau} \underbrace{\mathcal{L}_{\text{DSM}}(\theta)}_{\text{conditional score-matching}} + \underbrace{\mathcal{L}_\varepsilon(\theta)}_{\text{covariance regularization}} d\tau.$$




FIGURE – Architecture¹ of the entire diffusion model (+ SDE and sampling procedure).

¹Backbone of the model: <https://huggingface.co/blog/annotated-diffusion>

Results

Pressure field predictions: extrapolation test




FIGURE – predictions of the pressure field at Mach 0.5.

Results

Energy spectrum





FIGURE – Energy density spectrum at Mach 0.5.

Results

Energy spectrum



- ▶ Energy density spectrum:
 $E(k_x, k_y) = |\hat{u}(k_x, k_y)|^2 + |\hat{v}(k_x, k_y)|^2$
- ▶ Small scale turbulence
→ large k (high frequency)
- ▶ Large scale turbulence
→ small k (low frequency)
- ▶ Size of flow structure/length scale of structures: $\lambda \sim 2\pi/k$

FIGURE – Energy density spectrum at Mach 0.5.

Results

Variance test

Mach: 0.5




FIGURE – Variance of 10 predictions **without** covariance regularization.

Mach: 0.5




FIGURE – Variance on 10 predictions **with** covariance regularization.

Results

Variance test

Mach: 0.51




FIGURE – Variance of 10 predictions **without** covariance regularization.

Mach: 0.51




FIGURE – Variance of 10 predictions **with** covariance regularization.

Results

Variance test

Mach: 0.52




FIGURE – Variance of 10 predictions **without** covariance regularization.

Mach: 0.52




FIGURE – Variance of 10 predictions **with** covariance regularization.

Pros:

- ▶ **Robust and reliable sampling procedure:** ensures stability in generated fields through well-designed diffusion steps, minimizing deviations during early inference,
- ▶ **Simultaneous multi-field generation:** concurrent generation of u , v , and P , preserving correlations and multi-scale resolution,
- ▶ **Accurate long-term predictions:** reliable predictions sustained up to $\tau \simeq 15 \times T_{\text{Ly}\alpha}$, where $T_{\text{Ly}\alpha}$ represents the Lyapunov timescale, ensuring coherence in turbulent flow dynamics.

Cons:


- ▶ **Slow inference speed:** the iterative nature of the sampling process, often requiring a high number of diffusion steps,
- ▶ **Error accumulation:** due to autoregressive propagation, errors can propagate easily,
- ▶ **Training instability:** handling very large datasets \mathcal{D} and high dimensionality leads to a very slow convergence.

Perspectives:

- ▶ **Latent space diffusion:** dimensionality reduction by learning a latent prior,
- ▶ **Efficient conditioning:** develop lighter conditioning methods to reduce the computational overhead of conditioning operations,
- ▶ **Density constraints:** introduce physical constraints on the density function $\rho(\mathbf{x})$ to improve the model's fidelity to conservation laws.

Thank you for listening! Questions?

Animated results are also available here:



Wilfried GENUIST

wilfried.genuist@onera.fr

wilfried.genuist@centralesupelec.fr

References

- [1] Brian D. O. Anderson. Reverse-time diffusion equation models. *Stochastic Processes and their Applications*, 12(3):313–326, 1982.
- [2] Georgios Batzolis, Jan Stanczuk, Carola-Bibiane Schönlieb, and Christian Etmann. Conditional image generation with score-based diffusion models. *arXiv:2111.13606*, 2021.
- [3] Hugh L. Dryden. A review of the statistical theory of turbulence. *Quarterly of Applied Mathematics*, 1(1): 7–42, 1943.
- [4] Ulrich G. Haussmann and Étienne Pardoux. Time reversal of diffusions. *The Annals of Probability*, 14(4): 1188–1205, 1986.
- [5] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.
- [6] Georg Kohl, Li-Wei Chen, and Nils Thuerey. Benchmarking autoregressive conditional diffusion models for turbulent flow simulation. *arXiv:2309.01745*, 2023.
- [7] Bernt Oksendal. *Stochastic Differential Equations: an Introduction with Applications*. Springer, 2013.
- [8] Yang Song, Sahaj Garg, Jiaxin Shi, and Stefano Ermon. Sliced score matching: A scalable approach to density and score estimation. In *Uncertainty in Artificial Intelligence*, pages 574–584. PMLR, 2020.
- [9] Pascal Vincent. A connection between score matching and denoising autoencoders. *Neural Computation*, 23(7):1661–1674, 2011.