

1 Workflow: dataset preprocessing and running experiments

1.1 Dataset preprocessing (KuaiRec)

The KuaiRec raw data must be preprocessed before training. The provided script in `dataset/kuaiREC/kuaiREC_preprocess.py`

- merges multiple KuaiRec feature CSVs into a single table,
- builds vocabularies for sparse/sequence features,
- constructs a feature `description` schema used by models and dataloaders,
- splits into `train/test`,
- writes `kuaiREC_data.pkl` containing the processed data and schema.

It also produces duration buckets and per-bucket play-time quantiles used by the D2Q baseline.

1.2 Training / evaluation entrypoints

Each method has a `run_*.py` entrypoint. Typical usage is:

- `python run_egmn.py -dataset_name kuaiREC`
- `python run_cread.py -dataset_name kuaiREC`
- `python run_d2q.py -dataset_name kuaiREC`

These scripts:

- load `./dataset/kuaiREC/kuaiREC_data.pkl` through `dataloader/kuaiREC.py`,
- train for a fixed number of epochs,
- evaluate on the test set,
- print MAE, XAUC, and KL divergence.

1.3 Dependencies

The README indicates the project was tested with Python 3.x and PyTorch (e.g. 2.1.0), and expects common scientific Python packages (NumPy, pandas, scikit-learn).