

CSE 4701 Spring 2020

Homework 2: Due March 4 (Wed) 2020, midnight, at HuskyCT

Problem 1. (35 pts)

Consider a disk with block size $B = 512$ bytes. A block pointer is $P = 6$ bytes long, and a record pointer is $P_R = 7$ bytes long. A file has $r = 100,000$ EMPLOYEE records of fixed length. Each record has the following fields: NAME (25 bytes), SSN (9 bytes), DEPARTMENTCODE (9 bytes), ADDRESS (40 bytes), PHONE (9 bytes), BIRTHDATE (8 bytes), SEX (1 byte), JOBCODE (5 bytes), SALARY (4 bytes).

- a. Calculate the record size R in bytes.
- b. Calculate the blocking factor bfr and the number of file blocks b , assuming an unspanned organization.
- c. Suppose that the file is ordered by the key field SSN and we want to construct a primary index on SSN. Calculate
 - (i) the index blocking factor $bfri$
 - (ii) the number of first-level index entries and the number of first-level index blocks
 - (iii) the number of levels needed if we make it into a multilevel index
 - (iv) the total number of blocks required by the multilevel index, and
 - (v) the number of block accesses needed to search for and retrieve a record from the file—given its SSN value—using the primary index.

Problem 2. (15 pts)

Given the same specifications of Problem 1, consider this time you are building a primary index on SSN using B-tree. Calculate (i) the order p for the B-tree, (ii) the number of levels needed if blocks are approximately 69% full (round up for convenience), and (iii) the worst-case number of blocks needed to search for and retrieve a record from the file—given its SSN value—using the B-tree you are estimating.

Problem 3. (25 pts)

A PARTS file with Part# as key field includes records with the following Part# values: 12, 33, 22, 15, 19, 55, 25, 11, 16, 13, 29, 44, 71, 21, 4, 42, 68, 78. Suppose that the search field values are inserted in the given order in a B+-tree of order $p = 4$ and $p_{leaf} = 3$.

- (i) Show how the tree will expand (show all steps as in Fig 18.12 (6th ed)) and what the final tree will look like.
- (ii) What is the fill ratio of the final B+-tree you created? (Note: we learned 69% is the average fill ratio in class.) Here the fill ratio is defined as $(\# \text{ of filled key values})/(\# \text{ of maximally allowed key values})$ regardless each key value resides in index node or sequence set node.

Note: 5% penalty for one day late submission