


In-vitro selection algorithm

- for finding RNA strand that binds to protein

Make tube of *random* RNA strands




for $t=1$ to 20 do

- 1 Dip sheet coated with protein into tube
- 2 Pull out and wash off RNA that stuck
- 3 Multiply washed off RNA back to original amount (normalization)

In-vitro selection algorithm

- for finding RNA strand that binds to protein

Make tube of *random* RNA strands



for $t=1$ to 20 do

- 1 Dip sheet coated with protein into tube
- 2 Pull out and wash off RNA that stuck
- 3 Multiply washed off RNA back to original amount (normalization)

Can't be done with computer

because 10^{15} RNA strands per liter of soup

Start with unit amount of random RNA

Loop

- 1 Functional separation into good RNA and bad RNA
- 2 Amplify good RNA to unit amount

Duplicating DNA with PCR

needed for normalization step

- Invented by Kary Mullis 1985
- Heat - double stranded DNA comes apart
- Cool - Short primers hybridize at the ends
- Taq Polymerase runs along DNA strand and complements bases
- Back to double stranded DNA

Duplicating DNA with PCR

needed for normalization step

- Invented by Kary Mullis 1985
 - Heat - double stranded DNA comes apart
 - Cool - Short primers hybridize at the ends
 - Taq Polymerase runs along DNA strand and complements bases
 - Back to double stranded DNA
-
- Ideally all DNA strands multiplied by factor of 2

The caveat

- Not many interesting/specific functional separations found
- Need high throughput for functional separation

Mathematical description of in-vitro selection

- Number the **unknown** RNA strands as $1, 2, \dots, n$ where $n \approx 10^{15}$ (# of strands in 1 liter)
- $s_i \geq 0$ is share of RNA i

Mathematical description of in-vitro selection

- Number the **unknown** RNA strands as $1, 2, \dots, n$ where $n \approx 10^{15}$ (# of strands in 1 liter)
- $s_i \geq 0$ is share of RNA i
- Contents of tube represented as share vector $\mathbf{s} = (s_1, s_2, \dots, s_n)$
- When tube has unit amount, then $s_1 + s_2 + \dots + s_n = 1$

Mathematical description of in-vitro selection

- Number the **unknown** RNA strands as $1, 2, \dots, n$ where $n \approx 10^{15}$ (# of strands in 1 liter)
- $s_i \geq 0$ is share of RNA i
- Contents of tube represented as share vector $\mathbf{s} = (s_1, s_2, \dots, s_n)$
- When tube has unit amount, then $s_1 + s_2 + \dots + s_n = 1$
- $W_i \in [0, 1]$ is the fraction of one unit of RNA i that is good
- **W_i is fitness of RNA strand i for attaching to protein**
- Protein represented as fitness vector $\mathbf{W} = (W_1, W_2, \dots, W_n)$

Mathematical description of in-vitro selection

- Number the **unknown** RNA strands as $1, 2, \dots, n$ where $n \approx 10^{15}$ (# of strands in 1 liter)
- $s_i \geq 0$ is share of RNA i
- Contents of tube represented as share vector $\mathbf{s} = (s_1, s_2, \dots, s_n)$
- When tube has unit amount, then $s_1 + s_2 + \dots + s_n = 1$
- $W_i \in [0, 1]$ is the fraction of one unit of RNA i that is good
- **W_i is fitness of RNA strand i for attaching to protein**
- Protein represented as fitness vector $\mathbf{W} = (W_1, W_2, \dots, W_n)$
- Vectors \mathbf{s}, \mathbf{W} unknown: **Blind Computation!**

Mathematical description of in-vitro selection

- Number the **unknown** RNA strands as $1, 2, \dots, n$ where $n \approx 10^{15}$ (# of strands in 1 liter)
- $s_i \geq 0$ is share of RNA i
- Contents of tube represented as share vector $\mathbf{s} = (s_1, s_2, \dots, s_n)$
- When tube has unit amount, then $s_1 + s_2 + \dots + s_n = 1$
- $W_i \in [0, 1]$ is the fraction of one unit of RNA i that is good
- **W_i is fitness of RNA strand i for attaching to protein**
- Protein represented as fitness vector $\mathbf{W} = (W_1, W_2, \dots, W_n)$
- Vectors \mathbf{s}, \mathbf{W} unknown: **Blind Computation!**

Strong assumption:

- Fitness W_i independent of share vector \mathbf{s}

Update

Good RNA in tube \mathbf{s} :

$$s_1 W_1 + s_2 W_2 + \cdots + s_n W_n = \mathbf{s} \cdot \mathbf{W}$$

Bad RNA:

$$s_1(1 - W_1) + s_2(1 - W_2) + \cdots + s_n(1 - W_n) = 1 - \mathbf{s} \cdot \mathbf{W}$$

- Amplification:

- Good share of RNA i is $s_i W_i$ - multiplied by factor F
- If precise, then all good RNA multiplied by same factor F
- Final tube at end of loop

$$F \mathbf{s} \cdot \mathbf{W}$$

- Since final tube has unit amount of RNA

$$F \mathbf{s} \cdot \mathbf{W} = 1 \text{ and } F = \frac{1}{\mathbf{s} \cdot \mathbf{W}}$$

- Update in each loop


$$s_i := \frac{s_i W_i}{\mathbf{s} \cdot \mathbf{W}}$$

Implementing Bayes rule in RNA

- s_i is prior $P(i)$
- $W_i \in [0..1]$ is probability $P(\text{Good}|i)$
- $\mathbf{s} \cdot \mathbf{W}$ is probability $P(\text{Good})$
-


$$s_i := \frac{s_i W_i}{\mathbf{s} \cdot \mathbf{W}} \quad \text{is Bayes rule} \quad \underbrace{P(i|\text{Good})}_{\text{posterior}} = \frac{\overbrace{P(i)}^{\text{prior}} P(\text{Good}|i)}{P(\text{Good})}$$

Iterating Bayes Rule with same data likelihoods



Initial $\mathbf{s} = (.01, .39, .6)$
 $\mathbf{W} = (.9, .75, .8)$

$\max_i W_i$ eventually wins



$$s_{t,i} = \frac{s_{0,i} W_i^t}{\text{normalization}}$$

t is speed parameter

The best are *too* good

- Multiplicative update

$$s_i \sim s_i \underbrace{\text{fitness factor}_i}_{\geq 0}$$

The best are *too* good

- Multiplicative update

$$s_i \sim s_i \underbrace{\text{fitness factor}_i}_{\geq 0}$$

- Blessing

Best get amplified exponentially fast
Can do this with 10^{15} variables

The best are *too* good

- Multiplicative update

$$s_i \sim s_i \underbrace{\text{fitness factor}_i}_{\geq 0}$$

- Blessing

Best get amplified exponentially fast
Can do this with 10^{15} variables

- Curse

The best wipe out the others
Loss of diversity

View of evolution

Simple view

- Inheritance
 - mutation
 - selection for the fittest with multiplicative update