

README

Last Ten Yards — website + store (Phoenix)

Mobile-first. / shows the posts. /store is the store; **Buy** sends the buyer to a Stripe-hosted checkout page, so card numbers never touch this app.

Piece	Where
Posts, renderer, theme	<code>priv/static/assets/</code>
Business lines	63 lines , one row each in <code>priv/lines.json</code> , each citing where the record names it: the 13 line folders, the business marks in the IP register, the pinboard, the forest plan and the sky-layer steps. Each line gets its own storefront at <code>/l/<slug></code> ; the directory is <code>/lines</code> . Adding a line is one row — no code.
Database	Postgres via Ecto: <code>business_lines</code> , <code>products</code> (each on a line) and <code>orders</code> tables (<code>priv/repo/migrations/</code>). Orders are made only by a signed Stripe webhook. No card data and no buyer contact data are stored — Stripe keeps those
Products for sale	Live in the <code>products</code> table. <code>priv/products.json</code> (empty on purpose) seeds it: <code>mix run priv/repo/seeds.exs</code> . Each item: <code>id</code> , <code>name</code> , <code>blurb</code> , <code>cents</code> , <code>stripe_price</code>
Stripe webhook	POST <code>/stripe/webhook</code> — checks the Stripe-Signature (HMAC-SHA256, 5-minute window), records paid orders once, marks refunds (<code>lib/last_ten_yards/stripe_webhook.ex</code>)
Stripe checkout logic	<code>lib/last_ten_yards/checkout.ex</code>
Heroku	Procfile (release phase runs <code>mix ecto.migrate</code>), <code>elixir_buildpack.config</code> , <code>config/runtime.exs</code> (reads <code>DATABASE_URL</code>)

Specs: 70 core specs — checkout, store rules, lines file, webhook signature, schema-in-step (`elixir test/run_core.exs`, all pass) · **20 database checks in real Postgres 16**, plus all 24 lines loaded into it (`priv/repo/structure.sql` + `test/sql/schema_check.sql`, all pass) · **mix test: 94 specs, 0 failures** on the real stack (Phoenix 1.7.14, Ecto 3.12, Postgres 16), 2026-09-25. The server boots and serves every page: `/`, `/lines`, `/l/<slug>`, `/store`, `/store/thanks`; unknown line → 404.

Heroku config vars it reads: `DATABASE_URL` (set by the Heroku Postgres add-on), `SECRET_KEY_BASE`, `PHX_HOST`, `STRIPE_SECRET_KEY`, `STRIPE_WEBHOOK_SECRET`. Nothing secret lives in the code.

His hand (accounts, keys, money): Heroku account + app, the Heroku Postgres add-on (a paid plan), Stripe account + products/prices + a webhook pointed at `/stripe/webhook`, the config vars above, the domain.