



NATIONAL RESEARCH
UNIVERSITY

Random graphs

Network Science

Lecture 3

Leonid Zhukov

lzhukov@hse.ru

www.leonidzhukov.net/hse/2021/networks

National Research University Higher School of Economics
School of Data Analysis and Artificial Intelligence, Department of Computer Science

Empirical network features:

- Power-law (heavy-tailed) degree distribution
- Small average distance (graph diameter)
- Large clustering coefficient (transitivity)

Generative models:

- Random graph model (Erdos & Renyi, 1959)
- "Small world" model (Watts & Strogatz, 1998)
- Preferential attachment model (Barabasi & Albert, 1999)

Graph $G\{E, V\}$, nodes $n = |V|$, edges $m = |E|$

Erdos and Renyi, 1959.

Random graph models


- $G(n, m)$ a randomly selected graph from the set of C_N^m graphs, $N = \frac{n(n-1)}{2}$, with n nodes and m edges
- $G(n, p)$ each pair out of $N = \frac{n(n-1)}{2}$ pairs of nodes is connected with probability p , m - random number

$$\langle m \rangle = p \frac{n(n-1)}{2}$$

$$\langle k \rangle = \frac{1}{n} \sum_i k_i = \frac{2\langle m \rangle}{n} = p(n-1) \approx pn$$

$$\rho = \frac{\langle m \rangle}{n(n-1)/2} = p$$

Random graph model $G(n, p)$



$n = 12, p = 1/6$

$n = 100, p = 0.03$

- In $G(n, p)$ model, probability for a network to have m links is given by binomial distribution:

$$P(m) = C_N^m p^m (1 - p)^{N-m}$$

where $N = \frac{n(n-1)}{2}$

- p^m - probability that m links are present
 $(1 - p)^{N-m}$ - probability that other links are not
 C_N^m - number of ways to select m links out of all N ,
 $C_N^m = \frac{N!}{m!(N-m)!}$
- expected number of links

$$\langle m \rangle = \sum_{m=0}^N m P(m) = pN = p \frac{n(n-1)}{2}$$

- Probability that i -th node has a degree $k_i = k$ is given by Binomial distribution:

$$P(k_i = k) = P(k) = C_{n-1}^k p^k (1-p)^{n-1-k}$$


p^k - probability that connects to k nodes (has k -edges)

$(1-p)^{n-k-1}$ - probability that does not connect to any other node



C_{n-1}^k - number of ways to select k nodes out of all to connect to, $C_{n-1}^k = \frac{(n-1)!}{k!(n-k-1)!}$

- Binomial distribution, when $\langle k \rangle \ll N$ or $n \rightarrow \infty$ and $p \rightarrow 0$ at fixed $\langle k \rangle$, is well approximated by Poisson distribution:

$$P(k) = \frac{\langle k \rangle^k e^{-\langle k \rangle}}{k!} = \frac{\lambda^k e^{-\lambda}}{k!}, \quad \langle k \rangle = pn = \lambda$$






$$P(k_i = k) = \frac{\lambda^k e^{-\lambda}}{k!}, \quad \lambda = \langle k \rangle = pn$$



$$\langle k \rangle = pn = 5$$

Consider $G_{n,p}$ as a function of p

- $p = 0$, empty graph - $\langle k \rangle = 0$
- $p = 1$, complete (full) graph - $\langle k \rangle = n - 1$
- n_G -largest connected component, $s = \frac{n_G}{n}$



p

Let u – fraction of nodes that do not belong to GCC. The probability that a node does not belong to GCC

$$\begin{aligned} u &= \frac{n - n_G}{n} = P(k=0) + P(k=1) \cdot u + P(k=2) \cdot u^2 + P(k=3) \cdot u^3 \dots = \\ &= \sum_{k=0}^{\infty} P(k) u^k = \sum_{k=0}^{\infty} \frac{\lambda^k e^{-\lambda}}{k!} u^k = e^{-\lambda} e^{\lambda u} = e^{\lambda(u-1)} \end{aligned}$$

Let s -fraction of nodes belonging to GCC (size of GCC)

$$u = e^{\lambda(u-1)}$$


$$s = 1 - u, \quad 1 - s = e^{-\lambda s}$$

$$\lambda = pn = \langle k \rangle$$

when $\lambda \rightarrow \infty$, $s \rightarrow 1$

when $\lambda \rightarrow 0$, $s \rightarrow 0$

$$s = 1 - e^{-\lambda s}$$




non-zero solution exists when (at $s = 0$):

$$\lambda e^{-\lambda s} > 1$$

critical value:


$$\lambda_c = 1$$

$$\lambda_c = \langle k \rangle = p_c n = 1, \quad p_c = \frac{1}{n}$$



$$\langle k \rangle = pn$$

Evolution of random network




from A-L. Barabasi, 2016

Graph $G(n, p)$, for $n \rightarrow \infty$, critical value $p_c = 1/n$


- Subcritical regime: $p < p_c$, $\langle k \rangle < 1$ there is no components with more than $O(\ln n)$ nodes, largest component is a tree
- Critical point: $p = p_c$, $\langle k \rangle = 1$ the largest component has $O(n^{2/3})$ nodes
- Supercritical regime: $p > p_c$, $\langle k \rangle > 1$ gigantic component has all $O((p - p_c)n)$ nodes
- Connected regime: $p \gg \ln n/n$, $\langle k \rangle > \ln n$ gigantic component has all $O(n)$ nodes

Critical value: $\langle k \rangle = p_c n = 1$ - on average one neighbor for a node



Graph $G(n, p)$

Threshold probabilities when different subgraphs of k -nodes and l -edges appear in a random graph $p_s \sim n^{-k/l}$



When $p > p_s$:

- $p_s \sim n^{-k/(k-1)}$, having a tree with k nodes
- $p_s \sim n^{-1}$, having a cycle with k nodes
- $p_s \sim n^{-2/(k-1)}$, complete subgraph with k nodes


- Clustering coefficient (probability that two neighbors link to each other):

$$C_i(k) = \frac{\text{\#of links between NN}}{\text{\#max number of links NN}} = \frac{pk(k-1)/2}{k(k-1)/2} = p$$

$$C = p = \frac{\langle k \rangle}{n}$$

- when $n \rightarrow \infty$, $C \rightarrow 0$

- $G(n, p)$ is locally tree-like (GCC) (no loops; low clustering coefficient)




- on average, the number of nodes d steps away from a node

$$n = 1 + \langle k \rangle + \langle k \rangle^2 + \dots \langle k \rangle^D = \frac{\langle k \rangle^{D+1} - 1}{\langle k \rangle - 1} \approx \langle k \rangle^D$$

- around p_c , $\langle k \rangle^D \sim n$,

$$D \sim \frac{\ln n}{\ln \langle k \rangle}$$



- Node degree distribution function - Binomial/Poisson:

$$P(k) = \frac{\lambda^k e^{-\lambda}}{k!}, \quad \lambda = pn = \langle k \rangle$$




- Average path length:

$$\langle L \rangle = \frac{\ln n}{\ln \langle k \rangle}$$


- Clustering coefficient:

$$C = \frac{\langle k \rangle}{n}$$

Degree distribution in real networks



- Random network with a predefined degree sequence:
 $D = \{k_1, k_2, k_3 \dots k_n\}$, n - nodes and $m = 1/2 \sum_i k_i$ edges.
- Construct by randomly matching two stubs and connecting them by an edge.




- Can contain self loops and multiple edges
- Probability that two nodes i and j are connected


$$p_{ij} = \frac{k_i k_j}{2m - 1}$$

- Will be a simple graph for special "graphical degree sequence"

Can be used as a "null model" for comparative network analysis



karate club



configuration model

Clauset, 2014

- On random graphs I, P. Erdos and A. Renyi, Publicationes Mathematicae 6, 290–297 (1959).
- On the evolution of random graphs, P. Erdos and A. Renyi, Publication of the Mathematical Institute of the Hungarian Academy of Sciences, 17-61 (1960)