

applied science such as machine learning [1, 3, 4], control [42] and computer vision, see [48]. As a motivating example, consider the problem of recovering a data matrix from a sampling of its entries. This routinely comes up whenever one collects partially filled out surveys, and one would like to infer the many missing entries. In the area of recommender systems, users submit ratings on a subset of entries in a database, and the vendor provides recommendations based on the user's preferences. Because users only rate a few items, one would like to infer their preference for unrated items; this is the famous Netflix problem [2]. Recovering a rectangular matrix from a sampling of its entries is known as the *matrix completion* problem. The issue is of course that this problem is extraordinarily ill posed since with fewer samples than entries, we have infinitely many completions. Therefore, it is apparently impossible to identify which of these candidate solutions is indeed the "correct" one without some additional information.

In many instances, however, the matrix we wish to recover has low rank or approximately low rank. For instance, the Netflix data matrix of all user-ratings may be approximately low-rank because it is commonly believed that only a few factors contribute to anyone's taste or preference. In computer vision, inferring scene geometry and camera motion from a sequence of images is a well-studied problem known as the structure-from-motion problem. This is an ill-conditioned problem for objects may be distant with respect to their size, or especially for "missing data" which occur because of occlusion or tracking failures. However, when properly stacked and indexed, these images form a matrix which has very low rank (e.g. rank 3 under orthography) [21, 48]. Other examples of low-rank matrix fitting abound; e.g. in control (system identification), machine learning (multi-class learning) and so on. Having said this, the premise that the unknown has (approximately) low rank radically changes the problem, making the search for solutions feasible since the lowest-rank solution now tends to be the right one.

In a recent paper [13], Candès and Recht showed that matrix completion is not as ill-posed as people thought. Indeed, they proved that most low-rank matrices can be recovered *exactly* from most sets of sampled entries even though these sets have surprisingly small cardinality, and more importantly, they proved that this can be done by solving a simple *convex* optimization problem. To state their results, suppose to simplify that the unknown matrix $\mathbf{M} \in \mathbb{R}^{n \times n}$ is square, and that one has available m sampled entries $\{\mathbf{M}_{ij} : (i, j) \in \Omega\}$ where Ω is a random subset of cardinality m . Then [13] proves that most matrices $\mathbf{M}$ of rank r can be perfectly recovered by solving the optimization problem

$$\begin{aligned} & \text{minimize} && \|\mathbf{X}\|_* \\ & \text{subject to} && X_{ij} = M_{ij}, \quad (i, j) \in \Omega, \end{aligned} \tag{1.1}$$

provided that the number of samples obeys

$$m \geq Cn^{6/5}r \log n \tag{1.2}$$

for some positive numerical constant C .¹ In (1.1), the functional $\|\mathbf{X}\|_*$ is the nuclear norm of the matrix $\mathbf{M}$, which is the sum of its singular values. The optimization problem (1.1) is convex and can be recast as a semidefinite program [29, 30]. In some sense, this is the tightest convex relaxation of the NP-hard rank minimization problem

$$\begin{aligned} & \text{minimize} && \text{rank}(\mathbf{X}) \\ & \text{subject to} && X_{ij} = M_{ij}, \quad (i, j) \in \Omega, \end{aligned} \tag{1.3}$$

¹Note that an $n \times n$ matrix of rank r depends upon $r(2n - r)$ degrees of freedom.