

A Singular Value Thresholding Algorithm for Matrix Completion

Jian-Feng Cai[†] Emmanuel J. Candès[‡] Zuowei Shen[§]

[†] Temasek Laboratories, National University of Singapore, Singapore 117543

[‡] Applied and Computational Mathematics, Caltech, Pasadena, CA 91125

[§] Department of Mathematics, National University of Singapore, Singapore 117543

September 2008

Abstract

This paper introduces a novel algorithm to approximate the matrix with minimum nuclear norm among all matrices obeying a set of convex constraints. This problem may be understood as the convex relaxation of a rank minimization problem, and arises in many important applications as in the task of recovering a large matrix from a small subset of its entries (the famous Netflix problem). Off-the-shelf algorithms such as interior point methods are not directly amenable to large problems of this kind with over a million unknown entries.

This paper develops a simple first-order and easy-to-implement algorithm that is extremely efficient at addressing problems in which the optimal solution has low rank. The algorithm is iterative and produces a sequence of matrices $\{\mathbf{X}^k, \mathbf{Y}^k\}$ and at each step, mainly performs a soft-thresholding operation on the singular values of the matrix $\mathbf{Y}^k$. There are two remarkable features making this attractive for low-rank matrix completion problems. The first is that the soft-thresholding operation is applied to a sparse matrix; the second is that the rank of the iterates $\{\mathbf{X}^k\}$ is empirically nondecreasing. Both these facts allow the algorithm to make use of very minimal storage space and keep the computational cost of each iteration low. On the theoretical side, we provide a convergence analysis showing that the sequence of iterates converges. On the practical side, we provide numerical examples in which $1,000 \times 1,000$ matrices are recovered in less than a minute on a modest desktop computer. We also demonstrate that our approach is amenable to very large scale problems by recovering matrices of rank about 10 with nearly a billion unknowns from just about 0.4% of their sampled entries. Our methods are connected with the recent literature on linearized Bregman iterations for ℓ_1 minimization, and we develop a framework in which one can understand these algorithms in terms of well-known Lagrange multiplier algorithms.

Keywords. Nuclear norm minimization, matrix completion, singular value thresholding, Lagrange dual function, Uzawa's algorithm.

1 Introduction

1.1 Motivation

There is a rapidly growing interest in the recovery of an unknown low-rank or approximately low-rank matrix from very limited information. This problem occurs in many areas of engineering and

applied science such as machine learning [1, 3, 4], control [42] and computer vision, see [48]. As a motivating example, consider the problem of recovering a data matrix from a sampling of its entries. This routinely comes up whenever one collects partially filled out surveys, and one would like to infer the many missing entries. In the area of recommender systems, users submit ratings on a subset of entries in a database, and the vendor provides recommendations based on the user's preferences. Because users only rate a few items, one would like to infer their preference for unrated items; this is the famous Netflix problem [2]. Recovering a rectangular matrix from a sampling of its entries is known as the *matrix completion* problem. The issue is of course that this problem is extraordinarily ill posed since with fewer samples than entries, we have infinitely many completions. Therefore, it is apparently impossible to identify which of these candidate solutions is indeed the "correct" one without some additional information.

In many instances, however, the matrix we wish to recover has low rank or approximately low rank. For instance, the Netflix data matrix of all user-ratings may be approximately low-rank because it is commonly believed that only a few factors contribute to anyone's taste or preference. In computer vision, inferring scene geometry and camera motion from a sequence of images is a well-studied problem known as the structure-from-motion problem. This is an ill-conditioned problem for objects may be distant with respect to their size, or especially for "missing data" which occur because of occlusion or tracking failures. However, when properly stacked and indexed, these images form a matrix which has very low rank (e.g. rank 3 under orthography) [21, 48]. Other examples of low-rank matrix fitting abound; e.g. in control (system identification), machine learning (multi-class learning) and so on. Having said this, the premise that the unknown has (approximately) low rank radically changes the problem, making the search for solutions feasible since the lowest-rank solution now tends to be the right one.

In a recent paper [13], Candès and Recht showed that matrix completion is not as ill-posed as people thought. Indeed, they proved that most low-rank matrices can be recovered *exactly* from most sets of sampled entries even though these sets have surprisingly small cardinality, and more importantly, they proved that this can be done by solving a simple *convex* optimization problem. To state their results, suppose to simplify that the unknown matrix $\mathbf{M} \in \mathbb{R}^{n \times n}$ is square, and that one has available m sampled entries $\{\mathbf{M}_{ij} : (i, j) \in \Omega\}$ where Ω is a random subset of cardinality m . Then [13] proves that most matrices $\mathbf{M}$ of rank r can be perfectly recovered by solving the optimization problem

$$\begin{aligned} & \text{minimize} && \|\mathbf{X}\|_* \\ & \text{subject to} && X_{ij} = M_{ij}, \quad (i, j) \in \Omega, \end{aligned} \tag{1.1}$$

provided that the number of samples obeys

$$m \geq Cn^{6/5}r \log n \tag{1.2}$$

for some positive numerical constant C .¹ In (1.1), the functional $\|\mathbf{X}\|_*$ is the nuclear norm of the matrix $\mathbf{M}$, which is the sum of its singular values. The optimization problem (1.1) is convex and can be recast as a semidefinite program [29, 30]. In some sense, this is the tightest convex relaxation of the NP-hard rank minimization problem

$$\begin{aligned} & \text{minimize} && \text{rank}(\mathbf{X}) \\ & \text{subject to} && X_{ij} = M_{ij}, \quad (i, j) \in \Omega, \end{aligned} \tag{1.3}$$

¹Note that an $n \times n$ matrix of rank r depends upon $r(2n - r)$ degrees of freedom.