

Scorecard Update

Erik Larsen

2026-07-08

Overview

This markdown shows the data logging process of each round, and shows performance trends and metric averages

Set-Up Environment

Attach Packages

```
library(golf)
library(tidyverse)
library(DBI)
library(duckdb)
```

Record New Scorecard

Input the Scores Data

```
# required inputs to fill out the scorecard

round_course <- 'Randolph North'
round_date <- '2026-07-05'
round_teens <- 'white'

hole_scores <- c(4, 4, 5, 5, 5, 3, 4, 5, 4,
                 6, 3, 4, 5, 4, 4, 4, 5, 4)

FIRs <- c(rep(1, 5), 0, 1, 0, 1,
          rep(0, 4), 1, 0, 0, 0, 1)

GIRs <- c(1, 1, 0, 0, 1, 1, 1, 0, 1,
          rep(0, 4), 1, 0, 1, 1, 0)

putts_rec <- c(2, 2, 1, 1, 3, 2, 2, 3, 1,
              2, 1, 1, 1, 2, 1, 1, 3, 1)

chips_rec <- c(0, 0, 2, 2, 0, 0, 0, 1, 0,
```

```

        0, 1, 1, 1, 0, 2, 1, 0, 1)

penalties_rec <- c(rep(0, 9), 1, rep(0, 8))

tee_clubs <- c(rep('D', 5), 'GW', 'D', '6', 'D',
               'D', '6', rep('D', 3), '7', rep('D', 3))

index <- 10.5

```

Specify Course and Tees

```

# get the scorecard for the new round, ensuring hole-by-hole scores are filled
if ( length(hole_scores) > 0 ) {
  Card <- golf::get_course(course = round_course, date = round_date, tees = round_tees)
}

```

Get Scoring Metrics

```

# fill the scorecard for the new round, ensuring hole-by-hole scores are filled
if ( length(hole_scores) > 0 ) {
  Card <- golf::log_score(Scorecard = Card,
                        hole_by_hole = hole_scores,
                        name = 'Erik Larsen',
                        index = index,
                        FIR = FIRs,
                        GIR = GIRs,
                        putts = putts_rec,
                        chips = chips_rec,
                        penalties = penalties_rec,
                        tee_club = tee_clubs)
}

```

Update the db

Update the Players Table

```

con <- golf::get_db_connection()

# if the logged data is newer than the last logged round in the 'rounds' table,
# update the 'players' table

if ( DBI::dbGetQuery(conn = con, statement = paste0("SELECT DISTINCT date FROM rounds ORDER BY date DESC"))
    dplyr::distinct(date) |>
  unlist() %>%
  lubridate::as_date(.) |>
  as.character() < round_date &

  length(hole_scores) > 0

```

```

    ) {

DBI::dbAppendTable(conn = con,
  name = 'players',
  value = players <- Card |>
    dplyr::select(GHIN, index, date) |>
    dplyr::distinct() |>
    dplyr::rename(handicap_index = index) |>
    dplyr::mutate(date = as.character(date))
  )
}

```

Update the Courses Table

```

con <- golf::get_db_connection()

# if the logged data is newer than the last logged round in the 'rounds' table,
# update the 'courses' table

if ( DBI::dbGetQuery(conn = con, statement = paste0("SELECT DISTINCT date FROM rounds ORDER BY date DESC")) |>
  dplyr::distinct(date) |>
  unlist() %>%
  lubridate::as_date(.) |>
  as.character() < round_date &

  length(hole_scores) > 0
) {
DBI::dbAppendTable(conn = con,
  name = 'courses',
  value = course <- Card |>
    dplyr::select(course, tees, to_par, slope, course_rating, hole, yds, par, hole_handicap) |>
    dplyr::distinct() |>
    dplyr::rename(course_name = course) |>
    dplyr::mutate(hole = gsub(hole,
      pattern = 'hole_',
      replacement = '') |> as.numeric())
  )
}

```

Update the Rounds Table

```

con <- golf::get_db_connection()

# if the logged data is newer than the last logged round in the 'rounds' table,
# update the 'rounds' table

if ( DBI::dbGetQuery(conn = con, statement = paste0("SELECT DISTINCT date FROM rounds ORDER BY date DESC")) |>
  dplyr::distinct(date) |>
  unlist() %>%

```

```

lubridate::as_date(.) |>
as.character() < round_date &

length(hole_scores) > 0
) {
DBI::dbAppendTable(conn = con,
  name = 'rounds',
  value = Card |>
    dplyr::select(-to_par, -slope, -course_rating, -yds, -par) |>
    dplyr::distinct() |>
    dplyr::rename(handicap_index = index) |>
    dplyr::rename(course_name = course) |>
    dplyr::mutate(date = as.character(date)) |>
    dplyr::mutate(hole = gsub(hole,
      pattern = 'hole_',
      replacement = '') |> as.numeric()) |>
    dplyr::group_by(course_name, date) |>
    dplyr::arrange(hole) |>
    dplyr::ungroup() |>
    dplyr::relocate(c(tot_gross, tot_net), .after = IN_net) |>
    dplyr::relocate(course_handicap, .after = tees)
  )
}

```

Get Club Metrics df

```

# create a dataframe, specifying the shape for tracked shots on each hole
# -> all strokes from off the green

club_metrics_df <- golf::get_tracked_shots_data_shape(round_date = round_date) |>
  dplyr::arrange(hole)

```

Annotate Club Metrics

```

# manually annotate from Garmin Golf App log
club_choice <- c(
  'D', 'SW',
  'D', 'SW',
  'D', '3W', 'PW', 'PW',
  'D', '8', 'GW', 'P',
  'D', 'PW',
  'GW',
  'D', 'SW',
  '6', 'PW',
  'D', '9', 'PW',

  'D', 'D', '8',
  '6', 'GW',
  'D', 'GW', 'PW',
  'D', '5', '7', 'PW',

```

```

'D', '7',
'7', 'GW', 'P',
'D', '3W', 'PW',
'D', 'GW',
'D', 'GW', 'SW'
)

dist_to_target <- c(
  270, 79,
  270, 85,
  270, 255, 70, 24,
  270, 132, 23, 12,
  270, 138,
  120,
  270, 88,
  201, 45,
  270, 151, 13,

  270, 270, 149,
  189, 40,
  270, 124, 21,
  270, 213, 79, 17,
  270, 154,
  183, 42, 12,
  270, 245, 10,
  270, 148,
  270, 123, 43
)

yds <- c(
  271, 79,
  258, 85,
  254, 303, 46, 24,
  280, 145, 33, 8,
  271, 138,
  110,
  279, 97,
  182, 31,
  290, 157, 13,
  NA_real_, 256, 152,
  200, 34,
  264, 104, 20,
  276, 147, 69, 15,
  244, 149,
  212, 30, 12,
  248, 238, 9,
  222, 128,
  296, 84, 44
)

lie_type <- c(
  'tee', 'fairway',
  'tee', 'fairway',
  'tee', 'fairway', 'rough', 'rough',

```

```

'tee', 'fairway', 'rough', 'fairway',
'tee', 'fairway',
'tee',
'tee', 'fairway',
'tee', 'rough',
'tee', 'fairway', 'rough',

'tee', 'tee', 'fairway',
'tee', 'rough',
'tee', 'rough', 'fairway',
'tee', 'sand', 'rough', 'fairway',
'tee', 'fairway',
'tee', 'rough', 'fairway',
'tee', 'rough', 'fairway',
'tee', 'fairway',
'tee', 'fairway', 'rough'
)

target_status <- c(
  'yes', 'yes',
  'yes', 'yes',
  'yes', 'no', 'no', 'yes',
  'yes', 'no', 'no', 'yes',
  'yes', 'yes',
  'yes',
  'yes', 'yes',
  'no', 'yes',
  'yes', 'no', 'yes',

  'no', 'yes', 'yes',
  'no', 'yes',
  'no', 'no', 'yes',
  'no', 'no', 'yes', 'yes',
  'yes', 'yes',
  'no', 'no', 'yes',
  'no', 'yes', 'yes',
  'no', 'yes',
  'yes', 'no', 'yes'
)

location <- c(
  'on_target', 'on_target',
  'on_target', 'on_target',
  'on_target', 'long', 'short', 'on_target',
  'on_target', 'long', 'long', 'on_target',
  'on_target', 'on_target',
  'on_target',
  'on_target', 'on_target',
  'right', 'on_target',
  'on_target', 'long', 'on_target',

  'right', 'on_target', 'on_target',
  'long', 'on_target',

```

```

'long', 'short', 'on_target',
'long', 'short', 'short', 'on_target',
'on_target', 'on_target',
'long', 'short', 'on_target',
'right', 'on_target', 'on_target',
'right', 'on_target',
'on_target', 'short', 'on_target'
)

type_of_shot <- c(
  'tee', 'full',
  'tee', 'full',
  'tee', 'full', 'chip', 'chip',
  'tee', 'full', 'chip', 'chip',
  'tee', 'full',
  'tee',
  'tee', 'full',
  'tee', 'chip',
  'tee', 'full', 'chip',
  'tee', 'fwbunker', 'punch', 'chip',
  'tee', 'full',
  'tee', 'chip', 'chip',
  'tee', 'full', 'chip',
  'tee', 'full',
  'tee', 'choked', 'chip'
)

```

Get Shot Metrics

```

con <- golf::get_db_connection()

# if the data is newer than the last round in the 'club_metrics' table, append
# the new annotations (expands from 18 rows by the number determined from the
# get_tracked_shots_data_shape function)

if ( DBI::dbGetQuery(conn = con, statement = paste0("SELECT DISTINCT date FROM club_metrics ORDER BY date")) %>%
  dplyr::distinct(date) |>
  unlist() %>%
  lubridate::as_date(.) |>
  as.character() < round_date &

  length(hole_scores) > 0
) {
  length(club_choice)
  club_metrics <- golf::harmonize_club_metrics(club_metrics = club_metrics_df,
                                              club_choice = club_choice,
                                              distance_to_target = dist_to_target,
                                              distance_traveled = yds,

```

```

lie_type = lie_type,
target_status = target_status,
location = location,
type_of_shot = type_of_shot
)

club_metrics <- club_metrics |>
  dplyr::mutate(dplyr::across(c(dplyr::contains("yds")), ~as.numeric(.x)))
head(club_metrics)
}

club_metrics_df |> dplyr::select(tracked_shots) |> dplyr::mutate(sum(tracked_shots))

```

```

##   tracked_shots sum(tracked_shots)
## 1             2             47
## 2             2             47
## 3             4             47
## 4             4             47
## 5             2             47
## 6             1             47
## 7             2             47
## 8             2             47
## 9             3             47
## 10            3             47
## 11            2             47
## 12            3             47
## 13            4             47
## 14            2             47
## 15            3             47
## 16            3             47
## 17            2             47
## 18            3             47

```

Update the Club Metrics Table

```

con <- golf::get_db_connection()

# if the data is newer than the last round in the 'club_metrics' table, append
# the new data to the table

if ( DBI::dbGetQuery(conn = con, statement = paste0("SELECT DISTINCT date FROM club_metrics ORDER BY date"))
  dplyr::distinct(date) |>
  unlist() %>%
  lubridate::as_date(.) |>
  as.character() < round_date &

  length(hole_scores) > 0
) {
  DBI::dbAppendTable(conn = con,
    name = 'club_metrics',
    value = club_metrics |>
      dplyr::mutate(date = as.character(date))
  )
}

```



```

    )
}

# clean the global environment
rm(list = ls()[which(grepl(ls(), pattern= 'con|round_course|round_date|index|real_db')==F)])

```

Summarize Metrics

Gather and Format

Gather and format from the database

```

con <- golf::get_db_connection()

# get the hole-by-hole scores from each round in the database

# join the hole-by-hole scores from the 'rounds' table to the 'courses' table
# need each hole's par rating
# need each course's course_rating from the 'courses' table

# join the 'rounds' and 'courses' tables to the 'players' table
# need handicap_index from the 'players' table

scores <- DBI::dbGetQuery(conn = con, statement = paste0(
  "SELECT DISTINCT r.*, c.par, c.course_rating FROM rounds r
  INNER JOIN courses c
  ON c.tees = r.tees
  AND c.course_name = r.course_name
  AND c.hole = r.hole
  INNER JOIN players p
  ON r.GHIN = p.GHIN
  AND r.handicap_index = p.handicap_index
  AND r.date = p.date;"
)) |>
  dplyr::mutate(date = lubridate::as_date(date)) |> # convert strings to date's
  dplyr::relocate(par, .after = hole) |>
  dplyr::relocate(course_rating, .after = tees) |>
  dplyr::group_by(date) |>
  dplyr::arrange(desc(date), hole) |>
  dplyr::ungroup()

```

```

con <- golf::get_db_connection()

# get stroke metrics from the 'club_metrics' table

stroke_quality <- DBI::dbGetQuery(conn = con, statement = paste0(
  "SELECT DISTINCT * FROM club_metrics;"
)) |>
  dplyr::mutate(date = lubridate::as_date(date)) |> # convert strings to date's
  dplyr::group_by(date) |>
  dplyr::arrange(desc(date), hole, stroke) |>
  dplyr::ungroup()

```

```
## [1] "BEFORE TRY BLOCK"
## [1] "TRY BLOCK START"
## [1] "TABLES INSIDE TRY, AFTER DEV WRITES:"
## [1] "club_metrics"          "courses"          "dev_club_metrics"  "dev_courses"
## [8] "dev_scores_sum"        "pipeline_run_log"  "players"           "predictions_round"
## [1] "INSIDE TRY BLOCK - END"
```

Compute Metrics

Compute standard metrics

```
# define metrics
scores_sum <- scores |>
  dplyr::mutate(date_course = paste0(date,
                                     '\n',
                                     course_name, '\n',
                                     handicap_index),
               chips = dplyr::case_when(
                 grepl(date, pattern = '07-13') ~ NA_real_, TRUE ~ chips),
               `chips+putts` = chips+putts,
               FIR_opps = dplyr::case_when(par > 3 ~ 1, TRUE ~ NA),
               `Iron FIRs` = dplyr::case_when(par > 3 &
                                               grepl(tee_club, pattern = '4|5') &
                                               FIR == 1 ~ 1,
                                               TRUE ~ 0),
               `Iron FIR opps` = dplyr::case_when(par > 3 &
                                                  grepl(tee_club, pattern = '4|5') ~ 1,
                                                  TRUE ~ 0),
               `Driver FIRs` = dplyr::case_when(par > 3 &
                                                  tee_club == 'D' &
                                                  FIR == 1 ~ 1,
                                                  TRUE ~ 0),
               `Driver FIR opps` = dplyr::case_when(par > 3 &
                                                  tee_club == 'D' ~ 1,
                                                  TRUE ~ 0),
               `Par 3 GIRs` = dplyr::case_when(par == 3 &
                                                  GIR == 1 ~ 1,
                                                  TRUE ~ 0),
               greenie_putts = dplyr::case_when(GIR == 1 ~ putts, TRUE ~ NA_real_),
               updown_conv = dplyr::case_when(GIR == 0 &
                                               par == gross ~ 1,
                                               TRUE ~ 0),
               updown_opps = dplyr::case_when(GIR == 0 &
                                               chips > 0 ~ 1,
                                               TRUE ~ 0)
  ) |>
  dplyr::rename(`Handicap Index` = handicap_index)

# summarize by round
scores_sum <- scores_sum |>
  dplyr::group_by(date, date_course, course_rating, `Handicap Index`) |>
  dplyr::summarize(
    FIRs = sum(FIR, na.rm = F),
```

```

`Iron FIRs` = sum(`Iron FIRs`, na.rm = T),
`Iron FIR%` = round(((sum(`Iron FIRs`, na.rm = T)/sum(`Iron FIR opps`, na.rm = T))*100, 1),
`Driver FIRs` = sum(`Driver FIRs`, na.rm = T),
`Driver FIR%` = round(((sum(`Driver FIRs`, na.rm = T)/sum(`Driver FIR opps`, na.rm = T))*100, 1),
`FIR%` = round((sum(FIRs, na.rm = T)/sum(FIR_opps, na.rm = T))*100, 1),
GIRs = sum(GIR, na.rm = F),
`Par 3 GIRs` = sum(`Par 3 GIRs`, na.rm = T),
`GIR%` = round((sum(GIRs, na.rm = T)/18)*100, 1),
putts = sum(putts, na.rm = F),
`Avg GIR putts` = round(mean(greenie_putts, na.rm = T), 2),
chips = sum(chips, na.rm = F),
`chips+putts` = sum(`chips+putts`, na.rm = F),
`UpDown%` = round(((sum(updown_conv, na.rm = T)/sum(updown_opps, na.rm = T))*100), 1),
pars = sum(is_gross_par, na.rm = F),
birdies = sum(is_gross_birdie, na.rm = F),
bogies = sum(is_gross_bogey, na.rm = F),
`doubles+` = sum(is_gross_bogey_worse, na.rm = F),
penalties = sum(penalties, na.rm = T),
`Gross Score` = mean(tot_gross, na.rm = F),
`Net Score` = mean(tot_net, na.rm = F)) %>%
dplyr::mutate(dplyr::across(c(`Iron FIRs`, `Driver FIRs`,
                             `Iron FIR%`, `Driver FIR%`, `FIR%`),
                             ~dplyr::if_else(is.na(FIRs), NA, .)),

              dplyr::across(c(`Par 3 GIRs`, `Avg GIR putts`,
                             `UpDown%`, `GIR%`),
                             ~dplyr::if_else(is.na(GIRs), NA, .)),

              `chips+putts` = dplyr::case_when(is.na(chips) ~ NA_real_,
                                              TRUE ~ `chips+putts`)) %>%

dplyr::mutate(

  `UpAndDown%` = dplyr::case_when(

    grepl(date, pattern = '07-13|09-21') ~ NA, TRUE ~ `UpDown%`),

  `Iron FIR%` = dplyr::case_when(`Iron FIR%` == NaN ~ 0.0, TRUE ~ `Iron FIR%`))

head(scores_sum |>
      dplyr::arrange(desc(date)))

```

```

## # A tibble: 6 x 26
## # Groups:   date, date_course, course_rating [6]
##   date      date_course      course_rating `Handicap` Index`  FIRs `Iron FIRs` `Iron FIR%` `Driver
##   <date>      <chr>          <dbl>          <dbl> <int>  <dbl>      <dbl>      <dbl>
## 1 2026-07-05 "2026-07-05\nRand~    69.8          10.5     9      0        NaN
## 2 2026-07-03 "2026-07-03\nRand~    69.8          10.6     1      0        NaN
## 3 2026-06-28 "2026-06-28\nSilv~    68           10.4     4      0        NaN
## 4 2026-06-28 "2026-06-28\nSilv~    68.9          10.4     4      0        NaN
## 5 2026-06-21 "2026-06-21\nRand~    69.8          10.4     6      1      100
## 6 2026-06-07 "2026-06-07\nRand~    69.8          11      4      1      100
## # i 9 more variables: `UpDown%` <dbl>, pars <int>, birdies <int>, bogies <int>, `doubles+` <int>, per

```

View Metrics

Separate and view metrics

Scoring Metrics Scores and Handicap

```
scoring_metrics <- scores_sum |>
  dplyr::select(`Handicap Index`, `Gross Score`, `Net Score`)
head(scoring_metrics |>
  dplyr::arrange(desc(date)))
```

```
## # A tibble: 6 x 6
## # Groups:   date, date_course, course_rating [6]
##   date      date_course      course_rating `Handicap Index` `Gross Score` `Net Score`
##   <date>    <chr>          <dbl>          <dbl>          <dbl>          <dbl>
## 1 2026-07-05 "2026-07-05\nRandolph North\n10.5"      69.8           10.5           78
## 2 2026-07-03 "2026-07-03\nRandolph North\n10.6"      69.8           10.6           81
## 3 2026-06-28 "2026-06-28\nSilverbell\n10.4"          68            10.4           89
## 4 2026-06-28 "2026-06-28\nSilverbell\n10.4"      68.9           10.4           89
## 5 2026-06-21 "2026-06-21\nRandolph North\n10.4"      69.8           10.4           83
## 6 2026-06-07 "2026-06-07\nRandolph North\n11"        69.8           11            77
```

Stroke Metrics In golf, every hole has a **par**— an average number of strokes taken to get the ball in the hole

There are (almost always), three different **pars** on every course:

- par 3s
- par 4s
- par 5s

A shorthand to determine how a golfer performed across holes is to rate how many strokes *relative to par* they were (-1, -2, +1, +2, etc)

These numbers are given names:

- 0 = par
- -2 = eagle
- -1 = birdie
- +1 = bogey
- +2 = double bogey

I quantify these below:

```
stroke_metrics <- scores_sum |>
  dplyr::select(`doubles+`, bogies, pars, birdies)
head(stroke_metrics |>
  dplyr::arrange(desc(date)))
```

```
## # A tibble: 6 x 7
## # Groups:   date, date_course, course_rating [6]
```

	date	date_course	course_rating	`doubles+`	bogies	pars	birdies
	<date>	<chr>	<dbl>	<int>	<int>	<int>	<int>
## 1	2026-07-05	"2026-07-05\nRandolph North\n10.5"	69.8	2	4	10	2
## 2	2026-07-03	"2026-07-03\nRandolph North\n10.6"	69.8	2	6	9	1
## 3	2026-06-28	"2026-06-28\nSilverbell\n10.4"	68	5	7	6	0
## 4	2026-06-28	"2026-06-28\nSilverbell\n10.4"	68.9	5	7	6	0
## 5	2026-06-21	"2026-06-21\nRandolph North\n10.4"	69.8	1	9	8	0
## 6	2026-06-07	"2026-06-07\nRandolph North\n11"	69.8	1	8	5	3

Around-the-Green Metrics Chips: + strokes around the green taken to get onto the green

Putts: + strokes taken with the putter on the green

Avg GIR putts: + Average # of putts on holes where the ball was hit on to the green within 2 strokes of par (green in regulation, GIR)

UpDown% (aka Scramble%): + # of holes without a GIR but par was made / # of holes without a GIR

```
atg_metrics <- scores_sum |>
  dplyr::select(chips, `chips+putts`, `UpAndDown%`, putts, `Avg GIR putts`)
head(atg_metrics |>
  dplyr::arrange(desc(date)))
```

## # A tibble: 6 x 8							
## # Groups: date, date_course, course_rating [6]							
	date	date_course	course_rating	chips	`chips+putts`	`UpAndDown%`	putts
	<date>	<chr>	<dbl>	<dbl>	<dbl>	<dbl>	<int>
## 1	2026-07-05	"2026-07-05\nRandolph North\n10.5"	69.8	12	42	62.5	30
## 2	2026-07-03	"2026-07-03\nRandolph North\n10.6"	69.8	15	44	41.7	29
## 3	2026-06-28	"2026-06-28\nSilverbell\n10.4"	68	16	50	25	34
## 4	2026-06-28	"2026-06-28\nSilverbell\n10.4"	68.9	16	50	25	34
## 5	2026-06-21	"2026-06-21\nRandolph North\n10.4"	69.8	12	50	25	38
## 6	2026-06-07	"2026-06-07\nRandolph North\n11"	69.8	15	42	25	27

Ball Striking Metrics Approach and tee accuracy

GIR (green in regulation): + hole where the ball was hit on to the green within 2 strokes of par

FIR (fairway in regulation): + hole where the ball was hit on to the fairway from the tee box (only on par 4's and par 5's)

Iron FIR: + hole where an iron was used off the tee for a FIR

Driver FIR: + hole where driver was used off the tee for a FIR

```
ball_striking_metrics <- scores_sum |>
  dplyr::select(GIRs, `GIR%`, `Par 3 GIRs`,
    FIRs, `FIR%`, `Iron FIRs`, `Iron FIR%`,
    `Driver FIRs`, `Driver FIR%`)
head(ball_striking_metrics |>
  dplyr::arrange(desc(date)))
```

## # A tibble: 6 x 12								
## # Groups: date, date_course, course_rating [6]								
	date	date_course	course_rating	GIRs	`GIR%`	`Par 3 GIRs`	FIRs	`FIR%`

```
##   <date>      <chr>                                <dbl> <int> <dbl>          <dbl> <int> <dbl>
## 1 2026-07-05 "2026-07-05\nRandolph North\n10.5"      69.8   9   50             1     9   64.3
## 2 2026-07-03 "2026-07-03\nRandolph North\n10.6"      69.8   5   27.8          1     1    7.1
## 3 2026-06-28 "2026-06-28\nSilverbell\n10.4"          68     4   22.2          0     4   30.8
## 4 2026-06-28 "2026-06-28\nSilverbell\n10.4"          68.9   4   22.2          0     4   30.8
## 5 2026-06-21 "2026-06-21\nRandolph North\n10.4"      69.8   9   50             1     6   42.9
## 6 2026-06-07 "2026-06-07\nRandolph North\n11"        69.8   6   33.3          1     4   28.6
```

Club Metrics Yardage and accuracy for each club

```
## # A tibble: 6 x 6
## # Groups:   date [1]
##   date      club      n rd_min_yds_to_target rd_min_yds_traveled rd_min_yd_diff
##   <date>    <chr> <int>          <dbl>          <dbl>          <dbl>
## 1 2026-07-05 3W      2            245            238            -48
## 2 2026-07-05 5        1            213            147             66
## 3 2026-07-05 6        2            189            182            -11
## 4 2026-07-05 7        3             79             69            -29
## 5 2026-07-05 8        2            132            145            -13
## 6 2026-07-05 9        1            151            157             -6
```

```
## # A tibble: 6 x 6
## # Groups:   date [1]
##   date      club      n rd_max_yds_to_target rd_max_yds_traveled rd_max_yd_diff
##   <date>    <chr> <int>          <dbl>          <dbl>          <dbl>
## 1 2026-07-05 3W      2            255            303             7
## 2 2026-07-05 5        1            213            147             66
## 3 2026-07-05 6        2            201            200             19
## 4 2026-07-05 7        3            183            212             10
## 5 2026-07-05 8        2            149            152             -3
## 6 2026-07-05 9        1            151            157             -6
```

```
## # A tibble: 6 x 10
## # Groups:   date [1]
##   date      club `rd club strokes` miss_direction `rd club miss dir` rd_avg_yds_to_target rd_avg_yd_diff
##   <date>    <chr>          <int> <chr>          <int>          <dbl>
## 1 2026-07-05 3W      2 long          1            250
## 2 2026-07-05 3W      2 on_target    1            250
## 3 2026-07-05 6        2 long          1            195
## 4 2026-07-05 6        2 right        1            195
## 5 2026-07-05 7        2 long          1            168.
## 6 2026-07-05 7        2 on_target    1            168.
```

Plot Metric Summaries

Scoring Metrics


```
scoring_metrics |>
  dplyr::mutate(course_rating = dplyr::case_when(grepl(date_course, pattern = 'Sewailo') ~ 68.9, TRUE ~
    `Handicap Index` = `Handicap Index`*4.5) |>
  dplyr::rename(`Course Rating` = course_rating) |>
```

```

dplyr::group_by(date, date_course, `Handicap Index`) |>
tidyr::pivot_longer(cols = c(`Course Rating`, `Net Score`), names_to = 'metric', values_to = 'value', 'I
ggplot2::ggplot(aes(x = date_course, y = value)) +
ggplot2::geom_point(aes(x = date, y = value, size = 4, alpha = 0.1,
                        color = factor(metric,
                                      levels = c('Handicap Index', 'Course Rating', 'Gross Score', 'I
                        fill = factor(metric,
                                      levels = c('Handicap Index', 'Course Rating', 'Gross Score', 'I
ggplot2::geom_line(aes(x = date, y = value, size = 1, alpha = 0.1,
                      color = factor(metric,
                                      levels = c('Handicap Index', 'Course Rating', 'Gross Score', 'I
                      fill = factor(metric,
                                      levels = c('Handicap Index', 'Course Rating', 'Gross Score', 'I
ggplot2::geom_smooth(aes(x = date, y = value, group = metric,
                        color = factor(metric,
                                      levels = c('Handicap Index', 'Course Rating', 'Gross Score',
                                      fill = factor(metric,
                                      levels = c('Handicap Index', 'Course Rating', 'Gross Score',
                                      alpha = 0.3, method = 'lm')) +
ggplot2::scale_y_continuous(sec.axis = ggplot2::sec_axis(~./4.5, name = 'Handicap Index'))+
ggplot2::labs(title = paste0('Performance Over Time\n',
                             scores |>
                               dplyr::distinct(date) |>
                               dplyr::last() |>
                               unlist() %>% lubridate::as_date(.) |>
                               as.character(),
                             ' - ',
                             scores |>
                               dplyr::distinct(date) |>
                               dplyr::first() |>
                               unlist() %>% lubridate::as_date(.) |>
                               as.character()),
                             x = 'date',
                             y = 'metric',
                             color = 'metric'
                             ) +
ggplot2::guides(alpha = 'none', size = 'none', fill = 'none') +
ggplot2::theme_bw() +
ggplot2::theme(panel.grid.minor = ggplot2::element_blank(),
               axis.title = ggplot2::element_text(face = 'bold'),
               axis.text.y = ggplot2::element_text(face = 'bold'),
               axis.text.x = ggplot2::element_text(face = 'bold', angle = 0, hjust = 0, vjust = 0),
               title = ggplot2::element_text(face = 'bold')
               ) +
ggplot2::scale_x_date(date_breaks = '1 month', date_labels = '%b')

```

Performance Over Time 2025-05-04 - 2026-07-05



Stroke Metrics

```
stroke_metrics |>
  tidyr::pivot_longer(cols = c(`doubles+`:birdies), names_to = 'metric', values_to = 'value', values_drop_na = T) +
  ggplot2::ggplot(aes(x = date_course, y = value, group = metric, color = metric, fill = metric)) +
  ggplot2::geom_point(aes(x = date, y = value, size = 4, alpha = 0.1), na.rm = T) +
  ggplot2::geom_line(aes(x = date, y = value, size = 1, alpha = 0.1), na.rm = T) +
  ggplot2::geom_smooth(aes(x = date, y = value), alpha = 0.3, method = 'lm') +
  ggplot2::labs(title = paste0('Hole-by-Hole Scores Over Time\n',
                                scores |>
                                  dplyr::distinct(date) |>
                                    dplyr::last() |>
```




```

        unlist() %>% lubridate::as_date(.) |>
        as.character(),
        ' - ',
        scores |>
        dplyr::distinct(date) |>
        dplyr::first() |>
        unlist() %>% lubridate::as_date(.) |>
        as.character()),
    x = 'date',
    y = 'metric',
    color = 'metric', fill = 'metric') +
ggplot2::guides(alpha = 'none', size = 'none') +
ggplot2::theme_bw() +
ggplot2::theme(legend.position = 'none',
    panel.grid.minor = ggplot2::element_blank(),
    axis.title = ggplot2::element_text(face = 'bold'),
    axis.text.y = ggplot2::element_text(face = 'bold'),
    axis.text.x = ggplot2::element_text(face = 'bold', angle = 270, hjust = 0, vjust = 0.5),
    title = ggplot2::element_text(face = 'bold'),
    strip.text.x.top = ggplot2::element_text(face = 'bold'),
    strip.background = ggplot2::element_rect(color = 'black',
        fill = 'white')) +
ggplot2::scale_x_date(date_breaks = '1 month', date_labels = '%b') +
ggplot2::facet_wrap(~factor(metric, levels = c('doubles+', 'bogies', 'pars', 'birdies')), nrow = 1)

```

Hole-by-Hole Scores Over Time
2025-05-04 - 2026-07-05



Around the Green Metrics


```
atg_metrics |>
  tidyr::pivot_longer(cols = c(chips:`Avg GIR putts`), names_to = 'metric', values_to = 'value', values_from = NA) +
  ggplot2::ggplot(aes(x = date_course, y = value, group = metric, color = metric, fill = metric)) +
  ggplot2::geom_point(aes(x = date, y = value, size = 4, alpha = 0.1), na.rm = T) +
  ggplot2::geom_line(aes(x = date, y = value, size = 1, alpha = 0.1), na.rm = T) +
  ggplot2::geom_smooth(aes(x = date, y = value), alpha = 0.3, method = 'lm') +
  ggplot2::labs(title = paste0('Around the Green Metrics Over Time\n',
                                scores |>
                                  dplyr::distinct(date) |>
                                    dplyr::last() |>
```

```

        unlist() %>% lubridate::as_date(.) |>
        as.character(),
        ' - ',
        scores |>
        dplyr::distinct(date) |>
        dplyr::first() |>
        unlist() %>% lubridate::as_date(.) |>
        as.character()),
    x = 'date',
    y = 'metric',
    color = 'metric', fill = 'metric') +
ggplot2::guides(alpha = 'none', size = 'none') +
ggplot2::theme_bw() +
ggplot2::theme(legend.position = 'none',
    panel.grid.minor = ggplot2::element_blank(),
    axis.title = ggplot2::element_text(face = 'bold'),
    axis.text.y = ggplot2::element_text(face = 'bold'),
    axis.text.x = ggplot2::element_text(face = 'bold', angle = 270, hjust = 0, vjust = 0.5),
    title = ggplot2::element_text(face = 'bold'),
    strip.text.x.top = ggplot2::element_text(face = 'bold'),
    strip.background = ggplot2::element_rect(color = 'black',
        fill = 'white')) +
ggplot2::scale_x_date(date_breaks = '1 month', date_labels = '%b') +
ggplot2::facet_wrap(~factor(metric, levels = c('chips', 'putts', 'chips+putts', 'UpAndDown%', 'Avg GII

```

Around the Green Metrics Over Time 2025-05-04 - 2026-07-05



Ball Striking Metrics


```
ball_striking_metrics |>
  tidyr::pivot_longer(cols = c(GIRs:`Driver FIR%`), names_to = 'metric', values_to = 'value', values_drop_na = T) +
  ggplot2::ggplot(aes(x = date_course, y = value, group = metric, color = metric, fill = metric)) +
  ggplot2::geom_point(aes(x = date, y = value, size = 4, alpha = 0.1), na.rm = T) +
  ggplot2::geom_line(aes(x = date, y = value, size = 1, alpha = 0.1), na.rm = T) +
  ggplot2::geom_smooth(aes(x = date, y = value), alpha = 0.3, method = 'lm') +
  ggplot2::labs(title = paste0('Ball Striking Over Time\n',
                                scores |>
                                  dplyr::distinct(date) |>
                                    dplyr::last() |>
```

```

        unlist() %>% lubridate::as_date(.) |>
        as.character(),
        ' - ',
        scores |>
        dplyr::distinct(date) |>
        dplyr::first() |>
        unlist() %>% lubridate::as_date(.) |>
        as.character()),
    x = 'date',
    y = 'metric',
    color = 'metric', fill = 'metric') +
ggplot2::guides(alpha = 'none', size = 'none') +
ggplot2::theme_bw() +
ggplot2::theme(legend.position = 'none',
               panel.grid.minor = ggplot2::element_blank(),
               axis.title = ggplot2::element_text(face = 'bold'),
               axis.text.y = ggplot2::element_text(face = 'bold'),
               axis.text.x = ggplot2::element_text(face = 'bold', angle = 270, hjust = 0, vjust = 0.5),
               title = ggplot2::element_text(face = 'bold'),
               strip.text.x.top = ggplot2::element_text(face = 'bold'),
               strip.background = ggplot2::element_rect(color = 'black',
                                                         fill = 'white')) +
ggplot2::scale_x_date(date_breaks = '1 month', date_labels = '%b') +
ggplot2::facet_wrap(~factor(metric, levels = c('Driver FIRs', 'Iron FIRs', 'FIRs',
                                              'Driver FIR%', 'Iron FIR%', 'FIR%',
                                              'GIRs', 'Par 3 GIRs', 'GIR%')), scales = 'free')

```

Ball Striking Over Time 2025-05-04 - 2026-07-05



Stroke Quality Metrics

```
stroke_quality_min |>
  dplyr::ungroup() %>%
  dplyr::mutate(dplyr::across(c(date:n), ~as.character(.x))) |>
  tidyr::pivot_longer(cols = c(dplyr::contains('yd')), names_to = 'metric', values_to = 'vals') |>
  dplyr::mutate(metric = dplyr::case_when(
    grepl(metric, pattern = 'target') ~ 'min. target distance',
    grepl(metric, pattern = 'traveled') ~ 'min. shot distance',
    grepl(metric, pattern = 'diff') ~ 'min. \ntarget dist. - shot d

  dplyr::mutate(date = lubridate::as_date(date),
    club = as.character(club),
```


```

      n = as.integer(n)) |>
ggplot2::ggplot(aes(x = date, y = vals, group = metric, color = club, fill = club)) +
ggplot2::geom_point(alpha = 0.4, size = 3) +
ggplot2::geom_line(alpha = 0.4, size = 2) +
ggplot2::geom_smooth(method = 'lm', se = F) +
ggplot2::labs(title = 'Stroke Yardage Minima by Club', x = 'date', y = 'value (yards)', fill = 'club')
ggplot2::guides(alpha = 'none', size = 'none') +
ggplot2::theme_bw() +
ggplot2::theme(title = ggplot2::element_text(face = 'bold', size = 12),
               axis.title = ggplot2::element_text(face = 'bold', size = 10),
               axis.text = ggplot2::element_text(face = 'bold', size = 10),
               axis.text.x = ggplot2::element_text(face = 'bold', size = 7, angle = 270, hjust = 0, vjust = 1),
               legend.position = 'none',
               strip.background = ggplot2::element_rect(fill = 'white'),
               strip.text.y.right = ggplot2::element_text(face = 'bold', size = 9),
               strip.text.x.top = ggplot2::element_text(face = 'bold', size = 10)) +
ggplot2::scale_x_date(date_breaks = 'weeks', date_labels = '%b %d') +
ggplot2::facet_grid(

  rows = vars(metric),

  cols = vars(factor(club, levels = c('D', '3W', '4', '5',
                                     '6', '7', '8', '9',
                                     'PW', 'GW', 'SW', 'LW', 'P'))),
          scales = 'free')

```



Minima

```
stroke_quality_max |>
  dplyr::ungroup() %>%
  dplyr::mutate(dplyr::across(c(date:n), ~as.character(.x))) |>
  tidyr::pivot_longer(cols = c(dplyr::contains('yd')), names_to = 'metric', values_to = 'vals') |>
  dplyr::mutate(metric = dplyr::case_when(grepl(metric, pattern = 'target') ~ 'max. target distance',
                                          grepl(metric, pattern = 'traveled') ~ 'max. shot distance',
                                          grepl(metric, pattern = 'diff') ~ 'max.\ntarget dist. - shot dist.'))
  dplyr::mutate(date = lubridate::as_date(date),
                club = as.character(club),
                n = as.integer(n)) |>
  ggplot2::ggplot(aes(x = date, y = vals, group = metric, color = club, fill = club)) +
  ggplot2::geom_point(alpha = 0.4, size = 3) +
  ggplot2::geom_line(alpha = 0.4, size = 2) +
  ggplot2::geom_smooth(method = 'lm', se = F) +
  ggplot2::labs(title = 'Stroke Yardage Maxima by Club', x = 'date', y = 'value (yards)', fill = 'club')
```




```

ggplot2::guides(alpha = 'none', size = 'none') +
ggplot2::theme_bw() +
ggplot2::theme(title = ggplot2::element_text(face = 'bold', size = 12),
               axis.title = ggplot2::element_text(face = 'bold', size = 10),
               axis.text = ggplot2::element_text(face = 'bold', size = 10),
               axis.text.x = ggplot2::element_text(face = 'bold', size = 7, angle = 270, hjust = 0, vjust = 1),
               legend.position = 'none',
               strip.background = ggplot2::element_rect(fill = 'white'),
               strip.text.y.right = ggplot2::element_text(face = 'bold', size = 9),
               strip.text.x.top = ggplot2::element_text(face = 'bold', size = 10)) +
ggplot2::scale_x_date(date_breaks = 'weeks', date_labels = '%b %d') +
ggplot2::facet_grid(

  rows = vars(metric),

  cols = vars(factor(club, levels = c('D', '3W', '4', '5',
                                     '6', '7', '8', '9',
                                     'PW', 'GW', 'SW', 'LW', 'P'))),
          scales = 'free')

```




Maxima

```
full_stroke_quality_avg |>
  dplyr::ungroup() %>%
  dplyr::mutate(dplyr::across(dplyr::everything(), ~as.character(.x))) |>
  tidyr::pivot_longer(cols = c(dplyr::contains("rd")), names_to = 'metric', values_to = 'vals') |>
  dplyr::mutate(metric = dplyr::case_when(grepl(metric, pattern = 'target') ~ 'avg. target distance',
    grepl(metric, pattern = 'traveled') ~ 'avg. shot distance',
    grepl(metric, pattern = 'diff') ~ 'avg. target dist. - shot dist.',
    # grepl(metric, pattern = 'accuracy') ~ 'avg. accuracy',
    grepl(metric, pattern = 'strokes') ~ 'n strokes',
    grepl(metric, pattern = 'dir') ~ 'strokes w/club\nin round\nby',
    grepl(metric, pattern = 'acc') ~ '% accuracy')) |>
  dplyr::filter(!grepl(metric, pattern = 'strokes')) |>
  dplyr::mutate(date = lubridate::as_date(date),
    club = as.character(club),
    vals = as.numeric(vals))
```

```

    ) |>
ggplot2::ggplot(aes(x = date, y = vals, group = metric, color = club, fill = club)) +
ggplot2::geom_point(alpha = 0.4, size = 3) +
ggplot2::geom_line(alpha = 0.4, size = 2) +
ggplot2::geom_smooth(method = 'lm', se = F) +
ggplot2::labs(title = 'Full Stroke Averages by Club', x = 'date', y = 'value (yards or units)', fill = club) +
ggplot2::guides(alpha = 'none', size = 'none') +
ggplot2::theme_bw() +
ggplot2::theme(
  title = ggplot2::element_text(face = 'bold', size = 12),
  axis.title = ggplot2::element_text(face = 'bold', size = 10),
  axis.text = ggplot2::element_text(face = 'bold', size = 10),
  axis.text.x = ggplot2::element_text(face = 'bold', size = 7, angle = 270, hjust = 0, vjust = 1),
  legend.position = 'none',
  strip.background = ggplot2::element_rect(fill = 'white'),
  strip.text.y.right = ggplot2::element_text(face = 'bold', size = 9),
  strip.text.x.top = ggplot2::element_text(face = 'bold', size = 10)) +
ggplot2::scale_x_date(date_breaks = 'weeks', date_labels = '%b %d') +
ggplot2::facet_grid(
  rows = vars(metric),
  cols = vars(factor(club, levels = c('D', '3W', '4', '5',
                                     '6', '7', '8', '9',
                                     'PW', 'GW', 'SW', 'LW', 'P'))),
  scales = 'free')

```



Full Stroke Average

Main Metrics

```
scores_sum |>
  dplyr::mutate(course_rating = dplyr::case_when(grepl(date_course, pattern = 'Sewailo') ~ 68.9, TRUE ~
  tidyr::pivot_longer(cols = c(`Handicap Index`, `Gross Score`, `Net Score`,
    `doubles+`, bogies, pars, birdies, chips, putts,
    `UpDown%`, `Avg GIR putts`, `GIR%`, `Par 3 GIRs`,
    `Iron FIR%`, `Driver FIR%`), names_to = 'metric', values_to = 'value', v
  ggplot2::ggplot(aes(x = date_course, y = value, group = metric, color = metric, fill = metric)) +
  ggplot2::geom_point(aes(x = date, y = value, size = 4, alpha = 0.1), na.rm = T) +
  ggplot2::geom_line(aes(x = date, y = value, size = 1, alpha = 0.1), na.rm = T) +
  ggplot2::geom_smooth(aes(x = date, y = value), alpha = 0.3, method = 'lm') +
  ggplot2::labs(title = paste0('Performance Over Time\n',
    scores |>
      dplyr::distinct(date) |>
      dplyr::last() |>
```

```

        unlist() %>% lubridate::as_date(.) |>
        as.character(),
        ' - ',
        scores |>
        dplyr::distinct(date) |>
        dplyr::first() |>
        unlist() %>% lubridate::as_date(.) |>
        as.character()),
    x = 'date',
    y = 'metric',
    color = 'metric', fill = 'metric') +
ggplot2::guides(alpha = 'none', size = 'none') +
ggplot2::theme_bw() +
ggplot2::theme(legend.position = 'none',
    panel.grid.minor = ggplot2::element_blank(),
    axis.title = ggplot2::element_text(face = 'bold'),
    axis.text.y = ggplot2::element_text(face = 'bold'),
    axis.text.x = ggplot2::element_text(face = 'bold', angle = 270, hjust = 0, vjust = 0.5),
    title = ggplot2::element_text(face = 'bold'),
    strip.text.x.top = ggplot2::element_text(face = 'bold'),
    strip.background = ggplot2::element_rect(color = 'black',
        fill = 'white')) +
ggplot2::scale_x_date(date_breaks = '1 month', date_labels = '%b') +
ggplot2::facet_wrap(~factor(metric,
    levels = c('Handicap Index', 'Gross Score', 'Net Score',
        'doubles+', 'bogies', 'pars', 'birdies',
        'chips', 'putts', 'UpDown%', 'Avg GIR putts',
        'GIR%', 'Par 3 GIRs', 'Iron FIR%', 'Driver FIR%')),
    scales = 'free',
    ncol = 4)

```

Performance Over Time
2025-05-04 - 2026-07-05

