

Assignment 3, TTK4190

Shiv Jeet Rai
Arne Selle
Erik Liland

17. November 2015

Contents

1	Autopilot design	2
1.1	Heading autopilot	2
1.2	Speed autopilot	7
2	Path following and Path tracking	8
2.1	Path Generation	8
2.2	Path following	8
2.3	Path Tracking	8

1 Autopilot design

1.1 Heading autopilot

Analysis of ship characteristics

To be able to model the ship in a good way we ran many simulations with different rudder angle and measured the steady-state yaw rate. We then made a $\delta - r$ plot of the result. Since the ship was turning port while giving a positive rudder command, this plot the rest of the assignment is made with a fixed gain of -1 on δ_c .




Figure 1: $\delta - r$ plot

From figure 1 we clearly see the non-linear behavior of the ship. This motivates a 1-DOF heading model i.e. first- or second order Monoto model with non-linear extensions. To further investigate the effect of the non-linear characteristics of this ship, we compare the actual response with different models at different rudder angles. It should also be noticed that the ship has a constant drift to starboard with $\delta_c = 0$, as seen by the curve not passing through the origin. We compensate for this through the rest of the modeling part by adding a fixed rudder angle of 0.52° to the rudder input. We only need this correction while estimating the model parameters. In a closed loop, the integral effect will cancel both this drift and drift caused by wind, current and waves.

2. order linear Nomoto

$$\frac{r}{\delta}(s) = \frac{K_\nu(1 + T_3s)}{(1 + T_1s)(1 + T_2s)} \quad (1)$$

$$T_1T_2\ddot{\psi} + (T_1 + T_2)\dot{\psi} + \psi = K(\delta + T_3\dot{\delta})$$

The second order Nomoto model follows the ships overshoot some, but not enough.




Figure 2: 2.order linear Nomoto model

1. order linear Nomoto

$$\frac{r}{\delta}(s) = \frac{K}{(1 + Ts)} \quad (2)$$

$$T\ddot{\psi} + \dot{\psi} = K\delta$$

We also tried the first order version Nomoto, and as expected the model will only be accurate for small rudder angles, and is therefore not very good for modeling the non-linearities.




Figure 3: 1.order linear Nomoto model

2. order non-linear Nomoto

$$\begin{aligned} T_1 T_2 \ddot{r} + (T_1 + T_2) \dot{r} + K H_B(r) &= K(\delta + T_3 \dot{\delta}) \\ H_B(r) &= b_3 r^3 + b_2 r^2 + b_1 r + b_0 \end{aligned} \tag{3}$$

Where the steady state of $H_B(r) = \delta$. b_0 have already been taken care of in the fixed rudder offset, and by symmetry in the hull leads to $b_2 = 0$. We then only need the first- and third-order term to describe the maneuvering characteristics. By curve fitting $H_B(r) = b_3 r^3 + b_1 r = \delta$ to the obtained delta-r curve, we estimate the parameters b_3 and b_1 .

1. order non-linear Nomoto

Norbins' extension of the linear first order model:

$$\begin{aligned} T\dot{r} + H_N(r) &= K\delta \\ H_N(r) &= n_3 r^3 + n_2 r^2 + n_1 r + n_0 \end{aligned} \tag{4}$$

Where the steady state of $H_N(r) = K\delta$. We know that $n_i = \frac{b_i}{|b_1|}$, and since our ship is stable we know that $n_1 = 1$, and $n_3 = \text{sign}(b_3) = 1$ thus resulting in following model.

$$T\dot{r} + r^3 + r = K\delta \tag{5}$$

1.2 Speed autopilot

To control the surge speed of MS Fartøystyring we suggest using a linearized model, where the surge speed is decoupled from the rest of the system. We are assuming

$$u \gg v$$

which leads to

$$U = u$$

. We then use a quadratic speed model

$$K_1 \dot{u} - X_u u_r - X_{|u|u} |u_r| u_r = \tau \quad (6)$$

which leads to

$$\dot{u} = \frac{\tau + X_{|u|u} |u_r| u_r + X_u u_r}{m - X_{\dot{u}}} = \frac{X_{|u|u} |u_r| u_r + X_u u_r}{m - X_{\dot{u}}} + \tau_{nl} \quad (7)$$

where

$$\tau_{nl} = \frac{\tau}{m - X_{\dot{u}}} \Rightarrow \tau = \tau_{nl} (m - X_{\dot{u}}) \quad (8)$$

2 Path following and Path tracking

2.1 Path Generation

Her skriver vi om Path generation

2.2 Path following

Her skriver vi om Path following

2.3 Path Tracking

Her skriver vi om Path tracking




Figure 4: Third degree approximation of ship characteristics




Figure 5: 2.order non-linear Nomoto model




Figure 6: 1.order non-linear Nomoto model




Figure 7: Different trajectories