

- 1. Columnas
- 2. Tablas

Columnas y Tablas tipo objeto

Columnas

1. Columnas



```
CREATE OR REPLACE TYPE person_typ AS OBJECT(
idno VARCHAR2(9),
firstname VARCHAR2(25),
lastname VARCHAR2(25),
email VARCHAR2(25),
phone VARCHAR2(20),
MEMBER FUNCTION getIdno RETURN VARCHAR2,
MEMBER PROCEDURE displayDetails);
CREATE TYPE BODY person_typ AS
MEMBER FUNCTION getIdno RETURN VARCHAR2 IS
 BEGIN
 RETURN idno;
 END;
MEMBER PROCEDURE displayDetails IS
 BEGIN
 dbms_output.put_line(idno||' '||firstname||' '||lastname||' '||email||' '||phone);
 END;
END;
```

1. Columnas



```
CREATE TABLE contacts(
  contact person_typ,
  contact_date DATE);
```

1. Columnas



INSERCIONES

```
INSERT INTO contacts VALUES (person_typ('22446688A','Veronica','Mils','vmils@oracle.com','93456987'),sysdate);
```

CONSULTAS

```
DECLARE

persona person_typ;

BEGIN

SELECT contact INTO persona FROM contacts c WHERE c.contact.idno='22446688A';

persona.displayDetails();

END;
```

MODIFICACIONES

UPDATE contacts c SET c.contact.phone = '88888888' WHERE c.contact.idno='22446688A';

BORRADO

DELETE FROM contacts c WHERE c.contact.idno='22446688A';

Tablas

2. Tablas



CREATE TABLE person_table OF person_typ;

CREATE TABLE person_table OF person_typ (idno PRIMARY KEY, firstname NOT NULL, lastname NOT NULL);

2. Tablas

INSERCIONES

MODIFICACIONES

BORRADO



```
INSERT INTO person_table VALUES (person_typ('22446688A','Veronica','Mils','vmils@oracle.com','93456987'));

CONSULTAS

DECLARE

persona person_typ;

BEGIN

SELECT VALUE(p) INTO persona FROM person_table p WHERE p.idno='22446688A';

persona.displayDetails();

END;
```

UPDATE person_table p SET p.phone = '88888888' WHERE p.idno='22446688A';

DELETE FROM person table p WHERE p.idno='22446688A';

"Nada es absoluto. Todo cambia, todo se mueve, todo gira, todo vuela y desaparece"

FRIDA KAHLO

