

Standard GA theory

- Schema theory, schema theorem
- Two-armed bandit analogy
- Almost sure convergence
- Building block hypothesis
- Implicit parallelism
- Deceptive problems

Evolutionary Computing

GA Theory

1

Standard GA theory

Dominating theoretical paradigm 1975-1992:

Central notion: schema

schema analysis in many forms

Most recently:

- No Free Lunch Theorem (NFL)
- theoretical analysis with stronger predictive capabilities (\Rightarrow time complexity!)
- ideas from quantitative genetics, physics, etc.

Evolutionary Computing

GA Theory

2

Schemata (1)

Schema (definition):

A schema H in IB^l is a *partial* instantiation of a string in IB^l . Usually the uninstantiated elements are denoted by '*', sometimes called "don't care" symbol or "wild card". A schema defines a subset of IB^l :

$$H \in \{0, 1, *\}^l$$

Example:

$$H = \{1, 0, 0, *, 1, *, 1, 0, *, *, *\}$$

Further definitions:

- Instance of the schema H : $1\ 0\ 0\ * \ 1\ * \ 1\ 0\ * \ * \ *$
 $1\ 0\ 0\ 0\ 1\ 0\ 1\ 0\ 1\ 0\ 1$

- Set of all instances of schema $H = (h_1, \dots, h_\ell)$:
 $I(H) = \{(a_1, \dots, a_\ell) \in IB^l \mid h_i \neq * \Rightarrow a_i = h_i\}$

Evolutionary Computing

GA Theory

3

Schemata (2)

Further definitions continued:

- Order of the schema: Number of instantiated elements (6 in our example).

$$o(H) = |\{i \mid h_i \in \{0, 1\}\}|$$

- Defining length of the schema: length of the sub-string starting at the first and ending at the last instantiated element (7 in our example). Idea: it is the number of possible breakpoints

$$1\ 0\ 0\ * \ 1\ * \ 1\ 0\ * \ * \ *$$

$$d(H) = \max\{i \mid h_i \in \{0, 1\}\} - \min\{i \mid h_i \in \{0, 1\}\}$$

Evolutionary Computing

GA Theory

4


Schemata (3)

Some numbers:

- In total there are 3^l different schemata.
- Each chromosome (in IB^l) is an instance of 2^l different schemata.
- Thus: at most $N \cdot 2^l$ schemata are represented in a population of size N .

A schema can be viewed as a hyperplane of an n -dimensional space.

Examples in a 3-dimensional (hyper)cube:




Evolutionary Computing

GA Theory

5

Schemata (4)

A function and various (schema) partitions of hyperspace:



Evolutionary Computing

GA Theory

6

Schema Theorem (1)

Theorem (Holland '75):

$$m(H, t+1) \geq m(H, t) \cdot \frac{f(H)}{\bar{f}} \cdot \left(1 - p_c \frac{d(H)}{l-1}\right) \cdot (1 - p_m)^{o(H)}$$

- f to be maximised, \bar{f} : mean fitness in population
- l : length of the string
- H : a schema
- $d(H)$: defining length
- $o(H)$: order
- p_m : mutation rate
- p_c : crossover rate
- $\bar{f}(H)$: (estimated) schema fitness
- $m(H, t)$: expected number of instantiations of H in generation t

Evolutionary Computing

GA Theory

7

Schema Theorem (2)

- Expected number of instantiations of H selected for the gene pool:

$$m(H, t) \cdot \frac{f(H)}{\bar{f}}$$

- Probability that crossover does not occur within the defining length:

$$1 - p_c \frac{d(H)}{l-1}$$

- Probability that the schema is not mutated:

$$(1 - p_m)^{o(H)}$$

Evolutionary Computing

GA Theory

8

Schema Theorem (3)

Critique on the schema theorem (Bäck '96):

- Most of Holland's approximations are only true for very large numbers (trials and population size).
- Within finite populations, exponentially increasing/decreasing the number of schema instances, leads to entirely filling the population and complete elimination, respectively.
- Not all schemata are represented in a typical population.
- Schemata of large defining length are likely to be destroyed by crossover (even highly fit ones).

Evolutionary Computing

GA Theory

9

The Goldberg example (1)

String number	Initial population	x value	$f(x)$	select _i	Expected count	Actual count
	(Randomly generated)	(Unsigned integer)	(x^2)	$\left(\frac{f_i}{\sum f_i}\right)$	$\left(\frac{f_i}{\bar{f}}\right)$	(From roulette wheel)
1	0 1 1 0 1	13	169	0.14	0.58	1
2	1 1 0 0 0	24	576	0.49	1.97	2
3	0 1 0 0 0	8	64	0.06	0.22	0
4	1 0 0 1 1	19	361	0.31	1.23	1
Sum			1170	1.00	4.00	4.0
Average			293	0.25	1.00	1.0
Max			576	0.49	1.97	2.0

Schema Processing			Strings		Schema Average
			Representatives	Fitness	$f(H)$
H_1	1 * * * *	2,4			469
H_2	* 1 0 * *	2,3			320
H_3	1 * * * 0	2			576

Evolutionary Computing

GA Theory

10

The Goldberg example (2)

Mating pool after reproduction	Mate	Crossover site	New population	x Value	$f(x)$
(Cross site shown)	(Randomly selected)	(Randomly selected)		(x^2)	
0 1 1 0 1	2	4	0 1 1 0 0	12	144
1 1 0 0 0	1	4	1 1 0 0 1	25	625
1 1 0 0 0	4	2	1 1 0 1 1	27	729
1 0 0 1 1	3	2	1 0 0 0 0	16	256
					1754
					439
					729


Schema Processing					
After reproduction			After all operations		
Expected Count	Actual Count	String Representatives	Expected Count	Actual Count	String Representatives
3.20	3	2,3,4	3.20	3	2,3,4
2.18	2	2,3	1.64	2	2,3
1.97	2	2	0.00	1	4

Evolutionary Computing

GA Theory

11

K-armed bandits and GA's (1)



Two-armed bandit problem:

- arm₁: award μ_1 with variance σ_1^2
- arm₂: award μ_2 with variance σ_2^2
- $\mu_1 > \mu_2$
- Which arm (left/right) is which (1,2)?

- N = total number of trials

$$b = \frac{\sigma_1}{\mu_1 - \mu_2}$$

Evolutionary Computing

GA Theory

12

K-armed bandits and GA's (2)

Theorem (Holland '75)

Expected loss is minimal if approximately:

$$[1] \quad n^* \approx b^2 \cdot \ln \left(\frac{N^2}{8\pi \cdot b^4 \cdot \ln(N^2)} \right)$$

trials are allocated to the observed worst arm.

Corollary:

Expected loss is minimal if approximately:

$$[2] \quad N - n^* \approx \sqrt{8\pi \cdot b^4 \cdot \ln(N^2)} \cdot e^{\frac{n^*}{2b^2}}$$

trials are allocated to the observed best arm.

Evolutionary Computing

GA Theory

13

K-armed bandits and GA's (3)

We can generalize the two-armed bandit to a k-armed bandit, this gives us:

1. Generalized corollary:

Optimal strategy is to allocate an exponentially increasing number of trials to the observed best arms.

2. A link to GA's:

Minimizing expected losses from k-armed bandits

\approx

Minimizing expected losses while sampling from order $\log_2(k)$ schemata.

Thus, GA's allocate trials (near-)optimally.

Point of critique (Fogel '95): Why would this be optimal for *global* optimization? (Minimizing expected losses does not always correspond to maximizing potential gains.)

Evolutionary Computing

GA Theory

14

Almost sure convergence (1)

Theorem (Eiben et al. '91):

$$P[\lim_{t \rightarrow \infty} P_t \cap Optima \neq \emptyset] = 1$$

- P_t : population at time t
- *Optima*: Set of global optima
- Prerequisites:
 - $\max_{\bar{x} \in P(t)} f(\bar{x}) \geq \max_{\bar{x} \in P(t-1)} f(\bar{x})$ (e.g. by elitist selection)
 - any point is accessible from any other point (OK if $p_m > 0$).

Evolutionary Computing

GA Theory

15

Almost sure convergence (2)

Critique on the theorem:

- It says nothing about convergence speed
- Theory people: I don't care if it works if only it converges
- Practice people: I don't care if it converges if only it works

Theorem later generalized by Rudolph

Evolutionary Computing

GA Theory

16

Implicit parallelism

- Implicit parallelism: a GA with population size N processes more than N different schemata effectively
- Reason: individuals are instantiations of more than one schema

- Effectively processing of a schema:

Sampled at the desirable exponentially increasing rate.

- Why wouldn't a schema be processed effectively?

Schema disruption by genetic operators!

- Holland's estimate: $O(N^3)$ schemata are processed effectively when using a population of size N

Evolutionary Computing

GA Theory

17

The Building Block Hypothesis

Building Block Hypothesis (Holland '75):

GA's are able to detect short, low order and highly fit schemata and combine these into highly fit individuals.

Building blocks are small and good schemata, where:

- small is:
 - short (i.e. have a small defining length)
 - of low order, and
- good is: highly fit (estimated fitness in present population).

Implicit parallelism and the Building Block Hypothesis are seen as explanations for the power of GA's.

Evolutionary Computing

GA Theory

18

The minimal deceptive problem (1)

Goal: Define problems that mislead GA's (Goldberg '89)

- Deceptive: building blocks (small and good schemata) lead to incorrect, i.e. suboptimal, solutions
- Minimal: smallest case with such deception (two bits)
- Next we show how to construct a minimal deceptive problem

Evolutionary Computing

GA Theory

19

The minimal deceptive problem (2)

schema 1:	*	*	*	0	*	*	*	0	*	*	f_{00}
schema 2:	*	*	*	0	*	*	*	1	*	*	f_{01}
schema 3:	*	*	*	1	*	*	*	0	*	*	f_{10}
schema 4:	*	*	*	1	*	*	*	1	*	*	f_{11}

$| \leftarrow \delta(H) \rightarrow |$

- f_{xy} is the *average* fitness of the schema $* * * x * * y * *$ (assume no variance; for expected performance this assumption can be left out).
- Assume the global optimum is an instance of schema 1 and

$$[1] \quad f_{11} > \begin{cases} f_{01} \\ f_{10} \\ f_{00} \end{cases}$$

- For the problem to be deceptive, we need:

$$[2] \quad f_{0*} > f_{1*} \quad \text{and/or} \quad [3] \quad f_{*0} > f_{*1}$$

Evolutionary Computing

GA Theory

20

The minimal deceptive problem (3)

- This is true iff: $[2] \quad \frac{f_{00} + f_{01}}{2} > \frac{f_{10} + f_{11}}{2}, \text{ or}$

$$[3] \quad \frac{f_{00} + f_{10}}{2} > \frac{f_{01} + f_{11}}{2}$$

- Choosing (arbitrarily) for [2] we normalise with:

$$r = \frac{f_{11}}{f_{00}} \quad c = \frac{f_{01}}{f_{00}} \quad c' = \frac{f_{10}}{f_{00}}$$

- Using [1] we get: $[4] \quad r > c', r > 1 \text{ and } r > c.$

- Using [2] we get: $[5] \quad r < 1 + c - c'.$

- From [4] and [5] we can conclude: $[6] \quad c' < 1 \text{ and } c' < c.$

Evolutionary Computing

GA Theory


21

The minimal deceptive problem (4)

- This leaves us with two possibilities:

Type I: $f_{01} > f_{00} \quad (c > 1)$

Type II: $f_{01} \leq f_{00} \quad (c \leq 1)$



Evolutionary Computing

GA Theory

22