

Chapter 01

(version 30th August 2001)

Maarten van Steen

Vrije Universiteit Amsterdam, Faculty of Science

Dept. Mathematics and Computer Science

Room R4.20. Tel: (020) 444 7784

E-mail: steen@cs.vu.nl, URL: www.cs.vu.nl/~steen

- 01 Introduction
- 02 Communication
- 03 Processes
- 04 Naming
- 05 Synchronization
- 06 Consistency and Replication
- 07 Fault Tolerance
- 08 Security
- 09 Distributed Object-Based Systems
- 10 Distributed File Systems
- 11 Distributed Document-Based Systems
- 12 Distributed Coordination-Based Systems

00 – 1


/

Distributed System: Definition

A distributed system is a piece of software that ensures that:

A collection of independent computers that appears to its users as a single coherent system

Two aspects: (1) independent computers and
(2) single system \Rightarrow **middleware**.



01 – 1

Introduction/1.1 Definition

[illegible]

-
- This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

Introduction/1.2 Goals

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

Note: Distribution transparency may be set as a goal, but achieving it is a different story.

Introduction/1.2 Goals

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

- [illegible]

Introduction/1.2 Goals

[illegible]

Policies versus Mechanisms

Implementing openness: Requires support for different **policies** specified by applications and users:

- What level of consistency do we require for client-cached data?
- Which operations do we allow downloaded code to perform?
- Which QoS requirements do we adjust in the face of varying bandwidth?
- What level of secrecy do we require for communication?

Implementing openness: Ideally, a distributed system provides only **mechanisms**:

- Allow (dynamic) setting of caching policies, preferably per cachable item
- Support different levels of trust for mobile code
- Provide adjustable QoS parameters per data stream
- Offer different encryption algorithms

Scale in Distributed Systems

Observation: Many developers of modern distributed system easily use the adjective “scalable” without making clear *why* their system actually scales.

Scalability: At least three components:

- Number of users and/or processes
(size scalability)
- Maximum distance between nodes
(geographical scalability)
- Number of administrative domains
(administrative scalability)

Most systems account only, to a certain extent, for size scalability. The (non)solution: powerful servers.

Today, the challenge lies in geographical and administrative scalability.

Techniques for Scaling

Distribution: Partition data and computations across multiple machines:

- Move computations to clients (Java applets)
- Decentralized naming services (DNS)
- Decentralized information systems (WWW)

Replication: Make copies of data available at different machines:

- Replicated file servers (mainly for fault tolerance)
- Replicated databases
- Mirrored Web sites
- Large-scale distributed shared memory systems

Caching: Allow client processes to access local copies:

- Web caches (browser/Web proxy)
- File caching (at server and client)

Scaling – The Problem

Observation: Applying scaling techniques is easy, except for one thing:

*Having multiple copies (cached or replicated), leads to **inconsistencies**: modifying one copy makes that copy different from the rest.*

*Always keeping copies consistent and in a general way requires **global synchronization** on each modification.*

Global synchronization precludes large-scale solutions.

Observation: If we can tolerate inconsistencies, we may reduce the need for global synchronization.

Observation: Tolerating inconsistencies is application dependent.


This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

-
- This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

-
- This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.



Networks of Computers

High degree of node heterogeneity:

- High-performance parallel systems (multiprocessors as well as multicomputers)
- High-end PCs and workstations (servers)
- Simple network computers (offer users only network access)
- Mobile computers (palmtops, laptops)
- Multimedia workstations

High degree of network heterogeneity:

- Local-area gigabit networks
- Wireless connections
- Long-haul, high-latency POTS connections
- Wide-area switched megabit connections

Observation: Ideally, a distributed system hides these differences

Distributed Systems: Software Concepts


- Distributed operating system
- Network operating system
- Middleware

System	Description	Main goal
DOS	Tightly-coupled OS for multiprocessors and homogeneous multicomputers	Hide and manage hardware resources
NOS	Loosely-coupled OS for heterogeneous multicomputers (LAN and WAN)	Offer local services to remote clients
Middleware	Additional layer atop of NOS implementing general-purpose services	Provide distribution transparency

Distributed Operating System

Some characteristics:

- OS on each computer knows about the other computers
- OS on different computers generally the same
- Services are generally (transparently) distributed across computers



Multicomputer Operating System

Harder than traditional (multiprocessor) OS: Because memory is not shared, emphasis shifts to processor communication by message passing:


- Often no simple global communication:
 - Only bus-based multicomputers provide hardware broadcasting
 - Efficient broadcasting may require network interface programming techniques
- No simple systemwide synchronization mechanisms
- Virtual (distributed) shared memory requires OS to maintain global memory map in software
- Inherent distributed resource management: no central point where allocation decisions can be made

Practice: Only very few truly multicomputer operating systems exist (example: Amoeba)

Network Operating System

Some characteristics:


- Each computer has its own operating system with networking facilities
- Computers work independently (i.e., they may even have different operating systems)
- Services are tied to individual nodes (ftp, telnet, WWW)
- Highly file oriented (basically, processors share *only* files)



Distributed System (Middleware)

Some characteristics:

- OS on each computer need not know about the other computers
- OS on different computers need not generally be the same
- Services are generally (transparently) distributed across computers



This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

This image shows a single sheet of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

Middleware Services (2/2)

Control services: Services giving applications control over when, where, and how they access data:

- Distributed transaction processing
- Code migration

Security services: Services for secure processing and communication:

- Authentication and authorization services
- Simple encryption services
- Auditing service

Comparison of DOS, NOS, and Middleware

- 1: Degree of transparency
- 2: Same operating system on each node?
- 3: Number of copies of the operating system
- 4: Basis for communication
- 5: How are resources managed?
- 6: Is the system easy to scale?
- 7: How open is the system?

Item	Distributed OS		Network OS	Middle-ware DS
	multiproc.	multicomp.		
1	Very High	High	Low	High
2	Yes	Yes	No	No
3	1	N	N	N
4	Shared memory	Messages	Files	Model specific
5	Global, central	Global, distributed	Per node	Per node
6	No	Moderately	Yes	Varies
7	Closed	Closed	Open	Open

Client–Server Model

- Basic model
- Application layering
- Client–Server architectures


01 – 22

Introduction/1.5 Client–Server Model

Basic Client–Server Model (1/2)

Characteristics:

- There are processes offering services (**servers**)
- There are processes that use services (**clients**)
- Clients and servers can be distributed across different machines
- Clients follow request/reply model with respect to using services



01 – 23

Introduction/1.5 Client–Server Model

Basic Client–Server Model (2/2)

Servers: Generally provide services related to a *shared resource*:

- Servers for file systems, databases, implementation repositories, etc.
- Servers for shared, linked documents (Web, Lotus Notes)
- Servers for shared applications
- Servers for shared distributed objects

Clients: Allow remote service access:

- Programming interface transforming client's local service calls to request/reply messages
- Devices with (relatively simple) digital components (barcode readers, teller machines, hand-held phones)
- Computers providing independent user interfaces for specific services
- Computers providing an integrated user interface for related services (compound documents)


Application Layering (1/2)

Traditional three-layered view:

- User-interface layer contains units for an application's user interface
- Processing layer contains the functions of an application, i.e. without specific data
- Data layer contains the data that a client wants to manipulate through the application components

Observation: This layering is found in many distributed information systems, using traditional database technology and accompanying applications.

Application Layering (2/2)




Client-Server Architectures

Single-tiered: dumb terminal/mainframe configuration

Two-tiered: client/single server configuration

Three-tiered: each layer on separate machine

Traditional two-tiered configurations:



Alternative C/S Architectures (1/2)

Observation: Multi-tiered architectures seem to constitute buzzwords that fail to capture many modern client-server organizations.

Cooperating servers: Service is physically distributed across a collection of servers:

- Traditional multi-tiered architectures
- Replicated file systems
- Network news services
- Large-scale naming systems (DNS, X.500)
- Workflow systems
- Financial brokerage systems

Cooperating clients: Distributed application exists by virtue of client collaboration:


- Teleconferencing where each client owns a (multimedia) workstation
- Publish/subscribe architectures in which role of client and server is blurred

01-28

Introduction/1.5 Client–Server Model

Alternative C/S Architectures (2/2)

Essence: Make distinction between vertical and horizontal distribution



01-29

Introduction/1.5 Client–Server Model