

# Assignment 4: Data Wrangling

Erin Ansbro

## OVERVIEW

This exercise accompanies the lessons in Environmental Data Analytics on Data Wrangling

## Directions

1. Rename this file `<FirstLast>_A04_DataWrangling.Rmd` (replacing `<FirstLast>` with your first and last name).
2. Change “Student Name” on line 3 (above) with your name.
3. Work through the steps, **creating code and output** that fulfill each instruction.
4. Be sure to **answer the questions** in this assignment document.
5. When you have completed the assignment, **Knit** the text and code into a single PDF file.
6. Ensure that code in code chunks does not extend off the page in the PDF.

The completed exercise is due on Thursday, Sept 28th @ 5:00pm.

## Set up your session

- 1a. Load the `tidyverse`, `lubridate`, and `here` packages into your session.
  - 1b. Check your working directory.
  - 1c. Read in all four raw data files associated with the EPA Air dataset, being sure to set string columns to be read in as factors. See the README file for the EPA air datasets for more information (especially if you have not worked with air quality data previously).
2. Apply the `glimpse()` function to reveal the dimensions, column names, and structure of each dataset.

```
#1a Loading packages
library(tidyverse)
library(lubridate)
library(here)

#1b Setting wd
setwd("/Users/eka19/OneDrive - Duke University/Documents/872/EDE_Fall2023")
getwd()
```

```
## [1] "C:/Users/eka19/OneDrive - Duke University/Documents/872/EDE_Fall2023"
```

```
#1c Loading the raw data
```

```
EPA_Air_03_2018 <- read.csv("./Data/Raw/EPAair_03_NC2018_raw.csv",
                             stringsAsFactors = TRUE)
EPA_Air_03_2019 <- read.csv("./Data/Raw/EPAair_03_NC2019_raw.csv",
                             stringsAsFactors = TRUE)
EPA_Air_PM25_2018 <- read.csv("./Data/Raw/EPAair_PM25_NC2018_raw.csv",
                               stringsAsFactors = TRUE)
EPA_Air_PM25_2019 <- read.csv("./Data/Raw/EPAair_PM25_NC2019_raw.csv",
                               stringsAsFactors=TRUE)
```

```
#2 Taking a lil peek at the data
```

```
glimpse(EPA_Air_03_2019)
```

```
## Rows: 10,592
## Columns: 20
## $ Date <fct> 01/01/2019, 01/02/2019, 01/03/201~
## $ Source <fct> AirNow, AirNow, AirNow, AirNow, A~
## $ Site.ID <int> 370030005, 370030005, 370030005, ~
## $ POC <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ~
## $ Daily.Max.8.hour.Ozone.Concentration <dbl> 0.029, 0.018, 0.016, 0.022, 0.037~
## $ UNITS <fct> ppm, ppm, ppm, ppm, ppm, ppm, ppm~
## $ DAILY_AQI_VALUE <int> 27, 17, 15, 20, 34, 34, 27, 35, 3~
## $ Site.Name <fct> Taylorsville Liledoun, Taylorsvil~
## $ DAILY_OBS_COUNT <int> 24, 24, 24, 24, 24, 24, 24, 24, 2~
## $ PERCENT_COMPLETE <dbl> 100, 100, 100, 100, 100, 100, 100~
## $ AQS_PARAMETER_CODE <int> 44201, 44201, 44201, 44201, 44201~
## $ AQS_PARAMETER_DESC <fct> Ozone, Ozone, Ozone, Ozone, Ozone~
## $ CBSA_CODE <int> 25860, 25860, 25860, 25860, 25860~
## $ CBSA_NAME <fct> "Hickory-Lenoir-Morganton, NC", "~
## $ STATE_CODE <int> 37, 37, 37, 37, 37, 37, 37, 37, 3~
## $ STATE <fct> North Carolina, North Carolina, N~
## $ COUNTY_CODE <int> 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, ~
## $ COUNTY <fct> Alexander, Alexander, Alexander, ~
## $ SITE_LATITUDE <dbl> 35.9138, 35.9138, 35.9138, 35.913~
## $ SITE_LONGITUDE <dbl> -81.191, -81.191, -81.191, -81.19~
```

```
glimpse(EPA_Air_03_2018)
```

```
## Rows: 9,737
## Columns: 20
## $ Date <fct> 03/01/2018, 03/02/2018, 03/03/201~
## $ Source <fct> AQS, AQS, AQS, AQS, AQS, AQS, AQS~
## $ Site.ID <int> 370030005, 370030005, 370030005, ~
## $ POC <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ~
## $ Daily.Max.8.hour.Ozone.Concentration <dbl> 0.043, 0.046, 0.047, 0.049, 0.047~
## $ UNITS <fct> ppm, ppm, ppm, ppm, ppm, ppm, ppm~
## $ DAILY_AQI_VALUE <int> 40, 43, 44, 45, 44, 28, 33, 41, 4~
## $ Site.Name <fct> Taylorsville Liledoun, Taylorsvil~
## $ DAILY_OBS_COUNT <int> 17, 17, 17, 17, 17, 17, 17, 17, 1~
## $ PERCENT_COMPLETE <dbl> 100, 100, 100, 100, 100, 100, 100~
## $ AQS_PARAMETER_CODE <int> 44201, 44201, 44201, 44201, 44201~
## $ AQS_PARAMETER_DESC <fct> Ozone, Ozone, Ozone, Ozone, Ozone~
## $ CBSA_CODE <int> 25860, 25860, 25860, 25860, 25860~
```

```
## $ CBSA_NAME          <fct> "Hickory-Lenoir-Morganton, NC", "~
## $ STATE_CODE         <int> 37, 37, 37, 37, 37, 37, 37, 37, 3~
## $ STATE              <fct> North Carolina, North Carolina, N~
## $ COUNTY_CODE        <int> 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, ~
## $ COUNTY             <fct> Alexander, Alexander, Alexander, ~
## $ SITE_LATITUDE      <dbl> 35.9138, 35.9138, 35.9138, 35.913~
## $ SITE_LONGITUDE     <dbl> -81.191, -81.191, -81.191, -81.19~
```

`glimpse(EPA_Air_PM25_2018)`

```
## Rows: 8,983
## Columns: 20
## $ Date              <fct> 01/02/2018, 01/05/2018, 01/08/2018, 01/~
## $ Source            <fct> AQS, AQS, AQS, AQS, AQS, AQS, AQS, AQS, ~
## $ Site.ID           <int> 370110002, 370110002, 370110002, 370110~
## $ POC               <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ~
## $ Daily.Mean.PM2.5.Concentration <dbl> 2.9, 3.7, 5.3, 0.8, 2.5, 4.5, 1.8, 2.5, ~
## $ UNITS             <fct> ug/m3 LC, ug/m3 LC, ug/m3 LC, ug/m3 LC, ~
## $ DAILY_AQI_VALUE   <int> 12, 15, 22, 3, 10, 19, 8, 10, 18, 7, 24~
## $ Site.Name         <fct> Linville Falls, Linville Falls, Linvill~
## $ DAILY_OBS_COUNT   <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ~
## $ PERCENT_COMPLETE <dbl> 100, 100, 100, 100, 100, 100, 100, 100, ~
## $ AQS_PARAMETER_CODE <int> 88502, 88502, 88502, 88502, 88502, 8850~
## $ AQS_PARAMETER_DESC <fct> Acceptable PM2.5 AQI & Speciation Mass, ~
## $ CBSA_CODE         <int> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ CBSA_NAME         <fct> "", "", "", "", "", "", "", "", "", "", ~
## $ STATE_CODE        <int> 37, 37, 37, 37, 37, 37, 37, 37, 37, 37, ~
## $ STATE             <fct> North Carolina, North Carolina, North C~
## $ COUNTY_CODE       <int> 11, 11, 11, 11, 11, 11, 11, 11, 11, 11, ~
## $ COUNTY            <fct> Avery, Avery, Avery, Avery, Avery, Aver~
## $ SITE_LATITUDE     <dbl> 35.97235, 35.97235, 35.97235, 35.97235, ~
## $ SITE_LONGITUDE    <dbl> -81.93307, -81.93307, -81.93307, -81.93~
```

`glimpse(EPA_Air_PM25_2019)`

```
## Rows: 8,581
## Columns: 20
## $ Date              <fct> 01/03/2019, 01/06/2019, 01/09/2019, 01/~
## $ Source            <fct> AQS, AQS, AQS, AQS, AQS, AQS, AQS, AQS, ~
## $ Site.ID           <int> 370110002, 370110002, 370110002, 370110~
## $ POC               <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ~
## $ Daily.Mean.PM2.5.Concentration <dbl> 1.6, 1.0, 1.3, 6.3, 2.6, 1.2, 1.5, 1.5, ~
## $ UNITS             <fct> ug/m3 LC, ug/m3 LC, ug/m3 LC, ug/m3 LC, ~
## $ DAILY_AQI_VALUE   <int> 7, 4, 5, 26, 11, 5, 6, 6, 15, 7, 14, 20~
## $ Site.Name         <fct> Linville Falls, Linville Falls, Linvill~
## $ DAILY_OBS_COUNT   <int> 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, ~
## $ PERCENT_COMPLETE <dbl> 100, 100, 100, 100, 100, 100, 100, 100, ~
## $ AQS_PARAMETER_CODE <int> 88502, 88502, 88502, 88502, 88502, 8850~
## $ AQS_PARAMETER_DESC <fct> Acceptable PM2.5 AQI & Speciation Mass, ~
## $ CBSA_CODE         <int> NA, NA, NA, NA, NA, NA, NA, NA, NA, NA, ~
## $ CBSA_NAME         <fct> "", "", "", "", "", "", "", "", "", "", ~
## $ STATE_CODE        <int> 37, 37, 37, 37, 37, 37, 37, 37, 37, 37, ~
## $ STATE             <fct> North Carolina, North Carolina, North C~
```

```
## $ COUNTY_CODE          <int> 11, 11, 11, 11, 11, 11, 11, 11, 11, 11,~
## $ COUNTY               <fct> Avery, Avery, Avery, Avery, Avery, Aver~
## $ SITE_LATITUDE        <dbl> 35.97235, 35.97235, 35.97235, 35.97235,~
## $ SITE_LONGITUDE       <dbl> -81.93307, -81.93307, -81.93307, -81.93~
```

## Wrangle individual datasets to create processed files.

3. Change the Date columns to be date objects.
4. Select the following columns: Date, DAILY\_AQI\_VALUE, Site.Name, AQS\_PARAMETER\_DESC, COUNTY, SITE\_LATITUDE, SITE\_LONGITUDE
5. For the PM2.5 datasets, fill all cells in AQS\_PARAMETER\_DESC with “PM2.5” (all cells in this column should be identical).
6. Save all four processed datasets in the Processed folder. Use the same file names as the raw files but replace “raw” with “processed”.

### *#3 Changing to Dates*

```
EPA_Air_03_2018$Date <- as.Date(EPA_Air_03_2018$Date,format = "%m/%d/%Y")
EPA_Air_03_2019$Date <- as.Date(EPA_Air_03_2019$Date, format = "%m/%d/%Y" )
EPA_Air_PM25_2018$Date <- as.Date(EPA_Air_PM25_2018$Date, format = "%m/%d/%Y" )
EPA_Air_PM25_2019$Date <- as.Date(EPA_Air_PM25_2019$Date, format = "%m/%d/%Y" )
```

### *#4 Choosing my columns*

```
EPA_Air_03_2018_subset <- select(EPA_Air_03_2018, Date,
                                DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC,
                                COUNTY, SITE_LATITUDE, SITE_LONGITUDE )

EPA_Air_03_2019_subset <- select(EPA_Air_03_2019, Date,
                                DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC,
                                COUNTY, SITE_LATITUDE, SITE_LONGITUDE )

EPA_Air_PM25_2018_subset <- select(EPA_Air_PM25_2018,Date,
                                DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC,
                                COUNTY, SITE_LATITUDE, SITE_LONGITUDE)

EPA_Air_PM25_2019_subset <- select(EPA_Air_PM25_2019,Date,
                                DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC,
                                COUNTY, SITE_LATITUDE, SITE_LONGITUDE)
```

### *#5 Filling column in with PM2.5*

#### *#changing 2018 data*

```
class(EPA_Air_PM25_2018_subset$AQS_PARAMETER_DESC)
```

```
## [1] "factor"
```

```
EPA_Air_PM25_2018_subset$AQS_PARAMETER_DESC <-
  as.character(EPA_Air_PM25_2018_subset$AQS_PARAMETER_DESC)
```

```
EPA_Air_PM25_2018_subset$AQS_PARAMETER_DESC[EPA_Air_PM25_2018_subset$AQS_PARAMETER_DESC
%in% c("PM2.5 - Local Conditions","Acceptable PM2.5 AQI &
Speciation Mass")] <- "PM2.5"
```

```
EPA_Air_PM25_2018_subset$AQS_PARAMETER_DESC<-
  as.factor(EPA_Air_PM25_2018_subset$AQS_PARAMETER_DESC)

class(EPA_Air_PM25_2018_subset$AQS_PARAMETER_DESC)
```

```
## [1] "factor"
```

```
#changing 2019 data
class(EPA_Air_PM25_2019_subset$AQS_PARAMETER_DESC)
```

```
## [1] "factor"
```

```
EPA_Air_PM25_2019_subset$AQS_PARAMETER_DESC<-
  as.character(EPA_Air_PM25_2019_subset$AQS_PARAMETER_DESC)

EPA_Air_PM25_2019_subset$AQS_PARAMETER_DESC[EPA_Air_PM25_2019_subset$AQS_PARAMETER_DESC
%in% c("PM2.5 - Local Conditions", "Acceptable PM2.5 AQI & Speciation Mass")] <- "PM2.5"

EPA_Air_PM25_2019_subset$AQS_PARAMETER_DESC <-
  as.factor(EPA_Air_PM25_2019_subset$AQS_PARAMETER_DESC)

class(EPA_Air_PM25_2018_subset$AQS_PARAMETER_DESC)
```

```
## [1] "factor"
```

```
#6 Saving processed data
write.csv(EPA_Air_03_2018_subset, row.names = FALSE, file = "./Data/Processed/EPAair_03_NC2018_processed.csv")
write.csv(EPA_Air_03_2019_subset, row.names = FALSE, file = "./Data/Processed/EPAair_03_NC2019_processed.csv")
write.csv(EPA_Air_PM25_2018_subset, row.names = FALSE, file = "./Data/Processed/EPAair_PM25_NC2018_processed.csv")
write.csv(EPA_Air_PM25_2019_subset, row.names = FALSE, file = "./Data/Processed/EPAair_PM25_NC2019_processed.csv")
```

## Combine datasets

7. Combine the four datasets with `rbind`. Make sure your column names are identical prior to running this code.
8. Wrangle your new dataset with a pipe function (`%>%`) so that it fills the following conditions:
  - Include only sites that the four data frames have in common: “Linville Falls”, “Durham Armory”, “Leggett”, “Hattie Avenue”, “Clemmons Middle”, “Mendenhall School”, “Frying Pan Mountain”, “West Johnston Co.”, “Garinger High School”, “Castle Hayne”, “Pitt Agri. Center”, “Bryson City”, “Millbrook School” (the function `intersect` can figure out common factor levels - but it will include sites with missing site information, which you don’t want...)
  - Some sites have multiple measurements per day. Use the split-apply-combine strategy to generate daily means: group by date, site name, AQS parameter, and county. Take the mean of the AQI value, latitude, and longitude.
  - Add columns for “Month” and “Year” by parsing your “Date” column (hint: `lubridate` package)
  - Hint: the dimensions of this dataset should be 14,752 x 9.

9. Spread your datasets such that AQI values for ozone and PM2.5 are in separate columns. Each location on a specific date should now occupy only one row.
10. Call up the dimensions of your new tidy dataset.
11. Save your processed dataset with the following file name: "EPAair\_O3\_PM25\_NC1819\_Processed.csv"

#### #7 Combining data sets

```
colnames(EPA_Air_O3_2018_subset)
```

```
## [1] "Date"          "DAILY_AQI_VALUE"  "Site.Name"
## [4] "AQS_PARAMETER_DESC" "COUNTY"          "SITE_LATITUDE"
## [7] "SITE_LONGITUDE"
```

```
colnames(EPA_Air_O3_2019_subset)
```

```
## [1] "Date"          "DAILY_AQI_VALUE"  "Site.Name"
## [4] "AQS_PARAMETER_DESC" "COUNTY"          "SITE_LATITUDE"
## [7] "SITE_LONGITUDE"
```

```
colnames(EPA_Air_PM25_2018_subset)
```

```
## [1] "Date"          "DAILY_AQI_VALUE"  "Site.Name"
## [4] "AQS_PARAMETER_DESC" "COUNTY"          "SITE_LATITUDE"
## [7] "SITE_LONGITUDE"
```

```
colnames(EPA_Air_PM25_2019_subset)
```

```
## [1] "Date"          "DAILY_AQI_VALUE"  "Site.Name"
## [4] "AQS_PARAMETER_DESC" "COUNTY"          "SITE_LATITUDE"
## [7] "SITE_LONGITUDE"
```

```
EPA_Air <- rbind(EPA_Air_O3_2018_subset,EPA_Air_O3_2019_subset,
                 EPA_Air_PM25_2018_subset, EPA_Air_PM25_2019_subset)
```

#### #8 Finding more specific data

```
EPA_Air_subset<-
```

```
  EPA_Air %>%
```

```
  filter(Site.Name %in% c("Linville Falls", "Durham Armory", "Leggett",
                          "Hattie Avenue", "Clemmons Middle", "Mendenhall School",
                          "Frying Pan Mountain", "West Johnston Co.", "Garinger High School",
                          "Castle Hayne", "Pitt Agri. Center", "Bryson City",
                          "Millbrook School"))%>%
```

```
  group_by(Date,Site.Name,AQS_PARAMETER_DESC,COUNTY) %>%
```

```
  summarise(meanAQI = mean(DAILY_AQI_VALUE),
            meanLAT = mean(SITE_LATITUDE),
            meanLONG = mean(SITE_LONGITUDE)) %>%
```

```
  mutate(Month=month(Date))%>%
```

```
  mutate(Year=year(Date))
```

```
## 'summarise()' has grouped output by 'Date', 'Site.Name', 'AQS_PARAMETER_DESC'.
## You can override using the '.groups' argument.
```

```
#9 Combining data
EPA_Air_subset_spread <- pivot_wider(EPA_Air_subset,
  names_from = AQS_PARAMETER_DESC, values_from = meanAQI)

#10 Dimensions of new data
dim(EPA_Air_subset_spread)
```

```
## [1] 8976 10
```

```
#11 Saving processed data
write.csv(EPA_Air_subset_spread, row.names = FALSE, file = "../Data/Processed/EPAair_03_PM25_NC1819_Processed.csv")
```

## Generate summary tables

12. Use the split-apply-combine strategy to generate a summary data frame. Data should be grouped by site, month, and year. Generate the mean AQI values for ozone and PM2.5 for each group. Then, add a pipe to remove instances where mean **ozone** values are not available (use the function `drop_na` in your pipe). It's ok to have missing mean PM2.5 values in this result.
13. Call up the dimensions of the summary dataset.

```
#12 Summarizing subset data
EPA_Air_subset_spread_summary <-
  EPA_Air_subset_spread %>%
  group_by(Site.Name, Month, Year) %>%
  summarise(meanAQI_PM = mean(PM2.5),
    meanAQI_O3 = mean(Ozone)) %>%
  drop_na(meanAQI_O3)
```

```
## 'summarise()' has grouped output by 'Site.Name', 'Month'. You can override
## using the '.groups' argument.
```

```
#13 What are the dimensions of summarized data
dim(EPA_Air_subset_spread_summary)
```

```
## [1] 182 5
```

14. Why did we use the function `drop_na` rather than `na.omit`?

Answer: Looking at the help section in R, it appears `na.omit` only works for vectors, matrices, and dataframes comprising of vectors and matrices. Does it have to do with that we had different data types within the data frame?