NAME

AtomTypesFingerprints

SYNOPSIS

use Fingerprints::AtomTypesFingerprints;

use Fingerprints::AtomTypesFingerprints qw(:all);

DESCRIPTION

AtomTypesFingerprints class provides the following methods:

new, GenerateFingerprints, GetDescription, SetAtomIdentifierType, SetAtomTypesSetToUse, SetAtomicInvariantsToUse, SetFunctionalClassesToUse, SetType, StringifyAtomTypesFingerprints

AtomTypesFingerprints is derived from Fingerprints class which in turn is derived from ObjectProperty base class that provides methods not explicitly defined in AtomNeighborhoodsFingerprints, Fingerprints or ObjectProperty classes using Perl's AUTOLOAD functionality. These methods are generated on-the-fly for a specified object property:

```
Set<PropertyName>(<PropertyValue>);
$PropertyValue = Get<PropertyName>();
Delete<PropertyName>();
```

The current release of MayaChemTools supports generation of AtomTypesFingerpritns corresponding to following AtomI dentifierTypes:

```
AtomicInvariantsAtomTypes, DREIDINGAtomTypes, EStateAtomTypes, FunctionalClassAtomTypes, MMFF94AtomTypes, SLogPAtomTypes, SYBYLAtomTypes, TPSAAtomTypes, UFFAtomTypes
```

Based on the values specified for AtomI dentifierType along with other specified parameters such as AtomicI nvariantsToUse and FunctionalClassesToUse, initial atom types are assigned to all non-hydrogen atoms or all atoms in a molecule.

Using the assigned atom types and specified Type, one of the following types of fingerprints are generated:

```
AtomTypesCount - A vector containing count of atom types
AtomTypesBits - A bit vector indicating presence/absence of atom types
```

For AtomTypesCount fingerprints, two types of atom types set size is allowed:

```
ArbitrarySize - Corresponds to only atom types detected in molecule FixedSize - Corresponds to fixed number of atom types previously defined
```

For AtomTypesBits fingerprints, only FixedSize atom type set is allowed.

ArbitrarySize corresponds to atom types detected in a molecule where as FixedSize implies a fix number of all possible atom types previously defined for a specific AtomIdentifierType.

Fix number of all possible atom types for supported AtomIdentifierTypes in current release of MayaChemTools are:

AtomIdentifier	Total	TotalWithoutHydrogens
DREIDINGAtomTypes	37	34
EStateAtomTypes	109	87
MMFF94AtomTypes	212	171
SLogPAtomTypes	72	67
SYBYLAtomTypes	45	44
TPSAAtomTypes	47	47
UFFAtomTypes	126	124

Combination of Type and AtomTypesSetToUse along with AtomtomI dentifierType allows generation of following different atom types fingerprints:

Туре	AtomIdentifierType	AtomTypesSetToUse
AtomTypesCount	AtomicInvariantsAtomTypes	ArbitrarySize
AtomTypesCount AtomTypesCount AtomTypesBits	DREIDINGAtomTypes DREIDINGAtomTypes DREIDINGAtomTypes	ArbitrarySize FixedSize FixedSize

www.MayaChemTools.org Page 1

AtomTypesCount	EStateAtomTypes	ArbitrarySize
AtomTypesCount	EStateAtomTypes	FixedSize
AtomTypesBits	EStateAtomTypes	FixedSize
AtomTypesCount	FunctionalClassAtomTypes	ArbitrarySize
AtomTypesCount	MMFF94AtomTypes	ArbitrarySize
AtomTypesCount	MMFF94AtomTypes	FixedSize
AtomTypesBits	MMFF94AtomTypes	FixedSize
AtomTypesCount	SLogPAtomTypes	ArbitrarySize
AtomTypesCount	SLogPAtomTypes	FixedSize
AtomTypesBits	SLogPAtomTypes	FixedSize
AtomTypesCount	SYBYLAtomTypes	ArbitrarySize
AtomTypesCount	SYBYLAtomTypes	FixedSize
AtomTypesBits	SYBYLAtomTypes	FixedSize
AtomTypesCount	TPSAAtomTypes	FixedSize
AtomTypesBits	TPSAAtomTypes	FixedSize
AtomTypesCount	UFFAtomTypes	ArbitrarySize
AtomTypesCount	UFFAtomTypes	FixedSize
AtomTypesBits	UFFAtomTypes	FixedSize

The current release of MayaChemTools generates the following types of atom types fingerprints bit-vector and vector strings:

FingerprintsVector;AtomTypesCount:AtomicInvariantsAtomTypes:ArbitrarySize;10;NumericalValues;IDsAndValuesString;C.X1.B01.H3 C.X2.B02.H2 C.X2.B03.H1 C.X3.B03.H1 C.X3.B04 F.X1.B01 N.X2.B02.H1 N.X3.B03 O.X1.B01.H1 O.X1.B02;2 4 14 3 10 1 1 1 3 2

FingerprintsVector;AtomTypesCount:DREIDINGAtomTypes:ArbitrarySize;8;Nu
mericalValues;IDsAndValuesString;C_2 C_3 C_R F_ N_3 N_R O_2 O_3;2 9 22
1 1 1 2 3

FingerprintsVector;AtomTypesCount:EStateAtomTypes:ArbitrarySize;11;Num ericalValues;IDsAndValuesString;aaCH aasC aasN dO dssC sCH3 sF sOH ssC H2 ssNH sssCH;14 8 1 2 2 2 1 3 4 1 3

FingerprintsVector;AtomTypesCount:FunctionalClassAtomTypes:ArbitrarySize;8;NumericalValues;IDsAndValuesString;Ar Ar.HBA HBA HBA.HBD HBD Hal NI None;22 1 2 3 1 1 1 10

FingerprintsVector;AtomTypesCount:MMFF94AtomTypes:ArbitrarySize;13;NumericalValues;IDsAndValuesString;C5A C5B C=ON CB COO CR F N5 NC=O O=CN O=CO OC=O OR;2 2 1 18 1 9 1 1 1 1 1 1 2

FingerprintsVector;AtomTypesCount:SLogPAtomTypes:ArbitrarySize;16;NumericalValues;IDsAndValuesString;C1 C10 C11 C14 C18 C20 C21 C22 C5 CS F N11 N4 O10 O2 O9;5 1 1 1 14 4 2 1 2 2 1 1 1 1 3 1

FingerprintsVector;AtomTypesCount:SYBYLAtomTypes:ArbitrarySize;9;Numer
icalValues;IDsAndValuesString;C.2 C.3 C.ar F N.am N.ar 0.2 0.3 0.co2;2
9 22 1 1 1 1 2 2

FingerprintsVector;AtomTypesCount:UFFAtomTypes:ArbitrarySize;8;Numeric alValues;IDsAndValuesString;C_2 C_3 C_R F_ N_3 N_R O_2 O_3;2 9 22 1 1 1 2 3

METHODS

new

```
$NewAtomTypesFingerprints = new AtomTypesFingerprints(%NamesAndValues);
```

Using specified *AtomTypesFingerprints* property names and values hash, new method creates a new object and returns a reference to newly created PathLengthFingerprints object. By default, the following properties are initialized:

```
Molecule = '';
   Type = ''
   AtomIdentifierType = ''
   AtomTypesSetToUse = ''
    IgnoreHydrogens = 1
   AtomicInvariantsToUse = ['AS', 'X', 'BO', 'H', 'FC', 'MN']
   FunctionalClassesToUse = ['HBD', 'HBA', 'PI', 'NI', 'Ar', 'Hal']
Examples:
    $AtomTypesFingerprints = new AtomTypesFingerprints(
                              'Molecule' => $Molecule,
                              'Type' => 'AtomTypesCount',
                               'AtomIdentifierType' =>
                                               'AtomicInvariantsAtomTypes');
    $AtomTypesFingerprints = new AtomTypesFingerprints(
                              'Molecule' => $Molecule,
                              'Type' => 'AtomTypesCount',
                              'AtomIdentifierType' =>
                                               'AtomicInvariantsAtomTypes',
                              'AtomicInvariantsToUse' =>
                                               ['AS', 'X', 'BO', 'H', 'FC'] );
    $AtomTypesFingerprints = new AtomTypesFingerprints(
                              'Molecule' => $Molecule,
                              'Type' => 'AtomTypesCount',
                              'AtomIdentifierType' =>
                                               'DREIDINGAtomTypes');
    $AtomTypesFingerprints = new AtomTypesFingerprints(
                              'Molecule' => $Molecule,
                               'Type' => 'AtomTypesCount',
                               'AtomIdentifierType' =>
                                               'EStateAtomTypes',
                              'AtomTypesSetToUse' =>
                                               'ArbitrarySize');
    $AtomTypesFingerprints = new AtomTypesFingerprints(
                              'Molecule' => $Molecule,
                               'Type' => 'AtomTypesCount',
                               'AtomIdentifierType' =>
                                               'SLogPAtomTypes',
                              'AtomTypesSetToUse' =>
                                               'FixedSize');
    $AtomTypesFingerprints = new AtomTypesFingerprints(
                              'Molecule' => $Molecule,
                              'Type' => 'AtomTypesBits',
                              'AtomIdentifierType' =>
                                               'MMFF94AtomTypes',
                              'AtomTypesSetToUse' =>
                                               'FixedSize');
    $AtomTypesFingerprints->GenerateFingerprints();
   print "$AtomTypesFingerprints\n";
```

GenerateFingerprints

```
$AtomTypesFingerprints->GenerateFingerprints();
```

Generates atom types fingerprints and returns AtomTypesFingerprints.

GetDescription

```
$Description = $AtomTypesFingerprints->GetDescription();
```

Returns a string containing description of atom types fingerprints.

SetAtomI dentifierType

```
$AtomTypesFingerprints->SetAtomIdentifierType($IdentifierType);
```

Sets atom IdentifierType to use during atom types fingerprints generation and returns AtomTypesFingerprints.

Possible values: AtomicInvariantsAtomTypes, DREIDINGAtomTypes, EStateAtomTypes, FunctionalClassAtomTypes, MMFF94AtomTypes, SLogPAtomTypes, SYBYLAtomTypes, TPSAAtomTypes, UFFAtomTypes.

SetAtomTypesSetToUse

```
$AtomTypesFingerprints->SetAtomTypesSetToUse($Value);
```

Sets Value of AtomTypesSetToUse and returns AtomTypesFingerprints. Possible values: ArbitrarySize or FixedSize. Default for AtomTypesCount value of AtomTypesSetToUse: ArbitrarySize.

SetAtomicInvariantsToUse

```
$AtomTypesFingerprints->SetAtomicInvariantsToUse($ValuesRef);
$AtomTypesFingerprints->SetAtomicInvariantsToUse(@Values);
```

Sets atomic invariants to use during *AtomicInvariantsAtomTypes* value of *AtomIdentifierType* for atom neighborhood fingerprints generation and returns *AtomTypesFingerprints*.

Possible values for atomic invariants are: AS, X, BO, LBO, SB, DB, TB, H, Ar, RA, FC, MN, SM. Default value: AS, X, BO, H, FC.

The atomic invariants abbreviations correspond to:

```
AS = Atom symbol corresponding to element symbol
```

Atom type generated by AtomTypes::AtomicInvariantsAtomTypes class corresponds to:

```
AS.X<n>.BO<n>.LBO<n>.<SB><n>.<DB><n>.<TB><n>.H<n>.Ar.RA.FC<+n/-n>.MN<n>.SM<n>
```

Except for AS which is a required atomic invariant in atom types, all other atomic invariants are optional. Atom type specification doesn't include atomic invariants with zero or undefined values.

In addition to usage of abbreviations for specifying atomic invariants, the following descriptive words are also allowed:

```
X : NumOfNonHydrogenAtomNeighbors or NumOfHeavyAtomNeighbors
BO : SumOfBondOrdersToNonHydrogenAtoms or SumOfBondOrdersToHeavyAtoms
LBO : LargestBondOrderToNonHydrogenAtoms or LargestBondOrderToHeavyAtoms
SB : NumOfSingleBondsToNonHydrogenAtoms or NumOfSingleBondsToHeavyAtoms
DB : NumOfDoubleBondsToNonHydrogenAtoms or NumOfDoubleBondsToHeavyAtoms
TB : NumOfTripleBondsToNonHydrogenAtoms or NumOfTripleBondsToHeavyAtoms
H : NumOfImplicitAndExplicitHydrogens
Ar : Aromatic
RA : RingAtom
FC : FormalCharge
MN : MassNumber
SM : SpinMultiplicity
```

AtomTypes::AtomicInvariantsAtomTypes module is used to assign atomic invariant atom types.

SetFunctionalClassesToUse

\$AtomTypesFingerprints->SetFunctionalClassesToUse(\$ValuesRef);

www.MayaChemTools.org Page 5

\$AtomTypesFingerprints->SetFunctionalClassesToUse(@Values);

Sets functional classes invariants to use during *FunctionalClassAtomTypes* value of *AtomIdentifierType* for atom types fingerprints generation and returns *AtomTypesFingerprints*.

Possible values for atom functional classes are: Ar, CA, H, HBA, HBD, Hal, NI, PI, RA. Default value [Ref 24]: HBD, HBA, PI, NI, Ar, Hal.

The functional class abbreviations correspond to:

HBD: HydrogenBondDonor
HBA: HydrogenBondAcceptor
PI : PositivelyIonizable
NI : NegativelyIonizable
Ar : Aromatic
Hal : Halogen
H : Hydrophobic

RA : RingAtom CA : ChainAtom

Functional class atom type specification for an atom corresponds to:

Ar.CA.H.HBA.HBD.Hal.NI.PI.RA or None

AtomTypes::FunctionalClassAtomTypes module is used to assign functional class atom types. It uses following definitions [Ref 60-61, Ref 65-66]:

```
HydrogenBondDonor: NH, NH2, OH
HydrogenBondAcceptor: N[!H], O
PositivelyIonizable: +, NH2
NegativelyIonizable: -, C(=0)OH, S(=0)OH, P(=0)OH
```

SetType

\$AtomTypesFingerprints->SetType(\$Type);

Sets type of AtomTypes fingerpritns and returns AtomTypesFingerprints. Possible values: AtomTypesFingerprintsBits or AtomTypesFingerprintsCount.

String if y Atom Types Finger prints

```
$String = $AtomTypesFingerprints->StringifyAtomTypesFingerprints();
```

Returns a string containing information about AtomTypesFingerprints object.

AUTHOR

Manish Sud <msud@san.rr.com>

SEE ALSO

Fingerprints.pm, FingerprintsStringUtil.pm, AtomNeighborhoodsFingerprints.pm, EStateIndiciesFingerprints.pm, ExtendedConnectivityFingerprints.pm, MACCSKeys.pm, PathLengthFingerprints.pm, TopologicalAtomPairsFingerprints.pm, TopologicalAtomTripletsFingerprints.pm, TopologicalAtomTorsionsFingerprints.pm,

 $Topological Pharmacophore Atom Pairs Finger prints.pm,\ Topological Pharmacophore Atom Triplets Finger prints.pm$

COPYRIGHT

Copyright (C) 2017 Manish Sud. All rights reserved.

This file is part of MayaChemTools.

MayaChemTools is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.