Brite-Kleen APT-DEOX NC-620

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 2/20/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Brite-Kleen APT-DEOX NC-620

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Deoxidizer for Aluminum

1.3. Supplier

A Brite Company
3217 Wood Dr
Garland, Dallas, TX 75041
USA
T 1-888-8ABRITE
www.abrite.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Oxidizing liquids Category 2	H272	May intensify fire; oxidizer
Corrosive to metals Category 1	H290	May be corrosive to metals
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Acute toxicity (inhalation:dust,mist) Category 2	H330	Fatal if inhaled
Skin corrosion/irritation Category 1A	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Carcinogenicity Category 1A	H350	May cause cancer (oral)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H272 - May intensify fire; oxidizer
H290 - May be corrosive to metals
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H330 - Fatal if inhaled
H350 - May cause cancer (oral)
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.
P220 - Keep/Store away from clothing and other combustible materials
P221 - Take any precaution to avoid mixing with combustibles
P234 - Keep only in original container.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P284 - [In case of inadequate ventilation] wear respiratory protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P320 - Specific treatment is urgent (see supplemental first aid instruction on this label).
P321 - Specific treatment (see supplemental first aid instruction on this label).
P330 - Rinse mouth.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P390 - Absorb spillage to prevent material-damage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P406 - Store in corrosive resistant container with a resistant inner liner.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

63.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
99.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
90.55% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
iron(III)sulphate	CAS-No.: 10028-22-5	20-30	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318

Name	Product identifier	%	GHS US classification
sulfuric acid	CAS-No.: 7664-93-9	1-10	Acute Tox. 1 (Inhalation:vapour), H330 Skin Corr. 1A, H314 Eye Dam. 1, H318 Carc. 1A, H350
nitric acid, conc≥99%	CAS-No.: 7697-37-2	1-10	Ox. Liq. 2, H272 Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately. Call a doctor.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : May intensify fire; oxidizer.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Incompatible materials : Combustible materials. Metals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Brite-Kleen APT-DEOX NC-620
No additional information available

iron(III)sulphate (10028-22-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m³

sulfuric acid (7664-93-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sulfuric acid
ACGIH OEL TWA	0.2 mg/m³ (Thoracic fraction)
Remark (ACGIH)	TLV® Basis: Pulm func. Notations: A2 (Suspected Human Carcinogen. Classification refers to sulfuric acid contained in strong inorganic acid mists)
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Sulfuric acid
OSHA PEL TWA [1]	1 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

nitric acid, conc≥99% (7697-37-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Nitric acid
ACGIH OEL TWA [ppm]	2 ppm
ACGIH OEL STEL [ppm]	4 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; dental erosion
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Nitric acid
OSHA PEL TWA [1]	5 mg/m³
OSHA PEL TWA [2]	2 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves

Eye protection:
Safety glasses

Skin and body protection:
Wear suitable protective clothing

Respiratory protection:
Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Color	:	Mixture contains one or more component(s) which have the following colour(s): White Pure substance: colourless Unpurified: yellow to brown Colourless
Odor	:	There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Almost odourless Characteristic odour Asphyxiating odour Irritating/pungent odour
Odor threshold	:	No data available
pH	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Flammability (solid, gas)	:	Not applicable.
Vapor pressure	:	No data available
Relative vapor density at 20 °C	:	No data available
Relative density	:	No data available
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosion limits	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

May intensify fire; oxidizer.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Combustible materials. metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Fatal if inhaled.

Brite-Kleen APT-DEOX NC-620	
ATE US (oral)	626.523 mg/kg body weight
ATE US (dust, mist)	0.414 mg/l/4h
Unknown acute toxicity (GHS US)	63.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 99.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 90.55% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

iron(III)sulphate (10028-22-5)	
LD50 oral rat	500 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Read-across, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 1.1 mg/l (EPA OPP 81-3: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (dust))
ATE US (oral)	500 mg/kg body weight

sulfuric acid (7664-93-9)	
LD50 oral rat	2140 mg/kg body weight (Rat, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	0.38 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 21 day(s))
ATE US (oral)	2140 mg/kg body weight
ATE US (vapors)	0.38 mg/l/4h
ATE US (dust, mist)	0.375 mg/l/4h

nitric acid, conc≥99% (7697-37-2)	
LC50 Inhalation - Rat	> 2.65 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : May cause cancer (oral).

sulfuric acid (7664-93-9)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

nitric acid, conc≥99% (7697-37-2)	
NOAEL (oral,rat,90 days)	1500 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation,rat,gas,90 days)	2.15 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Symptoms/effects after skin contact : Burns.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

iron(III)sulphate (10028-22-5)	
LC50 - Fish [1]	37.2 mg/l Source: HSDB
EC50 - Crustacea [1]	11.5 mg/l (48 h, Daphnia sp., Literature study)

sulfuric acid (7664-93-9)	
LC50 - Fish [1]	16 – 28 mg/l (96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	0.15 mg/l Test organisms (species): other:
NOEC chronic fish	0.31 mg/l Test organisms (species): Salvelinus fontinalis

nitric acid, conc≥99% (7697-37-2)	
LC50 - Fish [1]	1559 mg/l Test organisms (species): other:
LC50 - Fish [2]	1354 mg/l Test organisms (species): other:

12.2. Persistence and degradability

iron(III)sulphate (10028-22-5)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

sulfuric acid (7664-93-9)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

nitric acid, conc≥99% (7697-37-2)	
Persistence and degradability	Biodegradability: not applicable.

12.3. Bioaccumulative potential

iron(III)sulphate (10028-22-5)	
BCF - Fish [1]	2 – 20 (OECD 305: Bioconcentration: Flow-Through Fish Test, 28 day(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across, Fresh weight)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

sulfuric acid (7664-93-9)	
Partition coefficient n-octanol/water (Log Pow)	-2.2 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.

nitric acid, conc≥99% (7697-37-2)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

iron(III)sulphate (10028-22-5)	
Surface tension	No data available in the literature
Ecology - soil	Adsorbs into the soil.

sulfuric acid (7664-93-9)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.

nitric acid, conc≥99% (7697-37-2)	
Ecology - soil	No (test)data on mobility of the component(s) available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector’s sorting instructions.

SECTION 14: Transport information

DOT	TDG	IMDG	IATA
14.1. UN number			
3264	Not applicable	3264	3264
14.2. Proper Shipping Name			
Corrosive liquid, acidic, inorganic, n.o.s. (Sulfuric Acid, metallic salts)	Not applicable	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Sulfuric Acid, metallic salts)	Corrosive liquid, acidic, inorganic, n.o.s. (Sulfuric Acid, metallic salts)
14.3. Transport hazard class(es)			
8	Not applicable	8	8
 Not applicable			
14.4. Packing group			
II	Not applicable	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Not applicable	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN3264

DOT Special Provisions (49 CFR 172.102) : 386 - Notwithstanding the provisions of §177.834(l) of this subchapter, cargo heaters may be used when weather conditions are such that the freezing of a wetted explosive material is likely. Shipments must be made by private, leased or contract carrier vehicles under exclusive use of the offeror. Cargo heaters must be reverse refrigeration (heat pump) units. Shipments made in accordance with this Special provision are excepted from the requirements of §173.60(b)(4) of this subchapter.

B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx)	:	154
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	202
DOT Packaging Bulk (49 CFR 173.xxx)	:	242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	30 L
DOT Vessel Stowage Location	:	B - (i) The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) ‘‘On deck only’’ on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	:	40 - Stow ‘‘clear of living quarters’’,53 - Stow ‘‘separated from’’ alkaline compounds,58 - Stow ‘‘separated from’’ cyanides

TDG

Emergency Response Guide (ERG) Number	:	154

IMDG

Special provision (IMDG)	:	274
Limited quantities (IMDG)	:	1 L
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P001
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T11
Tank special provisions (IMDG)	:	TP2, TP27
EmS-No. (Fire)	:	F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	:	S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	:	B
Properties and observations (IMDG)	:	Causes burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y840
PCA limited quantity max net quantity (IATA)	:	0.5L
PCA packing instructions (IATA)	:	851
PCA max net quantity (IATA)	:	1L
CAO packing instructions (IATA)	:	855
CAO max net quantity (IATA)	:	30L
Special provision (IATA)	:	A3, A803
ERG code (IATA)	:	8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

sulfuric acid	CAS-No. 7664-93-9	1-10%

nitric acid, conc≥99%	CAS-No. 7697-37-2	1-10%

iron(III)sulphate (10028-22-5)	
CERCLA RQ	1000 lb

sulfuric acid (7664-93-9)	
CERCLA RQ	1000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

nitric acid, conc≥99% (7697-37-2)	
CERCLA RQ	1000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

15.2. International regulations

sulfuric acid (7664-93-9)
Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H272	May intensify fire; oxidizer
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H330	Fatal if inhaled
H350	May cause cancer

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.