

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 5/18/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Brite-Kleen SC-200-L
Product code : C2-17116

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Liquid Soak Cleaner for Ferrous and Non-Ferrous Metals

1.3. Supplier

A Brite Company
3217 Wood Dr
Garland, Dallas, TX 75041
USA
T 1-888-8ABRITE
www.abrite.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids, Category 4	H227	Combustible liquid
Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Acute toxicity (dermal), Category 3	H311	Toxic in contact with skin.
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled.
Skin corrosion/irritation, Category 1	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Carcinogenicity, Category 1A	H350	May cause cancer.
Specific target organ toxicity – Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H227 - Combustible liquid
H302+H332 - Harmful if swallowed or if inhaled
H311 - Toxic in contact with skin.
H314 - Causes severe skin burns and eye damage.
H318 - Causes serious eye damage.
H350 - May cause cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P312 - Call a poison center or doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P322 - Specific treatment (see supplemental first aid instruction on this label).
P330 - Rinse mouth.
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

85.26% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
59.66% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
91.56% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
sodium hydroxide, conc=50%, aqueous solution	CAS-No.: 1310-73-2	30-40	Acute Tox. 3 (Dermal), H311 Skin Corr. 1, H314 Eye Dam. 1, H318

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
butyl glycoether	CAS-No.: 111-76-2	1-10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373
dodecylbenzenesulphonic acid	CAS-No.: 27176-87-0	1-10	Acute Tox. 4 (Oral), H302 Skin Corr. 1, H314 Eye Dam. 1, H318 STOT RE 2, H373
D-Glucopyranose, oligomeric, decyl octyl glycoside	CAS-No.: 68515-73-1	1-10	STOT RE 2, H373
sodium xylenesulfonate	CAS-No.: 1300-72-7	<2	Acute Tox. 3 (Inhalation:vapour), H331 Eye Irrit. 2, H319
sulfuric acid	CAS-No.: 7664-93-9	0.1-1.0	Acute Tox. 1 (Inhalation:vapour), H330 Skin Corr. 1A, H314 Eye Dam. 1, H318 Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

- Fire hazard : Combustible liquid.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing.
Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up.

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Brite-Kleen SC-200-L	
No additional information available	
sodium hydroxide, conc=50%, aqueous solution (1310-73-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sodium hydroxide
ACGIH OEL C	2 mg/m ³
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Sodium hydroxide
OSHA PEL TWA [1]	2 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
dodecylbenzenesulphonic acid (27176-87-0)	
No additional information available	
sulfuric acid (7664-93-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sulfuric acid
ACGIH OEL TWA	0.2 mg/m ³ (Thoracic fraction)
Remark (ACGIH)	TLV® Basis: Pulm func. Notations: A2 (Suspected Human Carcinogen. Classification refers to sulfuric acid contained in strong inorganic acid mists)
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	Sulfuric acid
OSHA PEL TWA [1]	1 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
butyl glycolether (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2022
USA - ACGIH - Biological Exposure Indices	
Local name	2- BUTOXYETHANOL
BEI	200 mg/g creatinine Parameter: Butoxyacetic acid (BAA) (with hydrolysis) - Medium: urine - Sampling time: End of shift

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)	
Regulatory reference	ACGIH 2022
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL TWA [1]	240 mg/m ³
OSHA PEL TWA [2]	50 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
D-Glucopyranose, oligomeric, decyl octyl glycoside (68515-73-1)	
No additional information available	
sodium xylenesulfonate (1300-72-7)	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : dark brown
Odour : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure.
Mixture contains one or more component(s) which have the following odour:
Odourless Pleasant odour Characteristic odour Almost odourless Irritating/pungent odour
Asphyxiating odour Sweet odour Mild odour Fruity odour Aromatic odour
Odour threshold : No data available
pH : No data available

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 100 °C
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.2
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Toxic in contact with skin.
Acute toxicity (inhalation)	: Harmful if inhaled.

Brite-Kleen SC-200-L

ATE US (oral)	1966.467 mg/kg bodyweight
---------------	---------------------------

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Brite-Kleen SC-200-L	
ATE US (dermal)	354.338 mg/kg bodyweight
ATE US (dust,mist)	2.482 mg/l/4h
Unknown acute toxicity (GHS US)	85.26% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 59.66% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 91.56% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
sodium hydroxide, conc=50%, aqueous solution (1310-73-2)	
LD50 dermal rabbit	325 mg/kg Source: ECHA
ATE US (dermal)	325 mg/kg bodyweight
dodecylbenzenesulphonic acid (27176-87-0)	
LD50 oral rat	1080 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	0.31 mg/l air (4 h, Rat, Male, Read-across, Inhalation (aerosol), 14 day(s))
ATE US (oral)	1080 mg/kg bodyweight
sulfuric acid (7664-93-9)	
LD50 oral rat	2140 mg/kg bodyweight (Rat, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	0.38 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 21 day(s))
ATE US (oral)	2140 mg/kg bodyweight
ATE US (vapours)	0.38 mg/l/4h
ATE US (dust,mist)	0.375 mg/l/4h
butyl glycoether (111-76-2)	
LD50 oral rat	1746 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 4.26 mg/l (4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1414 mg/kg bodyweight
ATE US (gases)	4500 ppmv/4h
ATE US (vapours)	3 mg/l/4h
ATE US (dust,mist)	1.5 mg/l/4h
D-Glucopyranose, oligomeric, decyl octyl glycoside (68515-73-1)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

sodium xylenesulfonate (1300-72-7)	
LD50 oral rat	> 7000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 6.41 mg/l (Equivalent or similar to OECD 403, 232 minutes, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
ATE US (vapours)	3 mg/l/4h
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
sulfuric acid (7664-93-9)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens
butyl glycolether (111-76-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
dodecylbenzenesulphonic acid (27176-87-0)	
LOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
LOAEL (dermal, rat/rabbit, 90 days)	286 mg/kg bodyweight Animal: rat, Animal sex: male
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	< 286 mg/kg bodyweight Animal: rat, Animal sex: male
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
butyl glycolether (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
D-Glucopyranose, oligomeric, decyl octyl glycoside (68515-73-1)	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

sodium hydroxide, conc=50%, aqueous solution (1310-73-2)	
LC50 - Fish [1]	125 mg/l
EC50 - Crustacea [1]	40.4 mg/l Test organisms (species): Ceriodaphnia sp.
dodecylbenzenesulphonic acid (27176-87-0)	
LC50 - Fish [1]	4.1 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	2.5 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Similar product, Nominal concentration)
ErC50 algae	65.4 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)
sulfuric acid (7664-93-9)	
LC50 - Fish [1]	16 – 28 mg/l (96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	0.15 mg/l Test organisms (species): other:
NOEC chronic fish	0.31 mg/l Test organisms (species): Salvelinus fontinalis
butyl glycoether (111-76-2)	
LC50 - Fish [1]	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	1840 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
D-Glucopyranose, oligomeric, decyl octyl glycoside (68515-73-1)	
LC50 - Fish [1]	100.81 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	170 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
sodium xylenesulfonate (1300-72-7)	
LC50 - Fish [1]	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

sodium hydroxide, conc=50%, aqueous solution (1310-73-2)

Persistence and degradability	Biodegradability: not applicable.
-------------------------------	-----------------------------------

dodecylbenzenesulphonic acid (27176-87-0)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

Chemical oxygen demand (COD)	2.41 g O ₂ /g substance
------------------------------	------------------------------------

sulfuric acid (7664-93-9)

Persistence and degradability	Biodegradability: not applicable.
-------------------------------	-----------------------------------

Chemical oxygen demand (COD)	Not applicable
------------------------------	----------------

ThOD	Not applicable
------	----------------

BOD (% of ThOD)	Not applicable
-----------------	----------------

butyl glycoether (111-76-2)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

sodium xylenesulfonate (1300-72-7)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

12.3. Bioaccumulative potential

sodium hydroxide, conc=50%, aqueous solution (1310-73-2)

Partition coefficient n-octanol/water (Log Pow)	-3.88 Source: SRC
---	-------------------

Bioaccumulative potential	Does not contain bioaccumulative component(s).
---------------------------	--

dodecylbenzenesulphonic acid (27176-87-0)

BCF - Fish [1]	65 – 96 (OECD 305: Bioconcentration: Flow-Through Fish Test, 32 day(s), Pimephales promelas, Static system, Fresh water, Experimental value, Fresh weight)
----------------	--

Partition coefficient n-octanol/water (Log Pow)	1.96 (Weight of evidence approach, Equivalent or similar to OECD 107, 25 °C)
---	--

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
---------------------------	--

sulfuric acid (7664-93-9)

Partition coefficient n-octanol/water (Log Pow)	-2.2 (Estimated value)
---	------------------------

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

butyl glycoether (111-76-2)

Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value, BASF test, 25 °C)
---	---

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
---------------------------	--

sodium xylenesulfonate (1300-72-7)

Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
---	---

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

12.4. Mobility in soil

sodium hydroxide, conc=50%, aqueous solution (1310-73-2)

Ecology - soil	No (test)data on mobility of the component(s) available.
----------------	--

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

dodecylbenzenesulphonic acid (27176-87-0)	
Surface tension	29.3 – 31.8 N/m (25 °C, 120 mg/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.96 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Calculated value)
Ecology - soil	Low potential for mobility in soil.
sulfuric acid (7664-93-9)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.
butyl glycoether (111-76-2)	
Surface tension	65.03 mN/m (20 °C, 2 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.451 – 0.882 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
D-Glucopyranose, oligomeric, decyl octyl glycoside (68515-73-1)	
Mobility in soil	0.2624 Source: EPISUITE
sodium xylenesulfonate (1300-72-7)	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.42 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

DOT	TDG	IMDG	IATA
14.1. UN number			
3266	Not applicable	3266	3266
14.2. Proper Shipping Name			
Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide, potassium silicate)	Not applicable	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (sodium hydroxide, potassium silicate)	Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide, potassium silicate)
14.3. Transport hazard class(es)			
8	Not applicable	8	8

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	IATA
 Not applicable			
14.4. Packing group			
II	Not applicable	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Not applicable	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

DOT

UN-No.(DOT)	: UN3266
DOT Special Provisions (49 CFR 172.102)	: 386 - Notwithstanding the provisions of §177.834(l) of this subchapter, cargo heaters may be used when weather conditions are such that the freezing of a wetted explosive material is likely. Shipments must be made by private, leased or contract carrier vehicles under exclusive use of the offeror. Cargo heaters must be reverse refrigeration (heat pump) units. Shipments made in accordance with this Special provision are excepted from the requirements of §173.60(b)(4) of this subchapter. B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG

Emergency Response Guide (ERG) Number : 154

IMDG

Special provisions (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T11
Tank special provisions (IMDG) : TP2, TP27
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG) : B
Properties and observations (IMDG) : Reacts violently with acids. Causes burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y840
PCA limited quantity max net quantity (IATA) : 0.5L
PCA packing instructions (IATA) : 851
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 855
CAO max net quantity (IATA) : 30L
Special provisions (IATA) : A3, A803
ERG code (IATA) : 8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

sulfuric acid	CAS-No. 7664-93-9	0.1-1.0%
---------------	-------------------	----------

sodium hydroxide, conc=50%, aqueous solution (1310-73-2)

CERCLA RQ	1000 lb
-----------	---------

dodecylbenzenesulphonic acid (27176-87-0)

CERCLA RQ	1000 lb
-----------	---------

sulfuric acid (7664-93-9)

CERCLA RQ	1000 lb
-----------	---------

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
--	---------

Brite-Kleen SC-200-L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

sulfuric acid (7664-93-9)

SARA Section 302 Threshold Planning Quantity (TPQ)

1000 lb

15.2. International regulations

sulfuric acid (7664-93-9)

Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-statements

H227	Combustible liquid
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.