Overview

The data and code in this replication package reproduce all tables and figures in Hengel (2022). Raw data are in the O-data/fixed directory. Transformed data, estimation results and figures are saved in the O-data/generated, O-tex/genderated and O-images/generated directories, respectively. The replication code, described in detail below, will take about 10–11 hours to run.

The data in this replication package are publicly available and licensed under a Creative Commons Attribution 4.0 International License. See LICENSE.txt for details.

Data

Main dataset: read.db

Almost all figures and tables in Hengel (2022) were generated using the raw data in O-data/fixed/read.db. read.db is an SQLite database of biblio- and biographic data on articles and authors published in the American Economic Review (AER), Econometrica, Journal of Political Economy (JPE), Quarterly Journal of Economics (QJE) and the Review of Economic Studies (REStud). read.db contains 12 tables. Their contents and provenance are described below. Figure 1 displays read.db's entity-relationship diagram; Table 1 describes each column. Please see Hengel (2022), Section 2 and Appendices C and D (online appendix) for additional details on data provenance and variable construction.

• Article. The Article table contains bibliographic information from every English-language article published with an abstract in the AER, Econometrica, JPE and QJE between January 1950 and December 2015 (inclusive). It also contains data on REStud articles published with submission and acceptance dates during that same period.

All data were collected from publicly available sources (e.g., publishers' websites and JSTOR). The exception is citations which were obtained from Web of Science in September 2017 and January 2018. (Citation data are proprietary to Web of Science and are included here for replication purposes only; please do not distribute these data or publish online.) Data on submitaccept times and institutions were collected from journals' online archives, extracted from digitised articles using the open source command utility pdftotext or entered manually by me or a research assistant.

The column Abstract contains unicode textual data of articles' abstracts. When using the data, please ensure it is imported with the proper encoding (e.g., encoding("utf-8") in Stata (14+) or iconv(, from="macintosh", to="UTF-8") in R).

• Author. The Author table contains biographic details on authors. Gender was initially assigned using GenderChecker.com's database of male and female names. Three separate Mechanical Turk workers, a research assistant or I then manually verified them based on photos and other information found on faculty websites, Wikipedia articles, etc. In situations where the author could not be found, I emailed or telephoned colleagues and associated institutions.

Authors were assumed to be native-English speakers if one or more of the following criteria were satisfied: (i) they were raised in an English-speaking country; (ii) they obtained all post-secondary education from English speaking institutions; or (iii) they spoke with no discernible non-native accent. This information was almost always found on authors' CVs, websites, Wikipedia articles, faculty bios or obituaries. In a small number of cases the criteria were ambiguously satisfied or not available; in these instances I asked friends and colleagues of the author or inferred English fluency from the author's first name, country of residence or surname (in that order). If one co-author on a paper was found to be a native English speaker, I did not necessarily check whether any of the other co-authors were also native English speakers.

- AuthorCorr. The AuthorCorr table maps AuthorID in Author to ArticleID in Article.
- Children. The Children table contains data on the year female authors with at least one exclusively female-authored paper published in *Econometrica* gave birth. This information was obtained from authors' published profiles, CVs, acknowledgements, Wikipedia, personal websites, Facebook pages, background checks and by consulting local school district/popular extra-curricular activity websites. Exact years were recorded whenever found; otherwise, they were approximated by subtracting a




Figure 1: Entity-relationship diagram for $\mathtt{read.db}$

child's actual or estimated age from the date the source material was posted online. In several instances, I obtained or verified this information from acquaintances, friends and colleagues or by asking the woman directly. If an exhaustive search turned up no reference to children, I assumed the woman in question did not have any.

Please note that data on children's birth years were only systematically collected for children potentially born during the time a woman had an exclusively female-authored paper under review at *Econometrica*.

- EditorBoard. The EditorBoard table contains the AuthorID for every editor and each issue of a journal. Editors were identified from issue mastheads.
- Inst. The Inst table maps each unique InstID to an institution name.
- InstCorr. The InstCorr table maps each (ArticleID, AuthorID) combination in AuthorCorr to at least one InstID in Inst.
- **JEL**. The JEL table maps *JEL* codes to each ArticleID in Article. The *JEL* system was significantly revised in the 1990s; because exact mapping from one system to another is not possible, I collected these data only for articles published post-reform. Codes were recorded whenever found in the text of an article or on the websites where bibliographic information was scraped. Remaining articles were classified using data from the American Economic Association's Econlit database.
- NBER. The NBER table contains basic bibliographic data on the NBER working papers that were eventually published in a top-four journal. Data were scraped from the NBER website or extracted from digitised working papers.
- NBERCorr. The NBERCorr table maps each NberID in NBER to at least one ArticleID in Article. (The mapping is not one-for-one because a small number of working papers were eventually published as multiple articles or combined into one.) Matches were identified using citation data from RePEc and by searching NBER's database directly for unmatched papers authored by NBER family members. The column Note contains notes in situations where the matching process involved some degree of ambiguity (e.g., because of title changes between draft and final versions of the paper).
- ReadStat. The ReadStat table contains readability statistics for every article with an abstract in Article. Readability scores were generated with the Python module Textatistic using the text in the Abstract column of the Article table. Textatistic's code and documentation are available on GitHub; a brief description is provided in Hengel (2022), Appendix D.3.
- NberStat. The NberStat table contains readability statistics calculated from the Abstract text of every working paper in the NBER table. Statistics were generated using the Python module Textatistic.

Table 1: Description of variables in read.db

| Table | Column name | Description |
|---------|-------------|-----------------------------------------------------------|
| Article | ArticleID | Unique ID for each article |
| Article | Journal | Journal (AER , ECA , JPE , QJE , RES , $P&P$) |
| Article | PubDate | Date of publication (YYYY-MM-DD) |
| Article | Title | Title |
| Article | Abstract | Abstract |
| Article | Language | Language (e.g., English or French) |
| Article | Received | Date (YYYY-MM-01) manuscript first submitted |
| Article | Accepted | Date (YYYY-MM-01) manuscript finally accepted |
| Article | Volume | Volume |
| Article | Issue | Issue |
| Article | Part | Part |
| Article | FirstPage | First page number |
| Article | LastPage | Last page number |
| Article | CiteCount | Citation count (Web of Science) |
| Article | Note | Notes on observation |

| Table | Column name | Description |
|-------------|----------------|-------------------------------------------------------------------|
| Author | AuthorID | Unique ID for each author |
| Author | AuthorName | Author name |
| Author | Sex | Author gender |
| Author | NativeLanguage | Native-English speaking indicator (English, Non-English, Unknown) |
| AuthorCorr | AuthorID | Unique ID for each author (maps to Author table) |
| AuthorCorr | ArticleID | Unique ID for each article (maps to Article table) |
| Children | AuthorID | Unique ID for each author (maps to Author table) |
| Children | Year | Year a child was born |
| Children | BirthOrder | Order of birth if two children are born in the same year |
| EditorBoard | AuthorID | Unique ID for each editor (maps to Author table) |
| EditorBoard | Journal | Journal |
| EditorBoard | Part | Part |
| EditorBoard | Volume | Volume |
| EditorBoard | Issue | Issue |
| Inst | InstID | Unique ID for each institution |
| Inst | InstName | Institution name |
| InstCorr | InstID | Unique ID for each institution (maps to Inst table) |
| InstCorr | ArticleID | Unique ID for each article (maps to Article table) |
| InstCorr | AuthorID | Unique ID for each author (maps to Author table) |
| JEL | ArticleID | Unique ID for each article (maps to Article table) |
| JEL | JEL | Tertiary JEL code |
| NBER | NberID | Unique ID for each NBER working paper |
| NBER | WPDate | Date (YYYY-MM-DD) manuscript was released as a working paper |
| NBER | Title | Working paper title |
| NBER | Abstract | Working paper abstract |
| NBER | Note | Notes on observation and/or matching process |
| NBERCorr | NberID | Unique ID for each NBER working paper (maps to NBER table) |
| NBERCorr | ArticleID | Unique ID for each article (maps to Article table) |
| ReadStat | ArticleID | Unique ID for each article (maps to Article table) |
| ReadStat | StatName | Name of statistic (e.g., flesch) |
| ReadStat | StatValue | Value of statistic |
| NBERStat | NberID | Unique ID for each NBER working paper (maps to NBER table) |
| NBERStat | StatName | Name of statistic |
| NBERStat | StatValue | Value of statistic |

CSV files

To facilitate future third-party research, all tables and data in read.db—with the exception of citation counts, which are proprietary to Web of Science—have also been saved as CSV files in the O-data/fixed/read_excluding_confidential-csv directory.

Other datasets

A small number of figures and tables in Hengel (2022) are generated from data contained in introduction_text.txt, readability_corr.txt and JEL.csv. Their contents and provenance are described below and in Table 2.

- introduction_text.txt. This file contains the first paragraph of text to come after a heading explicitly titled "Introduction" in NBER working papers eventually published in top-four journals. Data are used to generate Figure D.2 in Appendix D.2 in Hengel (2022). Textual data kindly provided by Henrik Kleven and Dana Scott.
- readability_corr.txt. This file contains coefficients of correlations between the five readability scores used in Hengel (2022) and alternative measures of text difficulty. These figures are from the studies listed in Appendix D.4. They are used to produce the top graphic of Figure D.1 in Appendix D.1.
- JEL.csv. The file JEL.csv categorises all tertiary JEL codes as either theory/methodology, empirical or other. Categorisation was done manually by me. Data in JEL.csv are used to generate Table

C.1 and construct the theory/methodology, empirical and other dummies described in Appendix C.

Table 2: Description of variables in other datasets

| | Column | |
|-----------------------|-------------|---------------------------------------------------|
| File name | name | Description |
| introduction_text.txt | NberID | Unique ID for each NBER working paper |
| introduction_text.txt | Text | First paragraph of text |
| readability_corr.txt | StatName | Name of readability statistic |
| readability_corr.txt | Correlation | Coefficient of correlation |
| readability_corr.txt | Test | Name of alternative measure of text difficulty |
| readability_corr.txt | TestType | Type of alternative measure |
| readability_corr.txt | Source | BibTeX label for source study (e.g., SurnameYYYY) |
| readability_corr.txt | Note | Notes on calculations, etc. |
| JEL.csv | JEL | Tertiary JEL code |
| JEL.csv | Description | Long name of JEL code |
| JEL.csv | Туре | Classification (empirical, theory or other) |

Code

Software requirements

- Python 3.9.0
 - pandas (1.2.3)
 - Textatistic (0.0.1)
 - Please see below for instructions on how to install these packages.
- R 4.1.2
 - RSQLite (2.2.9)
 - tidyverse (1.3.1)
 - haven (2.4.3)
 - remotes (2.4.2)
 - lexicon (1.3.1, from https://github.com/trinker/readability)
 - textclean (0.9.7, from https://github.com/trinker/readability)
 - textshape (1.7.4, from https://github.com/trinker/readability)
 - syllable (0.2.0, from https://github.com/trinker/readability)
 - readability (0.1.2, from https://github.com/trinker/readability)
 - The file 2-update-readability.R installs the latest version of all dependencies.
- Stata 17.0
 - ftools (2.37.0)
 - estout (3.24)
 - psmatch2 (4.0.12)
 - xtabond2 (3.7.0)
 - listtex (25 September 2009)
 - reghdfe (5.7.3)
 - binscatter (7.02)
 - distinct (1.2.1)
 - labutil (1.0.0)
 - coefplot (1.8.5)
 - wordwrap (0.2, from https://mloeffler.github.io/stata/wordwrap)
 - The file 4-master.do locally installs the latest version of all dependencies.
- Mathematica 12.3.1

Optional portions of the code use bash scripting and WolframScript; instructions for installing the latter are provided below.

Instructions to replicators

To generate all figures and tables in Hengel (2022), first navigate to the project's root directory and then copy 4-confidential-data-not-for-publication/read.db to 0-data/fixed/read.db.¹ Next, execute the following five steps.

- 1. Run 1-update-textatistic.py in Python.
- 2. Run 2-update-readability.R in R.
- 3. Run 3-export-raw-data.py in Python.
- 4. Run 4-master.do in Stata.
- 5. Execute Figure-3.nb and Figure-G.2.nb (both in the 0-code/output directory) in Mathematica.

Each step can be executed individually by following the steps outlined below. Alternatively, the Bash script 5-master.sh completes all five steps automatically. To run 5-master.sh, install the latest version of WolframScript and follow the instructions under the 1-update-textatistic.py heading for installing Textatistic and pandas. Then, navigate to the project's root directory and issue the following command in a Bash shell:

```
sh 5-master.sh
```

5-master.sh was last run on 12 March 2022 on a 4-core Intel-based iMac running MacOS version 11.6.5. Computation took 10 hours, 12 minutes and 20 seconds.

1-update-textatistic.py

The Python script 1-update-textatistic.py calculates readability scores for every article and NBER working paper with an abstract in read.db and updates its ReadStat and NBERStat tables with the results. More details on the Textatistic program are available on GitHub. Documentation on how it calculates readability scores are available at erinhengel.com.

For 1-update-textatistic.py to work, you must first install the Python package Textatistic.² If you're lucky, this can be done in a single step by issuing the following command in your terminal application:

```
pip install textatistic
```

But you're probably not lucky. The problem is the PyHyphen dependency; for reasons I do not fully understand, pip does not always properly install it before trying to install Textatistic.

If you encounter this error, you will need to install both PyHyphen and Textatistic from source. But don't panic; it's not that hard. Just navigate to the project's root directory and issue the following sequence of commands in your terminal application.³

```
cd "0-code/programs/Textatistic/required_packages/PyHyphen-2.0.5/"
sudo python setup.py install
cd ../..
sudo python setup.py install
```

Once Textatistic has been properly installed, navigate back to the project's root directory and run the following command in the terminal application.

```
python 1-update-textatistic.py
```

You will be alerted when the ReadStat and NBERStat tables in read.db have been successfully updated with the newly calculated readability statistics.

1-update-textatistic.py was last run on 16 January 2022 on a 4-core Intel-based iMac running MacOS version 11.6.3. Computation took 2 minutes and 7 seconds.

 $^{^1\}mathrm{CiteCount}$ is proprietary to Web of Science and are included here for replication purposes only; please do not distribute these data or publish online.

²1-update-textatistic.py also requires the re, sys and sqlite3 (3.32.3) libraries, which are automatically installed with Python 3.9.0.

³PyHyphen may need to be installed using Python 3.7 or earlier.

2-update-readability.R

The R script 2-update-readability.R (R version 4.1.2) calculates readability scores using the R readability package. To run it, open R, set the current working directory as the project directory and issue the following command:

source("2-update-readability.R")

2-update-readability.R first installs the latest version of RSQLite, tidyverse, haven and remotes from CRAN. It then installs readability, syllable, textshape, textclean and lexicon from GitHub. Once these packages are installed and loaded, it connects to the read.db SQLite database, fetches published article and NBER abstracts, calculates readability scores and exports the results to readstat.dta and nberstat.dta in the 0-data/generated directory. Finally, it reads in introduction_text.txt, calculates readability scores and exports the result to articlestat.dta, also in the 0-data/generated directory.

2-update-readability.R was last run on 7 February 2022 on a 4-core Intel-based iMac running MacOS version 11.6.4 Computation took 2 minutes and 14 seconds to run.

3-export-raw-data.py

The Python script 3-export-raw-data.py (Python version 3.9.0) exports raw data from read.db as csv files for further processing in Stata. To run it, you will need to install the pandas module (version 1.2.3). Usually, this can be done with pip by issuing the following command in your terminal application.⁴

pip install pandas

Once pandas has been properly installed, navigate to the project's root directory and run the following command in the terminal application.

python 3-export-raw-data.py

The raw data generated by 3-export-raw-data.py are saved in the 0-data/generated directory.

3-export-raw-data.py was last run on 10 March 2022 on a 4-core Intel-based iMac running MacOS version 11.6.5. Computation took less than a minute.

4-master.do

The Stata script master.do (Stata version 17.0) generates all figures and tables in Hengel (2022) with the exception of Figure 3 and Figure G.2 (see below).

To run 4-master.do, open a Stata terminal, navigate to the project's root directory and issue the following command:

do 4-master.do

4-master.do first installs several third-party packages from SSC (ftools, estout, psmatch2, xtabond2, listtex, reghdfe, binscatter, distinct, labutil and coefplot) and wordwrap from GitHub. It then copies the ado, scheme, colors and estout definition files in the 0-code/programs/stata directory into your Stata personal ado directory. (Alternatively, manually load these files into Stata before running 4-master.do and comment out lines 25-29.) It then transforms the raw data (results are saved in 0-data/generated) and executes the Stata do files in the 0-code/output directory. A log of all output is saved in the 0-log directory as YYYY-MM-DD-HH-MM-SS.smcl.

Estimation results are either saved as LaTeX output in the O-tex/generated directory or as image files in the O-images/generated directory. All output (including output for the online appendix) are saved in these directories. Figures in the main body of Hengel (2022) are saved with their table/figure numbers, e.g., O-tex/generated/Table-2.tex or O-images/generated/Figure-1.pdf. Figures in the online appendix are saved either with their table or figure numbers (e.g., O-tex/generated/Table-J.1.tex or O-images/generated/Figure-G.2.pdf) or, in instances where they replicate a table in the main body of the paper, as Figure-X-<<modification>>.pdf or Table-X-<<modification>>.tex, where X is the number of the figure or table being replicated and <<modification>> is the modification applied to

⁴3-export-raw-data.py also requires the sqlite3 (3.32.3) library, which is automatically installed with Python 3.9.0.

it. For example, Table M.2 in the online appendix replicates Table 4 using only solo-authored papers. It is saved as O-tex/generated/Table-4-FemSolo.tex. Figure J.1 replicates Figure 5 controlling for primary *JEL* code; it is saved as O-images/generated/Figure-4-jel.pdf. See the Appendix for a table mapping figures and tables in Hengel (2022) to the appropriate output files.

4-master.do was last run on 11 March 2022 on a 4-core Intel-based iMac running MacOS version 11.6.5 Computation took 11 hours 13 minutes and 16 seconds.

Create Mathematica graphs

Figures 3 and G.2 in Hengel (2022) were created using Mathematica (version 12.3.1). To generate them, follow the three steps below:

- Navigate to the O-code/output directory and open the files Figure-3.nb and Figure-G.2.nb in Mathematica.
- 2. Select "Evaluate Notebook" from the Evaluation dropdown menu.
- 3. Click "Yes" to run the initialisation cells.

Figure-3.nb generates Figure-3.png; Figure-G.2.nb generates Figure-G.2.png. Both files are saved in the O-images/generated directory.

Figure-3.nb and Figure-G.2.nb were last run on 16 January 2022 on a 4-core Intel-based iMac running MacOS version 11.6.3. Combined computation took less than a minute.

References

American Economic Association (2022). *EconLit [database]*. American Economic Association, Nashville Tennessee. https://www.aeaweb.org/econlit/ (last accessed January 2019).

Clarivate (2022). Web of Science [database]. Clarivate, London https://www.webofknowledge.com/ (last accessed January 2018).

Hengel, E. (2022). "Publishing while female: Are women held to higher standards? Evidence from peer review." Mimeo.

Kleven, H. (2018). "Language trends in public economics". https://www.henrikkleven.com/uploads/3/7/3/1/37310663/languagetrends_slides_kleven.pdf (last accessed 2 December 2018).

Kleven, H. and D. Scott (2018). Language trends in public economics [database].

Appendix

Table 3: Tables and figures in Hengel (2022) mapped to output files

| Table/Figure | Output file |
|--------------|-------------------------------------------------|
| Figure 1 | 0-images/generated/Figure-1.pdf |
| Figure 2 | 0-images/generated/Figure-2-jel.pdf |
| 1184102 | 0-images/generated/Figure-2-time.pdf |
| Table 2 | 0-tex/generated/Table-2.tex |
| Table 3 | 0-tex/generated/Table-3-FemRatio.tex |
| Table 4 | 0-tex/generated/Table-4.tex |
| Table 5 | O-tex/generated/Table-5-FemRatio.tex |
| Figure 3 | 0-tex/generated/Figure-3.png |
| Table 6 | 0-tex/generated/Table-6-FemRatio.tex |
| Table 7 | 0-tex/generated/Table-7-FemRatio.tex |
| Figure 4 | 0-images/generated/Figure-4.pdf |
| Table 8 | 0-tex/generated/Table-8-FemRatio.tex |
| Table 9 | 0-tex/generated/Table-9-base.tex |
| Figure 5 | 0-images/generated/Figure-5-base.pdf |
| Figure 6 | 0-images/generated/Figure-6.pdf |
| Table 10 | 0-tex/generated/Table-10.tex |
| Table B.1 | 0-tex/generated/Table-B.1.tex |
| Table C.1 | 0-tex/generated/Table-C.1.tex |
| Figure D.1 | 0-images/generated/Figure-D.1-meta.pdf |
| | 0-images/generated/Figure-D.1-early.pdf |
| | 0-images/generated/Figure-D.1-late.pdf |
| Figure D.2 | 0-images/generated/Figure-D.2-fleschkincaid.pdf |
| 118010 212 | 0-images/generated/Figure-D.2-gunningfog.pdf |
| Table F.1 | 0-tex/generated/Table-F.1.tex |
| Figure F.1 | 0-images/generated/Figure-F.1.pdf |
| Table F.2 | O-tex/generated/Table-F.2-FemRatio.tex |
| Table G.1 | O-tex/generated/Table-G.1.tex |
| Table G.2 | 0-tex/generated/Table-G.2.tex |
| Table G.3 | O-tex/generated/Table-5-jel.tex |
| Figure G.1 | 0-images/generated/Figure-G.1-flesch.pdf |
| G | 0-images/generated/Figure-G.1-combo.pdf |
| Table G.4 | O-tex/generated/Table-G.4.tex |
| Figure G.2 | O-images/generated/Figure-G.2.png |
| Table G.5 | O-tex/generated/Table-5-wordlimit.tex |
| Table H.1 | O-tex/generated/Table-6-subyear.tex |
| Table H.2 | O-tex/generated/Table-6-pubyear.tex |
| Table H.3 | O-tex/generated/Table-H.3.tex |
| Table H.4 | O-tex/generated/Table-H.4.tex |
| Table I.2 | O-tex/generated/Table-I.2.tex |
| Table I.3 | O-tex/generated/Table-I.3.tex |
| Table J.1 | O-tex/generated/Table-J.1.tex |
| Table J.2 | O-tex/generated/Table-J.2.tex |
| Table J.3 | O-tex/generated/Table-J.3.tex |
| Table J.4 | O-tex/generated/Table-9-jel.tex |
| Figure J.1 | O-images/generated/Figure-5-jel.pdf |
| Table J.5 | O-tex/generated/Table-9-R.tex |
| Figure J.2 | O-images/generated/Figure-5-R.pdf |
| Figure K.1 | O-images/generated/Figure-K.1.pdf |
| Table L.1 | O-tex/generated/Table-3-R.tex |
| Table L.2 | O-tex/generated/Table-5-R.tex |
| Table L.3 | O-tex/generated/Table-8-R.tex |
| Table L.4 | O-tex/generated/Table-F.2-R.tex |
| | |

| Table/Figure | Output file |
|--------------|-----------------------------------------|
| Table M.2 | O-tex/generated/Table-3-FemSolo.tex |
| Table M.3 | O-tex/generated/Table-5-FemSolo.tex |
| Table M.4 | O-tex/generated/Table-6-FemSolo.tex |
| Table M.5 | O-tex/generated/Table-7-FemSolo.tex |
| Table M.6 | O-tex/generated/Table-8-FemSolo.tex |
| Table M.7 | O-tex/generated/Table-F.2-FemSolo.tex |
| Table M.8 | O-tex/generated/Table-3-FemSenior.tex |
| Table M.9 | O-tex/generated/Table-5-FemSenior.tex |
| Table M.10 | O-tex/generated/Table-6-FemSenior.tex |
| Table M.11 | O-tex/generated/Table-7-FemSenior.tex |
| Table M.12 | O-tex/generated/Table-8-FemSenior.tex |
| Table M.13 | O-tex/generated/Table-F.2-FemSenior.tex |
| Table M.14 | O-tex/generated/Table-3-Fem50.tex |
| Table M.15 | O-tex/generated/Table-5-Fem50.tex |
| Table M.16 | O-tex/generated/Table-6-Fem50.tex |
| Table M.17 | O-tex/generated/Table-7-Fem50.tex |
| Table M.18 | O-tex/generated/Table-8-Fem50.tex |
| Table M.19 | O-tex/generated/Table-F.2-Fem50.tex |
| Table M.20 | O-tex/generated/Table-3-Fem1.tex |
| Table M.21 | O-tex/generated/Table-5-Fem1.tex |
| Table M.22 | O-tex/generated/Table-6-Fem1.tex |
| Table M.23 | O-tex/generated/Table-7-Fem1.tex |
| Table M.24 | O-tex/generated/Table-8-Fem1.tex |
| Table M.25 | O-tex/generated/Table-F.2-Fem1.tex |
| Table M.26 | O-tex/generated/Table-3-Fem100.tex |
| Table M.27 | O-tex/generated/Table-5-Fem100.tex |
| Table M.28 | O-tex/generated/Table-6-Fem100.tex |
| Table M.29 | O-tex/generated/Table-7-Fem100.tex |
| Table M.30 | O-tex/generated/Table-8-Fem100.tex |
| Table M.31 | O-tex/generated/Table-F.2-Fem100.tex |
| Table M.32 | O-tex/generated/Table-3-FemJunior.tex |
| Table M.33 | O-tex/generated/Table-5-FemJunior.tex |
| Table M.34 | O-tex/generated/Table-6-FemJunior.tex |
| Table M.35 | O-tex/generated/Table-7-FemJunior.tex |