

Yield (multithreading)

In computer science, **yield** is an action that occurs in a computer program during multithreading of forcing a processor to relinquish control of the current running thread and sending it to the end of the running queue of the same scheduling priority.

Contents

- Examples**
- In coroutines**
- See also**
- References**

Examples

Different programming languages implement yielding in various ways.

- `pthread_yield()` in the language C, a low level implementation, provided by POSIX Threads^[1]
- `std::this_thread::yield()` in the language C++, introduced in C++11.
- The *Yield method* is provided in various object-oriented programming languages with multithreading support, such as C# and Java.^[2] OOP languages generally provide class abstractions for thread objects.

In coroutines

Coroutines are a fine-grained concurrency primitive, which may be required to yield explicitly. They may enable specifying another function to take control. Coroutines that explicitly yield allow cooperative multitasking

See also

- Coroutines
- Java (software platform)
- Common Language Runtime
- Java virtual machine
- Actor model

References

- "pthread_yield" (https://www.ibm.com/support/knowledgecenter/#!/SSLTBW_2.1.0/com.ibm.zos.v2r1.bpxbd00/ptyield.htm).
- "Thread.yield" (http://www.javamex.com/tutorials/threads/yeild.shtml). Javamex. Retrieved 24 June 2011.

Retrieved from "https://en.wikipedia.org/w/index.php?title=Yield_(multithreading)&oldid=772165168

This page was last edited on 25 March 2017, at 18:12.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

