CS2100 - L08 - MIPS: Memory & Branches

Week 4+5

- Memory

- MIPS Instructions Part II
  - Memory Instructions
  - Control Flow Instructions

- Handling Arrays

Memory

- The main memory can be viewed as a large, single-dimension array of memory locations.
- Each location of the memory has an **address**, which is an index into the array.
  - Given *k*-bit address, the address space is of size 2^k.



- Using distinct memory address, we can access:
  - a single **byte** (**byte addressable**) or
  - a single **word** (**word addressable**)

  → 4 bytes

  ← either one per hardware (implementation)
- **Word** is:
  - Usually 2^n bytes for 32-bit system : $2^2 = 4$ bytes
  - The common unit of transfer between processor and memory
  - Also commonly coincide with the register size, the integer size and instruction size in most architectures

- **Word alignment**:
  - Words are aligned in memory if they begin at a byte address that is a multiple of the number of bytes in a word.

Example: If a word consists of 4 bytes, then:



much slower, takes more transfer units

MIPS - Memory Instructions

- MIPS is a load-store register architecture
  - 32 registers, each 32-bit (4-byte) long
  - Each word contains 32 bits (4 bytes)
  - Memory addresses are 32-bit long

data must be in registers to perform arithmatic

MIPS uses byte addresses, so consecutive words differ by 4 bytes

each byte has a memory address

- Load word :

Memory Instruction: Load Word

pov of processor (from memory)

- Example: `lw $t0, 24($s0)`
  - load word
  - register
  - offset
  - memory address
  - base register



- Steps:
  1. Memory Address = **$s0** + 24 = 8000+24 = **8024**
  2. Memory word at **Mem[8024]** is loaded into **$t0**

- Store word :

Memory Instruction: Store Word

- Example: `sw $t0, 12($s0)` (pov of processor)
  - in memory



- Steps:
  1. Memory Address = **$s0** + 12 = **8012**
  2. Content of **$t0** is stored into word at **Mem[8012]**

- Load word , store word :

- Other than load word (**lw**) and store word (**sw**), there are:
  - load byte (**lb**)
  - store byte (**sb**)
- Similar in format:

```
lb   $t1, 12($s3)
sb   $t2, 13($s3)
```

byte stored in last 8 bits of 32-bit register

for char[] (1 byte)

- Similar in working except that one byte, instead of one word, is loaded or stored:

Address vs. Value

Key concept:

Registers do NOT have types

- A register can hold any 32-bit number:
  - The number has no implicit data type and is interpreted according to the instruction that uses it
- Example:
  - `add $t2, $t1, $t0`
  - ➔ `$t0` and `$t1` should contain data values
  - `lw $t2,0($t0)`
  - ➔ `$t0` should contain a memory address.

Byte vs. Word

Important:

Consecutive word addresses in machines with byte-addressing do not differ by 1

- Common error:
  - Assume that the address of the next word can be found by incrementing the address in a register by 1 instead of by the word size in bytes
- For both `lw` and `sw`: word alignment important
  - The sum of base address and offset must be multiple of 4 (i.e. word boundary)

MIPS - Other Memory Instructions

- MIPS disallows loading/storing **unaligned word** using `lw`/`sw`:
  - Pseudo-Instructions ***unaligned load word*** (`ulw`) and ***unaligned store word*** (`usw`) are provided for this purpose
  - Explore: How do we translate `ulw/usw`?
- Other memory instructions:
  - `lh` and `sh`: load halfword and store halfword
  - `lwl`, `lwr`, `swl`, `swr`: load word left / right, store word left / right.
  - etc…

MIPS - Control Flow Instructions

Translating C to Assembly: negate the condition for shorter code

- Two type of decision-making statements
  - **Conditional** (branch)

```
bne $t0, $t1, label
beq $t0, $t1, label
```

  - **Unconditional** (jump)

```
j label
```

Conditional Branch

- Processor follows the branch **only when the condition is satisfied (true)**

anchor

```
beq $r1, $r2, L1
```

- If [$r1] equals [$r2], go to statement labeled L1
- beq is "**branch if equal**"
- C code: `if (a == b) goto L1`

```
bne $r1, $r2, L1
```

- If [$r1] **not** equals to [$r2], go to statement labeled L1
- bne is "**branch if not equal**"
- C code: `if (a != b) goto L1`

Unconditional Jump

- Processor **always** follows the branch

```
j L1
```

- Jump to label L1 unconditionally
- C code: `goto L1`

Technically equivalent to:

- `beq $s0, $s0, L1`