# HARDWARE (COMPILERS, OS, RUNTIME) AND C, C++, TO CUDA

## ERNEST YEUNG ERNESTYALUMNI@GMAIL.COM

## Contents

1. Introduction; why I'm writing this	3
2. 80x86 Assembly; 80x86 Architecture	3
2.1. Basic 80x86 Architecture	3
2.2. Registers (for 80x86)	4
3. Compilers; Compiler Operation and Code Generation	4
4. gdp; good debugging processes (in C/C++/CUDA)	4
5. Pointers in C; Pointers in C categorified (interpreted in Category Theory) and its relation to actual, physical, computer memory and (memory) addresses ((address) bus; pointers, structs, arrays in C	4
5.1. Structs in C	5
Part 1. C, Stack, Heap Memory Management in C	6
6. C, Stack and Heap Memory Management, Heap and Stack Memory Allocation	6
7. Data segments; Towards Segmentation Fault	6
7.1. Stack	7
7.2. Stack overflow	7
7.3. Heap	7
7.4. More Segmentation Faults	8
Part 2. C++	8
8. static	8
9. Free Store	8
10. Copy vs. Move	8
10.1. Copy constructor	8
10.2. Move Constructor	9
11. vtable; virtual table	9
11.1. How are virtual functions and vtable implemented?	10
11.2. pImpl, shallow copy, deep copy	10
Part 3. Integers, numeric encodings, number representation, binary representation, hexidecimal representation	11
12. Introduction: $\mathtt{int} \neq \mathbb{Z}$ , $\mathtt{float} \neq \mathbb{R}$	11
13. Bits and Bytes	11
13.1. Machine Words	11
13.2. Word-oriented Memory Organization	11
13.3. Byte-ordering: Big-Endian, Little-Endian	11
13.4. Representing Strings	12
13.5. Machine-Level Code Representation	12
13.6. Boolean Algebra	12

Date: 1 Nov 2017.

Key words and phrases. C, C++, CUDA, CUDA C/C++, Compilers, OS, runtime, classes, Object Oriented Programming, Segmentation Fault, memory, memory addresses.

1

PRINCE VEING PRINCEPALLINGUE COLLINGOLOGICAL
ERNEST YEUNG ERNESTYALUMNI@GMAIL.COM

13.7. Representing and Manipulating Sets; bit vectors as sets	12
14. Unsigned integers	12
15. Two's complement	13
15.1. Numeric Ranges	13
15.2. Negating with complement	13
15.3. Power of 2 Multiply with shift (left shift bitwise operation)	13
15.4. Unsigned power-of-2 Divide, with shift (right shift bitwise operator)	13
16. Endianness	14
16.1. Big-endian	14
16.2. Little-endian	14
Part 4. Floating Point Numbers	14
17. Floating point, IEEE Floating	14
17.1. Fractional Binary Numbers	14
17.1. Tractional Binary (valued)	17
Part 5. Complexity, Data Structures, Algorithms	16
18. Complexity, Big-O	$\begin{array}{c} 16 \\ 16 \end{array}$
18.1. Multi-Part Algorithms: Add vs. Multiply, e.g. $O(A + B)$ vs. $O(A * B)$	16
18.2. Amoritized Time (e.g. dynamically resizing array "ArrayList" or maybe std::vector)	16
18.3. $\log N$ runtimes $(O(\log N))$	16
18.4. Recursive run times $O(2^N)$	16
19. Data Structures	17
19.1. Lists (arrays), Python Lists	17
19.2. Linked Lists, $O(1)$ insertion	17
19.2. Elliked Elsis, $O(1)$ insertion 19.3. Stack, $O(1)$ pop, $O(1)$ push	18
19.4. Queue, $O(1)$ insert, $O(1)$ delete, $O(N)$ search, $O(N)$ space complexities	18
19.5. STL Containers	18
19.6. vector	19
19.7. Trees	19
19.8. Graphs	19
20. Search	$\frac{13}{20}$
20.1. Binary Search $O(\log(N))$	$\frac{20}{20}$
20.2. Breadth-first search (BFS)	$\frac{20}{20}$
20.3. Depth-first search	$\frac{20}{20}$
20.4. Binary Search Tree (BST), $O(\log N)$ height of the tree, run-time complexity, worst case $O(N)$	$\frac{20}{20}$
20.4. Binary Scarch Tree (BST), $O(\log N)$ height of the tree, run-time complexity, worst case $O(N)$	$\frac{20}{20}$
20.6. Self-balancing tree	$\frac{20}{21}$
20.7. Red-Black Tree; search $O(\log N)$ , space $O(N)$ , insert $O(\log N)$ , delete $O(\log N)$	21
21. Recursion	21
22. Sorting	21
22.1. Bubble Sort, $O(N^2)$ in time, $O(1)$ in space	$\frac{21}{21}$
22.2. Merge Sort, $O(N \log N)$ in time, $O(N)$ in space	21
22.3. Quick Sort, $O(N \log N)$ average time complexity, $O(N^2)$ worst time complexity, $O(1)$ in space (if inplace)	21
22.4. Time Complexities of all Sorting Algorithms	$\frac{21}{22}$
22.4. This Complexities of an Softing Algorithms 22.5. Hashing, $O(1)$ lookup, or $O(n)$ bucket lookup	$\frac{22}{22}$
22.6. Hashing, O(1) wordp, of O(n) bucket wordp	22
Part 6. Linux System Programming	กา
23. File Descriptors	$\begin{array}{c} 22 \\ 22 \end{array}$
23.1. Creation and Release of Descriptors	$\frac{22}{22}$
20.1. Oromion and recease of Descriptors	$\mathcal{L}\mathcal{L}$

HARDWARE (COMPILERS, OS, RU	JNTIME) AND C, C++, TO CUDA
24. Unix execution model 24.1. Processes and Programs 24.2. File entry 24.3. Readiness of fds 24.4. Level Triggered 24.5. Edge Triggered 25. Multiplexing I/O on fds 25.1. Multiplexing I/O with Non-blocking I/O 25.2. Multiplexing I/O via signal driven I/O 25.3. Multiplexing I/O via polling I/O 26. epoll Event poll 26.1. epoll Syntax	22 23 23 23 23 24 24 24 24 24 24
art 7. C++ Template Metaprogramming	24
art 8. Functional Programming and Category Theory	24
art 9. Technical Interviews References	$\begin{array}{c} 24 \\ 25 \end{array}$
ABSTRACT. I review what, how, and why Segmentation Fault is and occurs in the specific context of C and hopefully to CUDA, virtual memory addresses in C++, and to CUDA.  1. INTRODUCTION; WHY I'M WRITING THIS  I didn't realize the importance of having a profound understanding of C/C++ and its relation to hardware, in particular	<ul> <li>2.1. Basic 80x86 Architecture. Intel CPU generally classified as a Von Neumann machine, containing 3 main building blocks: <ol> <li>(1) CPU</li> <li>(2) memory</li> <li>(3) input/output (I/O) devices</li> </ol> </li> <li>These 3 components are connected together using the system bus. System bus consists of <ol> <li>address bus</li> </ol> </li> </ul>
emory (addresses), until I learned more specifically about the work done at NVIDIA from its news and job postings. Coming om a theoretical and mathematical physics background, I wanted to get myself up to speed as fast as possible, provide good extbook and online references, and directly relate these topics, which seem to be classic topics in computer science (at hardware vel) and electrical engineering, to CUDA, to specifically GPU parallel programming with direct CUDA examples.  Note that there is a version of this LaTeX/pdf file in the usual "letter" format that is exactly the same as the content here, redwCCppCUDA.pdf.  Meyer (1997) [1]	<ul> <li>data bus</li> <li>control bus</li> <li>CPU communicates with memory and I/O devices by placing a numeric value on the address bus to select 1 of the memory locations or I/O device port locations, each of which has a unique binary numeric address.</li> <li>Then the CPU, I/O, and memory devices pass data among themselves by placing data on the data bus.</li> <li>Control bus contains signals that determine the direction of data transfer (to or from memory, and to or from an I/O device).</li> </ul>
"When programmers first began giving up assembly language in favor of using HLLs, they generally understood the low-level ramifications of the HLL statements they were using and could choose their HLL statements appropriately. Unfortunately, the generation of computer programmers that followed them did not have the benefit of mastering assembly language. As such, they were not in a position to wisely choose statements and data structures that HLLs could efficiently translate into machine code."	So $ \frac{\mathbf{Memory}}{\mathbf{Obj}(\mathbf{Memory}) = \text{ memory locations}} $ $ \frac{\mathbf{I/O}}{\mathbf{Obj}(\mathbf{I/O}) = \text{ I/O device port locations}} $
p. 2, Ch. 1 of Hyde (2006) [3], where HLL stands for high-level language. I was part of that generation and knew of nothing assembly.	and address bus
2. 80x86 Assembly; 80x86 Architecture	$\label{eq:obj} \text{Obj}(\textbf{address bus}) = \text{ unique binary numeric addresses}$ Likewise, $\textbf{data bus}$

And so

Main difference between complex instruction set computer (CISC) architectures such as 80x86 and reduced instruction set computer (RISC) architectures like PowerPC is the way they use memory. RISC provde relatively clumsy memory access, and

applications avoid accessing memory. 80x86 access memory in many different ways and applications take advantage of these

facilities.

 $Obj(\mathbf{data}\ \mathbf{bus}) = \mathrm{data}$ 

 $\mathrm{CPU}: \mathbf{Memory} \times \mathbf{address} \ \mathbf{bus} \to \mathrm{Hom}(\mathbf{Memory}, \mathbf{address} \ \mathbf{bus})$ 

CPU : (memory location, unique binary numeric address)  $\mapsto \&$ 

in the language of category theory.

2.2. Registers (for 80x86). cf. 3.3 Basic 80x86 Architecture, from pp. 23 of Hyde (2006) [3].

Example: to add 2 variables, x, y and store x + y into z, you must load 1 of the variables into a register, add the 2nd. operand to the register, and then store register's value into destination variable. "Registers are middlemen in almost every calculation." Hvde (2006) [3].

There are 4 categories of 80x86 CPU registers:

- general-purpose
- special-purpose application-accessible
- segment
- special-purpose kernel-mode

Segment registers not used very much in modern 32-bit operating systems (e.g. Windows, Linux; what about 64-bit?) and special-purpose kernel-mode registers are intended for writing operating systems, debuggers, and other system-level tools.

2.2.1. 80x86 General-Purpose Registers. 80x86 CPUs provide several general-purpose registers, including 8 32-bit registers having the following names: (8 bits in 1 byte, 32-bit is 4 bytes)

where E is extended; 32-bit registers distinguished from 8 16-bit registers with following names

and finally

Hyde says that it's important to note about the general-purpose registers is they're not independent. 80x86 doesn't provide 24 separate registers, but overlaps the 32-bit registers with 16-bit registers, and overlaps 16-bit registers with 8-bit registers. e.g.

$$\&AL \neq \&AH$$
, but  $\&AL, \&AH \in \&AX$  and  $\&AX \in \&EAX$ , so that  $\&AL, \&AH, \&AX \in \&EAX$ 

- 3. Compilers: Compiler Operation and Code Generation
- cf. Ch. 5 Compiler Operation and Code Generation, from pp. 62 and pp. 72- of Hyde (2006) [3]
  - 4. GDP; GOOD DEBUGGING PROCESSES (IN C/C++/CUDA)

Learn C the hard way Lecture 4, Using Debugger (GDB)

5. Pointers in C; Pointers in C categorified (interpreted in Category Theory) and its relation to actual, physical, computer memory and (memory) addresses ((address) bus; pointers, structs, arrays in C

From Shaw (2015) [4], Exercise 15,

e.g. ages[i], You're indexing into array ages, and you're using the number that's held in i to do it:

$$a: \mathbb{Z} \to \operatorname{Type} \in \mathbf{Type}$$
 e.g.  $a: \mathbb{Z} \to \mathbb{R}$  or  $\mathbb{Z}$   $a: i \mapsto a[i]$   $a: i \mapsto a[i]$ 

Index  $i \in \mathbb{Z}$  is a location *inside* ages or a, which can also be called address. Thus, a[i].

Indeed, from cppreference for Member access operators,

Built-in subscript operator provides access to an object pointed-to by pointer or array operand. And so E1[E2] is exactly identical to \*(E1+E2).

To C, e.g. ages, or a, is a location in computer's memory where, e.g., all these integers (of ages) start, i.e. where a starts.

**Memory**,  $Obj(Memory) \ni memory location. Also, to specify CPU,$ **Memory**<sub><math>CPU</sub>,  $Obj(Memory_{CPU}) \ni computer memory location$ 

It's also an address, and C compiler will replace e.g. ages or array a, anywhere you type it, with address of very 1st integer (or 1st element) in, e.g. ages, or array a.

$$\begin{array}{c} \mathbf{Arrays} \overset{\cong}{\longleftrightarrow} \mathbf{address} \\ \mathrm{Obj}(\mathbf{Arrays}) \overset{\cong}{\longleftrightarrow} \mathrm{Obj}(\mathbf{address}) \\ a \overset{\cong}{\longleftrightarrow} \mathtt{0x17} \end{array}$$

"But here's the trick": e.g. "ages is an address inside the entire computer." (Shaw (2015) [4]).

It's not like i that's just an address inside ages. ages array name is actually an address in the computer.

"This leads to a certain realization: C thinks your whole computer is 1 massive array of bytes."

"What C does is layer on top of this massive array of bytes the concept of types and sizes of those types." (Shaw (2015) [4]). Let

$$\mathbf{Type}$$

$$\mathrm{Obj}(\mathbf{Type})\ni \mathrm{int}, \mathrm{char}, \mathrm{float}$$

$$\mathbf{Memory}_{CPU} := 1 \text{ massive array of bytes}$$

$$\mathrm{Obj}(\mathbf{Memory}_{CPU})$$

$$Cbj(\mathbf{Memory}_{CPU})$$

$$Cbj(\mathbf{Type}) \xrightarrow{\mathtt{sizeof}} \mathbb{Z}^+$$

$$T \xrightarrow{\mathtt{sizeof}} \mathtt{sizeof}(T)$$

$$\mathsf{float} \xrightarrow{\mathtt{sizeof}} \mathtt{sizeof}(\mathrm{float})$$

How C is doing the following with your arrays:

• Create a block of memory inside your computer:

$$Obj(\mathbf{Memory}_{CPU}) \supset Memory block$$

Let  $\mathrm{Obj}(\mathbf{Memory}_{CPU})$  be an ordered set. Clearly, then memory can be indexed. Let  $b \in \mathbb{Z}^+$  be this index. Then  $\mathrm{Memory}_{block}(0) = \mathrm{Obj}(\mathbf{Memory}_{CPU})(b)$ .

• Pointing the name ages, or a, to beginning of that (memory) block. Entertain, possibly, a category of pointers, Pointers = ptrs.

$$\begin{array}{c} \mathbf{ptrs} \\ \mathrm{Obj}(\mathbf{ptrs}) \ni a, \text{ e.g. ages} \end{array}$$

 $a\mapsto \operatorname{Memory\ block}(0)$  $\operatorname{Obj}(\mathbf{ptrs})\to\operatorname{Obj}(\mathbf{Memory}_{CPU})$ 

• indexing into the block, by taking the base address of ages, or a

$$a \overset{\cong}{\mapsto} \text{ base address } 0x17$$

$$Obj((T)\mathbf{array}) \overset{\cong}{\to} Obj(\mathbf{addresses})$$

$$a[i] \equiv a + i \overset{\cong}{\mapsto} \text{ base address } + i * \mathbf{sizeof}(T) \overset{*}{\mapsto} a[i] \in T \text{ where } T, \text{ e.g. } T = \mathbb{Z}, \mathbb{R}$$

$$Obj((T)\mathbf{array} \overset{\cong}{\to} Obj(\mathbf{addresses}) \to T$$

<sup>&</sup>quot;A pointer is simply an address pointing somewhere inside computer's memory with a type specifier." Shaw (2015) [4] C knows where pointers are pointing, data type they point at, size of those types, and how to get the data for you.

- 5.0.1. Practical Pointer Usage.
  - Ask OS for memory block (chunk of memory) and use pointer to work with it. This includes strings and structs.
  - Pass by reference pass large memory blocks (like large structs) to functions with a pointer, so you don't have to pass the entire thing to the function.
  - Take the address of a function, for dynamic callback. (function of functions)

"You should go with arrays whenever you can, and then only use pointers as performance optimization if you absolutely have to." Shaw (2015) [4]

5.0.2. Pointers are not Arrays. No matter what, pointers and arrays are not the same thing, even though C lets you work with them in many of the same ways.

From Eli Bendersky's website, Are pointers and arrays equivalent in C?

He also emphasizes that

5.0.3. Variable names in C are just labels. "A variable in C is just a convenient, alphanumeric pseudonym of a memory location." (Bendersky, [5]). What a compiler does is, create label in some memory location, and then access this label instead of always hardcoding the memory value.

"Well, actually the address is not hard-coded in an absolute way because of loading and relocation issues, but for the sake of this discussion we don't have to get into these details." (Bendersky, [5]) (EY: 20171109 so it's on the address bus?)

Compiler assigns label at compile time. Thus, the great difference between arrays and pointers in C.

5.0.4. Arrays passed to functions are converted to pointers. cf. Bendersky, [5].

Arrays passed into functions are always converted into pointers. The argument declaration char arr\_place[] in

```
void foo(char arr_arg[], char* ptr_arg)
{
          char a = arr_arg[7];
          char b = ptr_arg[7];
}
```

is just syntactic sugar to stand for char\* arr\_place.

From Kernighan and Ritchie (1988) [6], pp. 99 of Sec. 5.3, Ch. 5 Pointers and Arrays,

When an array name is passed to a function, what is passed is the location of the initial element. Within the called function, this argument is a local variable, and so an array name parameter is a pointer, that is, a variable containing an address.

Why?

The C compiler has no choice here, since,

array name is a label the C compiler replaces at compile time with the address it represents (which for arrays is the address of the 1st element of the array).

But function isn't called at compile time; it's called at run time.

At run time, (where) something should be placed on the stack to be considered as an argument.

Compiler cannot treat array references inside a function as labels and replace them with addresses, because it has no idea what actual array will be passed in at run time.

EY: 20171109 It can't anticipate the exact arguments that'll it be given at run-time; at the very least, my guess is, it's given instructions.

Bendersky [5] concludes by saying the difference between arrays and pointers does affect you. One way is how arrays can't be manipulated the way pointers can. Pointer arithmetic isn't allowed for arrays and assignment to an array of a pointer isn't allowed. cf. van der Linden (1994) [7]. Ch. 4, 9, 10.

Bendersky [5] has this one difference example, "actually a common C gotcha":

"Suppose one file contains a global array:"

```
char mv_Arr[256]
```

Programmer wants to use it in another file, mistakingly declares as

```
extern char* my_arr;
```

When he tries to access some element of the array using this pointer, he'll most likely get a segmentation fault or a fatal exception (nomenclature is OS-dependent).

To understand why, Bendersky [5] gave this hint: look at the assembly listing

```
char a = array_place [7];

0041137E mov al, byte ptr [_array_place+7 (417007h)]
00411383 mov byte ptr [a], al

char b = ptr_place [7];

00411386 mov eax, dword ptr [_ptr_place (417064h)]
0041138B mov cl, byte ptr [eax+7]
0041138E mov byte ptr [b], cl
```

or my own, generated from gdb on Fedora 25 Workstation Linux:

"How will the element be accessed via the pointer? What's going to happen if it's not actually a pointer but an array?" Bendersky [5]

EY: 20171106. Instruction-level, the pointer has to

- mov 0x200be6(%rip), %rax 1st., copy value of the pointer (which holds an address), into %rax register.
- movzbl 0x7(%rax), %eax off that address in register
- mov %al,-0x2(%rbp) mov contents -0x2(%rbp)into register %al

If it's not actually a pointer, but an array, the value is copied into the **%rax** register is an actual **char** (or **float**, some type). *Not* an address that the registers may have been expecting!

## 5.1. **Structs in C.** From Shaw (2015) [4], Exercise 16,

struct in C is a collection of other data types (variables) that are stored in 1 block of memory. You can access each variable independently by name.

- The struct you make, i.e.g struct Person is now a *compound data type*, meaning you can refer to struct Person using the same kinds of expressions you would for other (data) types.
- This lets you pass the whole struct to other functions
- You can access individual members of struct by their names using x->y if dealing with a ptr.

If you didn't have struct, you'd have to figure out the size, packing, and location of memory of the contents. In C, you'd let it handle the memory structure and structuring of these compound data types, structs. (Shaw (2015) [4])

## Part 1. C, Stack, Heap Memory Management in C

6. C. Stack and Heap Memory Management, Heap and Stack Memory Allocation

cf. Ex. 17 of Shaw (2015) [4]

Consider chunk of RAM called stack, another chunk of RAM called heap. Difference between heap and stack depends on where you get the storage.

Heap is all the remaining memory on computer. Access it with malloc to get more.

Each time you call malloc, the OS uses internal functions (EY: 20171110 address bus or overall system bus?) to register that piece of memory to you, then returns ptr to it.

When done, use free to return it to OS so OS can use it for other programs. Failing to do so will cause program to *leak* memory. (EY: 20171110, meaning this memory is unavailable to the OS?)

Stack, on a special region of memory, stores temporary variables, which each function creates as locals to that function. How stack works is that each argument to function is *pushed* onto stack and then used inside the function. Stack is really a stack data structure, LIFO (last in, first out). This also happens with all local variables in main, such as char action, int id. The advantage of using stack is when function exits, C compiler pops these variables off of stack to clean up.

Shaw's mantra: If you didn't get it from malloc, or a function that got it from malloc, then it's on the stack.

3 primary problems with stacks and heaps:

- If you get a memory block from malloc, and have that ptr on the stack, then when function exits, ptr will get popped off and lost.
- If you put too much data on the stack (like large structs and arrays), then you can cause a *stack overflow* and program will abort. Use the heap with malloc.
- If you take a ptr, to something on stack, and then pass or return it from your function, then the function receiving it will *segmentation fault*, because actual data will get popped off and disappear. You'll be pointing at dead space.

cf. Ex. 17 of Shaw (2015) [4]

#### 7. Data segments; Towards Segmentation Fault

cf. Ferres (2010) [8]

When program is loaded into memory, it's organized into 3 segments (3 areas of memory): let executable program generated by a compiler (e.g. gcc) be organized in memory over a range of addresses (EY: 20171111 assigned to physical RAM memory by address bus?), ordered, from low address to high address.

• text segment or code segment - where compiled code of program resides (from lowest address); code segment contains code executable or, i.e. code binary.

As a memory region, text segment may be placed below heap, or stack, in order to prevent heaps and stack overflows from overwriting it.

Usually, text segment is sharable so only a single copy needs to be in memory for frequently executed programs, such as text editors, C compiler, shells, etc. Also, text segment is often read-only, to prevent program from accidentally modifying its instructions. cf. Memory Layout of C Programs; GeeksforGeeks

- Data segment: data segment subdivided into 2 parts:
  - initialized data segment all global, static, constant data stored in data segment. Ferres (2010) [8]. Data segment is a portion of virtual address of a program.

Note that, data segment not read-only, since values of variables can be altered at run time.

This segment can also be further classified into initialized read-only area and initialized read-write area.

e.g. char s[] = "hello world" and int debut = 1 outside the main (i.e. global) stored in initialized read-write area.

const char \*string = "hello world" in global C statement makes string literal "hello world" stored in initialized read-only area. Character pointer variable string in initialized read-write area. cf. Memory Layout of C Programs

- uninitialized data stored in BSS. Data in this segment is initialized by kernel (OS?) to arithmetic 0 before program starts executing.

Uninitialized data starts at end of data segment ("largest" address for data segment) and contains all global and static variables initialized to 0 or don't have explicit initialization in source code.

e.g. static int i; in BSS segment.

e.g. int j; global variable in BSS segment.

cf. Memory Layout of C Programs

Heap - "grows upward" (in (larger) address value, begins at end of BSS segment), allocated with calloc, malloc, "dynamic memory allocation".

Heap area shared by all shared libraries and dynamically loaded modules in a process.

Heap grows when memory allocator invokes brk() or sbrk() system call, mapping more pages of physical memory into process's virtual address space.

Stack - store local variables, used for passing arguments to functions along with return address of the instruction which
is to be executed after function call is over.

When a new stack frame needs to be added (resulting from a *newly called function*), stack "grows downward." (Ferres (2010) [8])

Stack grows automatically when accessed, up to size set by kernel (OS?) (which can be adjusted with setrlimit(RLIMIT\_STACK,...)).

7.0.1. Mathematical description of Program Memory (data segments), with Memory, Addresses. Let Address, with  $Obj(Address) \cong \mathbb{Z}^+$  be an ordered set.

Memory block  $\subset$  Obj(Memory), s.t.

 $\text{Memory block} \xrightarrow{\cong} \{ \text{ low address }, \text{ low address} + \texttt{sizeof}(T), \dots \text{ high address } \} \equiv \text{addresses}_{\text{Memory block}} \subset \mathbb{Z}^+$ 

where  $T \in \mathrm{Obj}(\mathbf{Types})$  and  $\cong$  assigned by address bus, or the virtual memory table, and addresses<sub>Memory block</sub>  $\subset \mathrm{Obj}(\mathbf{Addresses})$ .

Now.

text segment, (initialized) data segment, (uninitialized) data segment, heap, stack, command-line arguments and environmental variables  $\subset$  addresses<sub>Memory block</sub>, that these so-called data segments are discrete subsets of the set of all addresses assigned for the memory block assigned for the program.

Now,  $\forall i \in \text{text segment}$ ,  $\forall j \in \text{(initialized)}$  data segment, i < j and  $\forall j \in \text{(initialized)}$  data segment,  $\forall k \in \text{(uninitialized)}$  data segment, j < k, and so on. Let's describe this with the following notation:

(1) text segment < (initialized) data segment < (uninitialized) data segment < < heap < stack < command-line arguments and environmental variables

Consider stack of variable length  $n_{\text{stack}} \in \mathbb{Z}^+$ . Index the stack by  $i_{\text{stack}} = 0, 1, \dots n_{\text{stack}} - 1$ . "Top of the stack" is towards "decreasing" or "low" (memory) address, so that the relation between "top of stack" to beginning of the stack and high address to low address is reversed:


$$i_{\text{stack}} \mapsto \text{high address} - i_{\text{stack}}$$

Call stack is composed of stack frames (i.e. "activation records"), with each stack frame corresponding to a subroutine call that's not yet termined with a routine (at any time).

The frame pointer FP points to location where stack pointer was.

Stack pointer usually is a register that contains the "top of the stack", i.e. stack's "low address" currently, cf. Understanding the stack, i.e.

(2) 
$$\operatorname{eval}(RSP) = \operatorname{high} \operatorname{address} - i_{\operatorname{stack}}$$



7.0.2. Mathematical description of strategy for stack buffer overflow exploitation. Let  $n_{\text{stack}} = n_{\text{stack}}(t)$ . Index the stack with  $i_{\text{stack}}$  (from "bottom" of the stack to the "top" of the stack):

$$0 < i_{\text{stack}} < n_{\text{stack}} - 1$$

Recall that  $i_{\text{stack}} \in \mathbb{Z}^+$  and

$$i_{\text{stack}} \mapsto \text{high address } -i_{\text{stack}} \equiv x = x(i_{\text{stack}}) \in \text{Addresses}_{\text{Memory block}} \subset \text{Obj}(\mathbf{Address})$$

Let an array of length L (e.g. char array) buf, with  $\&buf = \&buf(0) \in Obj(Address)$ , be s.t.  $\&buf = x(n_{stack} - 1)$  (starts at "top of the stack and "lowest" address of stack at time t, s.t.

$$\&\mathtt{buf}(j) = \&\mathtt{buf}(0) + j\mathtt{sizeof}(T)$$

with  $T \in \mathbf{Types}$ ).

Suppose return address of a function (such as main), eval(RIP) be

$$eval(RIP) = \&buf + Lor at least eval(RIP) \ge \&buf + L$$

If we write to buf more values than L, we can write over eval(RIP), making eval(RIP) a different value than before.

### 7.1. Stack. cf. https://www.geeksforgeeks.org/memory-layout-of-c-program/

Traditionally, stack area adjoined heap area and they grow in opposite direction.

When stack ptr meets heap ptr, free memory exhausted.

(with modern large address spaces, virtual memory techniques, they may be placed almost anywhere, but they still typically grow opposite direction)

stack area contains program stack, UFO structure, typically located in higher parts of memory.

On standard x86, grows toward address 0.

"stack ptr" register tracks top of stack, adjusted to point to top each time a value is "pushed" onto stack.

set of values pushed for 1 function call is "stack frame", stack frame consists at minimum of return address.

Newly called function allocates room on stack for its automatic and temporary variables.

⇒ recursion: each time recursive function calls itself, new stack frame is used, so 1 set of variables (in recursion) doesn't interfere with variables from another instance of the function.

cf. Where are static variables in C/C++? Tutorials point

static variables remain in memory; lifetime is entire program, stored in data segment of memory (near heap); data segment is part of virtual address space of a program.

asked here https://www.codingame.com/work/cpp-interview-questions/, what is a static variable

cf. Ferres (2010) [8]

Stack and functions: When a function executes, it may add some of its state data to top of the stack (EY: 20171111, stack grows downward, so "top" is smallest address?); when function exits, stack is responsible for removing that data from stack.

In most modern computer systems, each thread has a reserved region of memory, stack. Thread's stack is used to store location of function calls in order to allow return statements to return to the correct location.

- OS allocates stack for each system-level thread when thread is created.
- Stack is attached to thread, so when thread exits, that stack is reclaimed, vs. heap typically allocated by application at runtime, and is reclaimed when application exits.
- When thread is created, stack size is set.
- Each byte in stack tends to be reused frequently, meaning it tends to be mapped to the processor's cache, making if very fast.
- Stored in computer RAM, just like the heap.
- Implemented with an actual stack data structure.
- stores local data, return addresses, used for parameter passing
- Stack overflow, when too much stack is used (mostly from infinite (or too much) recursion, and very large allocation)
- Data created on stack can be used without pointers.

Also note, for **physical location in memory**, because of Virtual Memory, makes your program think that you have access to certain addresses where physical data is somewhere else (even on hard disc!). Addresses you get for stack are in increasing order as your call tree gets deeper.

memory management - What and where are the stack and heap? Stack Overflow, Tom Leys' answer

 $cf.\ \texttt{https://stackoverflow.com/questions/79923/what-and-where-are-the-stack-and-heap/80113\#80113\%$ 

Stack is memory set aside for a thread of execution. Each thread gets a stack, while there's typically only 1 heap for the application (although it isn't uncommon to have multiple heaps for different types of allocation).

To what extent are they controlled by the OS or language runtime?

The OS allocates the stack for each system-level thread when the thread is created. Typically the OS is called by the language runtime to allocate the heap for the application.

What is their scope?

The stack is attached to a thread, so when the thread exits the stack is reclaimed. The heap is typically allocated at application startup by the runtime, and is reclaimed when the application (technically process) exits.

What determines the size of each of them?

The size of the stack is set when a thread is created. The size of the heap is set on application startup, but can grow as space is needed (the allocator requests more memory from the operating system).

7.2. **Stack overflow.** If you use heap memory, and you overstep the bounds of your allocated block, you have a decent chance of triggering a segmentation fault (not 100

On stack, since variables created on stack are always contiguous with each other; writing out of bounds can change the value of another variable. e.g. buffer overflow.

7.3. **Heap.** Heap contains a linked list of used and free blocks. New allocations on the heap (by new or malloc) are satisfied by creating suitable blocks from free blocks.

This requires updating list of blocks on the heap. This meta information about the blocks on the heap is stored on the heap often in a small area in front of every block.

- Heap size set on application startup, but can grow as space is needed (allocator requests more memory from OS)
- heap, stored in computer RAM, like stack.

7.3.1. *Memory leaks*. Memory leaks occurs when computer program consumes memory, but memory isn't released back to operating system.

"Typically, a memory leak occurs because dynamically allocated memory becomes unreachable." (Ferres (2010) [8]). Programs ./Cmemory/heapstack/Memleak.c deliberately leaks memory by losing the pointer to allocated memory.

Note, generally, the OS delays real memory allocation until something is written into it, so program ends when virtual with the condition that addresses run out of bounds (per process limits).

7.4. More Segmentation Faults. The operating system (OS) is running the program (its instructions). Only from the hardware, with memory protection, with the OS be signaled to a memory access violation, such as writing to read-only memory or writing outside of allotted-to-the-program memory, i.e. data segments. On x86\_64 computers, this general protection fault is initiated by protection mechanisms from the hardware (processor). From there, OS can signal the fault to the (running) process, and stop it (abnormal termination) and sometimes core dump.

For virtual memory, the memory addresses are mapped by program called *virtual addresses* into *physical addresses* and the OS manages virtual addresses space, hardcare in the CPU called memory management unit (*MMU*) translates virtual addresses to physical addresses, and kernel manages memory hierarchy (eliminating possible overlays). In this case, it's the *hardware* that detects an attempt to refer to a non-existent segment, or location outside the bounds of a segment, or to refer to location not allowed by permissions for that segment (e.g. write on read-only memory).

7.4.1. Dereferencing a ptr to a NULL ptr (in C) at OS, hardware level. The problem, whether it's for dereferencing a pointer that is a null pointer, or uninitialized pointer, appears to (see the ./Cmemory/ subfolder) be at this instruction at the register level:

```
x000000000040056c <+38>: movzbl (%rax),%eax

// or

0x00000000004004be <+24>: movss %mm0,(%rax)
```

involving the register RAX, a temporary register and to return a value, upon assignment. And in either case, register RAX has trying to access virtual (memory) address 0x0 (to find this out in gdb, do i r or info register).

Modern OS's run user-level code in a mode, such as *protected mode*, that uses "paging" (using secondary memory source than main memory) to convert virtual addresses into physical addresses.

For each process (thread?), the OS keeps a *page table* dictating how addresses are mapped. Page table is stored in memory (and protected, so user-level code can't modify it). For every memory access, given (memory) address, CPU translates address according to the page table.

When address translation fails, as in the case that *not all addresses are valid*, and so if a memory access generates an invalid address, the processor (hardware!) raises a *page fault exception*. "This triggers a transition from *user mode* (aka current privilege level (CPL) 3 on x86/x86-64) into kernel mode (aka CPL 0) to a specific location in the kernel's code, as defined by the *interrupt descriptor table* (IDT)." cf. [What happens in OS when we dereference a NULL pointer in C?](https://stackoverflow.com/questions/12645647/what-happens-in-os-when-we-dereference-a-null-pointer-in-c)

Kernel regains control and send signal (EY: 20171115 to the OS, I believe).

In modern OS's, page tables are usually set up to make the address 0 an invalid virtual address.

cf. [What happens in OS when we dereference a NULL pointer in C?](https://stackoverflow.com/questions/12645647/what-happens-in-os-when-we-dereference-a-null-pointer-in-c)

Part 2. C++

8. STATIC

9. Free Store

cf. GotW #9, Memory Management - Part I

Free store is 1 of the 2 dynamic memory areas, allocated/freed by new/delete (free store and heap). Object lifetime can be less than the time the storage is allocated.

```
Let t_{0,\text{obj}}, t_{f,\text{obj}}, t_{f,\text{obj}} \geq t_{0,\text{obj}},

t_{0,\text{alloc}}, t_{f,\text{alloc}}, t_{f,\text{alloc}} \geq t_{0,\text{alloc}},

with the condition that
```

$$t_{0,\mathrm{alloc}} \le t_{0,\mathrm{obj}} \le t_{f,\mathrm{obj}} \le t_{f,\mathrm{alloc}}$$

For  $t \in (t_{0,\text{alloc}}, t_{0,\text{obj}})$ , storage may be accessed and manipulated through a void\* but non of the proto-object's nonstatic members or member functions may be accessed, have their addresses taken, or be otherwise manipulated. cf. 11.2 Introduction of Ch. 11 Select Operations [9].

```
10. Copy vs. Move
```

cf. 17.1 Introduction of Ch. 17 Construction, Cleanup, Copy, and Move of Stroustrup [9].

Difference between *move* and *copy*: after a copy, 2 objects must have same value; whereas after a move, the source of the move isn't required to have its original value. So moves can be used when source object won't be used again.

Refs.: Sec. 3.2.1.2, Sec. 5.2, notion of moving a resource, Sec. 13.2-Sec.13.3, object lifetime and errors explored further in Stroustrup [9]

5 situations in which an object is copied or moved:

- as source of an assignment
- as object initializer
- as function argument
- as function return value
- as an exception

## 10.1. Copy constructor. cf. Copy constructors, cppreference.com

Copy constructor of class T is non-template constructor whose 1st parameter is T&, const T&, volatile T&, or const volatile T&.

```
class_name ( const class_name & )
class_name ( const class_name & ) = default;
class_name ( const class_name & ) = delete;
```

#### 10.1.2. Explanation.

- (1) Typical declaration of a copy constructor.
- (2) Forcing copy constructor to be generated by the compiler.
- (3) Avoiding implicit generation of copy constructor.

Copy constructor called whenever an object is **initialized** (by **direct-initialization** or **copy-initialization**) from another object of same type (unless **overload resolution** selects better match or call is **elided** (???)), which includes

- initialization T a = b; or T a(b);, where b is of type T;
- function argument passing: f(a);, where a is of type T and f is void f(T t);
- function return: return a; inside function such as T f(), where a is of type T, which has no move constructor.

**Definition 1.** Copy constructor is a member function which initializes an object using another object of the same class.

10.1.4. When is copy constructor called?

- (1) When object of class returned by value
- (2) When object of class is passed (to a function) by value as an **argument**.
- (3) When object is constructed based on another object of same class (or overloaded)
- (4) When compiler generates temporary object

However, it's not guaranteed copy constructor will be called in all cases, because C++ standard allows compiler to optimize the copy away in certain cases.

10.1.5. When is used defined copy constructor needed? shallow copy, deep copy. If we don't define our own copy constructor, C++ compiler creates default copy constructor which does member-wise copy between objects.

We need to define our own copy constructor only if an object has pointers or any run-time allocation of resource like file handle, network connection, etc.

- 10.1.6. Default constructor does only shallow copy.
- 10.1.7. Deep copy is possible only with user-defined copy constructor. We thus make sure pointers (or references) of copied object point to new memory locations.

Copy constructor called when new object created from an existing object, as copy of existing object, in (1). Assignment operator called when already initialized object is assigned a new value from another existing object, as assignment operator is called in (2).

10.1.9. Why argument to a copy constructor should be const? cf. Why copy constructor argument should be const in C++?, geeksforgeeks.org

- (1) Use const in C++ whenever possible so objects aren't accidentally modified.
- (2) e.g.

fun() returns by value, so compiler creates temporary object which is copied to t2 using copy constructor (because this temporary object is passed as argument to copy constructor since compiler generates temp. object). Compiler error is because compiler-created temporary objects cannot be bound to non-const references.

10.2. **Move Constructor.** For a class, to control what happens when we move, or move and assign object of this class type, use special member function *move constructor*, *move-assignment operator*, and define these operations. Move constructor and move-assignment operator take a (usually nonconst) rvalue reference, to its type. Typically, move constructor moves data from its parameter into the newly created object. After move, it must be safe to run the destructor on the given argument. cf. Ch. 13 of Lippman, Lajole, and Moo (2012) [11]

#### 11. VTABLE; VIRTUAL TABLE

I was given this answer to a question I posed to a 20 year C++ veteran and it was such an important answer (as I did not know a virtual table existed, at all before), that I will copy this, repeat this and explore this extensively:

"The keyword you're looking for is virtual table: "How are virtual functions and vtable implemented?, stackoverflow Original question, from Brian R. Bondy:

ERNEST YEUNG ERNESTYALUMNI@GMAIL.COM

11.1. **How are virtual functions and vtable implemented?** We all know what virtual functions are in C++, but how are they implemented at a deep level?

Can the vtable be modified or even directly accessed at runtime?

Does the vtable exist for all classes, or only those that have at least one virtual function?

Do abstract classes simply have a NULL for the function pointer of at least one entry?

Does having a single virtual function slow down the whole class? Or only the call to the function that is virtual? And does the speed get affected if the virtual function is actually overwritten or not, or does this have no effect so long as it is virtual.

Answer from *community wiki*:

11.1.1. How are virtual functions implemented at a deep level? From "Virtual Functions in C++"

Whenever a program has a virtual function declared, a v - table is constructed for the class. The v-table consists of addresses to the virtual functions for classes that contain one or more virtual functions. The object of the class containing the virtual function contains a virtual pointer that points to the base address of the virtual table in memory.

Whenever there is a virtual function call, the v-table is used to resolve to the function address.

An object of the class that contains one or more virtual functions contains a virtual pointer called the vptr at the very beginning of the object in the memory. Hence the size of the object in this case increases by the size of the pointer. This vptr contains the base address of the virtual table in memory.

Note that virtual tables are class specific, i.e., there is only one virtual table for a class irrespective of the number of virtual functions it contains. This virtual table in turn contains the base addresses of one or more virtual functions of the class. At the time when a virtual function is called on an object, the vptr of that object provides the base address of the virtual table for that class in memory. This table is used to resolve the function call as it contains the addresses of all the virtual functions of that class. This is how dynamic binding is resolved during a virtual function call.

cf. "Virtual Functions in C++"

- 11.1.2. What is a Virtual Function? A virtual function is a member function of a class, whose functionality can be over-ridden in its derived classes. It is one that is declared as virtual in the base class using the virtual keyword. The virtual nature is inherited in the subsequent derived classes and the virtual keyword need not be re-stated there. The whole function body can be replaced with a new set of implementation in the derived class.
- 11.1.3. What is Binding? Binding is associating an object or a class with its member. If we call a method fn() on an object o of a class c, we say that object o is binded with method fn().

This happens at *compile time* and is known as *static* - or *compile-time* binding.

Calls to virtual member functions are resolved during run-time. This mechanisms is known as dynamic-binding.

The most prominent reason why a virtual function will be used is to have a different functionality in the derived class. The difference between a non-virtual member function and a virtual member function is, the non-virtual member functions are resolved at compile time.

11.1.4. How does a Virtual Function work? When a program (code text?) has a virtual function declared, a **v-table** is constructed for the class.

The v-table consists of addresses to virtual functions for classes that contain 1 or more virtual functions.

The object of the class containing the virtual function contains a virtual pointer that points to the base address of the virtual implementation file," pp. 147 of Meyers (2014) [12]. table in memory. An object of the class that contains 1 or more virtual functions contains a virtual pointer called the **vptr** at the very beginning of the object in the memory. (Hence size of the object in this case increases by the size of the pointer; "memory/size overhead.")

\*\*Class\*\* Widget { // stimulation file," pp. 147 of Meyers (2014) [12].\*\*

\*\*Public:\*\*

\*\*Public:\*\*

\*\*Public:\*\*

\*\*Public:\*\*

This vptr is added as a hidden member of this object. As such, compiler must generate "hidden" code in the **constructors** of each class to initialize a new object's vptr to the address of its class's vtable.

Whenever there's a virtual function call, viable is used to resolve to the function address. This vptr contains base address of the virtual table in memory.

Note that virtual tables are class specific, i.e. there's only 1 virtual table for a class, irrespective of number of virtual functions it contains, i.e.

vtable is same for all objects belonging to the same class, and typically is shared between them.

This virtual table in turn contains base addresses of 1 or more virtual functions of the class.

At the time when a virtual function is called on an object, the vptr of that object provides the base address of the virtual table for that class in memory. This table is used to resolve the function call as it contains the addresses of all the virtual functions of that class. This is how dynamic binding is resolved during a virtual function call, i.e.

class (inherited or base/parent) cannot, generally, be determined *statically* (i.e. **compile-time**), so compiler can't decide which function to call at that (compile) time. (Virtual function) call must be dispatched to the right function *dynamically* (i.e. **run-time**).

11.1.5. Virtual Constructors and Destructors. A constructor cannot be virtual because at the time when constructor is invoked, the vtable wouldn't be available in memory. Hence, we can't have a virtual constructor.

A virtual destructor is 1 that's declared as virtual in the base class, and is used to ensure that destructors are called in the proper order. Remember that destructors are called in reverse order of inheritance. If a base class pointer points to a derived class object, and we some time later use the delete operator to delete the object, then the derived class destructor is not called.

Finally, the article "Virtual Functions in C++" concludes, saying, "Virtual methods should be used judiciously as they are slow due to the overhead involved in searching the virtual table. They also increase the size of an object of a class by the size of a pointer. The size of a pointer depends on the size of an integer." I will have to check this with other references, because, first of all, how then would class inheritance be otherwise implemented?

cf. How are virtual functions and vtable implemented?, stackoverflow

- 11.1.6. Can the vtable be modified or even directly accessed at runtime? No. "Universally, I believe the answer is "no". You could do some memory mangling to find the vtable but you still wouldn't know what the function signature looks like to call it. Anything that you would want to achieve with this ability (that the language supports) should be possible without access to the vtable directly or modifying it at runtime. Also note, the C++ language spec does not specify that vtables are required however that is how most compilers implement virtual functions."
- 11.1.7. Do abstract classes simply have a NULL for the function pointer of at least one entry? Some do place NULL pointer in vtable, some place pointer to dummy method; in general, undefined behavior. The answer is it is unspecified by the language spec so it depends on the implementation. Calling the pure virtual function results in undefined behavior if it is not defined (which it usually isn't) (ISO/IEC 14882:2003 10.4-2). In practice it does allocate a slot in the vtable for the function but does not assign an address to it. This leaves the vtable incomplete which requires the derived classes to implement the function and complete the vtable. Some implementations do simply place a NULL pointer in the vtable entry; other implementations place a pointer to a dummy method that does something similar to an assertion.

Note that an abstract class can define an implementation for a pure virtual function, but that function can only be called with a qualified-id syntax (ie., fully specifying the class in the method name, similar to calling a base class method from a derived class). This is done to provide an easy to use default implementation, while still requiring that a derived class provide an override.

11.2. **pImpl, shallow copy, deep copy.** cf. Item 22: "When using the Pimpl Idiom, define special member functions in the implementation file," pp. 147 of Meyers (2014) [12].

```
class Widget {
    public:
        Widget();
        Widget();
        // dtor is needed-see below
        ...

private:
        struct Impl; // declare implementation struct
```

```
Impl \ *pImpl; \ \ // \ and \ pointer \ to \ it : :
```

Because Widget no longer mentions types std::string, std::vector, and Gadget, Widget clients no longer need to \#include headers for these types. That speeds compilation.

incomplete type is a type that has been declared, but not defined, e.g. Widget::Impl. There are very few things you can do with an incomplete type, but declaring a pointer to it is 1 of them.

std::unique\_ptrs is advertised as supporting incomplete types. But, when Widget w;, w, is destroyed (e.g. goes out of scope), destructor is called and if in class definition using std::unique\_ptr, we didn't declare destructor, compiler generates destructor, and so compiler inserts code to call destructor for Widget's data member m\_Impl (or pImpl).

m\_Impl (or pImpl) is a std::unique\_ptr<Widget::Impl>, i.e., a std::unique\_ptr using default deleter. The default deleter is a function that uses delete on raw pointer inside the std::unique\_ptr. Prior to using delete, however, implementations typically have default deleter employ C++11's static\_assert to ensure that raw pointer doesn't point to an incomplete type. When compiler generates code for the destruction of the Widget w, then, it generally encounters a static\_assert that fails, and that's usually what leads to the error message.

To fix the problem, you need to make sure that at point where code to destroy std::unique\_ptr<Widget::Impl is generated, Widget::Impl is a complete type. The type becomes complete when its definition has been seen, and Widget::Impl is defined inside widget.cpp. For successful compilation, have compiler see body of Widget's destructor (i.e. place where compiler will generate code to destroy the std::unique\_ptr data member) only inside widget.cpp after Widget::Impl has been defined.

For compiler-generated move assignment operator, move assignment operator needs to destroy object pointed to by m\_Impl (or pImpl) before reassigning it, but in the Widget header file, m\_Impl (or pImpl) points to an incomplete type. Situation is different for move constructor. Problem there is that compilers typically generate code to destroy pImpl in the event that an exception arises inside the move constructor, and destroying pImpl requires Impl be complete.

Because problem is same as before, so is the fix - move definition of move operations into the implementation file.

For copying data members, support copy operations by writing these functions ourselves, because (1) compilers won't generate copy operations for classes with move-only types like std::unique\_ptr and (2) even if they did, generated functions would copy only the std::unique\_ptr (i.e. perform a shallow copy), and we want to copy what the pointer points to (i.e., perform a deep copy).

If we use std::shared\_ptr, there'd be no need to declare destructor in Widget.

unsigned and signed int: Yes!

Difference stems from differing ways smart pointers support custom deleters. For std::unique\_ptr, type of deleter is part of type of smart pointer, and this makes it possible for compilers to generate smaller runtime data structures and faster runtime code. A consequence of this greater efficiency is that pointed-to types must be complete when compiler-generated special functions (e.g. destructors or move operations) are used. For std::shared\_ptr, type of deleter is not part of the type of smart pointer. This necessitates larger runtime data structures and somewhat slower code, but pointed-to types need not be complete when compiler-generated special functions are employed.

Part 3. Integers, numeric encodings, number representation, binary representation, hexidecimal representation

12. Introduction: int  $\neq \mathbb{Z}$ , float  $\neq \mathbb{R}$ 

cf. Systems 1, Introduction to Computer Systems, Introduction lecture at University of Texas, CS429; Don Fussell. int  $\neq \mathbb{Z}$ , float  $\neq \mathbb{R}$  e.g.  $x^2 \geq 0$ ? float: Yes! int:  $40000 \times 40000 \rightarrow 1600000000$   $50000 \times 50000 \rightarrow ??$  Is (x+y)+z=x+(y+z)?

float's

$$(1e20 + -1e20) + 3.14 \rightarrow 3.14$$
  
 $1e20 + (-1e20 + 3.14) \rightarrow ??$ 

Can't assume "usual" properties due to finiteness of representations, so that integer operations satisfy "ring" properties commutativity, associativity, distributivity

floating point operations satisfy "ordering" properties - monotonicity, values of signs

#### 13. Bits and Bytes

#### cf. Lecture 2. Bits and Bytes, CS429.

Consider a (number) system with radix or base b (b > 1), string of digits  $d_1, \ldots, d_n$ ,

3) 
$$c = \sum_{i=1}^{n} d_i b^{n-i}, \quad 0 \le d_i < b \quad \forall i = 1 \dots n$$

with notation  $c \equiv c_b$  to help denote the base or "radix", e.g. 15213<sub>10</sub>, 00000000<sub>2</sub>.

Byte  $\equiv B$ , 1 Byte = 8 bits. Note that  $2^8 = 256$ 

e.g. Binary  $00000000_2$  to  $11111111_2$ 

Decimal:  $0_{10}$  to  $255_{10}$ Hexadecimal:  $00_{16}$  to  $FF_{16}$ 

#### 13.1. **Machine Words.** Machine has "Word size".

Nominal size of integer-valued data, including addresses.

### 13.2. Word-oriented Memory Organization. Addresses specify Byte locations.

Addresses of successive words differ by 4 (32-bit) or 8 (64-bit).

32-bit words:

Addr = 0000, Addr = 0004

64-bit words:

Addr = 0000, Addr = 0008

## 13.3. Byte-ordering: Big-Endian, Little-Endian. b = 8

(4) 
$$c = \sum_{i=0}^{n-1} d_i 8^{n-1-i}$$

**Big-Endian**: Least significant byte has highest address. For address a.

$$a \mapsto d_0$$

$$a+1 \mapsto d_1$$

$$\vdots$$

$$a+n-1 \mapsto d_{n-1}$$

**Little-Endian**: Least significant byte has lowest address

$$a \mapsto d_{n-1}$$

$$a+1 \mapsto d_{n-2}$$

$$\vdots$$

$$a+n-1 \mapsto d_0$$

### 13.4. Representing Strings. C Strings

- represented by array of characters, each character encoded in ASCII format - string should by null-terminated meaning and  $A \wedge A = 0$  is the additive inverse (existence) property. final character = 0

### 13.5. Machine-Level Code Representation. Encode program as sequence of Instructions.

Each simple operation - arithmetic operation, read or write memory, conditional branch. - instructions encoded as bytes, i.e. programs are byte sequences too!

### 13.6. Boolean Algebra. Boole's Algebraic representation of logic.

And:

A&B = 1 when both A = 1 and B = 1

Or:

A|B=1 when either A=1 or B=1

Not:

 $^{\sim}A = 1$  when A = 0.

 $^{\sim}A = 0$  when A = 1.

Exclusive-Or (Xor)  $A^{\wedge}B = 1$  when either A = 1 or B = 1, but not both

$$\begin{array}{c|cccc} ^{\wedge} & 0 & 1 \\ \hline 0 & 0 & 1 \\ 1 & 1 & 0 \\ \end{array}$$

13.6.1. Application of Boolean Algebra. Claude Shannon 1937 MIT Master's Thesis. Encode closed switch as 1, open switch as  $\wedge \rightarrow$  symmetric difference 0. Connection when  $A\& \sim B | \sim A\&B = A \wedge B$ 

13.6.2. Integer Algebra.  $(\mathbb{Z}, +, *, -, 0, 1)$  forms a ring

13.6.3. Boolean Algebra.  $\langle \{0,1\}, |, \&, \sim, 0, 1 \rangle$  forms a "Boolean algebra"

Or (|) is "sum" operation.

And (&) is "product" operation.

 $\sim$  is "complement" operation.

0 is additive identity.

1 is multiplicative identity.

#### cf. https://en.wikipedia.org/wiki/Bitwise\_operation

Bitwise OR may be used to set to 1 selected bits of register. e.g. fourth bit of 0010 may be set by performing bitwise OR with pattern with only 4th bit set.

Bitwise AND is equivalent to multiplying corresponding bits. Thus, if both bits in compared position are 1, bit in resulting binary representation is  $(1 \times 1 = 1)$ ; otherwise result is  $0 \ (1 \times 0 = 0 \text{ and } 0 \times 0 = 0)$ .

Operation may be used to determine whether particular bit is set (1) or clear (0), e.g. given bit pattern 0011 (decimal 3) to determine whether 2nd bit is set, use bitwise AND with bit pattern containing 1 only in 2nd. bit. Because result 0010 is non-zero, we know 2nd. bit in original pattern is set. This is often called bit masking (by analogy, use of masking tape covers, or *masks*, portions that are not of interest)

Bitwise AND may be used to clear selected bits (or flags) of a register in which each bit represents an individual Boolean state.

- This technique is an efficient way to store a number of Boolean values using as little memory as possible.
- Also, easy to check parity (even or odd?) of binary number by checking value of lowest valued bit.

Bitwise XOR may be used to invert selected bits in a register (also called toggle or flip). Any bit may be toggled by XORing with 1. e.g. given bit pattern 0010, 2nd and 4th bits may be toggled by bitwise XOR with bit pattern containing 1 in 2nd. and 4th. positions.

Consider Boolean Ring:

$$\langle \{0,1\}, \wedge, \&, I, 0, 1 \rangle \simeq \mathbb{Z}_2 \equiv \text{ integers} \mod 2$$

where I is identity operation I(A) = A,

13.6.4. De Morgan's Laws.

$$A\&B = \sim (\sim A|\sim B)$$
$$A|B = \sim (\sim A\&\sim B)$$

13.6.5. Exclusive-Or using Inclusive Or.

$$A \wedge B = (\sim A \& B) | (A \& \sim B)$$
$$A \wedge B = (A|B) \& \sim (A \& B)$$

All properties of Boolean Algebra apply to bit vectors.

13.7. Representing and Manipulating Sets; bit vectors as sets. Width w bit vector represents subsets of  $\{0, \dots, w-1\}$ , s.t. for  $a \in \{0,1\}^w$ ,  $a_i \in \{0,1\}$ ,  $\forall j = 0,1,\ldots w-1$ .

If 
$$a_j = 1, j \in A$$
; otherwise,  
If  $a_i = 0, j \notin A$ 

13.7.1. Operations.

 $\& \rightarrow intersection$ 

 $\rightarrow$  union

(5)

 $\sim \rightarrow$  complement

Logic operations in C: &&, ||, !

Shift operations

cf. Systems 1, Integers lecture at University of Texas, CS429 is a very good lecture; both mathematically rigorous and full of useful, *clear* examples.

#### 14. Unsigned integers

Consider  $\mathbb{Z}_{2w}^+ \to \mathbb{Z}^+$ , where  $\mathbb{Z}_{2w}^+$  represent "unsigned" integers.

$$\mathbb{Z}_{2^w}^+ \to \mathbb{Z}^+$$

$$(x_0, x_1, \dots, x_{w-1}) \mapsto \sum_{i=0}^{w-1} x_i \cdot 2^i$$

To recap using CS429's notation, for an unsigned integer x,  $B2U \equiv base-2$ -unsigned

$$B2U(x) = \sum_{i=0}^{w-1} x_i \cdot 2^i$$

where  $B2U: \mathbb{Z}^+ \to \mathbb{Z}_{2^w}^+$ 

So w is the total number of "bits" to represent x.

For hexidecimal (-based) numbers, observe this relationship:

(6) 
$$2^w = 16^v = 2^{4v} \text{ so } w = 4v$$

So for a hexidecimal number, v hexidecimal numbers represent w = 4v bits. Observe that

$$\mathbb{Z}_{2^w}^+ = \{0, \dots 2^w - 1\}$$

Also, modular addition  $(\mathbb{Z}_{2^w}^+,+)$  forms an abelian group.

### 15. Two's complement

Denote the notation for so-called "two's complement" numbers as  $\mathbb{Z}_{2^w}$ , which is a representation for integers in such a manner:

$$\mathbb{Z}_{2^w} \to \mathbb{Z}$$

(8) 
$$(x_0, x_1, \dots x_{w-1}) \mapsto -x_{w-1} \cdot 2^{w-1} + \sum_{i=0}^{w-2} x_i \cdot 2^i$$

with

(9) 
$$\mathbb{Z}_{2^w} = \{-2^{w-1} \dots 2^{w-1} - 1\}$$

To recap using CS429's notation, for integer  $x \in \mathbb{Z}$ ,  $B2T \equiv \text{base-2-Two's complement}$ 

$$B2T(x) = -x_{w-1} \cdot 2^{w-1} + \sum_{i=0}^{w-2} x_i \cdot 2^i$$

where  $B2T : "\mathbb{Z}" \to \mathbb{Z}_{2^w} = \{-2^{w-1} \dots 2^{w-1} - 1\}$ 

Observe that

(10) 
$$\max \left( \mathbb{Z}_{2^w}^+ \right) = 2 \max \mathbb{Z}_{2^w} + 1$$
$$|\min \mathbb{Z}_{2^w}| = \max \mathbb{Z}_{2^w} + 1$$

To recap and to clean up and unify the notation, recall the following: radix (i.e. base) b string of digits  $d_1, \ldots d_n$ ,

$$c = \sum_{i=1}^{n} d_i b^{n-i}, \quad 0 \le d_i < b \quad \forall i = 1 \dots n$$

cf. wikipedia, "Radix" i.e.

$$\{0, 1, \dots b - 1\}^n \to \mathbb{Z}$$
  
 $(d_1, \dots d_n) \mapsto c = \sum_{i=1}^n d_i b^{n-i}$ 

or (alternative notation),

$$\{01,\ldots b-1\}^w\to\mathbb{Z}$$

$$(d_{w-1}, d_{w-2}, \dots, d_0) \mapsto c = \sum_{i=0}^{w-1} d_i b^i$$

In Fussell's notation, Fussell (2011) [13].

$$\{0, 1, \dots b - 1\}^w \to \mathbb{Z} \text{ or } \mathbb{Z}_{2^w}^+ \to \mathbb{Z}^+$$

$$(x_{w-1}, x_{w-2}, \dots x_0) \mapsto c = \sum_{i=0}^{w-1} x_i 2^i, \ x_i < 2$$

$$B2U(X) = B2U(x_{w-1}, \dots x_0) = \sum_{i=0}^{w-1} x_i 2^i$$

I will use this notation:

$$B2U(x_w, x_{w-1}, \dots x_1) = \sum_{i=1}^{w} x_i 2^{i-1}$$

For the Two's Complement,

$$B2T(X) = B2T(-x_{w-1}, x_{w-2}, \dots x_0) = -x_{w-1}2^{w-1} + \sum_{i=0}^{w-2} x_i 2^i$$
$$\{0, 1, \dots b-1\}^w \to \mathbb{Z}$$

or with the notation I'll use,

$$B2T(-x_w, x_{w-1}, \dots x_1) = -x_w 2^{w-1} + \sum_{i=1}^{w-1} x_i 2^{i-1}$$

Note that for hexadecimal,

$$c = \sum_{i=1}^{w} x_i 2^{i-1} = \sum_{i=1}^{v} y_i (16)^{i-1} = \sum_{i=1}^{v} y_i 2^{4i-4}$$

v hexadecimal digits  $\leftrightarrow 4v = w$  bits.

15.1. Numeric Ranges. For unsigned values,

$$UMin = 0$$
$$000...0$$
$$UMax = 2^{w} - 1$$

For why UMax =  $2^w - 1$ , consider the geometric progression:

$$\sum_{k=1}^{n} ar^{k-1}$$

$$(1-r)\sum_{k=1}^{n} ar^{k-1} = a - ar^{n} \text{ or } \sum_{k=1}^{n} ar^{k-1} = \frac{a(1-r^{n})}{1-r}$$

$$\Longrightarrow \sum_{i=1}^{w} 2^{i-1} = \frac{1-2^{w}}{1-2} = 2^{w} - 1$$

$$TMin = -2^{w-1}$$

$$100 \dots 0$$

$$TMax = 2^{w-1} - 1011 \dots 1$$

 $-1 \leftrightarrow 111 \dots 1$ 

15.2. Negating with complement.

(11) 
$$\sim: \mathbb{Z}_{2^w} \to \mathbb{Z} \text{ s.t.}$$
$$\sim x + 1 = -x \quad \forall x \in \mathbb{Z}_{2^w}$$
$$\sim: \mathbb{Z}_{2^w}^+ \to \mathbb{Z} \text{ s.t.}$$
$$\sim x = 2^w - 1 - x$$

15.3. Power of 2 Multiply with shift (left shift bitwise operation). For both  $\mathbb{Z}_{2^w}^+$ ,  $\mathbb{Z}_{2^w}$ ,

(12) 
$$u << k = u \cdot 2^k \qquad \forall u \in \mathbb{Z}_{2^w}^+ \text{ or } \mathbb{Z}_{2^w} \text{ and } k \in \mathbb{Z}$$

15.4. Unsigned power-of-2 Divide, with shift (right shift bitwise operator).

(13) 
$$u >> k = \lfloor u/2^k \rfloor \qquad \forall u \in \mathbb{Z}_{2^w}^+, \quad k \in \mathbb{Z}$$

#### 14

#### 16. Endianness

Consider  $address \in \mathbb{Z}_{2^3}^+$ . Consider a  $value \in \mathbb{Z}_{2^3}^+$  or  $\mathbb{Z}_{2^3}$ .  $\forall (x_0, x_1, \dots x_{w-1}) \in \mathbb{Z}_{2^3}^+$  or  $\mathbb{Z}_{2^3}$ . Given address a.

## 16.1. Big-endian.

**Definition 2** (Big-endian). Most-significant byte value is at the lowest address, i.e.

$$a \mapsto x_{w-1}$$

$$a+1 \mapsto x_{w-2}$$

$$a+2 \mapsto x_{w-3}$$

$$\vdots$$

$$a+w-1 \mapsto x_0$$

### 16.2. Little-endian.

**Definition 3** (Little-endian). Least-significant byte value is at the lowest address, i.e.

(15) 
$$a \mapsto x_0$$

$$a+1 \mapsto x_1$$

$$\vdots$$

$$a+w-1 \mapsto x_{w-1}$$

For Little-endian  $\to \mathbb{Z}$ , ( addresses )  $\in \mathbb{Z}_{2^3}^+ \mapsto \mathbb{Z}$ ,  $a \mapsto (x_0, x_1, \dots x_{w-1})$ For  $\mathbb{Z} \to Big\text{-endian}$ ,  $n \mapsto (x_{w-1}, x_{w-2}, \dots x_0)$ .

Instead, to tackle the confusing problem of byte ordering, think about the integer as itself first, and then consider mapping multibyte binary values to memory.

$$\mathbb{Z} \to \left( \mathbb{Z}_{2^w} \longleftarrow \mathbb{Z}_{(2^3)^w} = addresses \right)$$

$$(16) \qquad \mathbb{Z} \ni (x_{w-1}, x_{w-2}, \dots x_1, x_0) \xrightarrow{Little-Endian} \quad \left( (x_0, x_1, \dots x_{w-2}, x_{w-1}) \longleftarrow (a, a+1, \dots a+w-2, a+w-1) \right)$$

$$\mathbb{Z} \ni (x_{w-1}, x_{w-2}, \dots x_1, x_0) \xrightarrow{Big-Endian} \quad \left( (x_{w-1}, x_{w-2}, \dots x_1, x_0) \longleftarrow (a, a+1, \dots a+w-2, a+w-1) \right)$$

#### Part 4. Floating Point Numbers

#### 17. FLOATING POINT, IEEE FLOATING

IEEE Standard 754

Recall our previous notation for the sum representation of a number c:

(17) 
$$c = \sum_{i=1}^{n} d_i b^{n-i}; \qquad 0 \le d_i < b, \quad \forall i = 1 \dots n$$

e.g.

$$c = 42_{10} = 4 \cdot 10^{2-1} + 2 \cdot 10^{2-2} = d_1 b^{n-1} + d_2 b^{n-2}$$

ERNEST YEUNG ERNESTYALUMNI@GMAIL.COM

By writing the exponent to be n-i, then we can write the digit representing the largest value in the summation "starting from the left" as such:

$$c = (d_1, d_2, \dots d_{n-1}, d_n)$$

e.g. (4,2) = 42.

However, the CS429h lectures uses the following notation for the unsigned int:

$$B2U(X) = \sum_{i=0}^{w-1} x_i 2^i \text{ or } (x_{w-1}, x_{w-2}, \dots x_1, x_0) \mapsto \sum_{i=0}^{w-1} x_i 2^i$$

e.g.  $(x_3, x_2, x_1, x_0) = (1, 0, 1, 1) \mapsto x_0 2^0 + x_1 2^1 + x_2 2^2 + x_3 2^3$ 

#### 17.1. Fractional Binary Numbers.

17.1.1. Representation. Bits to right of "binary point" represent fractional powers of 2. Binary number is used to represent a rational number, which in turn is a floating-point representation.

$$\sum_{k=-j}^{i} b_k \cdot 2^k \equiv \sum_{k=-M}^{N} b_k 2^k$$

(19) 
$$b \equiv (b_N, b_{N-1}, \dots b_1, b_0, b_{-1}, \dots b_{-M}) \mapsto \sum_{k=-M}^n b_k 2^k \equiv c$$

i.e.

$$\sum_{k=-M}^{N} b_k 2^k = b_N \cdot 2^N + b_{N-1} 2^{N-1} + \dots + b_1 \cdot 2 + b_0 \cdot 1 + b_{-1} \cdot \frac{1}{2} + \dots + b_{-M} \cdot 2^{-M}$$

e.g.  $101.11_2 \mapsto 5\frac{3}{4}$ 

Divide by 2 by shifting right:

(20) 
$$\frac{c}{2} = \sum_{k=-M}^{N} b_k 2^k / 2 = \sum_{k=-M-1}^{N-1} b_{k+1} 2^k$$

$$(b_N, b_{N-1}, \dots b_{-M}) \xrightarrow{\frac{1}{2}} (0, b_N, b_{N-1}, \dots b_{-M-1}, b_{-M})$$

Multiply by 2 by shifting left:

(21) 
$$2 \cdot c = \sum_{k=-M}^{N} b_k \cdot 2^k \cdot 2 = \sum_{k=-M+1}^{N+1} b_{k-1} 2^k$$

$$(b_N, b_{N-1}, \dots b_{-M}) \xrightarrow{\cdot 2} (b_N, b_{N-1}, \dots b_{-M}, 0)$$

This implies that we first choose the "most significant bit", the digit  $b_k$  representing the largest value in the sum representation to start from the left.

Numbers of form  $0.1111111..._2$  just below 1.0 (remember those are bits, 0 or 1).

$$\frac{1}{2} + \frac{1}{4} + \frac{1}{8} + \dots + \frac{1}{2^M} + \dots \to 1.0$$

Use  $1.0 - \epsilon$  notation.

17.1.2. Limitation of representable numbers. Can only exactly represent numbers of form  $\frac{x}{2^k}$ . The other numbers have repeating bit representations.

Value	Representation
$\frac{1}{3}$	0.0101010101[01]2
$\frac{1}{5}$	0.001100110011[0011]2
$\frac{1}{10}$	0.0001100110011[0011]2

## 17.1.3. Floating Point Representation. Numerical Form:

$$-1^{s} M 2^{E}$$

where

sign bit s, +1 or -1

significand (mantissa, or coefficient) M, normally a fractional value in range [1.0, 2.0) Exponent E weights value by power of 2.

From wikipedia,

$$\frac{s}{b^{p-1}} \cdot i$$

where s significand (ignoring an implied decimal point), p precision (number of digits in significand), base b. e.g.

$$1.528535047 \times 10^5 = \frac{1528535047}{10^9} \times 10^5$$

Another example:

$$\left(\sum_{n=0}^{p-1} c_n 2^{-n}\right) \times 2^e =$$

$$(1 \times 2^{-0} + 1.2^{-1} + 0 \cdot 2^{-2} + 0 \cdot 2^{-3} + 1 \cdot 2^{-4} + \dots + 1 \cdot 2^{-23}) \times 2^1$$

$$\approx 1.5707964 \times 2 \approx 3.1415928$$

For the encoding of this numerical form,

Most significant bit (MSB) is sign bit.

exp field encodes E frac field encodes M

s exp frac

Sizes for the encoding:

Single precision: 8 exp bits, 23 frac bits; 31 bits + 1 s bit = 32 bit and so  $2^{8-1}$ 

$$\sum_{i=0}^{M-1} c_i 2^{-i} \xrightarrow{\text{max}} 2^{M-1} = 2^{23-1}$$

Double precision: 11 exp bits, 52 frac bits; 63 bits + 1 s bit = 64 bits  $2^{\exp{-1}} = 2^{11-1} = 1024$ . This is the max value of e in decimal.  $2^{M-1} = 2^{52-1}$ 

17.1.4. "Normalized" Numeric Values. Condition:

$$\exp \neq 000...0$$
and  $\exp \neq 111...1$ 

Exponent coded as biased value:

(24) 
$$E = \text{Exp} - \text{Bias}$$

Exp: unsigned value determined by exp

Bias: Bias value

Note that E is the actual value desired, e.g.  $2^{13} = 2^{E}$ , whereas Exp is the actual binary representation.

- Single precision: 127 (Exp: 1...254, E: -126...127)
- Double precision: 1023 (Exp: 1...2046, E: -1022...1023)

In general

(25) Bias = 
$$2^{e-1} - 1$$

where e is number of exponent bits.

wikipedia says this: the exponent is "biased" in the engineering sense of the word - value stored is offset from actual value by the **exponent bias**. Biasing is done because exponents have to be signed value in order to be able to represent both tiny and huge values. It's not represented in two's complement, usual representation for signed values; it'd make comparison harder.

Exponent is stored as unsigned value which is suitable for comparison, and when interpreted, it's converted into an exponent within a *signed* range by subtracting the bias.

wikipedia uses this notation:

$$2^{k-1} - 1 =$$
bias for floating point number

where k is number of bits in exponent.

Number of normalized floating-point numbers in system (B, P, L, U) where

- $\bullet$  base B
- precision of system to P numbers
- L smallest exponent representable in system
- U largest exponent used in system

(26) 
$$2(B-1)(B^{P-1})(U-L+1)+1$$

Smallest positive normalized floating-point number.

Underflow level = UFL =  $B^L$ 

TODO: Understand all of this in https://en.wikipedia.org/wiki/Floating-point\_arithmetic

Significand coded with implied leading 1:

Get extra leading bit for "free".

xxx...x: bits of frac

Minimum when 000...0 (M=1.0) Maximum when 111...1  $(M=2.0-\epsilon)$ 

16

17.1.5. Denormalized Values and other Special Values. Consider "denormalized" values, the special case with the following condition:

$$\exp = 000...0$$

The Value is this:

Exponent value E = -Bias + 1 (compare this to Eq. 24).

Significand value  $M = 0.xxx...x_2$ , i.e. xxx...x: bits of frac.

Consider these special cases:

- $\exp = 000...0$ , frac = 000...0, which represents value 0 Note that there are distinct values for +0 and -0
- $\exp = 000...0$ ,  $\operatorname{frac} \neq 000...0$

These represent numbers that are very close to 0.0. They lose precision as they get smaller. There's "gradual underflow". TODO: understand what it means for "gradual underflow", cf. https://www.cs.utexas.edu/users/fussell/courses/cs429h/lectures/Lecture\_4-429h.pdf, pp. 10

Consider special values with the condition that

$$\exp = 111...1$$

They include the following cases:

- $\exp = 111...1$ , frac = 000...0. This represents the value at infinity,  $\infty$ . Operation that overflows. There are positive infinity and negative infinity.
  - e.g.  $1.0/0.0 = -1.0/-0.0 = +\infty$ ,  $1.0/-0.0 = -\infty$
- exp = 111...1, frac  $\neq$  000...0 This is Not-a-Number (NaN). It represents case when no numeric value can be determined. e.g. sqrt(-1),  $\infty \infty$ .

### Part 5. Complexity, Data Structures, Algorithms

18. Complexity, Big-O

Also note, let N = number of elements in a collection.

$$\log_{k} N = n \leftrightarrow b^{n} = N$$

 $N \log_b N = n \leftrightarrow b^n = N^N$  but rather, use Stirling's approximation:

$$N \ln N \cong \log_b N! = \sum_{i=1}^N \log_b i = n$$

 $O(N \log_b N) = O(\log_b N!)$  via Stirling's approximation:  $\ln N! = N \ln N - N + O(\ln N)$ 

18.1. Multi-Part Algorithms: Add vs. Multiply, e.g. O(A + B) vs. O(A \* B). If your algorithm is "do this (A), then, when completed, do that (B)" then add runtimes: O(A + B).

If your algorithm is "do this for each time you do that", then multiply runtimes: O(A\*B).

18.2. Amoritized Time (e.g. dynamically resizing array "ArrayList" or maybe std::vector). Dynamically resize array x: if there are N elements, s.t.  $N = \max$  capacity at N,  $|x| = N \mapsto |x| = 2N$  and there are N copies to be made (27) (T = N).

Let X = number of elements to be inserted.

Suppose when  $x = 1, 2, 4, 8, 16, ... 2^{j}, ... X$ ,  $x = 2^{j}$  copies are made.

total number of copies:

$$\sum_{j=0}^{\lfloor \log_2 X \rfloor} 2^j = \sum_{j=0}^{\lfloor \log_2 X \rfloor} 2^{\lfloor \log_2 X \rfloor - j} = \sum_{j=0}^{\lfloor \log_2 X \rfloor} \frac{X}{2^j} = X \left( \frac{1 - 2^{-(\lfloor \log_2 X \rfloor + 1)}}{1 - 1/2} \right) = 2X \left( 1 - 2/X \right)$$

$$\approx 2X \text{ if } X \text{ large}$$

Note that  $X = 2^y$ 

$$\log_2 X = y$$

X insertions take O(2X). "Amoritized" time for each insertion is O(1).

18.3.  $\log N$  runtimes  $(O(\log N))$ . e.g. binary search. find element (example) c in N-element sorted array.  $x = x_i$ ,  $i = 0, 1, \ldots, N - 1 \mapsto i' = 1, 2 \ldots N$ .

First, compare c to midpoint of array.

If  $c = x_{\lceil \frac{N}{2} \rceil}$ , done.

So let  $n_1 = N$ .

if  $c < x_{\lceil \frac{N}{2} \rceil}$ , consider  $x_1, x_2, \dots x_{\lceil \frac{N}{2} \rceil}$ , if  $c > x_{\lceil \frac{N}{2} \rceil}$ , consider  $x_{\lceil \frac{N}{2} \rceil + 1}, \dots x_N$ 

Let  $n_2 = \lfloor \frac{N}{2} \rfloor$ .

By induction,  $n_i = \lfloor \frac{N}{2i-1} \rfloor$ 

We stop when we either find the value c or we're down to just 1 element.

 $\implies$  total runtime is the a matter of how many steps (dividing N by 2 each time).

$$J = ?$$
 s.t.  $n_J = 1 = \left| \frac{N}{2J-1} \right| \Longrightarrow 0 = \log_2 N + (-J+1)$  or

$$J = \log_2 N$$

When you see a problem where number of elements  $n_0 = N, \dots n_j$  gets halved each time, it'll likely be  $O(\log_2 N)$  runtime. Finding an element in a **balanced binary search tree**:  $O(\log N)$ ; with each comparison, we go either left or right.

## 18.4. Recursive run times $O(2^N)$ .

Let 
$$n_1 = N$$
 
$$2^1 \quad f(n_1 - 1) = f(N - 1) \text{ calls}$$

$$n_2 = N - 1 \qquad \qquad 4 = 2^2 \quad f(n_2 - 1) \text{ calls}$$

$$\dots \qquad \qquad \mapsto \qquad \dots$$

$$n_j = N - j + 1 \qquad \qquad 2^j \quad f(n_j - 1) \text{ calls}$$

$$\text{until } j = N \qquad \qquad 2^N$$

$$\sum_{j=1}^{N} 2^{j} = \sum_{j=0}^{N-1} 2^{N-j} = 2^{N} \sum_{j=0}^{N-1} 2^{-j} = 2^{N} \left( \frac{1 - 2^{-N}}{1 - 1/2} \right) = 2^{N+1} (1 - 2^{-N}) \cong 2^{N}$$
 (N large)

Try to remember this pattern. When you have a recursive function that makes multiple calls, runtime will often (not always) look like

$$O(\text{branches}^{\text{depth}})$$

branches = number of times each recursive call branches.

space complexity is O(N), only O(N) nodes exist at any time.

cf. VI Big O, pp. 46, McDowell, Example 1

for (int i=0; i < N; i++) { sum += array[i]; } 
$$O(N)$$
.

cf. VI Big O, pp. 46, McDowell, Example 2

```
for (int i = 0; i < N; i++)
for (int j = 0; j < N; j++)
std::cout << i << j;
  O(N*N) = O(N^2) Or see it as printing O(N^2) total number of pairs.
  cf. VI Big O, pp. 46, McDowell, Example 3
for (int i = 0; i < N; i++)
for (int j = i + 1; j < N; j++)
std::cout << i << j;
                                                        i = 1, 2 ... N
                                                        j = i + 1, \dots N
                                                     \sum_{j=i+1}^{N} 1 = N - i
                 \sum_{i=1}^{N} (N-i) = N \cdot N - \sum_{i=1}^{N} i = N^2 - \frac{N(N+1)}{2} = N^2 - \frac{N^2}{2} - \frac{N}{2} = \frac{N^2 - N}{2} \cong N^2 \quad \text{(large)}
  cf. VI Big O, pp. 46, McDowell, Example 4
for (int i = 0; i < NA; i++)
for (int j = i + 1; j < NB; j++)
if (a[i] < b[j])
std::cout << a[i] << b[j];
if statement within j's for loop is O(1) time since it's just a sequence of constant time statements.
  \Longrightarrow O(NA \cdot NB)
  cf. VI Big O, pp. 47, McDowell, Example 5
for (int i = 0; i < NA; i++)
for (int j = i + 1; j < NB; j++)
for (int k = 0; k < 1000000; k++)
//...
```

```
\Rightarrow O(NA \cdot NB \cdot 1000000) = O(100000(NA)(NB)) \cong O(NA \cdot NB) 100,000 units of work is still constant, so run time is O(NA \cdot NB). cf. VI Big O, pp. 48, McDowell, Example 6 void reverse(int array[], const int N) { for (int i = 0; i < N / 2; i++) {    int other = N - i - 1;    int temp = array[i];    array[i] = array[other];    array[other] = temp; } } } } } } }  O(N) time. The fact that it only goes through half of the array (in terms of iterations) doesn't impact big O time. cf. VI Big O, pp. 47, McDowell, Example 8 Let the longest string be of length L. sort each string \Rightarrow L\log L (merge sort or best "worst" case for a sort) N_a = \text{number of strings} in the array of strings. N_a L \log L = \text{total number of sorts}.
```

Sort the full array.

You should also take into account that you need to compare the strings. Each string comparison takes O(L) time (compare each string element at each position).  $O(N_a \log N_a)$  comparisons (sort the full array of strings)

$$\Longrightarrow O(N_a L \log L) + O(LN_a \log N_a) = O(N_a L (\log L N_a))$$

#### 19. Data Structures

19.1. Lists (arrays), Python Lists. cf. https://wiki.python.org/moin/TimeComplexity, from 4. Quiz: Python Lists, Lesson 2: List-Based Collections, Udacity, Data Structures and Algorithms in Python

Operation	Average	Amoritized Worst Case
Сору	O(N)	O(N)
Append(1)	O(1)	O(1)
pop last	O(1)	O(1)
insert	O(N)	O(N)
Get item	O(1)	O(1)
Set item	O(1)	O(1)
Delete item	O(N)	O(N)
Get slice	O(k)	O(k)
Get length	O(1)	O(1)

Insert and delete is O(N). Need to move every element with index greater than k, and reindex each element. Get array length is O(1). cf. https://stackoverflow.com/questions/21614298/what-is-the-runtime-of-array-length

#### 19.2. Linked Lists, O(1) insertion.

Dynamic Array

O(1)

O(N)

O(1) amoritized

O(N)

O(N)

 $O(\log N)$   $O(\log N)$ 

 $O(\log N)$ 

 $O(\log N)$ 

 $O(\log N)$ 

O(1)

0

19.2.1. Linked Lists vs. arrays. main difference: Linked lists and arrays store difference information in each element.

Both cases: each element stores a value. Both cases: stores 1 more information.

Array: index as a number.

Linked List: reference to next element, e.g. store addresses of next element, e.g. x0123

e.g.

x0122 x0122 value: 8 value: 8 next: x0123 next: nullptr

Trick to remember: Given elements at addresses 1, 2, 3. If you delete the next reference for 1 (to 2), and replace it with a new object, you'll lose your reference to 3.

Assign your next reference to object at 2 before assigning next reference to 1.

Insertion takes constant time since you're just shifting around (constant, finite number of) pointers, instead of iterating every element of the list.

Doubly linked list: Also have pointers to previous element, e.g.

1 2 3
value:8 value:2 value:6
next:2 next:3 next:4
prev:0 prev:1 prev:2

### cf. https://en.wikipedia.org/wiki/Linked\_list

Disadvantages of Linked Lists:

- Use more memory than arrays because storage used by their pointers
- Nodes in linked list must be read in order from beginning: inherently sequential access

Linked list

O(N)

O(1)

O(1) when last element is known

O(N) when last element is unknown

 $\overline{\text{search time}} + O(1)$ 

O(N)

- nodes stored in continguously (possibly)
- difficult to reverse traverse, doubly linked list helps, but memory consumed in allocating space for back-ptr

Linked lists vs. dynamic arrays:

List data structures comparison

indexing

19.4. Queue, O(1) insert, O(1) delete, O(N) search, O(N) space complexities. https://en.wikipedia.org/wiki/Queue\_(abstract\_data\_type) Lesson 2: List-Based Collections, 11. Queues

Oldest element (tail) comes out first.

First In, First Out.

first element you put in (tail) is the first out (when you pop).

19.4.1. Queue as Linked List. head. "oldest element in the queue", "first"

tail. "newest element in queue", "last",

(I guess it grows from the tail)

add element to tail, enqueue.

Dequeue, remove head.

peek - peek at head.

Save references to head and tail.

19.4.2. Deque. double-ended queue. One can enqueue and dequeue from either end.

19.4.3. Priority Queue. Assign each element in queue with a priority.

Remove oldest and highest priority element first.

```
19.5. STL Containers. cf. Ch. 31, STL Containers, Bjarne Stroustrup (2013) [9]
```

Balanced Tree | Hashed array tree | pp. 886 Stroustrup (2013) [9] std::vector<T, A> contiguous allocated sequence of Ts;

O(1) cf. pp. 888 Sec. 31.2.1 "Container Representation", [9] O(N) vector element data structure is most likely an array:

vector: rep  $\leftarrow$  elements — free space

O(N) list: likely represented by sequence of links pointing to elements and number of elements; doubly-linked list of T; use when

 $\overline{O(N_{\overline{Y}}^{0})}$  need to insert and delete elements without moving existing elements.

 $\overline{O(\sqrt{N})}$  map: likely implemented as (balanced) tree of nodes pointing to (key, value) pairs:

unordered\_map likely implemented as hash table

unordered\_map rep  $\leftarrow$  hash table  $\leftarrow$ ,  $\leftarrow$ , ... (k, v), (k, v), ...

string for short strings, characters are stored in the string handle itself, for longer strings elements are stored contiguously on free-store (like vector elements). Like vector, string can grow into "free space" allocated to avoid repeated reallocations.

string: rep  $\leftarrow$  characters – free space

Like a built-in array, array is simply sequence of elements, with no handle, array: elements

cf. pp. 894, Sec. 31.3, Operations Overview, Stroustrup (2013) [9]

Standard Container Operation Complexity

wasted space (average)
head of list is 1st. node.

insert/delete at beginning

insert/delete at end

insert/delete in middle

tail of 1st. last node in 1st. (or rest of list)

19.3. Stack, O(1) pop, O(1) push. "Stack Details", Udacity, Data Structures and Algorithms

top element  $\mapsto$  Linked List head

push top element, pop top element. Last in, first out.

Last element you put in (new head), is the First out (when you pop).

	[] Sec. 31.2.2	List Sec. 31.3.7	Front Sec. 31.4.2	Back Sec. 31.3.6	Iterators Sec. 33.1.2
vector	const	O(n)+		const +	Ran
list		const	const	const	Bi
forward_list		const	const		For
deque	const	O(N)	const	const	Ran
stack				const	
queue			const	const	
priority_queue			$O(\log(n))$	$O(\log(n))$	
map	$O(\log(n))$	$O(\log(n))+$			Bi
set		$O(\log(n))+$			Bi
unordered_map	const+	const+			For
unordered_set		const+			For
string	const	O(n)+	O(n)+	const+	Ran
array	const				Ran

Ran - random-access iterator, "For" - "forward iterator", "Bi" - "bidirectional iterator"

#### 19.6. **vector**.

19.6.1. vector and growth. Layout of vector: elem ← "front" of elements, space ← "front" of extra space (meets end of elements) last ← end of extra space alloc

Use of both size (number of elements), and capacity (number of available slots for elements without reallocation) makes growth through push\_back() reasonably efficient: there's not an allocation operation each time we add an element, only every time we exceed capacity (Sec. 13.6)

adding half the size is common, standard doesn't specify by how much capacity is increased

19.6.2. vector and Nesting, vector (and similarly contiguously allocated data structures) has 3 major advantages:

- elements of vector compactly stored; no per-element memory overhead (contiguous on memory address) amount of memory consumed by vec of type vector<X> roughly sizeof(vector<X>)+vec.size()\*sizeof(X); sizeof(vector<X>) is about 12 bytes, insignificant for large vectors
- fast traversal, consecutive access, to get to next element, code doesn't have to indirect through a pointer
- simple and efficient random access, makes sort and binary search efficient

vs. doubly-linked list, list, incurs 4-words-per-element memory overhead (2 links plus free-store allocation header) be careful don't unintentional compromise efficiency of access, e.g. 2-dim. matrix

don't do vector<vector<double>>.

do vector<double> and compute locations from the indices

19.6.3. vector vs. array. vector resource handle, i.e. allows it to be resized and enable efficient move semantics, disadvantage to arrays that don't rely on storing elements separately from handle; keeps sequence of elements on stack or in another object.

### 19.7. **Trees.** value, left pointer, right pointer,

levels - how many connections it takes to reach the root +1 child can only have 1 parent height - number of edges between it and farthest leaf

depth - number of edges to root.

height, depth are inverse

19.8. **Graphs.** edges can store data too.

Directed graph edges have a sense of direction.

A = set of ordered pairs of vertices.

undirected graph.

acyclic (no cycles)

DAG Directed graph with no cycles.

19.8.1. Connectivity. connected graph has only 1 connected component.  $\exists$  path  $\forall$  pair of vertices. minimum number of elements (edges) to remove, to disconnect a component.

weakly connected directed graph if replacing all its directed edges with undirected edges produces a connected (undirected)

19.8.2. Graph Representation. vertex object:

list of edges.

Edge Object

vertices.

Edge List: = E

Adjacency list l = l(i) s.t.  $\forall i \in V$ ,  $l(i) \in \mathbf{Set}$  s.t.  $l(i) = \mathbf{set}$  of all adjacent vertices.

Adjacent Matrix.

Let V = set of all vertices.

 $\forall v \in V$ , label them:  $v = v(i), i \in \mathbb{N}$ 

 $\forall v_i \in V$ , so  $\forall i = 0, 1, \dots N - 1$ , Consider  $\forall w = w_i \in V$ , so  $\forall j = 0, 1, \dots N - 1$ .

If  $v_i, w_j$  are adjacent, let a(i, j) = 1, otherwise w(i, j) = 0. (adjacent means  $\exists$  edge s.t.  $E = \{v_i, w_j\}$ )

 $\Longrightarrow a$  is an adjacency matrix.

Adjacency list.

 $\forall v = v_i \in V, i = 0, 1, ... N - 1$ 

 $E = \{(v_o, v_t) | v_o, v_t \in V\}$ 

if  $\exists e \in E$  s.t.  $v_i = e(0) = v_o$ , then  $e(1) = v_t$  is adjacent to it.

Adjacency list useful for counting number of edges that a node has or number of adjacencies.

19.8.3. Graph Traversal. Depth-first search (DFS)

Breadth-first search (BFS)

DFS.

implementation: stack.

keep 2 structures: 1. Seen list, 2. stack.

If seen before, pop stack and go back.

O(|E| + |V|) visit every edge twice O(2|E| + |V|) = O(|E| + |V|).

O(|V|) time to look up a vertex.

More on procedure:

begin with any node  $v_1$ . Put  $v(v_1)$  into seen. Put  $v_1$  on stack.

if  $\exists \{e\} \subset E$  s.t. for  $e = (v_o, v_t)$ ,  $v_o = v_1$ , then, put  $v(v_t)$  into seen. Put  $v_t$  on stack.

Then consider  $v_t$ .

If  $v(v_t) \in \text{seen}$ , consider another edge.

If you run out of edges with new node, pop stack.

Eulerian path O(|E|)

Hamiltonian path

#### 20. Search

20.1. Binary Search  $O(\log(N))$ . https://classroom.udacity.com/courses/ud513/lessons/7123524086/concepts/ 71154040750923

 $O(\log(N) + 1) = O(\log(N))$  Binary search efficiency.

Given array  $a = a_i$ ,  $i = 0, 1, \dots, N-1$ , N elements in an array, s.t. a(i) < a(j) if i < j,  $i, j \in \{0, 1, \dots, N-1\}$  (i.e. sorted array)

Given x to search for,

Consider  $m_i$  s.t.

For 
$$j = 1$$
, given  $N$ ,  $m_1 := \begin{cases} \frac{N}{2} & \text{if } N \text{ odd} \\ \frac{N}{2} - 1 & \text{if } N \text{ even} \end{cases}$ 

 $m_1 = \text{midpoint to compare against.}$ 

if 
$$x = a(m_1)$$
 done.  
if  $x < a(m_1)$ , consider  $a_i$  s.t.  $i = 0, ..., m_1 - 1$   
if  $x > a(m_1)$ , consider  $a_i$  s.t.  $i = m_1 + 1 ..., N - 1$ 

For j, given  $a_i$ ,  $i = l, \dots r$  l < r, (l, r) are included in the range). Let  $L_i := r - l + 1$ 

$$m_j := \begin{cases} \frac{L_j}{2} + l & \text{if } L_j \text{ odd} \\ \frac{L_j}{2} - 1 + l & \text{if } L_j \text{ even} \end{cases}$$

If  $x = a(m_i)$  done,

if 
$$x < a(m_j)$$
, consider  $a_i$  s.t.  $i = 0, \dots m_j - 1$ 

If 
$$x > a(m_j)$$
, consider  $a_i$  s.t.  $i = m_j + 1, \dots N - 1$ 

Stop when  $L_i = 0$ .

## 20.2. Breadth-first search (BFS), https://en.wikipedia.org/wiki/Breadth-first\_search

starts at tree root, or some arbitrary node, and explores all neighbor nodes at present depth prior to moving on to nodes at next depth level.

Worst-cast performance  $O(|V| + |E|) = O(b^d)$ , Worst-case space complexity  $O(|V|) = O(b^d)$ 

https://www.quora.com/What-are-the-advantages-of-using-BFS-over-DFS-or-using-DFS-over-BFS-What-are-the-applications-adding-wandes-from-parthe-right. Pro:

1. Solution definitely found out by BFS, 2. never get trapped in blind alley, unwanted nodes, 3. if there are more than 1 solution, will find solution with shortest steps

- 1. Memory constraints: as it stores all nodes of present level to go for next level 2. if solution far away, consumes time Application of BFS:
- 1. Find shortest Path, 2. Check graph with bipertiteness
- 20.3. **Depth-first search.** Pre-order check off nodes as soon as you see it, before seeing children. root check it off, pick first left child, ...

In-order.

Con:

check off node once left child is seen.

went left most to right, went through all nodes in order.

Post-order.

Check off leaf, don't check off parent, check right child

Delete O(N), insert.

When do we want to use these structures? pros and cons.

20.4. Binary Search Tree (BST),  $O(\log N)$  height of the tree, run-time complexity, worst case O(N). Given node x, functions l, r, v s.t.  $l(x), r(x) \in \mathbf{Nodes} \cup \emptyset$ , v(x) is some ordered value, so  $v(x) \in \mathbf{OrderedSet}$ . Binary Search tree has the condition that  $\forall x$ ,

$$v(l(x)) \le v(x) \le v(r(x))$$

Given search value u.

if v(x) = y, done,

if  $v(x) < y, x_1 = r(x)$ 

if v(x) > y,  $x_1 = l(x)$ 

height of tree is  $O(\log N)$ , run-time complexity.

insert  $O(\log(N))$ 

delete  $O(\log(N))$ 

Unbalanced, distribution of nodes skewed, worse case O(N) search, insert, delete e.g.  $5 \to 10 \to 15 \to 20$ 

20.5. **Heaps.** max-heap: parent must always have bigger value than its child.

min-heap: parent must always have smaller value than its children.

Unlike binarytree, heap can have any number of children.

Pro:

- 1. heap finds max, min (root) 2. heap data structure efficiently use graph algorithm, e.g. Dijkstra Con:
- 1. takes more time to compare and execute.

heap = max. efficient implementation of priority queue.

Heap	find min	delete min	insert	decrease-value
Binary Heap	O(1)	$O(\log N)$	$O(\log N)$	$O(\log N)$

e.g. max binary heap.

"complete" all levels except last are completely full.

Search: O(N) no guarantee child is  $\leq$ . end up searching entire tree.

improved search: if x > root, quit search (for max-heap)

In general, if v(node) = node value  $\langle x, \text{no need to check children of node}$ .

Search: worse cast: O(N)

Average case: O(N/2) = O(N)

20.5.1. Heapify (Worst case  $O(\log N)$ ). stick new element in open spot of the tree.

heapify - reorder tree based on heap property:  $\forall$  given node C, if parent node P of C,  $v(P) \geq v(C)$  (max heap)

Swap P and C when v(C) > v(P)

Extract; remove root, replace root with right most element. Then swap when necessary,

Heapify: worst case  $O(\log N)$ .

As many operations as height of the tree.

20.5.2. Heap implementation (array). max-binary heap: since we know how may children (2),  $\forall$  parent. Use some math to find next mode. If level l, nodes per level  $l = 2^{l-1}$ 

Sorted array into tree.

Let sorted array be  $a = a_i$  s.t.

$$a_0 \mapsto l = 1$$

$$a_1, a_2 \mapsto l = 2$$

$$a_3, a_4, a_5, a_6 \mapsto l = 3$$

$$\left(\sum_{m=1}^{l-1} 2^{m-1}\right) - 1 = k$$
 index to start from.

Tree vs. Array

if tree uses nodes, need pointers: Arrays save space.

### 20.6. Self-balancing tree. Balanced minimize number of levels to use

20.7. Red-Black Tree; search  $O(\log N)$ , space O(N), insert  $O(\log N)$ , delete  $O(\log N)$ . root black,

level 1 black

level 2 red

level 3 black

null leaf nodes must be colored black (i.e. all leaves are black)

Rule 4 (optional) root must be black.

Rule 5 every node; every path descending down must contain same number of black nodes. i.e.  $\forall$  path from given node, to any of its descendant NIL nodes (leaf) must contain same number of black nodes.

red-black tree = self balancing binary search tree  $(\forall \text{ node } x, v(l(x)) \leq v(x) \leq v(r(x)))$ 

### 20.7.1. Red-Black Trees, insertion. Insert Red Nodes Only.

runtime for insertion worst case  $O(\log N)$ . Binary search tree worse case O(N) because BST could be unbalanced.

#### 21. Recursion

### cf. https://en.wikipedia.org/wiki/Recursion, Udacity

Recursion

- must call itself at some pt.
- base case
- alter input parameter

**Theorem 1** (Recursion (from set theory)). Given  $X \in Set$ ,  $a \in X$ ,  $f: X \to X$ 

$$\exists ! F : \mathbb{N} \to X \text{ s.t.}$$
$$F(0) = a$$

$$F(n+1) = f(F(n))$$

e.g. 
$$Fib(0) = 0$$

$$Fib(1) = 1$$

$$\forall n > 1, n \in \mathbb{Z}, Fib(n) := Fib(n-1) + Fib(n-2) = f(Fib(n-1), Fib(n-2))$$

22. Sorting

22.1. Bubble Sort,  $O(N^2)$  in time, O(1) in space. cf. Efficiency of Bubble Sort, Lesson 3: Searching and Sorting, Data Structures and Algorithms, Python

Time complexity of bubble sort:

 $\forall$  iteration, there were N-1 comparisons. Worst case is N-1 iterations to order all N elements.

 $\Longrightarrow O(N^2)$  worse case

 $O(N^2)$  average case

O(N) best case (it was already sorted!)

Space complexity O(1) no extra arrays needed. Sort was "in-place."

From wikipedia, "Bubble Sort" (Optimizing Bubble Sort), cf. https://en.wikipedia.org/wiki/Bubble\_sort, Observe that for an array of elements a indexed by i = 1, 2 ... N,

 $j=1\mapsto a(N)$  largest (otherwise it would not have been swapped; contradiction)

```
j = 2 \mapsto a(N-1) 2nd. largest. Iterated on 2, \dots N-1 N-2 total (don't include the first). \vdots j \mapsto a(N-j+1) jth largest, iterated on 2, \dots N-j+1, N-j total.
```

22.2. Merge Sort,  $O(N \log N)$  in time, O(N) in space. cf. Efficiency of Merge Sort, Lesson 3: Searching and Sorting, Data Structures and Algorithms, Python

Use approximation (approximate to the *worse case!*) to count the number of comparisons (operations) in a "pass" (iteration) multiply each iteration with number of comparisons per iteration.

Number of iterations  $\cong \log N$  since  $2^J - 1 = \text{array size}$ .

N comparisons for  $\log(N)$  steps  $\Longrightarrow O(N \log N)$ 

Space complexity. Auxilliary space = O(N) at each step we need total arraying size N to copy into.

22.3. Quick Sort,  $O(N \log N)$  average time complexity,  $O(N^2)$  worst time complexity, O(1) in space (if inplace).

22.3.1. First element pivot Implementation. cf. https://stackoverflow.com/questions/22504837/how-to-implement-quick-sort-Consider array  $a = a_i$ , i = 0, 1, ..., N-1; |a| = N (array of length N).

```
Given l, r \in [0, 1, ..., N-1,
```

Let p := a(l) (pivot value)

 $i = i_i; i_1 = l$ 

Let  $j = j_i$  s.t.  $j_1 = l + 1, \dots, j_{r-l-1} = r - 1$  (range over r - 1 - (l+1) + 1 = r - l - 1)

if  $a(j_j) \leq p$ 

 $i_{j+1} = i_j + 1$ 

 $a(i_{j+1}) = a(i_j + 1) \leftrightarrow a(j_j)$ 

$$a(i_{r-l-1}) \leftrightarrow a(l)$$

 $\mapsto i_{r-l-1}$ .

Let's work out a table for the first few steps:

iteration	i	j	swaps	condition	example
1	l	l+1			
	l+1	l+1	$a(l+1) \leftrightarrow a(l+1)$	$p \ge a(l+1)$	5 3 4
2		l+2			
	l+1	l+2			
	l+1	l+2	$a(l+1) \leftrightarrow a(l+2)$	$p \ge a(l+2)$	5 6 3
	l+2	l+2	$a(l+2) \leftrightarrow a(l+2)$	$p \ge a(l+2)$	5 3 4
3	l+1	l+3	$a(l+1) \leftrightarrow a(l+3)$	$p \ge a(l+3)$	$5 \ 8 \ 6 \ 3 \mapsto 5 \ 3 \ 6 \ 8$

22.3.2. Complexity of Quick Sort. Worst case if all pivots are in place, e.g. 1, 2, 8, 13

Cannot "split" (partition) by pivots since it's already sorted  $\Longrightarrow O(N^2)$ .

Average case  $O(N \log N)$  (N iterations (for each element)  $\log N$  comparisons (via split))

O(1) space complexity.

Best case; move pivot to middle and divide each partition by 2. Bad case; array already somewhat sorted, hard to move pivot to middle.

to middle.

22.4. Time Complexities of all Sorting Algorithms. https://www.geeksforgeeks.org/time-complexities-of-all-sorting 100 / 87 / 100 gorithms/100 = 0.1 but waste memory, ton of empty buckets. "Best" complexity (best of worst case) sort is  $O(N \log N)$ .

22.5. Hashing, O(1) lookup, or O(n) bucket lookup.

22.5.1. Hash maps. key 
$$\xrightarrow{\text{Hash function}}$$
 Hash: Key Value:

$$\langle \text{Key, Value} \rangle \xrightarrow{\text{Hash function on Key}} \text{Hash:} \qquad \langle K, V \rangle$$
 Value:

Use keys are inputs to has function.

Store Key, Value pair in map  $\langle K, V \rangle$ 

22.5.2. Hash Functions. Value Hash function Hash Value (often index in an array)

Fast O(1) look up

e.g. ticket number

 $8675309 \stackrel{?}{\rightarrow} \text{some index.}$ 

Take last two digits of a big number

 $01234956 \mapsto 56 \mapsto 56/100 = 5$ 

"last few digits are the most random" collisions

e.g.  $0123456 \mapsto 56\%10$ 

 $6543216 \mapsto 16\%10$ 

To deal with collisions 1) change value(s used in hash function) in hash function or change hash function completely, or 2) change structure of array  $\mapsto$  buckets.

Normal Array vs. Bucket

Value collection

- (1) X%1000000, O(1)
- (2) Bucket, iterate through bucket O(n), n allocated size of each bucket
  - (a) Hash function inside

load factor - how "full" has table is.

Load factor = number of entries / number of buckets

e.g. 10 values in 1000 buckets, load factor = 0.01, majority of buckets in table will be empty.

waste memory with empty buckets, so rehash i.e. come up with new hash function with less resulting buckets.

closer load factor to 1, better to rehash and add more buckets any table with load value greater than 1, guaranteed to have collisions.

100 numbers N

a number is a multiple of 5: x = 5n

ERNEST YEUNG ERNESTYALUMNI@GMAIL.COM

Number of values = 100 numbers = NNumber of buckets = 100 (0 to 99) $\implies 100/100 = 1$  load factor.

 $100/107 < 1 \pmod{}$ 

125 is a multiple of 5.

x=5n.  $\frac{x}{125}=\frac{5n}{125}=\frac{n}{25}\mapsto$  loss of collisions.

22.5.3. Hash Table. Constant time lookup important to speed up.

String Keys.

ASCII values from letters.

30 or less words, Use ASCII.

e.g. "UD" 
$$\mapsto U = 85$$

$$D = 68$$

31 = (32 : 326)

Huge has values for 4-letter strings

$$s(0)31^{n-1} + s(1)32^{n-2} + \cdots + s(n-1)$$

## Part 6. Linux System Programming

### 23. File Descriptors

cf. https://medium.com/@copyconstruct/nonblocking-i-o-99948ad7c957

Let byte  $b \in (\mathbb{Z}_2)^8 \equiv B \equiv o$  (when referring to exactly 8 bits).

The fundamental building block of I/O in Unix is a sequence of bytes  $(b_n)_{n\in\mathbb{N}}, b_n\in B$ .

Most programs work with an even simpler abstraction - a stream of bytes or an I/O stream.

File descriptors  $\equiv fd$ . fd references I/O streams.  $fd \in \mathbb{N}$  (by definition and the Linux programmer's manual).

$$\mathbb{N} \to B^{\mathbb{N}}$$

$$fd \xrightarrow{\operatorname{surj}} (b_n)_{n \in \mathbb{N}}$$

e.g. Pipes, files, FIFOs, POSIX IPC's (message queues, semaphores, shared memory), event queues are examples of I/O streams referenced by a fd, i.e.  $fd \xrightarrow{\text{surj}} (b_n)_{n \in \mathbb{N}}$ .

### 23.1. Creation and Release of Descriptors. fd's are either

- explicitly created by system calls like open, pipe, socket, etc. or
- inherited from parent process

fd's released when

- process exists
- calling close system call
- implicitly after an exec when fd marked as close on exec; i.e. fd automatically (and atomically) closed when execfamily function succeeds

#### 24. Unix execution model

cf. https://stackoverflow.com/questions/4204915/please-explain-the-exec-function-and-its-family/37558902

24.1. Processes and Programs. A process is something in which a program executes.  $pid \in \mathbb{N} \xrightarrow{\text{surj}}$  process

These 2 operations that you can do is the entire UNIX execution model:

fork - creates new process containing duplicate of current program, including its state. There are differences between the processes so to be able to distinguish which is parent, which is child:

$$pid_P \xrightarrow{\text{surj}} pid_C > 0$$
  
 $prog_i \text{ s.t. } prog_i \in pid_P \mapsto prog_i \in pid_C$ 

exec - replaces program in current process with brand new program:

$$\operatorname{prog}_i \in pid_i \mapsto \operatorname{prog}_{i'} \in pid_i$$
  
s.t.  $\operatorname{prog}_i = \emptyset$ ,  $\operatorname{prog}_i \neq \operatorname{prog}_{i'}$ 

More details:

fork() makes a near duplicate of current process, identical in almost every way; 1 process calls fork() while 2 processes return from it:

$$pid_P \xrightarrow{\text{fork()}} pid_P, pid_C > 0$$

Examples:

- When fork, exec used in sequence: In shells, find:

$$pid_{\text{shell}} \xrightarrow{\text{fork()}} pid_{\text{shell}}, pid_C \qquad \text{prog}_j, pid_C \xrightarrow{\text{exec()}} \text{prog}_{j'} \in pid_C$$

Shell forks, then child loads find program into memory, setting up all command line arguments, standard I/O, etc.

- fork() only. Daemons simply listening on TCP port and fork copy of themselves to process specific request, while parent goes back to listening.

Notice that nominally, parent waits for child to exit.

close-on-exec flag, if set, will have fd automatically be closed during a successful execve (or exec) (cf. http://man7.org/ linux/man-pages/man2/fcnt1.2.html)

24.2. File entry. Every fd points to a data structure called *file entry* in the kernel.

$$fd \mapsto \text{ file entry}$$

i.e.  $\forall fd, \exists$  file entry and pointer to that file entry.

open file description - an entry in system-wide table of open files.

open file description records file offset and file status flags.

 $n_{\text{offset}} \equiv \text{file offset}$ , per fd, from the beginning of file entry.

fork() results in both parent and child processes using same fd and reference to same offset  $n_{\text{offset}}$  in file entry.

If process was last to reference file entry, kernel then deallocates that file entry.

Each file entry contains

- the type
- array of function pointers, that translates generic operations on fds to file-type specific implementations.

open call implementation greatly varies for different file types, even if higher level API exposed is the same.

e.g. sockets - Same read, write used for byte-stream type connections, but different system calls handle addressed messages like network datagrams.

For a process pid, consider fd table of fds.  $\forall$  fd,  $fd \mapsto$  open file description  $\in$  open file table (system-wide).

 $\forall$  open file description  $\in$  open file table.

open file description =  $n_{\text{offset}}$ , status flags, and

open file description  $\stackrel{\text{inode ptr}}{\longmapsto}$  inode table.

A blocking system call is 1 that suspends or puts calling process on wait until an event occurs <sup>1</sup>

A fd is considered *ready* if process can perform I/O operation on fd without blocking (i.e. without process having to wait or be suspended). For fd to be considered "ready", it doesn't matter if **the operation actually transfer any data** - all that matters is that the I/O operation can be performed without blocking (i.e. the calling process won't wait or be suspended).

A fd changes into a *ready* state when an I/O *event* happens, such as the arrival of new input or completion of a socket connection or when space is available on previously full socket send buffer after TCP transmits queued data to the socket peer.

There are 2 ways to find out about the readiness status of a descriptor - edge triggered and level-triggered.

### 24.4. Level Triggered. cf. https://medium.com/@copyconstruct/nonblocking-i-o-99948ad7c957

To determine if fd is ready, the process tries to perform a non-blocking I/O operation. Also seen as "pull" or "poll" model. (User "pull" on the fd).

At time  $t_0$ , process pid tries I/O operation on non-blocking fd. If I/O operation blocks, system call returns error err.

At time  $t_1 > t_0$ , pid tries I/O on fd (again). Say call blocks again, and returns err.

At time  $t_2 > t_1$ , pid tries I/O on fd (again). Assume call blocks again, and returns err.

At time  $t_3 > t_2$ , pid polls status of fd, and fd is ready. pid can then choose to actually perform entire I/O operation (e.g. read all data available on socket).

At time  $t_4 > t_3$ , assume pid polls status of fd, and fd isn't ready; call blocks (again), and I/O operation returns err.

At time  $t_5 > t_4$ , pid polls for status of fd, and fd is ready. pid can then choose to only perform a partial I/O operation (e.g., reading only half of all data available)

At time  $t_6 > t_5$ , pid polls status of fd, and fd is ready. This time, pid can choose to perform no I/O.

24.5. **Edge Triggered.** Process *pid* receives a notification only when fd is "ready" (usually when there's any new activity on fd since it was last monitored). This can be seen as the "push" model, in that a notification is pushed to the process about readiness of a fd.

process pid only notified that fd is ready for I/O, but not provided additional information like for instance how many bytes arrived on socket buffer.

Thus, pid only armed with incomplete data as it tries to perform any subsequent I/O operation e.g. at  $t_2 > t_0$ , pid gets notification about fd being ready.

byte stream  $(b_n)_{n\in\mathbb{N}}$  available for I/O stored in buffer.

Assume  $N_b = 1024$  bytes available for reading, when pid gets notification at  $t = t_2$ .

$$\Longrightarrow (b_n)_{n < N_b} \subset (b_n)_{n \in \mathbb{N}}$$

Assume pid only reads  $N_h' = 500$  bytes  $< N_h$ 

That means for  $t = t_3, t_4, \dots t_{i_2}$ , there are still  $N_b - N_b' = 524$  bytes available in  $(b_n)_{n < N_b}$  that pid can read without blocking. But since pid can only perform I/O once it gets next notification, these  $N_b - N_b'$  bytes remain sitting in buffer for that duration

Assume pid gets next notification at  $t_{i_2} = t_6$ , when additional  $N_b$  bytes have arrived in buffer.

Then total amount of data available on  $(b_n)_{n\in\mathbb{N}}=2N_b-N_b'=1548=524+1024$ .

Assume pid reads in  $N_b = 1024$  bytes.

This means that at end of 2nd. I/O operation,  $N_b - N_b' = 524$  bytes still remain in  $(b_n)_{n \in \mathbb{N}}$  that pid won't read before next notification arrives.

While it might be tempting to perform all I/O immediately once notification arrives, doing so has consequences.

- large I/O operation on single fd has potential to starve other fd's
- Furthermore, even with case of level-triggered notifications, an extremely large Write or send call has potential to block.

<sup>24.3.</sup> Readiness of fds. cf. https://medium.com/@copyconstruct/nonblocking-i-o-99948ad7c957

<sup>1</sup> https://stackoverflow.com/questions/19309136/what-is-meant-by-blocking-system-call, https://www.quora.com/What-is-the-difference-between-a-blocking-system-call-and-an-non-blocking-system-call

24 ERNEST YEUNG ERNESTYALUMNI@GMAIL.COM

#### 25. Multiplexing I/O on FDS

In above, we only described how pid handles I/O on a single fd.

Often, pid wants to handle I/O on more than 1 fd.

e.g. program prog needs to log to stdout, stderr, while accept socket connections, and make outgoing RPC connections to other services.

There are several ways of multiplexing I/O on fds.

- nonblocking I/O (fd itself is marked as non-blocking; operations may finish partially)
- signal-drive I/O (pid owning fd is notified when I/O state of fd changes)
- polling I/O (e.g. select, poll, both provide level-triggered notifications about readiness of fd)

### 25.1. Multiplexing I/O with Non-blocking I/O. We could put all fds in non-blocking mode.

pid can try to perform I/O operations on fds to check if any I/O operations result in error.

kernel performs I/O operation on fd and returns err, or partial output, or result of I/O operation if it succeeds.

#### Cons:

- Frequent checks
- Infrequent checks. If such operations are conducted infrequently, then it might take pid unacceptably long time to respond to I/O event that's available.

When does this approach make sense?

Operations on output fds (e.g. writes) don't generally block.

- In such cases, it might help to try to perform I/O operation first, and revert back to polling when operation returns err.

It might also make sense to use non-blocking approach with edge-triggered notifications, where fds can be put in nonblocking mode, and once pid gets notified of I/O event, it can repeatedly try I/O operations until system calls would block with an EAGAIN or EWOULDBLOCK.

### 25.2. Multiplexing I/O via signal driven I/O.

Kernel instructed to send the pid a signal when I/O can be performed on any of the fds.

pid will wait for signals to be delivered when an of the fds is ready for I/O operation.

Cons: Signals are expensive to catch, rendering signal drive I/O impractical for cases where large amount of I/O is performed. Typically used for "exceptional conditions."

## 25.3. Multiplexing I/O via polling I/O. $\cdot$

fds placed in non-blocking mode.

pid uses **level triggered mechanism** to ask kernel by means of system call (select or poll) which fds are capable of performing I/O.

25.3.1. poll, and select vs. poll. With select, we pass in 3 sets of fds we want to monitor for reads, writes, and exceptional cases.

With poll, we pass in a set of fds, each marked with the events it specifically needs to track.

- 25.3.2. What happens in the kernel (with select and poll)? Both select and poll are stateless, meaning, every time a select or poll system call is made, the kernel checks every fd, in the input array passed as 1st. argument, for the occurrence of an event and return the result to the pid.
- $\implies$  this means that the cost of select/poll is O(N), where N is the number of fds monitored.

The implementation of select and poll comprises 2 tiers:

- Specific top tier which decodes incoming request, as well as several device or socket specific bottom layers
- bottom layers comprise of kernel poll functions used both by select, poll

26. EPOLL EVENT POLL

#### cf. "The method to epoll's madness" by Cindy Sridharan[14]

epoll, a Linux specific construct, allows for a pid to monitor multiple fds and get notifications when I/O is possible on them.

26.1. epoll **Syntax.** epoll, unlike poll, is not a system call. It's a kernel data structure that allows a pid to multiplex I/O on multiple fds.

This data structure can be created, modified, deleted by 3 system calls: epoll\_create, epoll\_ctl, epoll\_wait.

#### 27. References and Resources for Linux System Programming

```
http://igm.univ-mlv.fr/~yahya/progsys/linux.pdf
http://www.cs.fsu.edu/~baker/opsys/examples/forkexec/fork_wait.c
```

## Part 7. C++ Template Metaprogramming

From this question on  ${\color{blue} stack}$  overflow, comes this tutorial.

cf. Vandevoorde, Josuttis, and Gregor (2017) [15].

#### Part 8. Functional Programming and Category Theory

Best discussion of the relation to monads in category theory to monads in "computer science": https://ncatlab.org/nlab/show/monad+%28in+computer+science%29

Best article on practical implementation (real daily programming, real programming experiences) of functional programming without pulling punches on Category Theory:

https://nalaginrut.com/archives/2019/10/31/8%20essential%20patterns%20you%20should%20know%20about%20functional%20programming%20in%20c%2B%2B14

More links

https://nbviewer.jupyter.org/github/ivanmurashko/articles/blob/master/cattheory/cattheory.pdf https://wiki.ifs.hsr.ch/SemProgAnTr/files/mof\_categories\_final.pdf

#### Part 9. Technical Interviews

"Interview Introduction", Data Structures and Algorithms in Python, Udacity

- Clarifying the Question
- Generating Inputs and Outputs
- Generating Test Cases
- Brainstorming
- Runtime Analysis
- Coding
- Debugging

#### References

- [1] Bertrand Meyer. Object-Oriented Software Construction (Book/CD-ROM) (2nd Edition) 2nd Edition. Prentice Hall; 2 edition (April 13, 1997). ISBN-13: 978-0136291558
- [2] Randall Hyde. Write Great Code: Volume 1: Understanding the Machine October 25, 2004. No Starch Press; 1st edition (October 25, 2004). ISBN-13: 978-1593270032
- [3] Randall Hyde. Write Great Code, Volume 2: Thinking Low-Level, Writing High-Level. 1st Edition. No Starch Press; 1 edition (March 18, 2006). ISBN-13: 978-1593270650
- [4] Zed A. Shaw. Learn C the Hard Way: Practical Exercises on the Computational Subjects You Keep Avoiding (Like C) (Zed Shaw's Hard Way Series) 1st Edition. Addison-Wesley Professional; 1 edition (September 14, 2015) ISBN-13: 978-0321884923.
- [5] Eli Bendersky. Are pointers and arrays equivalent in C?
- [6] Brian W. Kernighan, Dennis M. Ritchie. C Programming Language, 2nd Ed. 1988.
- [7] Peter van der Linden. Expert C Programming: Deep C Secrets 1st Edition. Prentice Hall; 1st edition (June 24, 1994) ISBN-13: 978-0131774292
- [8] Leo Ferres. "Memory management in C: The heap and the stack". Memory management in C: The heap and the stack
- [9] Bjarne Stroustrup. The C++ Programming Language, 4th Edition. Addison-Wesley Professional; 4 edition (May 19, 2013). ISBN-13: 978-0321563842
- [10] Carlo Ghezzi, Mehdi Jazayeri. Programming Language Concepts 3rd Edition. Wiley; 3 edition (June 23, 1997). ISBN-13: 978-0471104261 https://vowi.fsinf.at/images/7/72/TU\_Wien-Programmiersprachen\_VL\_(Puntigam)\_-\_E-Book\_SS08.pdf
- [11] Stanley B. Lippman, Josée Lajoie, Barbara E. Moo, C++ Primer (5th Edition), Addison-Wesley Professional; 5 edition (August 16, 2012) ISBN-13: 978-0321714114
- [12] Scott Meyers. Effective Modern C++: 42 Specific Ways to Improve Your Use of C++11 and C++14. 1st Edition. O'Reilly Media; 1 edition (December 5, 2014) ISBN-13: 978-1491903995
- [13] Prof. Donald S. Fussell (Instructor). CS429H (378H) Systems I (Honors) (Computer Organization, Architecture, and Programming). Spring 2011. University of Texas. https://www.cs.utexas.edu/users/fussell/courses/cs429h/
- [14] Cindy Sridharan. "The method to epoll's madness." Medium. Oct. 29, 2017. https://medium.com/@copyconstruct/the-method-to-epolls-madness-d9d2d6378642
- [15] David Vandevoorde, Nicolai M. Josuttis, Douglas Gregor. C++ Templates: The Complete Guide (2nd Edition). Addison-Wesley Professional; 2 edition (September 18, 2017). ISBN-13: 978-0321714121