



# LECTURE 07 – DECREASE & CONQUER

Paul Doliotis (PhD)  
Adjunct Assistant Professor  
Portland State University

# What is Decrease & Conquer?

---

- Solves a problem instance of size  $n$  by:

# What is Decrease & Conquer?

---

- Solves a problem instance of size  $n$  by:
  - decreasing  $n$  by a constant, e.g., 1, or

# What is Decrease & Conquer?

---

- Solves a problem instance of size  $n$  by:
  - decreasing  $n$  by a constant, e.g., 1, or
  - decreasing  $n$  by a constant factor, e.g., 2, or

# What is Decrease & Conquer?

---

- Solves a problem instance of size  $n$  by:
  - decreasing  $n$  by a constant, e.g., 1, or
  - decreasing  $n$  by a constant factor, e.g., 2, or
  - decreasing  $n$  by a variable amount

# What is Decrease & Conquer?

---

- Solves a problem instance of size  $n$  by:
  - decreasing  $n$  by a constant, e.g., 1, or
  - decreasing  $n$  by a constant factor, e.g., 2, or
  - decreasing  $n$  by a variable amount (e.g., Euclid's algorithm)

# What is Decrease & Conquer?

---

- Solves a problem instance of size  $n$  by:
  - decreasing  $n$  by a constant, e.g., 1, or
  - decreasing  $n$  by a constant factor, e.g., 2, or
  - decreasing  $n$  by a variable amount (e.g., Euclid's algorithm)

... to get a problem instance of size  $k < n$

# What is Decrease & Conquer?

---

- Solves a problem instance of size  $n$  by:
  - decreasing  $n$  by a constant, e.g., 1, or
  - decreasing  $n$  by a constant factor, e.g., 2, or
  - decreasing  $n$  by a variable amount (e.g., Euclid's algorithm)

... to get a problem instance of size  $k < n$

- Solve the instance of size  $k$ , using the same algorithm recursively.



# What is Decrease & Conquer?

---

- Solves a problem instance of size  $n$  by:
  - decreasing  $n$  by a constant, e.g., 1, or
  - decreasing  $n$  by a constant factor, e.g., 2, or
  - decreasing  $n$  by a variable amount (e.g., Euclid's algorithm)
- ... to get a problem instance of size  $k < n$ 
  - Solve the instance of size  $k$ , using the same algorithm recursively.
  - Use that solution to get the solution to the original problem.

# What is Decrease & Conquer?

---

- Also known as the inductive or incremental approach

# What is Decrease & Conquer?

---

- Also known as the inductive or incremental approach
- Implement it recursively (top-down)


# What is Decrease & Conquer?

---

- Also known as the inductive or incremental approach
- Implement it recursively (top-down)
- Implement it iteratively (bottom-up)

# Decrease & Conquer by one

---



**FIGURE 4.1** Decrease-(by one)-and-conquer technique.

# Example - Decrease & Conquer by one

---

- Exponentiation using  $a^n = a^{n-1} \times a$ ,  $a \neq 0$ ,  $n$  non-negative integer

# Example - Decrease & Conquer by one

---

- Exponentiation using  $a^n = a^{n-1} \times a$ ,  $a \neq 0$ ,  $n$  non-negative integer

**FIGURE 4.1** Decrease-(by one)-and-conquer technique.

$$f(n) = \begin{cases} f(n-1) \cdot a & \text{if } n > 0, \\ 1 & \text{if } n = 0, \end{cases} \quad (4.1)$$

# Example - Decrease & Conquer by one

---

- Exponentiation using  $a^n = a^{n-1} \times a$ ,  $a \neq 0$ ,  $n$  non-negative integer

**FIGURE 4.1** Decrease-(by one)-and-conquer technique.

$$f(n) = \begin{cases} f(n-1) \cdot a & \text{if } n > 0, \\ 1 & \text{if } n = 0, \end{cases} \quad (4.1)$$

What about running time function complexity?



# Example - Decrease & Conquer by one

---

- How does the decrease-and-conquer algorithm differ from the Brute-force algorithm?
  1. the brute-force algorithm is more efficient
  2. the decrease-and conquer algorithm is more efficient
  3. the two algorithms are identical
  4. the two algorithms have the same asymptotic efficiency, but decrease-and conquer has a better constant.

# Example - Decrease & Conquer by constant


---

**FIGURE 4.2** Decrease-(by half)-and-conquer technique.

$$a^n = \begin{cases} (a^{n/2})^2 & \text{if } n \text{ is even and positive,} \\ (a^{(n-1)/2})^2 \cdot a & \text{if } n \text{ is odd,} \\ 1 & \text{if } n = 0. \end{cases} \quad (4.2)$$

# Example - Decrease & Conquer by constant

---



**FIGURE 4.2** Decrease-(by half)-and-conquer technique.

# Example - Decrease & Conquer by constant

---

**FIGURE 4.2** Decrease-(by half)-and-conquer technique.

$$a^n = \begin{cases} (a^{n/2})^2 & \text{if } n \text{ is even and positive,} \\ (a^{(n-1)/2})^2 \cdot a & \text{if } n \text{ is odd,} \\ 1 & \text{if } n = 0. \end{cases} \quad (4.2)$$

What about running time function complexity?

# Binary Search

---


- Search for an element  $K$  in an already sorted array  $A$

$$\begin{array}{c} K \\ \updownarrow \\ \underbrace{A[0] \dots A[m-1]}_{\text{search here if } K < A[m]} \quad A[m] \quad \underbrace{A[m+1] \dots A[n-1]}_{\text{search here if } K > A[m]} \end{array}$$

# Binary Search

---


- Search for an element  $K$  in an already sorted array  $A$
- Compare  $K$  with array's middle element



# Binary Search

---

- Search for an element  $K$  in an already sorted array  $A$
- Compare  $K$  with array's middle element  $A[m]$
- If they match stop. Otherwise do the same recursively for the first half if  $k < A[m]$ , otherwise look at second half of the array



# Binary Search

---

**ALGORITHM** *BinarySearch*( $A[0..n-1]$ ,  $K$ )

//Implements nonrecursive binary search

//Input: An array  $A[0..n-1]$  sorted in ascending order and

// a search key  $K$

//Output: An index of the array's element that is equal to  $K$

// or  $-1$  if there is no such element

$l \leftarrow 0$ ;  $r \leftarrow n - 1$

**while**  $l \leq r$  **do**

$m \leftarrow \lfloor (l + r) / 2 \rfloor$

**if**  $K = A[m]$  **return**  $m$

**else if**  $K < A[m]$   $r \leftarrow m - 1$

**else**  $l \leftarrow m + 1$

**return**  $-1$



# Binary Search

---

```
ALGORITHM BinarySearch( $A[0..n-1]$ ,  $K$ )  
  //Implements nonrecursive binary search  
  //Input: An array  $A[0..n-1]$  sorted in ascending order and  
  //       a search key  $K$   
  //Output: An index of the array's element that is equal to  $K$   
  //       or  $-1$  if there is no such element  
   $l \leftarrow 0$ ;  $r \leftarrow n - 1$   
  while  $l \leq r$  do  
     $m \leftarrow \lfloor (l + r) / 2 \rfloor$   
    if  $K = A[m]$  return  $m$   
    else if  $K < A[m]$   $r \leftarrow m - 1$   
    else  $l \leftarrow m + 1$   
  return  $-1$ 
```

- What is the basic operation?

# Binary Search

---

```
ALGORITHM BinarySearch( $A[0..n-1]$ ,  $K$ )  
  //Implements nonrecursive binary search  
  //Input: An array  $A[0..n-1]$  sorted in ascending order and  
  //       a search key  $K$   
  //Output: An index of the array's element that is equal to  $K$   
  //       or  $-1$  if there is no such element  
   $l \leftarrow 0$ ;  $r \leftarrow n - 1$   
  while  $l \leq r$  do  
     $m \leftarrow \lfloor (l + r) / 2 \rfloor$   
    if  $K = A[m]$  return  $m$   
    else if  $K < A[m]$   $r \leftarrow m - 1$   
    else  $l \leftarrow m + 1$   
  return  $-1$ 
```

- What is the basic operation?
- What about worst case complexity?

# Binary Search

---

```
ALGORITHM BinarySearch( $A[0..n - 1]$ ,  $K$ )
//Implements nonrecursive binary search
//Input: An array  $A[0..n - 1]$  sorted in ascending order and
//       a search key  $K$ 
//Output: An index of the array's element that is equal to  $K$ 
//        or  $-1$  if there is no such element
 $l \leftarrow 0$ ;  $r \leftarrow n - 1$ 
while  $l \leq r$  do
     $m \leftarrow \lfloor (l + r) / 2 \rfloor$ 
    if  $K = A[m]$  return  $m$ 
    else if  $K < A[m]$   $r \leftarrow m - 1$ 
    else  $l \leftarrow m + 1$ 
return  $-1$ 
```

- What is the basic operation?
- What about worst case complexity?  $C(n) = C(n/2) + 1$ ,  $n > 1$   $C(1)=1$

# Insertion Sort

---

- Decrease-by-one, sort array  $A[0\dots n-1]$

# Insertion Sort

---

- Decrease-by-one, sort array  $A[0\dots n-1]$
- If  $A[0\dots n-2]$  is sorted, how can we solve  $A[0\dots n-1]$ ?

# Insertion Sort

---

- Decrease-by-one, sort array  $A[0\dots n-1]$
- If  $A[0\dots n-2]$  is sorted, how can we solve  $A[0\dots n-1]$ ?
- All we have to do is put  $A[n-1]$  in the correct position.

# Insertion Sort

---

- Decrease-by-one, sort array  $A[0\dots n-1]$

# Insertion Sort

---

- Decrease-by-one, sort array  $A[0\dots n-1]$
- Decrease-by-one,  $A[0\dots n-2]$  is sorted:  
how can we solve  $A[0\dots n-1]$ ?



# Insertion Sort

---

- Decrease-by-one, sort array  $A[0\dots n-1]$
- Decrease-by-one,  $A[0\dots n-2]$  is sorted:  
how can we solve  $A[0\dots n-1]$ ?
- All we have to do is put  $A[n-1]$  in the correct position.

# Insertion Sort

---

- Decrease-by-one, sort array  $A[0...n-1]$
- Decrease-by-one,  $A[0...n-2]$  is sorted:  
how can we solve  $A[0...n-1]$ ?
- All we have to do is put  $A[n-1]$  in the correct position.
  - Scan sorted subarray from right to left until you find a smaller element than  $A[n-1]$
- Though insertion is based on a recursive idea its easier to implement bottom-up, iteratively.

# Insertion Sort

---

89		<b>45</b>	68	90	29	34	17					
45		89		<b>68</b>	90	29	34	17				
45		68		89		<b>90</b>	29	34	17			
45		68		89		90		<b>29</b>	34	17		
29		45		68		89		90		<b>34</b>	17	
29		34		45		68		89		90		<b>17</b>
17		29		34		45		68		89		90

**FIGURE 4.4** Example of sorting with insertion sort. A vertical bar separates the sorted part of the array from the remaining elements; the element being inserted is in bold.

# Insertion Sort

---

**ALGORITHM** *InsertionSort*( $A[0..n - 1]$ )

//Sorts a given array by insertion sort

//Input: An array  $A[0..n - 1]$  of  $n$  orderable elements

//Output: Array  $A[0..n - 1]$  sorted in nondecreasing order

**for**  $i \leftarrow 1$  **to**  $n - 1$  **do**

$v \leftarrow A[i]$

$j \leftarrow i - 1$

**while**  $j \geq 0$  **and**  $A[j] > v$  **do**

$A[j + 1] \leftarrow A[j]$

$j \leftarrow j - 1$

$A[j + 1] \leftarrow v$

# Insertion Sort

---

- Run animation: <https://visualgo.net/bn/sorting>

# Runtime Analysis of Insertion Sort

---

- $C(n) = \sum_{i=1}^{n-1} \sum_{j=0}^{i-1} 1 = \sum_{i=1}^{n-1} i = \frac{(n-1)n}{2} \in \Theta(n^2)$

# Runtime Analysis of Insertion Sort

---

- $C(n) = \sum_{i=1}^{n-1} \sum_{j=0}^{i-1} 1 = \sum_{i=1}^{n-1} i = \frac{(n-1)n}{2} \in \Theta(n^2)$
- This is worst case complexity (array of strictly decreasing values)

# Runtime Analysis of Insertion Sort

---

- $C(n) = \sum_{i=1}^{n-1} \sum_{j=0}^{i-1} 1 = \sum_{i=1}^{n-1} i = \frac{(n-1)n}{2} \in \Theta(n^2)$
- This is worst case complexity (array of strictly decreasing values)
- In the best case, comparison  $A[j] > u$  is executed only once (array is already sorted in non-decreasing order)



# Runtime Analysis of Insertion Sort

---

- $C(n) = \sum_{i=1}^{n-1} \sum_{j=0}^{i-1} 1 = \sum_{i=1}^{n-1} i = \frac{(n-1)n}{2} \in \Theta(n^2)$
- This is worst case complexity (array of strictly decreasing values)
- In the best case, comparison  $A[j] > u$  is executed only once (array is already sorted in non-decreasing order)

$$\sum_{i=1}^{n-1} 1 = n - 1 \in \Theta(n)$$

# Runtime Analysis of Insertion Sort

---

- $C(n) = \sum_{i=1}^{n-1} \sum_{j=0}^{i-1} 1 = \sum_{i=1}^{n-1} i = \frac{(n-1)n}{2} \in \Theta(n^2)$
- This is worst case complexity (array of strictly decreasing values)
- In the best case, comparison  $A[j] > u$  is executed only once (array is already sorted in non-decreasing order)

$$\sum_{i=1}^{n-1} 1 = n - 1 \in \Theta(n)$$

- almost-sorted files do arise in a variety of applications, and insertion sort preserves its excellent performance on such inputs.

# Runtime Analysis of Insertion Sort

---

- $C_{avg}(n) \approx \frac{n^2}{4} \in \Theta(n^2)$ , average case
- In the worst case Insertion Sort makes same number of comparisons as Selection Sort

# Is Insertion Sort Stable?

---

- Is Insertion sort stable?

# Is Insertion Sort Stable?

---

- Is Insertion sort stable?
  - Yes, it is stable

# Euclid's Algorithm

---

```
int gcd(int m, int n)
{
    if (n == 0) return m;
    return gcd(n, m % n);
}
```

# Euclid's Algorithm

---

```
int gcd(int m, int n)
{
    if (n == 0) return m;
    return gcd(n, m % n);
}
```

- One of the most ancient algorithms.

# Euclid's Algorithm

---

```
int gcd(int m, int n)
{
    if (n == 0) return m;
    return gcd(n, m % n);
}
```

- One of the most ancient algorithms.
- Computes the greatest common divisor of two numbers.



# Euclid's Algorithm

---

```
int gcd(int m, int n)
{
    if (n == 0) return m;
    return gcd(n, m % n);
}
```

- One of the most ancient algorithms.
- Computes the greatest common divisor of two numbers.
- It is based on the property that if  $T$  divides  $X$  and  $Y$ , then  $T$  also divides  $X \bmod Y$ .

# Euclid's Algorithm

---

```
int gcd(int m, int n)
{
    if (n == 0) return m;
    return gcd(n, m % n);
}
```

- One of the most ancient algorithms.
- Computes the greatest common divisor of two numbers.
- It is based on the property that if  $T$  divides  $X$  and  $Y$ , then  $T$  also divides  $X \bmod Y$ .
- How is  $\text{gcd}(96, 36)$  evaluated?

# Euclid's Algorithm

---

```
int gcd(int m, int n)
{
    if (n == 0) return m;
    return gcd(n, m % n);
}
```

- One of the most ancient algorithms.
- Computes the greatest common divisor of two numbers.
- It is based on the property that if  $T$  divides  $X$  and  $Y$ , then  $T$  also divides  $X \bmod Y$ .
- How is  $\text{gcd}(96, 36)$  evaluated?
- $\text{gcd}(96, 36) = \text{gcd}(36, 24) = \text{gcd}(24, 12) = \text{gcd}(12, 0) = 12$