

Algorithms

Decision trees and random forests

Emanuele Rodolà
rodola@di.uniroma1.it



Learning from data

We are looking at a family of techniques known as supervised learning.

Learning from data

We are looking at a family of techniques known as **supervised learning**.

- Classification

The output is **categorical** (yes/no, animal/human/plant, etc.).

Decision trees and random forests.

Learning from data

We are looking at a family of techniques known as **supervised learning**.

- Classification

The output is **categorical** (yes/no, animal/human/plant, etc.).

Decision trees and random forests.

- Regression

The output is a **continuous** value (quantities, temperature, etc.).

Regression forests.

Learning from data

We are looking at a family of techniques known as **supervised learning**.

- Classification

The output is **categorical** (yes/no, animal/human/plant, etc.).

Decision trees and random forests.

- Regression

The output is a **continuous** value (quantities, temperature, etc.).

Regression forests.

Overall idea: Given a large dataset where each data point also has a **label**, construct a machine that can **predict** the label of a new data point.

Learning from data

We are looking at a family of techniques known as **supervised learning**.

- Classification

The output is **categorical** (yes/no, animal/human/plant, etc.).

Decision trees and random forests.

- Regression

The output is a **continuous** value (quantities, temperature, etc.).

Regression forests.

Overall idea: Given a large dataset where each data point also has a **label**, construct a machine that can **predict** the label of a new data point.

- **Training** set: data points with “ground-truth” labels.

Learning from data

We are looking at a family of techniques known as **supervised learning**.

- **Classification**

The output is **categorical** (yes/no, animal/human/plant, etc.).

Decision trees and random forests.

- **Regression**

The output is a **continuous** value (quantities, temperature, etc.).

Regression forests.


Overall idea: Given a large dataset where each data point also has a **label**, construct a machine that can **predict** the label of a new data point.

- **Training** set: data points with “ground-truth” labels.
- **Test** set: data points with unknown labels.

Random forest: Intuition




Random forest: Intuition



Construct multiple **decision trees**.

Each decision tree outputs a **prediction** for a given input.


Random forest: Intuition



Construct multiple **decision trees**.

Each decision tree outputs a **prediction** for a given input.

Random forest: Intuition




Construct multiple **decision trees**.

Each decision tree outputs a **prediction** for a given input.

The predictions from each tree are **combined** into one final prediction.

Decision tree

A **decision tree** is a binary tree in which each branch represents a possible decision. A path through the tree is therefore a course of action.



The data is iteratively **partitioned** into subsets from the root to the leaves.

Information gain

Each intermediate node is called a **decision node**.

Each leaf node stores the final decision (i.e. the **classification** result).

Information gain

Each intermediate node is called a **decision node**.

Each leaf node stores the final decision (i.e. the **classification** result).

We use **entropy** as a measure to choose what is done at each node.

Entropy measures the **uncertainty** for a given data distribution.


Information gain

Each intermediate node is called a **decision node**.

Each leaf node stores the final decision (i.e. the **classification** result).

We use **entropy** as a measure to choose what is done at each node.

Entropy measures the **uncertainty** for a given data distribution.




Information gain

Each intermediate node is called a **decision node**.

Each leaf node stores the final decision (i.e. the **classification** result).

We use **entropy** as a measure to choose what is done at each node.

Entropy measures the **uncertainty** for a given data distribution.



Ideally we want each split to be as discriminative as possible, and thus maximize the **information gain** $E2 - E1$.

Training

Problem: Classify the types of fruit based on their features.



We start from a set of data points that have **high entropy**.

Training

Problem: Classify the types of fruit based on their features.



We start from a set of data points that have **high entropy**.

Define the **features** (diameter, color, etc.) on which to base our decisions.

Training

Problem: Classify the types of fruit based on their features.



We start from a set of data points that have **high entropy**.

Define the **features** (diameter, color, etc.) on which to base our decisions.

At each node, choose the question that maximizes the information gain.

Training

Problem: Classify the types of fruit based on their features.




We start from a set of data points that have **high entropy**.

Define the **features** (diameter, color, etc.) on which to base our decisions.

At each node, choose the question that maximizes the information gain.


Keep splitting until the dataset is empty or **accuracy** is high enough.

Accuracy



A **leaf** is where no more splitting is required or possible (zero entropy).

Accuracy




A **leaf** is where no more splitting is required or possible (zero entropy).

At each leaf, **accuracy** with respect to label ℓ is measured as:

$$\frac{\# \text{ data points with label } \ell}{\# \text{ data points}}$$

Accuracy



Random forest

The pipeline is as follows:

- Split the given training data into random partitions ([bagging](#)).

Random forest

The pipeline is as follows:

- Split the given training data into random partitions ([bagging](#)).
- With each partition, construct a decision tree.

Random forest

The pipeline is as follows:

- Split the given training data into random partitions (**bagging**).
- With each partition, construct a decision tree.

Each tree asks **different** questions, has different depth, and different accuracy at the leaves.

Random forest

The pipeline is as follows:

- Split the given training data into random partitions (**bagging**).
- With each partition, construct a decision tree.

Each tree asks **different** questions, has different depth, and different accuracy at the leaves.

However, all the trees try to solve the **same** classification problem.

Random forest

The pipeline is as follows:

- Split the given training data into random partitions (**bagging**).
- With each partition, construct a decision tree.
Each tree asks **different** questions, has different depth, and different accuracy at the leaves.
However, all the trees try to solve the **same** classification problem.
- Given a new data point (**test set**), route it through each tree.

Random forest

The pipeline is as follows:

- Split the given training data into random partitions (**bagging**).
- With each partition, construct a decision tree.
Each tree asks **different** questions, has different depth, and different accuracy at the leaves.
However, all the trees try to solve the **same** classification problem.
- Given a new data point (**test set**), route it through each tree.
Each tree gives a prediction (a **probability distribution** over all the classes).

Random forest

The pipeline is as follows:

- Split the given training data into random partitions (**bagging**).
- With each partition, construct a decision tree.
Each tree asks **different** questions, has different depth, and different accuracy at the leaves.
However, all the trees try to solve the **same** classification problem.
- Given a new data point (**test set**), route it through each tree.
Each tree gives a prediction (a **probability distribution** over all the classes).
Average the tree predictions to get the forest prediction.

Example

In scikit-learn:

<https://scikit-learn.org/stable/modules/ensemble.html>

Exercise: Use the iris dataset to predict flower species.

Reading: "Understanding random forests: from theory to practice"

<https://arxiv.org/pdf/1407.7502>